



EVERLAST®

Advanced Composite Siding

CERTIFICATE OF CONFORMANCE

Everlast® Composite Siding

Everlast® Composite Siding panels are manufactured to the following specifications.

PHYSICAL DATA

Panel Thickness: 0.22" (± 0.005 ")
 Panel Projection: $\frac{7}{16}$ "
 Width: $8\frac{1}{2}$ " $\pm \frac{1}{16}$ " and $6\frac{3}{8}$ " $\pm \frac{1}{16}$ "
 Exposure: $6\frac{7}{8}$ " & $4\frac{1}{2}$ "
 Length: 12'
 Weight: $6\frac{7}{8}$ " plank = 7.8#, $4\frac{1}{2}$ " plank = 6.4#
 Packaging: 8 planks/bundle
 Color: Uniformity is spectrophotometrically controlled.
 Texture: Embossed with a rough cut cedar finish
 Gloss: Uniform low gloss maintained with a 75° gloss meter

PRODUCT TEST DATA

Heat Shrinkage:	0.1% at 160°F
Static Windload Test Pressure:	93 psf. (>250mph)
Squareness:	<1/16" of square
Length:	Within - 1/4" of specification
Warp/Camber:	<1/16"
Coefficient of Linear Expansion (in/in/°F):	8.38×10^{-6}
Weathering and Flexural:	104.4% Strength Retention
Freeze Thaw and Flexural:	94.1% Strength Retention
Water Absorption per ASTM D-570:	<2.0% Long Term (3 weeks)

FIRE RESISTANCE

ASTM E84:

Flame Spread Index: 75
 Smoke Developed Index: >450

ASTM D635:

Classified CC1
 Rate of burn: No Self Sustained Burn

ASTM D-1929:

Self Ignition/Flash Ignition Temperature: 430°C/400°C

RELEVANT CODES AND REGULATIONS COMPLIANCE

Code Compliance Research Report #0201

COLORS

- Antique Ivory
- Cabernet Red
- Canvas
- Chestnut
- Flagstone
- Harbor Blue
- Heritage Cream
- Misty Taupe
- Polar White
- Sand Dune
- Seaside Gray
- Slate
- Spanish Moss
- Willow

All colors feature capping resins, a UV- Stable acrylic polymer for exceptional color retention.



0201