



Contract - Detailed

Sales Rep Name: Reeves, Dana
Sales Rep Phone: 248-464-8601
Sales Rep Fax: 248-292-5031
Sales Rep E-Mail: reevesdj@pella.com

Table with 3 columns: Customer Information, Project/Delivery Address, and Order Information. Includes details for WEST CONSTRUCTION SERVICES, 910 Marlborough apartments, and various order numbers and dates.

Customer Notes: ROOM LOCATION: Listed as: Window Type_Elevation_Room Location_(Floor_ Opening # on Floor, Starting at Left Corner of Elv.)
What is shown in parenthesis above will not print out on unit label.

The line item number will print on product's label, and all 2-digit line item #'s are lower level, all 100's are first floor, all 200's are 2nd floor and all 300's are third floor.

*** West Constructions original PO #3325 dated 5/29/20 remains the contract of record. Signoff on this Pella contract is to confirm new sizes, as field measured by Joe Owens, and to confirm all product, attributes, and line item notes. ***

See Masonry Opening schedule, provided separately, for all clearances between frame and MO size. See provided specification sheet, for easy view of all attributes. Original shops still accurate for head, jamb and sill details, though not for unit sizes.

DISREGARD all performance ratings listed for the Reserve product, with LowE 272 glass. Because these units are special order, they have not been tested and have NO PERFORMANCE RATING

MK initial here that you have reviewed the above notes

Line #	Location:	Attributes
--------	-----------	------------

5 E W K/Din Lwr1

Special Pella® Reserve, Traditional, 2-Wide Double Hung, 68.25 X 48.75, AlmondQty

1



PK #

2073

Viewed From Exterior

1: Traditional, 32.62548.75 Double Hung, Equal**Frame Size:** 32 5/8 X 48 3/4**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 32.62548.75 Double Hung, Equal****Frame Size:** 32 5/8 X 48 3/4**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, Pella Recommended Clearance, Perimeter Length = 234".**Rough Opening:** 69" X 49.5"

Customer Notes: TEMPERED - proximity to exterior stair

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

10 E W LR Lwr2

Special Pella® Reserve, Traditional, 2-Wide Double Hung, 80.25 X 48.75, AlmondQty

1



PK #

2073

Viewed From Exterior

1: Traditional, 38.62548.75 Double Hung, Equal**Frame Size:** 38 5/8 X 48 3/4**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.53, CPD PEL-N-232-00253-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 38.62548.75 Double Hung, Equal****Frame Size:** 38 5/8 X 48 3/4**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.53, CPD PEL-N-232-00253-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, Pella Recommended Clearance, Perimeter Length = 258".**Rough Opening:** 81" X 49.5"

Custom Product Instructions:

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

15 Foyer N/S

Special Pella® Reserve, Traditional, Sash Set Fixed, 24.5 X 31.25, AlmondQty

2



PK #

2073

Viewed From Exterior

1: Traditional, 24.531.25 Fixed Sash Set**Frame Size:** 24 1/2 X 31 1/4**General Information:** Standard, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Performance Information:** U-Factor 0.27, SHGC 0.30, VLT 0.55, CPD PEL-N-1-53567-00002, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 11**Grille:** No Grille,**Wrapping Information:** 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, Pella Recommended Clearance, Perimeter Length = 112".**Rough Opening:** 25 - 1/4" X 32"

Customer Notes: 3-11/16" - No JE

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

20 E W LR Lwr3

Special Pella® Reserve, Traditional, 2-Wide Double Hung, 80.5 X 48.75, AlmondQty

1



PK #

2073

Viewed From Exterior

1: Traditional, 38.7548.75 Double Hung, Equal**Frame Size:** 38 3/4 X 48 3/4**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.53, CPD PEL-N-232-00253-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 38.7548.75 Double Hung, Equal****Frame Size:** 38 3/4 X 48 3/4**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.53, CPD PEL-N-232-00253-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, Pella Recommended Clearance, Perimeter Length = 259".**Rough Opening:** 81 - 1/4" X 49 - 1/2"

Custom Product Instructions:

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

25 G W Hall Lwr4

Special Pella® Reserve, Traditional, Double Hung, 30.5 X 48, AlmondQty

1

PK #
2073

Viewed From Exterior

1: Traditional, 30.548 Double Hung, Equal**Frame Size:** 30 1/2 X 48**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.53, CPD PEL-N-232-00253-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, Pella Recommended Clearance, Perimeter Length = 157".**Rough Opening:** 31 - 1/4" X 48 - 3/4"

Customer Notes: ADDED TEMPERING to this unit

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

30 F W K/Din Lwr5

Special Pella® Reserve, Traditional, 2-Wide Double Hung, 68.5 X 48.75, AlmondQty

1

PK #
2073

Viewed From Exterior

1: Traditional, 32.7548.75 Double Hung, Equal**Frame Size:** 32 3/4 X 48 3/4**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.53, CPD PEL-N-232-00253-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 32.7548.75 Double Hung, Equal****Frame Size:** 32 3/4 X 48 3/4**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.53, CPD PEL-N-232-00253-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, Pella Recommended Clearance, Perimeter Length = 235".**Rough Opening:** 69 - 1/4" X 49 - 1/2"

Custom Product Instructions:

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

35 F S BR3 Lwr1

Pella 250 Series, 2-Wide Double Hung, 68.25 X 47.75, AlmondQty

1

PK #
2073

Viewed From Exterior

1: 32.62547.75 Double Hung, Equal**Frame Size:** 32 5/8 X 47 3/4**General Information:** Standard, Vinyl, Block, No Foam Insulated, 3 1/4", 3 1/4", Sill Adapter Included, Head Expander Included**Exterior Color / Finish:** Almond**Interior Color / Finish:** Almond**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Cam-Action Lock, Almond, Standard Vent Stop, No Limited Opening Hardware**Screen:** Full Screen, Conventional Fiberglass**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.53, CPD PEL-N-211-00057-00001, Performance Class R, PG 35, Calculated Positive DP Rating 35, Calculated Negative DP Rating 35, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** AlignedWith, 3"**2: 32.62547.75 Double Hung, Equal****Frame Size:** 32 5/8 X 47 3/4**General Information:** Standard, Vinyl, Block, No Foam Insulated, 3 1/4", 3 1/4", Sill Adapter Included, Head Expander Included**Exterior Color / Finish:** Almond**Interior Color / Finish:** Almond**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Cam-Action Lock, Almond, Standard Vent Stop, No Limited Opening Hardware**Screen:** Full Screen, Conventional Fiberglass**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.53, CPD PEL-N-211-00057-00001, Performance Class R, PG 35, Calculated Positive DP Rating 35, Calculated Negative DP Rating 35, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Pella Recommended Clearance, Perimeter Length = 232".**Rough Opening:** 33 - 1/8" X 48 - 1/4"

Customer Notes: Ships as two separate units. Install with units 3" apart, framing structure between. Mull covers & framing by others. Full screens.


PERFORMANCE CLASS of R does not meet specs

Line #	Location:	Attributes
--------	-----------	------------

40 K S BR3 Lwr2

Pella 250 Series, Awning Vent, 36.75 X 17.5, Almond

Qty
1



PK #
2073

Viewed From Exterior

1: 36.7517.5 Vent Awning
Frame Size: 36 3/4 X 17 1/2

General Information: Standard, Vinyl, Block, No Foam Insulated, 3 1/4", 3 1/4", Sill Adapter Included, Head Expander Included

Exterior Color / Finish: Almond

Interior Color / Finish: Almond

Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude

Hardware Options: Standard, Wash Hinge Hardware, Fold-Away Crank, Almond, No Limited Opening Hardware

Screen: Full Screen, Conventional Fiberglass

Performance Information: U-Factor 0.27, SHGC 0.25, VLT 0.46, CPD PEL-N-241-00005-00001, Performance Class LC, PG 35, Calculated Positive DP Rating 35, Calculated Negative DP Rating 35, Year Rated 08|11, Egress Not Applicable

Grille: No Grille,

Wrapping Information: User Defined Rough Opening Clearance, 3/8", 1/4", 1/4", 3/8", Perimeter Length = 109".

Rough Opening: 37 - 1/4" X 18 - 1/4"

Customer Notes: Standard Advnced LowE glass


Does NOT meet egress

Line #	Location:	Attributes
--------	-----------	------------

45 K S BR2 Lwr3

Pella 250 Series, Awning Vent, 36.75 X 17.5, Almond

Qty
1



PK #
2073

Viewed From Exterior

1: 36.7517.5 Vent Awning

Frame Size: 36 3/4 X 17 1/2

General Information: Standard, Vinyl, Block, No Foam Insulated, 3 1/4", 3 1/4", Sill Adapter Included, Head Expander Included

Exterior Color / Finish: Almond

Interior Color / Finish: Almond

Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude

Hardware Options: Standard, Wash Hinge Hardware, Fold-Away Crank, Almond, No Limited Opening Hardware

Screen: Full Screen, Conventional Fiberglass

Performance Information: U-Factor 0.27, SHGC 0.25, VLT 0.46, CPD PEL-N-241-00005-00001, Performance Class LC, PG 35, Calculated Positive DP Rating 35, Calculated Negative DP Rating 35, Year Rated 08|11, Egress Not Applicable


Grille: No Grille,

Wrapping Information: Pella Recommended Clearance, Perimeter Length = 109".

Rough Opening: 37 - 1/4" X 18"

Customer Notes: Standard Advnced LowE glass


Does NOT meet egress

Line #	Location:	Attributes		Qty
50	I E Bath Lwr1	Pella 250 Series, Direct Set Fixed, 36.5 X 25, Almond		1
		 <p>PK # 2073</p> <p>Viewed From Exterior</p>	<p>1: Non-Standard Size Non-Standard Size Fixed Direct Set Frame Size: 36 1/2 X 25 General Information: Standard, Vinyl, Block, No Foam Insulated, 3 1/4", 3 1/4", Sill Adapter Included, Head Expander Included Exterior Color / Finish: Almond Interior Color / Finish: Almond Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.27, SHGC 0.30, VLT 0.57, CPD PEL-N-240-00005-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08 11 Grille: No Grille, Wrapping Information: Pella Recommended Clearance, Perimeter Length = 123".</p>	

Rough Opening: 37" X 25.5"

Customer Notes: 1/2" shorter than other (3) units on this floor/elv, but not directly adjacent

Standard Advnced LowE glass

Line #	Location:	Attributes		Qty
55	K E BR1 Lwr2	Pella 250 Series, Awning Vent, 36.5 X 17.5, Almond		1
		 <p>PK # 2073</p> <p>Viewed From Exterior</p>	<p>1: Non-Standard Size Vent Awning Frame Size: 36 1/2 X 17 1/2 General Information: Standard, Vinyl, Block, No Foam Insulated, 3 1/4", 3 1/4", Sill Adapter Included, Head Expander Included Exterior Color / Finish: Almond Interior Color / Finish: Almond Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Hardware Options: Standard, Wash Hinge Hardware, Fold-Away Crank, Almond, No Limited Opening Hardware Screen: Full Screen, Conventional Fiberglass Performance Information: U-Factor 0.27, SHGC 0.25, VLT 0.46, CPD PEL-N-241-00005-00001, Performance Class LC, PG 35, Calculated Positive DP Rating 35, Calculated Negative DP Rating 35, Year Rated 08 11, Egress Not Applicable Grille: No Grille, Wrapping Information: Pella Recommended Clearance, Perimeter Length = 108".</p>	

Rough Opening: 37" X 18"

Customer Notes: Standard Advnced LowE glass

Does NOT meet egress


Line #	Location:	Attributes
--------	-----------	------------

60 I E BR1 Lwr3

Pella 250 Series, Double Hung, 36.5 X 25, Almond

Qty

1



PK #
2073

Viewed From Exterior

1: Non-Standard Size Non-Standard Size Double Hung, Equal

Frame Size: 36 1/2 X 25

General Information: Standard, Vinyl, Block, No Foam Insulated, 3 1/4", 3 1/4", Sill Adapter Included, Head Expander Included

Exterior Color / Finish: Almond

Interior Color / Finish: Almond

Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude

Hardware Options: Cam-Action Lock, Almond, Standard Vent Stop, No Limited Opening Hardware

Screen: Full Screen, Conventional Fiberglass

Performance Information: U-Factor 0.29, SHGC 0.28, VLT 0.53, CPD PEL-N-211-00057-00001, Performance Class R, PG 30, Calculated Positive DP Rating 30, Calculated Negative DP Rating 30, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements

Grille: No Grille,

Wrapping Information: User Defined Rough Opening Clearance, 1/2", 1/4", 1/4", 1/2", Perimeter Length = 123".

Rough Opening: 37" X 26"

Customer Notes: MO hgt. 1/2" taller than left & right end units on this floor/elv

Standard Advnced LowE glass


Line #	Location:	Attributes
--------	-----------	------------

65 K E BR1 Lwr4

Pella 250 Series, Awning Vent, 36.5 X 17.5, Almond

Qty

1



PK #
2073

Viewed From Exterior

1: Non-Standard Size Vent Awning

Frame Size: 36 1/2 X 17 1/2

General Information: Standard, Vinyl, Block, No Foam Insulated, 3 1/4", 3 1/4", Sill Adapter Included, Head Expander Included

Exterior Color / Finish: Almond

Interior Color / Finish: Almond

Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude

Hardware Options: Standard, Wash Hinge Hardware, Fold-Away Crank, Almond, No Limited Opening Hardware

Screen: Full Screen, Conventional Fiberglass

Performance Information: U-Factor 0.27, SHGC 0.25, VLT 0.46, CPD PEL-N-241-00005-00001, Performance Class LC, PG 35, Calculated Positive DP Rating 35, Calculated Negative DP Rating 35, Year Rated 08|11, Egress Not Applicable

Grille: No Grille,

Wrapping Information: User Defined Rough Opening Clearance, 3/8", 1/4", 1/4", 3/8", Perimeter Length = 108".

Rough Opening: 37" X 18.25"


Customer Notes: Does NOT meet egress

Line #	Location:	Attributes
--------	-----------	------------

70 I E BR2 Lwr5

Pella 250 Series, Double Hung, 36.5 X 25, AlmondQty

1

PK #
2073

Viewed From Exterior

1: 36.525 Double Hung, Equal**Frame Size:** 36 1/2 X 25**General Information:** Standard, Vinyl, Block, No Foam Insulated, 3 1/4", 3 1/4", Sill Adapter Included, Head Expander Included**Exterior Color / Finish:** Almond**Interior Color / Finish:** Almond**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Cam-Action Lock, Almond, Standard Vent Stop, No Limited Opening Hardware**Screen:** Full Screen, Conventional Fiberglass**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.53, CPD PEL-N-211-00057-00001, Performance Class R, PG 30, Calculated Positive DP Rating 30, Calculated Negative DP Rating 30, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** User Defined Rough Opening Clearance, 1/2", 1/4", 1/4", 1/2", Perimeter Length = 123".**Rough Opening:** 37" X 26"

Customer Notes: MO hgt. 1/2" taller than left & right end units on this floor/elv

Standard Advnced LowE glass

PERFORMANCE CLASS of R does not meet specs


Does NOT meet egress

Line #	Location:	Attributes
--------	-----------	------------

75 I E BR2 Lwr6

Pella 250 Series, Double Hung, 36.25 X 25, Almond

Qty
1



PK #
2073

Viewed From Exterior

1: 36.2525 Double Hung, Equal

Frame Size: 36 1/4 X 25

General Information: Standard, Vinyl, Block, No Foam Insulated, 3 1/4", 3 1/4", Sill Adapter Included, Head Expander Included

Exterior Color / Finish: Almond

Interior Color / Finish: Almond

Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude

Hardware Options: Cam-Action Lock, Almond, Standard Vent Stop, No Limited Opening Hardware

Screen: Full Screen, Conventional Fiberglass

Performance Information: U-Factor 0.29, SHGC 0.28, VLT 0.53, CPD PEL-N-211-00057-00001, Performance Class R, PG 30, Calculated Positive DP Rating 30, Calculated Negative DP Rating 30, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements

Grille: No Grille,

Wrapping Information: User Defined Rough Opening Clearance, 1/2", 1/4", 1/4", 1/2", Perimeter Length = 123".

Rough Opening: 36 - 3/4" X 26"

Customer Notes: 1/4" narrower than similar units on this floor/elv

Standard Advnced LowE glass


PERFORMANCE CLASS of R does not meet specs

Line #	Location:	Attributes
--------	-----------	------------

80 K N BR2 Lwr1

Pella 250 Series, Awning Vent, 36.5 X 17.5, Almond

Qty
1



PK #
2073

Viewed From Exterior

1: Non-Standard Size Vent Awning

Frame Size: 36 1/2 X 17 1/2

General Information: Standard, Vinyl, Block, No Foam Insulated, 3 1/4", 3 1/4", Sill Adapter Included, Head Expander Included

Exterior Color / Finish: Almond

Interior Color / Finish: Almond

Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude

Hardware Options: Standard, Wash Hinge Hardware, Fold-Away Crank, Almond, No Limited Opening Hardware

Screen: Full Screen, Conventional Fiberglass

Performance Information: U-Factor 0.27, SHGC 0.25, VLT 0.46, CPD PEL-N-241-00005-00001, Performance Class LC, PG 35, Calculated Positive DP Rating 35, Calculated Negative DP Rating 35, Year Rated 08|11, Egress Not Applicable

Grille: No Grille,

Wrapping Information: User Defined Rough Opening Clearance, 3/8", 1/4", 1/4", 3/8", Perimeter Length = 108".

Rough Opening: 37" X 18.25"

Customer Notes: Standard Advnced LowE glass


For more information regarding the finishing, maintenance, service and warranty of all Pella® products, visit the Pella® website at www.pella.com

Line #	Location:	Attributes	
--------	-----------	------------	--

85 J N Bath Lwr2

Pella 250 Series, Double Hung, 36.5 X 25.5, Almond

Qty
1



PK #
2073

Viewed From Exterior

1: Non-Standard Size Non-Standard Size Double Hung, Equal

Frame Size: 36 1/2 X 25 1/2

General Information: Standard, Vinyl, Block, No Foam Insulated, 3 1/4", 3 1/4", Sill Adapter Included, Head Expander Included

Exterior Color / Finish: Almond

Interior Color / Finish: Almond

Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude

Hardware Options: Cam-Action Lock, Almond, Standard Vent Stop, No Limited Opening Hardware

Screen: Full Screen, Conventional Fiberglass

Performance Information: U-Factor 0.29, SHGC 0.28, VLT 0.53, CPD PEL-N-211-00057-00004, Performance Class R, PG 30, Calculated Positive DP Rating 30, Calculated Negative DP Rating 30, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements

Grille: No Grille,

Wrapping Information: Pella Recommended Clearance, Perimeter Length = 124".

Rough Opening: 37" X 26"

Customer Notes: Added TEMPERING due to proximity to tub

Standard Advanced LowE glass

PERFORMANCE CLASS of R does not meet specs

Line #	Location:	Attributes
--------	-----------	------------

90 H N Bath Lwr3

Pella 250 Series, Double Hung, 31 X 47.875, AlmondQty

1

PK #
2073

Viewed From Exterior

1: 3147.875 Double Hung, Equal**Frame Size:** 31 X 47 7/8**General Information:** Standard, Vinyl, Block, No Foam Insulated, 3 1/4", 3 1/4", Sill Adapter Included, Head Expander Included**Exterior Color / Finish:** Almond**Interior Color / Finish:** Almond**Glass:** Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Cam-Action Lock, Almond, Standard Vent Stop, No Limited Opening Hardware**Screen:** Full Screen, Conventional Fiberglass**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.53, CPD PEL-N-211-00057-00004, Performance Class R, PG 35, Calculated Positive DP Rating 35, Calculated Negative DP Rating 35, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Pella Recommended Clearance, Perimeter Length = 158".**Rough Opening:** 31 - 1/2" X 48 - 3/8"

Customer Notes: Ships as two separate units. Install with units 3" apart, framing structure between. Mull covers & framing by others. Full screens.


PERFORMANCE CLASS of R does not meet specs

Line #	Location:	Attributes
--------	-----------	------------

100 D W K/Din 1st 1

Special Pella® Reserve, Traditional, Double Hung, 32.75 X 61, AlmondQty

1

PK #
2073

Viewed From Exterior

1: Traditional, 32.7561 Double Hung, Equal**Frame Size:** 32 3/4 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Meets Typical for ground floor 5.0 sqft (E1) (United States Only)**Grille:** No Grille,**Wrapping Information:** 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, Pella Recommended Clearance, Perimeter Length = 188".**Rough Opening:** 33 - 1/2" X 61 - 3/4"

Custom Product Instructions:

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

105 C W K/Din 1st 2

Special Pella® Reserve, Traditional, Double Hung, 30.625 X 49.25, Almond**Qty**

1



PK #

2073

Viewed From Exterior

1: Traditional, 30.62549.25 Double Hung, Equal**Frame Size:** 30 5/8 X 49 1/4**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, User Defined Rough Opening Clearance, 3/8", 7/16", 7/16", 3/8", Perimeter Length = 160".**Rough Opening:** 31 - 1/2" X 50"

Customer Notes: this opening 1/4" wider than opening above it

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

110 B W LR 1st 3

PK #
2073

Viewed From Exterior

Special Pella® Reserve, Traditional, 3-Wide Double Hung, 76.375 X 61, AlmondQty

1

1: Traditional, Non-Standard Size Double Hung, Equal**Frame Size:** 21 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal****Frame Size:** 28 3/8 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 2:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**3: Traditional, Non-Standard Size Double Hung, Equal****Frame Size:** 21 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, User Defined Rough Opening Clearance, 3/8", 5/16", 5/16", 3/8", Perimeter Length = 275".**Rough Opening:** 77" X 61.75"


Customer Notes: **REVISED size to 3-wide unequal 10/30/20**

this opening 1/4" narrower than opening above it

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

10/29/20: New size flankers & center unit - - PLEASE RUSH REPRICING GLASS FOR NEW SIZES!!! Thanks,
Nancy

Line #	Location:	Attributes		Qty
115	A W Stair 1st 4	Special Support Product, Direct Set Fixed Frame, 68.25 X 61, Almond		1
		 <p>Viewed From Exterior</p>	<p>1: 68.2561 Fixed Frame Frame Size: 68 1/4 X 61 General Information: Interior Glazed, Factory Assembled, Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Almond Interior Color / Finish: Primed Interior Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.28, SHGC 0.32, VLT 0.60, CPD PEL-N-18-02827-00001, Performance Class CW, PG 60, Calculated Positive DP Rating 60, Calculated Negative DP Rating 60, Year Rated 08 11 Grille: No Grille, Wrapping Information: 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, Pella Recommended Clearance, Perimeter Length = 259".</p>	
	PK # 2073			

Rough Opening: 69" X 61.75"

Customer Notes: REV to FIXED DH, tempered - - so unit has a sash profile, same as other units (prior Support was frame, glass & glass stops only - - no sash) - - will cover higher cost of sash set fixed unit

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

120 B W LR 1st 5

PK #
2073

Viewed From Exterior

Special Pella® Reserve, Traditional, 3-Wide Double Hung, 76.125 X 61, AlmondQty

1

1: Traditional, Non-Standard Size Double Hung, Equal**Frame Size:** 21 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal****Frame Size:** 28 1/8 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 2:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**3: Traditional, Non-Standard Size Double Hung, Equal****Frame Size:** 21 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, User Defined Rough Opening Clearance, 3/8", 7/16", 7/16", 3/8", Perimeter Length = 275".**Rough Opening:** 77" X 61.75"


Customer Notes: **REVISED size to 3-wide unequal 10/30/20**

this opening 1/4" wider than opening above it

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

10/29/20: New size flankers & center unit - - PLEASE RUSH REPRICING GLASS FOR NEW SIZES!!! Thanks,
Nancy

Line #	Location:	Attributes	Qty
125	C W K/Din 1st 6	<p>Special Pella® Reserve, Traditional, Double Hung, 30.625 X 49.25, Almond</p> <p>1: Traditional, 30.62549.25 Double Hung, Equal Frame Size: 30 5/8 X 49 1/4 General Information: Standard, Luxury, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Almond Interior Color / Finish: Primed Interior Sash / Panel: Ogee, Ogee, Standard, No Sash Lugs Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm Hardware Options: Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor Screen: Integrated Rolscreen® Lower Sash Only Performance Information: U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08 11, Egress Does not meet typical United States egress, but may comply with local code requirements Grille: No Grille, Wrapping Information: 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, User Defined Rough Opening Clearance, 3/8", 7/16", 7/16", 3/8", Perimeter Length = 160".</p>	1
	 <p>PK # 2073</p> <p>Viewed From Exterior</p>		

Rough Opening: 31 - 1/2" X 50"


Customer Notes: this opening 1/4" wider than opening above it on 3rd floor

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

130 D W K/Din 1st 7

PK #
2073

Viewed From Exterior

Special Pella® Reserve, Traditional, Double Hung, 32.75 X 61, AlmondQty

1

1: Traditional, 32.7561 Double Hung, Equal**Frame Size:** 32 3/4 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Meets Typical for ground floor 5.0 sqft (E1) (United States Only)**Grille:** No Grille,**Wrapping Information:** 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, User Defined Rough Opening Clearance, 1/2", 3/8", 3/8", 1/2", Perimeter Length = 188".**Rough Opening:** 33 - 1/2" X 62"

Customer Notes: on same floor as 61.75" units on this elevation

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

200 D W K/Din 2nd 1

Special Pella® Reserve, Traditional, Double Hung, 32.75 X 61, Almond

Qty

1



PK #

2073

Viewed From Exterior

1: Traditional, 32.7561 Double Hung, Equal

Frame Size: 32 3/4 X 61

General Information: Standard, Luxury, Clad, Pine, 5", 3 11/16"

Exterior Color / Finish: Painted, Standard Enduraclad, Almond

Interior Color / Finish: Primed Interior

Sash / Panel: Ogee, Ogee, Standard, No Sash Lugs

Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm

Hardware Options: Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor

Screen: Integrated Rolscreen® Lower Sash Only

Performance Information: U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Meets Typical for ground floor 5.0 sqft (E1) (United States Only)

Grille: No Grille,

Wrapping Information: 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, Pella Recommended Clearance, Perimeter Length = 188".

Rough Opening: 33 - 1/2" X 61 - 3/4"

Custom Product Instructions:

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

205 C W K/Din 2nd 2

Special Pella® Reserve, Traditional, Double Hung, 30.625 X 49.25, Almond**Qty**

1



PK #

2073

Viewed From Exterior

1: Traditional, 30.62549.25 Double Hung, Equal**Frame Size:** 30 5/8 X 49 1/4**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, User Defined Rough Opening Clearance, 7/16", 5/16", 5/16", 7/16", Perimeter Length = 160".**Rough Opening:** 31 - 1/4" X 50 - 1/8"

Customer Notes: this opening 1/4" narrower than 1st floor below it

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

210 B W LR 2nd 3



PK #

2073

Viewed From Exterior

Special Pella® Reserve, Traditional, 3-Wide Double Hung, 76.375 X 61, Almond**Qty**

1

1: Traditional, Non-Standard Size Double Hung, Equal**Frame Size:** 21 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal****Frame Size:** 28 3/8 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 2:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**3: Traditional, Non-Standard Size Double Hung, Equal****Frame Size:** 21 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, User Defined Rough Opening Clearance, 3/8", 7/16", 7/16", 3/8", Perimeter Length = 275".**Rough Opening:** 77 - 1/4" X 61 - 3/4"


Customer Notes: **REVISED size to 3-wide unequal 10/30/20**

this opening is 1/4" wider than opening below it

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

10/29/20: New size flankers & center unit - - PLEASE RUSH REPRICING GLASS FOR NEW SIZES!!! Thanks,
Nancy

Line #	Location:	Attributes	
215	A W Stair 2nd 4	Special Support Product, Direct Set Fixed Frame, 68.25 X 61, Almond	<u>Qty</u> 1
		 <p>PK # 2073</p> <p>Viewed From Exterior</p> <p>1: 68.2561 Fixed Frame Frame Size: 68 1/4 X 61 General Information: Interior Glazed, Factory Assembled, Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Almond Interior Color / Finish: Primed Interior Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.28, SHGC 0.32, VLT 0.60, CPD PEL-N-18-02827-00001, Performance Class CW, PG 60, Calculated Positive DP Rating 60, Calculated Negative DP Rating 60, Year Rated 08 11 Grille: No Grille, Wrapping Information: 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, Pella Recommended Clearance, Perimeter Length = 259".</p>	

Rough Opening: 69" X 61.75"

Customer Notes: REV to FIXED DH, tempered - - so unit has a sash profile, same as other units (prior Support was frame, glass & glass stops only - - no sash) - - will cover higher cost of sash set fixed unit

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

220 B W LR 2nd 5

PK #
2073

Viewed From Exterior

Special Pella® Reserve, Traditional, 3-Wide Double Hung, 76.125 X 61, AlmondQty

1

1: Traditional, Non-Standard SizeNon-Standard Size Double Hung, Equal**Frame Size:** 21 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, Non-Standard SizeNon-Standard Size Double Hung, Equal****Frame Size:** 28 1/8 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 2:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**3: Traditional, Non-Standard SizeNon-Standard Size Double Hung, Equal****Frame Size:** 21 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, User Defined Rough Opening Clearance, 3/8", 5/16", 5/16", 3/8", Perimeter Length = 275".**Rough Opening:** 76 - 3/4" X 61 - 3/4"


Customer Notes: **REVISED size to 3-wide unequal 10/30/20**

this opening 1/4" narrower than unit below & above it

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

10/29/20: New size flankers & center unit - - PLEASE RUSH REPRICING GLASS FOR NEW SIZE!!! Thanks, Nancy

Line #	Location:	Attributes	
225	C W K/Din 2nd 6	Special Pella® Reserve, Traditional, Double Hung, 30.625 X 49.25, Almond	<u>Qty</u> 1
	 <p>PK # 2073</p> <p>Viewed From Exterior</p>	<p>1: Traditional, 30.62549.25 Double Hung, Equal Frame Size: 30 5/8 X 49 1/4 General Information: Standard, Luxury, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Almond Interior Color / Finish: Primed Interior Sash / Panel: Ogee, Ogee, Standard, No Sash Lugs Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm Hardware Options: Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor Screen: Integrated Rolscreen® Lower Sash Only Performance Information: U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08 11, Egress Does not meet typical United States egress, but may comply with local code requirements Grille: No Grille, Wrapping Information: 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, User Defined Rough Opening Clearance, 3/8", 7/16", 7/16", 3/8", Perimeter Length = 160".</p>	

Rough Opening: 31 - 1/2" X 50"


Customer Notes: this opening 1/4" wider than opening above it

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

230 D W K/Din 2nd 7

PK #
2073

Viewed From Exterior

Special Pella® Reserve, Traditional, Double Hung, 32.75 X 61, AlmondQty

1

1: Traditional, 32.7561 Double Hung, Equal**Frame Size:** 32 3/4 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Meets Typical for ground floor 5.0 sqft (E1) (United States Only)**Grille:** No Grille,**Wrapping Information:** 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, Pella Recommended Clearance, Perimeter Length = 188".**Rough Opening:** 33 - 1/2" X 61 - 3/4"

Custom Product Instructions:

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

300 D W K/Din 3rd 1

Special Pella® Reserve, Traditional, Double Hung, 32.75 X 61, AlmondQty

1



PK #

2073

Viewed From Exterior

1: Traditional, 32.7561 Double Hung, Equal**Frame Size:** 32 3/4 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Meets Typical for ground floor 5.0 sqft (E1) (United States Only)**Grille:** No Grille,**Wrapping Information:** 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, User Defined Rough Opening Clearance, 5/8", 3/8", 3/8", 5/8", Perimeter Length = 188".**Rough Opening:** 33 - 1/2" X 62 - 1/4"

Customer Notes: on same floor as 61.75" units on this elevation

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

305 C W K/Din 3rd 2

Special Pella® Reserve, Traditional, Double Hung, 30.625 X 49.25, AlmondQty

1

PK #
2073

Viewed From Exterior

1: Traditional, 30.62549.25 Double Hung, Equal**Frame Size:** 30 5/8 X 49 1/4**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, User Defined Rough Opening Clearance, 3/8", 7/16", 7/16", 3/8", Perimeter Length = 160".**Rough Opening:** 31 - 1/2" X 50"

Customer Notes: this opening 1/4" wider than opening above it

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

310 B W LR 3rd 3

PK #
2073

Viewed From Exterior

Special Pella® Reserve, Traditional, 3-Wide Double Hung, 76.375 X 61, AlmondQty

1

1: Traditional, Non-Standard Size Double Hung, Equal**Frame Size:** 21 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal****Frame Size:** 28 3/8 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 2:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**3: Traditional, Non-Standard Size Double Hung, Equal****Frame Size:** 21 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, User Defined Rough Opening Clearance, 3/8", 7/16", 7/16", 3/8", Perimeter Length = 275".**Rough Opening:** 77 - 1/4" X 61 - 3/4"Customer Notes: **REVISED size to 3-wide unequal 10/30/20**

Custom Product Instructions:

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

10/29/20: New size flankers & center unit - - PLEASE RUSH REPRICING GLASS FOR NEW SIZES!!! Thanks,
Nancy

Line #	Location:	Attributes
--------	-----------	------------

315 B W LR 3rd 4

PK #
2073

Viewed From Exterior

Special Pella® Reserve, Traditional, 3-Wide Double Hung, 76.125 X 61, AlmondQty

1

1: Traditional, Non-Standard Size Double Hung, Equal**Frame Size:** 21 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal****Frame Size:** 28 1/8 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 2:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**3: Traditional, Non-Standard Size Double Hung, Equal****Frame Size:** 21 X 61**General Information:** Standard, Luxury, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Almond**Interior Color / Finish:** Primed Interior**Sash / Panel:** Ogee, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm**Hardware Options:** Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Integrated Rolscreen® Lower Sash Only**Performance Information:** U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, User Defined Rough Opening Clearance, 1/2", 7/16", 7/16", 1/2", Perimeter Length = 275".**Rough Opening:** 77" X 62"


Customer Notes: **REVISED size to 3-wide unequal 10/30/20**

this opening 1/4" wider than unit below it & 1/4" taller that B unit to it's left

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

10/29/20: New size flankers & center unit - - PLEASE RUSH REPRICING GLASS FOR NEW SIZES!!! Thanks,
Nancy

Line #	Location:	Attributes	
320	C W Hall 3rd 5	Special Pella® Reserve, Traditional, Double Hung, 30.625 X 49.25, Almond	<u>Qty</u> 1
		 <p>Viewed From Exterior</p> <p>PK # 2073</p> <p>1: Traditional, 30.625X49.25 Double Hung, Equal Frame Size: 30 5/8 X 49 1/4 General Information: Standard, Luxury, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Almond Interior Color / Finish: Primed Interior Sash / Panel: Ogee, Ogee, Standard, No Sash Lugs Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm Hardware Options: Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor Screen: Integrated Rolscreen® Lower Sash Only Performance Information: U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08 11, Egress Does not meet typical United States egress, but may comply with local code requirements Grille: No Grille, Wrapping Information: 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, User Defined Rough Opening Clearance, 7/16", 5/16", 5/16", 7/16", Perimeter Length = 160".</p>	

Rough Opening: 31 - 1/4" X 50 - 1/8"

Customer Notes: this opening 1/4" narrower than those below it

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

325 D W K/Din 3rd 6

Special Pella® Reserve, Traditional, Double Hung, 32.75 X 61, Almond



PK #
2073

Viewed From Exterior

Qty
1

1: Traditional, 32.7561 Double Hung, Equal

Frame Size: 32 3/4 X 61

General Information: Standard, Luxury, Clad, Pine, 5", 3 11/16"

Exterior Color / Finish: Painted, Standard Enduraclad, Almond

Interior Color / Finish: Primed Interior

Sash / Panel: Ogee, Ogee, Standard, No Sash Lugs

Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Upgrade To 3mm

Hardware Options: Cam-Action Lock, White, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor

Screen: Integrated Rolscreen® Lower Sash Only

Performance Information: U-Factor 0.29, SHGC 0.28, VLT 0.52, CPD PEL-N-232-00257-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, Year Rated 08|11, Egress Meets Typical for ground floor 5.0 sqft (E1) (United States Only)

Grille: No Grille,

Wrapping Information: 6" Installation Clips, Branch Supplied, No Exterior Trim, 3 11/16", 5", Factory Applied, User Defined Rough Opening Clearance, 1/2", 3/8", 3/8", 1/2", Perimeter Length = 188".

Rough Opening: 33 - 1/2" X 62"

Customer Notes: on same floor as 61.75" units on this elevation

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Quote with Cardinal Low E 272 / clear glass

Line #	Location:	Attributes
--------	-----------	------------

330

ALLOWAETM100006 - Sales Size

Qty
1

Customer Notes: Sales Error on Size: RTN of 189TDRC10 in its entirety, with full credit to customer

Thank You For Purchasing Pella® Products

PELLA WARRANTY:

Pella products are covered by Pella's limited warranties in effect at the time of sale. All applicable product warranties are incorporated into and become a part of this contract. Please see the warranties for complete details, taking special note of the two important notice sections regarding installation of Pella products and proper management of moisture within the wall system. Neither Pella Corporation nor the Seller will be bound by any other warranty unless specifically set out in this contract. However, Pella Corporation will not be liable for branch warranties which create obligations in addition to or obligations which are inconsistent with Pella written warranties.

Clear opening (egress) information does not take into consideration the addition of a Rolscreen [or any other accessory] to the product. You should consult your local building code to ensure your Pella products meet local egress requirements.

Per the manufacturer's limited warranty, unfinished mahogany exterior windows and doors must be finished upon receipt prior to installing and refinished annually, thereafter. Variations in wood grain, color, texture or natural characteristics are not covered under the limited warranty.

INSYNCTIVE PRODUCTS: In addition, Pella Insynctive Products are covered by the Pella Insynctive Products Software License Agreement and Pella Insynctive Products Privacy Policy in effect at the time of sale, which can be found at [Insynctive.pella.com](https://www.pella.com). By installing or using Your Insynctive Products you are acknowledging the Insynctive Software Agreement and Privacy Policy are part of the terms of sale.

Notice of Collection of Personal Information: We may collect your personal information when you interact with us. Under the California Consumer Privacy Act (CCPA), California residents have specific rights to request this information, request to delete this information, and opt out of the sharing or sale of this information to third parties. To learn more about our collection practices and your rights under the CCPA please visit our link <https://www.pella.com/california-rights-policy/> at [pella.com](https://www.pella.com).

ARBITRATION AND CLASS ACTION WAIVER ("ARBITRATION AGREEMENT")

YOU and Pella and its subsidiaries and the Pella Branded Distributor AGREE TO ARBITRATE DISPUTES ARISING OUT OF OR RELATING TO YOUR PELLA PRODUCTS (INCLUDES PELLA GOODS AND PELLA SERVICES) AND WAIVE THE RIGHT TO HAVE A COURT OR JURY DECIDE DISPUTES. YOU WAIVE ALL RIGHTS TO PROCEED AS A MEMBER OR REPRESENTATIVE OF A CLASS ACTION, INCLUDING CLASS ARBITRATION, REGARDING DISPUTES ARISING OUT OF OR RELATING TO YOUR PELLA PRODUCTS. You may opt out of this Arbitration Agreement by providing notice to Pella no later than ninety (90) calendar days from the date You purchased or otherwise took ownership of Your Pella Goods. To opt out, You must send notice by e-mail to pellawebsupport@pella.com, with the subject line: "Arbitration Opt Out" or by calling (877) 473-5527. Opting out of the Arbitration Agreement will not affect the coverage provided by any applicable limited warranty pertaining to Your Pella Products. For complete information, including the full terms and conditions of this Arbitration Agreement, which are incorporated herein by reference, please visit www.pella.com/arbitration or e-mail to pellawebsupport@pella.com, with the subject line: "Arbitration Details" or call (877) 473-5527. D'ARBITRAGE ET RENONCIATION AU RECOURS COLLECTIF ("convention d'arbitrage") EN FRANÇAIS SEE PELLA.COM/ARBITRATION. DE ARBITRAJE Y RENUNCIA COLECTIVA ("acuerdo de arbitraje") EN ESPAÑOL VER PELLA.COM/ARBITRATION.

Seller shall not be held liable for failure or delay in the performance of its obligations under this Agreement, if such performance is hindered or delayed by the occurrence of an act or event beyond the Seller's reasonable control (force majeure event), including but not limited to earthquakes, unusually severe weather and other Acts of God, fire, strikes and labor unrest, epidemics, riots, war, civil unrest, and government interventions. Seller shall give timely notice of a force majeure event and take such reasonable action to mitigate the impacts of such an event.

Product Performance Information:

U-Factor, Solar Heat Gain Coefficient (SHGC), and Visible Light Transmittance (VLT) are certified by the National Fenestration Rating Council (NFRC).

For more information regarding the finishing, maintenance, service and warranty of all Pella® products, visit the Pella® website at www.pella.com

Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any products and does not warrant the suitability of any product for any specific use.

Design Pressure (DP), Performance Class, and Performance Grade (PG) are certified by a third party organization, in many cases the Window and Door Manufacturers Association (WDMA). The certification requires the performance of at least one product of the product line to be tested in accordance with the applicable performance standards and verified by an independent party. The certification indicates that the product(s) of the product line passed the applicable tests. The certification does not apply to mulled and/or product combinations unless noted. Actual product results will vary and change over the products life.

For more performance information along with information on Florida Product Approval System (FPAS) Number and Texas Dept. of Insurance (TDI) number go to www.pella.com/performance.

Pella products are covered by Pella's limited warranties in effect at the time of sale. All applicable product warranties are incorporated into and become a part of this contract. Please see the warranties for complete details, taking special note of the two important notice sections regarding installation of Pella products and proper management of moisture within the wall system. Neither Pella Corporation nor PWD, LLC ("Pella Windows and Doors") will be bound by any other warranty unless specifically set out in this contract. However, Pella Corporation will not be liable for branch warranties which create obligations in addition to or obligations which are inconsistent with Pella written warranties.

Clear opening (egress) information does not take into consideration the addition of a Rolscreen [or any other accessory] to the product. You should consult your local building code to ensure your Pella products meet local egress requirements.

Per the manufacturer's limited warranty, unfinished mahogany exterior windows and doors must be finished upon receipt prior to installing and refinished annually, thereafter. Variations in wood grain, color, texture or natural characteristics are not covered under the limited warranty.

GENERAL TERMS AND CONDITIONS: ACCEPTANCE: This order is subject to acceptance by an authorized agent of PWD, LLC. PRICING: All quote pricing is valid for a period of 30 days, at which time an adjustment may be made for product offering changes or transportation costs. CHANGES: Product manufactured or in process of manufacturing in accordance with the specifications, as outlined herein, cannot be returned or cancelled. Additional materials or services will be billed at the price prevailing at the time of order. INSPECTION: Buyer should carefully check material upon delivery and report any claim for product shortages or damages within 3 days. TERMS: Payment required with order unless upon approved credit. Net 30 Days on approved credit. Accounts not paid within terms are subject to finance charge of 1 1/2% per month which is an annual percentage rate of 18%. LIENS: Claim of Lien is automatically filed on delinquent jobs as required by law. Waivers of Lien (partial, full or conditional) are furnished upon request after payment. PERFORMANCE: Seller shall not be liable for any consequences of delay regardless of cause. INSTALLATION: Products purchased from and installed by seller under the "Retail" program are covered by a two-year limited installation warranty. With the exception of the "Retail" program, seller shall not be liable to buyer for any damages or problems resulting from installation of Pella products. In the event that buyer has been referred to an independent contractor, including a Certified Pella Contractor, buyer assumes full responsibility for all installation matters, including the selection of the contractor. WARRANTY: Pella products are covered by Pella's limited warranties in effect at the time of sale. All applicable product warranties are incorporated into and become a part of this contract. Please see the warranties for complete details. Neither Pella Corporation nor PWD, LLC will be bound by any other warranty.

See shops 206374.28, page 3 amendment to shops dated 10/07/20, Masonry Opening schedule dated 10/30/20, showing all clearances between frame and MO as well as above detailed information to confirm all sizing and attributes. New shops will not be generated, per customer.

Order Checklist

PWD, LLC

Our #1 Priority is Your Satisfaction!

Pella products are made to your specifications, carefully review the details of this contract as we have a NO Return Policy.

Initial below ALL items that have been verified

_____ Brand: _____	_____ Brand: _____
_____ Brand: _____	_____ Brand: _____
_____ Exterior Color: _____	_____ Grilles: (Exterior/Interior) _____
_____ Interior Stain/Finish: _____	_____ Glazing/Glass: _____
_____ Blinds/Shades: _____	_____ Wall Condition: _____

Check below ALL items that have been verified/reviewed

Other Product Attributes:

[] Reviewed Sizes on Contract _____ [] Window Hardware Color _____

For more information regarding the finishing, maintenance, service and warranty of all Pella® products, visit the Pella® website at www.pella.com

- Window Screens _____ Door Hardware/Key Cylinder _____
- Door Screens _____ Trim/Casing/Mull Covers _____
- Hinging/Sliding (exterior) _____ Tape/Foam/Caulk/Coil/Etc _____
- Handing (exterior) _____ Line Items Initialed _____

Other Items Special to this order:

- Item #1 _____ Item #3 _____
- Item #2 _____ Item #4 _____

Other Information:

- Customer Satisfaction! _____ Product Warranty Reviewed _____
- No Return Policy _____ I Have Received Interior Finish Disclaimer _____
- Delivery Date & Special Instructions _____ Sales & Service Contact Information Reviewed _____
- Delivery Confirmation Process & Expectations Reviewed _____ Service Contact Information #866-647-0570 _____
- Delivery Cancellation Fee \$150 if order rejected at job site _____ Accessory Hold Items Reviewed & Date Set _____
- Reschedule Fee \$75 if Cancelled within 24 hours of Scheduled Delivery _____ Other _____

I hereby authorize Pella Corporation, its affiliates and/or subsidiaries to use, reproduce, and/or publish photographs and/or video that may pertain to me and my project, including materials described below, without compensation. I understand that this material may be used in various communications (e.g. Website, e-newsletters, promotional materials, etc).


Consequently, the Corporation may publish materials, photographs, and/or make reference to the project in a manner that the Corporation or project sponsor deems appropriate.

Comments: _____

Thank You!!!

Marques King

Customer Name (Please print)



Customer Signature


Novemeber 6, 2020

Date

Credit Card Approval Signature

Nancy L Zagone

Pella Sales Rep Name (Please print)



Pella Sales Rep Signature

October 30, 2020

Date

Order Totals

Taxable Subtotal	\$0.00
Sales Tax @ 6%	\$0.00
Non-taxable Subtotal	\$0.00
Total	\$0.00
Deposit Received	\$0.00
Amount Due	\$0.00

Please print, sign & date above, to indicate you have read all notes and supporting documentation provided (referenced on page 39), and agree to have us proceed with this new order as shown. West Construction's original PO3325 dated 5/29/20 remains the contract of record. Net 60 day terms will begin with delivery of Pella order 189TDRC10A delivering to the jobsite.