



Contract - Detailed

Sales Rep Name: Reeves, Dana
Sales Rep Phone: 248-464-8601
Sales Rep Fax: 248-292-5031
Sales Rep E-Mail: reevesdj@pella.com

Customer Information	Project/Delivery Address	Order Information
Jefferson East, Inc 300 River Place Dr Suite 5250 DETROIT, MI 48207 Primary Phone: (313) 331-7939 Mobile Phone: Fax Number: E-Mail: Contact Name: Great Plains #: 1005798574 Customer Number: 1009652146 Customer Account: 1005798574	Marlborough Apartments 1031 Marlborough St 1031 Marlborough St Lot # DETROIT, MI 48215 County: WAYNE Owner Name: Jefferson East, Inc Owner Phone: (313) 331-7939	Quote Name: 1031 Marlborough - ASR - all wood Order Number: 189TDRC13 Quote Number: 12480357 Order Type: Non-Installed Sales Wall Depth: Payment Terms: Net 60 Days Tax Code: EXEMPT Cust Delivery Date: None Quoted Date: 4/8/2020 Contracted Date: Booked Date: Customer PO #:
Accessories Managed / Delivery Date		
Window Screens	4/9/2021	Window Hardware 4/9/2021

Customer Notes: NET PRICE (your cost)

Room Location shown as follows: WindowType Elevation Room-Unit

Frame sizes were calculated based on installer's MO field measurement, then adjusted as follows:

Frame width = MO - 3.125" {BM width of (1.1875" X 2) + 0.75" for clearance/sealant}

Frame hgt. = MO - 3" {(BM width of 1.1875" + subsill hgt. of 1.09375") + 0.75" for clearance/sealant}

Frame size then adjuste up or down (via a small fraction) to allow for alignment vertically on width and horizontally on hgt., while maintaining enough clearance to shim/caulk. As a result, some openings will vary from the factory recommended 3/8" clearance between frame & MO.

Almost all line item numbers have changed (this will cause the squareback brickmould line # listed in approval notes to differ unless changed by PAS). Numbered by floor, starting with right-most South elevation basement unit and counterclockwise by floor from there.

Basement is lines 5 - 98

First Floor is lines 100 - 198

Second Floor is lines 200 - 298

Third Floor is lines 300 - 398

Custom Brickmould for squarebacks is lines s 400 - 498

** As you go around the building, each vertical column of windows has the same last two digits for the line item number. **

No screens priced for squarebacks and the two rectangular units beneath the squareback on the south elevation. Screens for these can be ordered at a later date.

DISREGARD ALL PERFORMANCE DATA ON EACH LINE ITEM. AS SPECIAL UNITS, ALL WINDOWS ON THIS CONTRACT HAVE NO HALLMARK CERTIFICATION, DISREGARD ALL LINE ITEM NOTES THAT STATE PRICING IN INCOMPLETE. PRICE IS COMPLETE. UNITS WILL BE RESUBMITTED FOR FINAL DRAWINGS, NOW THAT ALL SIZE/ATTRIBUTES ARE FINAL. SQUAREBACK UNITS WILL NOT GO INTO PRODUCTION UNTIL TEMPLATES ARE DRAWN AN APPROVED.

MK (INITIAL HERE THAT YOU HAVE READ ALL ABOVE NOTES, INCLUDING THOSE ON PAGE ONE)

Customer: Jefferson East, Inc

Project Name: Marlborough Apartments 1031 Marlborough St

Order Number: 189TDRC13

Quote Number: 12480357


Line #	Location:	Attributes
--------	-----------	------------

5 T S Ktch-B

Special Architect, Traditional, Double Hung, 28.5 X 46.375

Qty

1



PK #

2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal

Frame Size: 28 1/2 X 46 3/8

General Information: Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"

Exterior Color / Finish: Primed, Primed Wood

Interior Color / Finish: Prefinished White Paint Interior

Sash / Panel: Putty Glaze, Ogee, Standard, No Sash Lugs

Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude

Hardware Options: Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor

Screen: Half Screen, Standard EnduraClad, Poplar White, Standard, InView™

Performance Information: U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements

Grille: No Grille,

Wrapping Information: Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 150".

Rough Opening: 29 - 1/4" X 48 - 1/4"

Customer Notes: MO = 31.5 X 49.5

TEMPERED AT GRADE LEVEL

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass


3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

10 P S Bath-B



Viewed From Exterior

PK #
2066**Special Architect, Traditional, Double Hung, 24.25 X 46.375**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 24 1/4 X 46 3/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 142".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 25" X 48.25"

Customer Notes: MO = 27.25 x 49.5

OBSCURE TEMPERED, AT GRADE LEVEL

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

15 U S BR-B

Special Architect, Traditional, 2-Wide Double Hung, 62 X 46.375Qty

1

PK #
2066

Viewed From Exterior

1: Traditional, 29,546.375 Double Hung, Equal**Frame Size:** 29 1/2 X 46 3/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 29,546.375 Double Hung, Equal****Frame Size:** 29 1/2 X 46 3/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 217".**Rough Opening:** 62 - 3/4" X 48 - 1/4"

Customer Notes: MO = 65.25 X 49.5

TEMPERED, AT GRADE LEVEL

Custom Product Instructions:

Quote with Cardinal Low E 272 / clear glass

3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Revised Mull. Please adjust drawings to account for change.


7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

20 U S BR1-C

Special Architect, Traditional, Double Hung, 34.375 X 46.25**Qty**

2

PK #
2066

Viewed From Exterior

1: Traditional, 34.37546.25 Double Hung, Equal**Frame Size:** 34 3/8 X 46 1/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 162".**Rough Opening:** 35 - 1/8" X 48 - 1/8"

Customer Notes: MO = 37.5 X 49.5, EACH

TEMPERED, AT GRADE LEVEL

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


*** Please note due to design change your half screen has been pulled off. Please order out of unit under the Non-Reserve Arch Series Tree in the Feb 2011- Feb 2017 vintage to ensure a correct fit. ***

Revised Mull. Please adjust drawings to account for change.

7/10/20 & 7/14/20 - revised size & changed sash profile to putty glaze - - revised to primed wood jambliner - - REMOVED OBSCURE GLASS, but keep Cardinal Low E 272 / clear glass - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

25 T S Bth1-C



Viewed From Exterior

PK #
2066**Special Architect, Traditional, Double Hung, 24.25 X 46.125**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 24 1/4 X 46 1/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 141".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 25" X 48"

Customer Notes: MO = 27.5 X 49

OBSCURE TEMPERED, AT GRADE LEVEL

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

30 S S BR2-C

Special Architect, Traditional, Double Hung, 34.375 X 46.125**Qty**

1

PK #
2066

Viewed From Exterior

1: Traditional, 34.375x46.125 Double Hung, Equal**Frame Size:** 34 3/8 X 46 1/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 161".**Rough Opening:** 35 - 1/8" X 48"

Customer Notes: MO = 37.5 X 49

TEMPERED, AT GRADE LEVEL

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

*** Please note due to design change your half screen has been pulled off. Please order out of unit under the Non-Reserve Arch Series Tree in the Feb 2011- Feb 2017 vintage to ensure a correct fit. ***

Revised Mull. Please adjust drawings to account for change.


7/10/20 - revised size & changed sash profile to putty glaze - - revised to primed wood jambliner - NZ 7/16/20 - added Poplar White screen - NZ

Line #	Location:	Attributes
--------	-----------	------------

35 P S Bth2-C

Special Architect, Traditional, Double Hung, 34.375 X 46.125**Qty**

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 34 3/8 X 46 1/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 161".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 35 - 1/8" X 48"

Customer Notes: MO = 37.5 X 49

OBSCURE TEMPERED, AT GRADE LEVEL

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White- NZ

Line #	Location:	Attributes
--------	-----------	------------

40 P S Ktch-C

Special Architect, Traditional, Double Hung, 34.375 X 46.25Qty

1



PK #

2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 34 3/8 X 46 1/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 162".**Rough Opening:** 35 - 1/8" X 48 - 1/8"

Customer Notes: MO = 37.5 X 49

TEMPERED, AT GRADE LEVEL

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 - revised size only - NZ 7/16/20 - revised Poplar Whiteto Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

50 E2 W Din-C

Special Architect, Traditional, Double Hung, 34.375 X 46.25**Qty**

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 34 3/8 X 46 1/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 162".**Rough Opening:** 35 - 1/8" X 48 - 1/8"

Customer Notes: MO = 37.5 X 49.5

TEMPERED, AT GRADE LEVEL

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 & 7/14/20 - revised size and removed LOH - NZ 7/16/20 - revised screen to Poplar White- NZ

Line #	Location:	Attributes
--------	-----------	------------

55 E2 W Liv-C

Special Architect, Traditional, Double Hung, 34.375 X 46.25**Qty**

1



PK #

2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 34 3/8 X 46 1/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 162".**Rough Opening:** 35 - 1/8" X 48 - 1/8"

Customer Notes: MO = 37.5 X 49.5

TEMPERED, AT GRADE LEVEL

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 & 7/14/20- revised size & removed LOH - NZ 7/16/20 - revised screen to Poplar White- NZ

Line #	Location:	Attributes
--------	-----------	------------

91 J N BR1-A

Special Architect, Traditional, Double Hung, 34.375 X 46.5**Qty**

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 34 3/8 X 46 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 162".**Rough Opening:** 35 - 1/8" X 48 - 3/8"

Customer Notes: MO = 37.5 X 50

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 & 7/14/20 - revised size and removed WOCD hdw - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

92 T W Bth1-A

Special Architect, Traditional, Double Hung, 24.5 X 46.5Qty

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 24 1/2 X 46 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 142".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 25 - 1/4" X 48 - 3/8"

Customer Notes: MO = 27.625 X 49.5

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH + TEMPERED - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 & 7/14/20 - revised size & removed LOH - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

93 V W BR2-A

Special Architect, Traditional, Double Hung, 46.375 X 46.5**Qty**

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 46 3/8 X 46 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 186".**Rough Opening:** 47 - 1/8" X 48 - 3/8"

Customer Notes: MO = 49.5 X 49.5 (width revised on 7/17/20 after field check/client agreed via email)

TEMPERED, AT GRADE LEVEL

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z


***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

7/23/20 - revised width only - NZ

Line #	Location:	Attributes
--------	-----------	------------

94 E E Din-A

PK #
2066

Viewed From Exterior

Special Pella® Reserve, Traditional, Double Hung, 38.25 X 50.5Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 1/4 X 50 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** No Screen**Performance Information:** U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00259-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** ILT, No Custom Grille, 7/8", Traditional (3W2H / 0W0H), Putty Glaze, Ogee**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 178".**Rough Opening:** 39" X 52.375"

Customer Notes: MO = 41.25 X 53.625

TEMPERED, AT GRADE LEVEL

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass


3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 & 7/14/20 - revised size & REMOVED OBSCURE glass - - price with Cardinal Low E 272 / clear glass - NZ

Line #	Location:	Attributes
--------	-----------	------------

95 F E Liv-A



Viewed From Exterior

PK #
2066**Special Pella® Reserve, Traditional, Double Hung, 37.5 X 50.5**Qty

2

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 37 1/2 X 50 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** No Screen**Performance Information:** U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00259-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** ILT, No Custom Grille, 7/8", Traditional (3W2H / 0W0H), Putty Glaze, Ogee**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 176".**Rough Opening:** 38 - 1/4" X 52 - 3/8"

Customer Notes: MO = 40.875 X 53.75 & 40.5 x 53.75

TEMPERED, AT GRADE LEVEL

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass


3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 & 7/14/20 - revised size & REMOVED OBSCURE glass - - price with Cardinal Low E 272 / clear glass - NZ

Line #	Location:	Attributes
--------	-----------	------------

97 F E Liv-B

PK #
2066

Viewed From Exterior

Special Pella® Reserve, Traditional, Double Hung, 37.75 X 50.5Qty

2

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 37 3/4 X 50 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** No Screen**Performance Information:** U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00259-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local requirements**Grille:** ILT, No Custom Grille, 7/8", Traditional (3W2H / 0W0H), Putty Glaze, Ogee**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 177".**Rough Opening:** 38 - 1/2" X 52 - 3/8"

Customer Notes: MO = 41.125 X 53.375 & 41.125 x 53.625

TEMPERED, AT GRADE LEVEL

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass


3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 & 7/14/20 - revised size & REMOVED OBSCURE glass - - price with Cardinal Low E 272 / clear glass - NZ

Line #	Location:	Attributes
--------	-----------	------------

98 E E Din-B

PK #
2066

Viewed From Exterior

Special Pella® Reserve, Traditional, Double Hung, 38.5 X 50.5Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 1/2 X 50 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** No Screen**Performance Information:** U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00259-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** ILT, No Custom Grille, 7/8", Traditional (3W2H / 0W0H), Putty Glaze, Ogee**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 178".**Rough Opening:** 39 - 1/4" X 52 - 3/8"

Customer Notes: MO = 41..5 x 53.5

TEMPERED, AT GRADE LEVEL

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass


3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 & 7/14/20 - revised size & REMOVED OBSCURE glass - - price with Cardinal Low E 272 / clear glass - NZ

Line #	Location:	Attributes
--------	-----------	------------

100 A3 S Din-B



Viewed From Exterior

PK #
2066**Special Pella® Reserve, Traditional, Double Hung, 38.625 X 66.75**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 5/8 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** No Screen**Performance Information:** U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00255-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** ILT, No Custom Grille, 7/8", Traditional (3W2H / 0W0H), Putty Glaze, Ogee**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 211".**Rough Opening:** 39 - 3/8" X 68 - 5/8"

Customer Notes: MO = 41.625 X 69.75

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20


3/9/20: reprice w/ Std Ext Half Screen and Top Sash ILT - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 & 7/14/20 - revised size & deleted screen - NZ

Line #	Location:	Attributes
--------	-----------	------------

105 T S Ktch-B



Viewed From Exterior

PK #
2066**Special Architect, Traditional, Double Hung, 28.5 X 46.625**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 28 1/2 X 46 5/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 151".**Rough Opening:** 29 - 1/4" X 48 - 1/2"

Customer Notes: MO = 31.75 X 49.5

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH- 1/15/20

3/9/20: reprice w/ Std Ext Half Screen & NO LOH - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

110 P S Bath-B



Viewed From Exterior

PK #
2066**Special Architect, Traditional, Double Hung, 24.25 X 46.625**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 24 1/4 X 46 5/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 142".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 25" X 48.5"

Customer Notes: MO = 27.375 X 49.625

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20


3/9/20: reprice w/ Std Ext Half Screen & NO LOH - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

115 L S BR-B

PK #
2066

Viewed From Exterior

Special Architect, Traditional, 2-Wide Double Hung, 62 X 66.625Qty

1

1: Traditional, 29,566.625 Double Hung, Equal**Frame Size:** 29 1/2 X 66 5/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 29,566.625 Double Hung, Equal****Frame Size:** 29 1/2 X 66 5/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 258".**Rough Opening:** 62 - 3/4" X 68 - 1/2"

Customer Notes: MO = 65.125 X 69.5

LOH

Custom Product Instructions:

Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z


***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Revised Mull. Please adjust drawings to account for change.

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White 7 changed to LOH - NZ

Line #	Location:	Attributes
--------	-----------	------------

120 L S BR1-C

PK #
2066

Viewed From Exterior

Special Architect, Traditional, 2-Wide Double Hung, 70 X 66.625Qty

1

1: Traditional, 33,566.625 Double Hung, Equal**Frame Size:** 33 1/2 X 66 5/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 33,566.625 Double Hung, Equal****Frame Size:** 33 1/2 X 66 5/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 274".**Rough Opening:** 70 - 3/4" X 68 - 1/2"

Customer Notes: MO = 73 X 69.5

LOH

Custom Product Instructions:

Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, WOCD - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z


***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Revised Mull. Please adjust drawings to account for change.

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White & changed to LOH - NZ

Line #	Location:	Attributes
--------	-----------	------------

125 R S Bth1-C



Viewed From Exterior

PK #
2066**Special Architect, Traditional, Double Hung, 24.25 X 46.875**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 24 1/4 X 46 7/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 143".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 25" X 48.75"

Customer Notes: MO = 27.25 X 50

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH + TEMPERED- 1/15/20


3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

130 Q S BR2-C

PK #
2066

Viewed From Exterior

Special Architect, Traditional, 2-Wide Double Hung, 62 X 66.625Qty

1

1: Traditional, 29,566.625 Double Hung, Equal**Frame Size:** 29 1/2 X 66 5/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 29,566.625 Double Hung, Equal****Frame Size:** 29 1/2 X 66 5/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 258".**Rough Opening:** 62 - 3/4" X 68 - 1/2"

Customer Notes: MO = 65 X 69.625

LOH

Custom Product Instructions:

Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, WOOD
- 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z


***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Revised Mull. Please adjust drawings to account for change.

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White & changed to LOH - NZ

Line #	Location:	Attributes
--------	-----------	------------

135 P S Bth2-C



Viewed From Exterior

PK #
2066**Special Architect, Traditional, Double Hung, 24.25 X 46.875**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 24 1/4 X 46 7/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 143".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 25" X 48.75"

Customer Notes: MO = 27.375 X 50.125

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH + TEMPERED- 1/15/20


3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

140 P S Ktch-C



Viewed From Exterior

PK #
2066**Special Architect, Traditional, Double Hung, 28.25 X 46.875**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 28 1/4 X 46 7/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 151".**Rough Opening:** 29" X 48.75"

Customer Notes: MO = 31.25 X 49.75

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20


3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

145 O S Din-C



Viewed From Exterior

PK #
2066**Special Architect, Traditional, Double Hung, 28.5 X 66.75**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 28 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 191".**Rough Opening:** 29 - 1/4" X 68 - 5/8"

Customer Notes: MO = 31.5 X 69.75

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE. LOH - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

150 A2 W Din-C

Special Architect, Traditional, Double Hung, 28.5 X 66.625Qty

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 28 1/2 X 66 5/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 191".**Rough Opening:** 29 - 1/4" X 68 - 1/2"

Customer Notes: MO = 31.5 X 69.75

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20


3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

155 L W Liv-C

PK #
2066

Viewed From Exterior

Special Architect, Traditional, 2-Wide Double Hung, 70 X 66.625Qty

1

1: Traditional, 33,566.625 Double Hung, Equal**Frame Size:** 33 1/2 X 66 5/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 33,566.625 Double Hung, Equal****Frame Size:** 33 1/2 X 66 5/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 274".**Rough Opening:** 70 - 3/4" X 68 - 1/2"

Customer Notes: MO = 72.875 X 69.75

LOH

Custom Product Instructions:

Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z


***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Revised Mull. Please adjust drawings to account for change.

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

165 L W Liv-D

PK #
2066

Viewed From Exterior

Special Architect, Traditional, 2-Wide Double Hung, 70 X 66.625Qty

1

1: Traditional, 33,566.625 Double Hung, Equal**Frame Size:** 33 1/2 X 66 5/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 33,566.625 Double Hung, Equal****Frame Size:** 33 1/2 X 66 5/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 274".**Rough Opening:** 70 - 3/4" X 68 - 1/2"

Customer Notes: MO = 73.25 X 69.5

LOH

Custom Product Instructions:

Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z


***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Revised Mull. Please adjust drawings to account for change.

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

170 A2 W Din-D



Viewed From Exterior

PK #
2066**Special Architect, Traditional, Double Hung, 38.25 X 66.625**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 1/4 X 66 5/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 210".**Rough Opening:** 39" X 68.5"

Customer Notes: MO = 41.5 X 69.5

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

175 G E BR2-D

Special Architect, Traditional, Double Hung, 38.25 X 66.5Qty

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 1/4 X 66 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 210".**Rough Opening:** 39" X 68.375"

Customer Notes: MO = 41.375 X 69.625

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, WOCD - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White & changed to LOH - NZ

Line #	Location:	Attributes
--------	-----------	------------

180 T E Bth2-D

Special Architect, Traditional, Double Hung, 22.125 X 54.5Qty

1



PK #

2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 22 1/8 X 54 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 154".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 22 - 7/8" X 56 - 3/8"

Customer Notes: MO = 25.125 X 57.5

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20


3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size & removed LOH - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

185 IN BR1-D



PK #

2066

Viewed From Exterior

Special Architect, Traditional, 2-Wide Double Hung, 69.25 X 66.5Qty

1

1: Traditional, 33.12566.5 Double Hung, Equal**Frame Size:** 33 1/8 X 66 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 33.12566.5 Double Hung, Equal****Frame Size:** 33 1/8 X 66 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 272".**Rough Opening:** 70" X 68.375"

Customer Notes: MO = 72.375 X 69.5

LOH

Custom Product Instructions:

Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, WOCD - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z


***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Revised Mull. Please adjust drawings to account for change.

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White & changed to LOH - NZ

Line #	Location:	Attributes
--------	-----------	------------

190 H N Bth1-D



Viewed From Exterior

PK #
2066**Special Architect, Traditional, Double Hung, 24.25 X 46.875**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 24 1/4 X 46 7/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 143".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 25" X 48.75"

Customer Notes: MO = 27.375 X 49.875

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH + TEMPERED - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 - revised size & removed LOH - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

191 G N BR1-A

Special Architect, Traditional, Double Hung, 38.375 X 66.5**Qty**

1

PK #
2066

Viewed From Exterior

1: Traditional, 38.37566.5 Double Hung, Equal**Frame Size:** 38 3/8 X 66 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 210".**Rough Opening:** 39 - 1/8" X 68 - 3/8"

Customer Notes: MO = 41.5 X 69.5

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, WOCD - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 & 7/14/20 - revised size and changed to annealed Cardinal Low E 272 / clear glass - NZ 7/16/20 - revised screen to Poplar White & changed to LOH - NZ

Line #	Location:	Attributes
--------	-----------	------------

192 T W Bth1-A

Special Architect, Traditional, Double Hung, 22.125 X 54.5Qty

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 22 1/8 X 54 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 154".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 22 - 7/8" X 56 - 3/8"

Customer Notes: MO = 25.125 X 57.625

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH + TEMPERED - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 - revised size & removed LOH - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

193 G W BR2-A

Special Architect, Traditional, Double Hung, 38.375 X 66.25**Qty**

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 3/8 X 66 1/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 210".**Rough Opening:** 39 - 1/8" X 68 - 1/8"

Customer Notes: MO = 41.5 X 69

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYL, WOCDE - 1/15/20


3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White & changed to LOH - NZ

Line #	Location:	Attributes
--------	-----------	------------

194 A3 E Din-A



Viewed From Exterior

PK #
2066**Special Pella® Reserve, Traditional, Double Hung, 38.5 X 66.75**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** No Screen**Performance Information:** U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00255-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** ILT, No Custom Grille, 7/8", Traditional (3W2H / 0W0H), Putty Glaze, Ogee**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 211".**Rough Opening:** 39 - 1/4" X 68 - 5/8"

Customer Notes: MO = 41.625 X 69.75

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 & 7/14/20 - revised size & REMOVED OBSCURE TEMP glass - - price with Annealed Cardinal Low E 272 / clear glass - NZ

Line #	Location:	Attributes
--------	-----------	------------

195 B2 E Liv1-A

Special Pella® Reserve, Traditional, Double Hung, 28.375 X 66.75Qty

3



PK #

2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 28 3/8 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** No Screen**Performance Information:** U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00255-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** ILT, No Custom Grille, 7/8", Traditional (3W2H / 0W0H), Putty Glaze, Ogee**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 191".**Rough Opening:** 29 - 1/8" X 68 - 5/8"

Customer Notes: MO = 31.625 / 31.5 / 31.625 X 69.875 / 70 / 70

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 & 7/14/20 - revised size & REMOVED OBSCURE TEMP glass - - price with Annealed Cardinal Low E 272 / clear glass - NZ

Line #	Location:	Attributes
--------	-----------	------------

197 B2 E Liv1-B

Special Pella® Reserve, Traditional, Double Hung, 28.375 X 66.75Qty

3



PK #

2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 28 3/8 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** No Screen**Performance Information:** U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00255-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** ILT, No Custom Grille, 7/8", Traditional (3W2H / 0W0H), Putty Glaze, Ogee**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 191".**Rough Opening:** 29 - 1/8" X 68 - 5/8"

Customer Notes: MO = 31.625 X 69.75 / 69.875 / 69.875

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass


3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 & 7/14/20 - revised size & REMOVED OBSCURE TEMP glass - - price with Annealed Cardinal Low E 272 / clear glass - NZ

Line #	Location:	Attributes
--------	-----------	------------

198 A3 E Din-B



Viewed From Exterior

PK #
2066**Special Pella® Reserve, Traditional, Double Hung, 38.75 X 66.5**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 3/4 X 66 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** No Screen**Performance Information:** U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00255-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** ILT, No Custom Grille, 7/8", Traditional (3W2H / 0W0H), Putty Glaze, Ogee**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 211".**Rough Opening:** 39 - 1/2" X 68 - 3/8"

Customer Notes: MO = 41.875 X 69.875

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass


3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 & 7/14/20 - revised size & REMOVED OBSCURE glass - - price with Cardinal Low E 272 / clear glass - NZ

Line #	Location:	Attributes
--------	-----------	------------

200 A3 S Din-B



Viewed From Exterior

PK #
2066**Special Pella® Reserve, Traditional, Double Hung, 38.625 X 66.5**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 5/8 X 66 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** No Screen**Performance Information:** U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00255-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** ILT, No Custom Grille, 7/8", Traditional (3W2H / 0W0H), Putty Glaze, Ogee**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 211".**Rough Opening:** 39 - 3/8" X 68 - 3/8"

Customer Notes: MO = 42 X 69.375

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20


3/9/20: reprice w/ Std Ext Half Screen and Top Sash ILT - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 & 7/14/20 - revised size & deleted screen - NZ

Line #	Location:	Attributes
--------	-----------	------------

205 T S Ktch-B



Viewed From Exterior

PK #
2066**Special Architect, Traditional, Double Hung, 28.5 X 46.5**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 28 1/2 X 46 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 150".**Rough Opening:** 29 - 1/4" X 48 - 3/8"

Customer Notes: MO = 31,875 X 49,375

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH- 1/15/20


3/9/20: reprice w/ Std Ext Half Screen & NO LOH - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

210 P S Bath-B

PK #
2066

Viewed From Exterior

Special Architect, Traditional, Double Hung, 24.25 X 46.5Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 24 1/4 X 46 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 142".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 25" X 48.375"

Customer Notes: MO = 27.375 X 49.5

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20


3/9/20: reprice w/ Std Ext Half Screen & NO LOH - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

215 L S BR-B

PK #
2066

Viewed From Exterior

Special Architect, Traditional, 2-Wide Double Hung, 62 X 66.5Qty

1

1: Traditional, 29,566.5 Double Hung, Equal**Frame Size:** 29 1/2 X 66 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 29,566.5 Double Hung, Equal****Frame Size:** 29 1/2 X 66 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 257".**Rough Opening:** 62 - 3/4" X 68 - 3/8"

Customer Notes: MO = 65.125 X 69.5

LOH

Custom Product Instructions:

Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z


***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Revised Mull. Please adjust drawings to account for change.

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White & changed to LOH- NZ

Line #	Location:	Attributes
--------	-----------	------------

220 L S BR1-C



PK #

2066

Viewed From Exterior

Special Architect, Traditional, 2-Wide Double Hung, 70 X 66.5Qty

1

1: Traditional, 33,566.5 Double Hung, Equal**Frame Size:** 33 1/2 X 66 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 33,566.5 Double Hung, Equal****Frame Size:** 33 1/2 X 66 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 273".**Rough Opening:** 70 - 3/4" X 68 - 3/8"

Customer Notes: MO = 73.25 X 69.625

LOH

Custom Product Instructions:

Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, WOCD - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Revised Mull. Please adjust drawings to account for change.

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White & changed to LOH- NZ

Line #	Location:	Attributes
--------	-----------	------------

225 R S Bth1-C

Special Architect, Traditional, Double Hung, 24.25 X 46.75Qty

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 24 1/4 X 46 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 142".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 25" X 48.625"

Customer Notes: MO = 27.5 X 50

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH + TEMPERED- 1/15/20


3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

230 Q S BR2-C

PK #
2066

Viewed From Exterior

Special Architect, Traditional, 2-Wide Double Hung, 62 X 66.5Qty

1

1: Traditional, 29,566.5 Double Hung, Equal**Frame Size:** 29 1/2 X 66 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 29,566.5 Double Hung, Equal****Frame Size:** 29 1/2 X 66 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 257".**Rough Opening:** 62 - 3/4" X 68 - 3/8"

Customer Notes: MO = 65.125 X 69.5

LOH

Custom Product Instructions:

Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, WOOD
- 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Revised Mull. Please adjust drawings to account for change.

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White & changed to LOH - NZ

Line #	Location:	Attributes
--------	-----------	------------

235 P S Bth2-C

Special Architect, Traditional, Double Hung, 24.25 X 46.75Qty

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 24 1/4 X 46 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 142".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 25" X 48.625"

Customer Notes: MO = 27.375 X 49.75

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH + TEMPERED- 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

240 P S Ktch-C

Special Architect, Traditional, Double Hung, 28.25 X 46.75Qty

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 28 1/4 X 46 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 150".**Rough Opening:** 29" X 48.625"

Customer Notes: MO = 31.625 X 49.75

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

245 O S Din-C

Special Architect, Traditional, Double Hung, 28.5 X 66.75Qty

1



PK #

2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 28 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 191".**Rough Opening:** 29 - 1/4" X 68 - 5/8"

Customer Notes: MO = 31.5 X 70.125

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE. LOH - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

250 A2 W Din-C

Special Architect, Traditional, Double Hung, 28.5 X 66.75Qty

1



PK #

2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 28 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 191".**Rough Opening:** 29 - 1/4" X 68 - 5/8"

Customer Notes: MO = 31.5 X 69.625

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20


3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

255 L W Liv-C

PK #
2066

Viewed From Exterior

Special Architect, Traditional, 2-Wide Double Hung, 70 X 66.75Qty

1

1: Traditional, 33,566.75 Double Hung, Equal**Frame Size:** 33 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 33,566.75 Double Hung, Equal****Frame Size:** 33 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 274".**Rough Opening:** 70 - 3/4" X 68 - 5/8"

Customer Notes: MO = 73.125 X 69.625

LOH

Custom Product Instructions:

Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z


***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Revised Mull. Please adjust drawings to account for change.

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

260 N W Stair

PK #
2066

Viewed From Exterior

Special Architect, Traditional, Double Hung, 38.25 X 67Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 1/4 X 67**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 211".**Rough Opening:** 39" X 68.875"

Customer Notes: MO = 41.375 X 70

TEMPERED, in stairwell

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE N+ TEMPERED, LOH - 1/15/20


3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

265 L W Liv-D

PK #
2066

Viewed From Exterior

Special Architect, Traditional, 2-Wide Double Hung, 70 X 66.75Qty

1

1: Traditional, 33,566.75 Double Hung, Equal**Frame Size:** 33 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 33,566.75 Double Hung, Equal****Frame Size:** 33 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 274".**Rough Opening:** 70 - 3/4" X 68 - 5/8"

Customer Notes: MO = 73.125 X 69.75

LOH

Custom Product Instructions:

Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Revised Mull. Please adjust drawings to account for change.


7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

270 A2 W Din-D

Special Architect, Traditional, Double Hung, 38.25 X 66.75Qty

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 1/4 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 210".**Rough Opening:** 39" X 68.625"

Customer Notes: MO = 41.5 X 69.875

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

275 G E BR2-D

Special Architect, Traditional, Double Hung, 38.25 X 66.75Qty

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 1/4 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 210".**Rough Opening:** 39" X 68.625"

Customer Notes: MO = 41.375 X 69.75

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, WOCD - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White & changed to LOH - NZ

Line #	Location:	Attributes
--------	-----------	------------

280 T E Bth2-D

Special Architect, Traditional, Double Hung, 22.125 X 54.875Qty

1



PK #

2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 22 1/8 X 54 7/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 154".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 22 - 7/8" X 56 - 3/4"

Customer Notes: MO = 25.125 X 58

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20


3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size & removed LOH - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

285 IN BR1-D

PK #
2066

Viewed From Exterior

Special Architect, Traditional, 2-Wide Double Hung, 69.5 X 66.75Qty

1

1: Traditional, 33,256.75 Double Hung, Equal**Frame Size:** 33 1/4 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 33,256.75 Double Hung, Equal****Frame Size:** 33 1/4 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 273".**Rough Opening:** 70 - 1/4" X 68 - 5/8"

Customer Notes: MO = 72.75 X 70

LOH

Custom Product Instructions:

Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, WOCD - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Revised Mull. Please adjust drawings to account for change.

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White & changed to LOH - NZ

Line #	Location:	Attributes
--------	-----------	------------

290 H N Bth1-D

PK #
2066

Viewed From Exterior

Special Architect, Traditional, Double Hung, 24.25 X 47Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 24 1/4 X 47**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 143".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 25" X 48.875"

Customer Notes: MO = 27.5 X 50

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH + TEMPERED - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size & removed LOH - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

291 G N BR1-A

Special Architect, Traditional, Double Hung, 38.375 X 66.625**Qty**

1



PK #

2066

Viewed From Exterior

1: Traditional, 38.37566.625 Double Hung, Equal**Frame Size:** 38 3/8 X 66 5/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 210".**Rough Opening:** 39 - 1/8" X 68 - 1/2"

Customer Notes: MO = 41.5 X 69.5

LOH

Custom Product Instructions:

Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, WOCD - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 & 7/14/20 - revised size and change to annealed Cardinal Low E 272 / clear glass - NZ 7/16/20 - revised screen to Poplar White & changed to LOH - NZ

Line #	Location:	Attributes
--------	-----------	------------

292 T W Bth1-A

Special Architect, Traditional, Double Hung, 22.125 X 54.75Qty

1



PK #

2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 22 1/8 X 54 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 154".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 22 - 7/8" X 56 - 5/8"

Customer Notes: MO = 25.5 X 59.625

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH + TEMPERED - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 - revised size & removed LOH - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

293 G W BR2-A

Special Architect, Traditional, Double Hung, 38.375 X 66.625Qty

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 3/8 X 66 5/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 210".**Rough Opening:** 39 - 1/8" X 68 - 1/2"

Customer Notes: MO = 41.625 X 69.625

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYL, WOCDE - 1/15/20


3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White & changed to LOH - NZ

Line #	Location:	Attributes
--------	-----------	------------

294 A3 E Din-A



Viewed From Exterior

PK #
2066**Special Pella® Reserve, Traditional, Double Hung, 38.75 X 66.5**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 3/4 X 66 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** No Screen**Performance Information:** U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00255-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local requirements**Grille:** ILT, No Custom Grille, 7/8", Traditional (3W2H / 0W0H), Putty Glaze, Ogee**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 211".**Rough Opening:** 39 - 1/2" X 68 - 3/8"

Customer Notes: MO = 42.25 X 69.625


LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 & 7/14/20 - revised size & REMOVED OBSCURE TEMP glass - - price with Annealed Cardinal Low E 272 / clear glass - NZ

Line #	Location:	Attributes	
295	B2 E Liv1-A	Special Pella® Reserve, Traditional, Double Hung, 28.375 X 66.5	<u>Qty</u> 3
	 <p>Viewed From Exterior</p>	<p>1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal Frame Size: 28 3/8 X 66 1/2 General Information: Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16" Exterior Color / Finish: Primed, Primed Wood Interior Color / Finish: Prefinished White Paint Interior Sash / Panel: Putty Glaze, Ogee, Standard, No Sash Lugs Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Hardware Options: Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor Screen: No Screen Performance Information: U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00255-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08 11, Egress Does not meet typical United States egress, but may comply with local code requirements Grille: ILT, No Custom Grille, 7/8", Traditional (3W2H / 0W0H), Putty Glaze, Ogee Wrapping Information: Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 190".</p>	<p>PK # 2066</p>

Rough Opening: 29 - 1/8" X 68 - 3/8"

Customer Notes: MO = 31.5 / 31.75 / 31.75 X 70 / 69.625 / 69.625

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass


3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 & 7/14/20 - revised size & REMOVED OBSCURE TEMP glass - - price with Annealed Cardinal Low E 272 / clear glass - NZ

Line #	Location:	Attributes
--------	-----------	------------

296 D E Stair



Viewed From Exterior

PK #

2066

Special Pella® Reserve, Traditional, Double Hung, 38.125 X 66.875**Qty**

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 1/8 X 66 7/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** No Screen**Performance Information:** U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00259-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** ILT, No Custom Grille, 7/8", Traditional (3W2H / 0W0H), Putty Glaze, Ogee**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 210".**Rough Opening:** 38 - 7/8" X 68 - 3/4"

Customer Notes: MO = 41.25 X 69.875

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 & 7/14/20 - revised size & REMOVED OBSCURE glass -- price with Tempered Cardinal Low E 272 / clear glass - NZ

Line #	Location:	Attributes
--------	-----------	------------

297 B2 E Liv1-B

Special Pella® Reserve, Traditional, Double Hung, 28.375 X 66.375Qty

3

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 28 3/8 X 66 3/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** No Screen**Performance Information:** U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00255-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** ILT, No Custom Grille, 7/8", Traditional (3W2H / 0W0H), Putty Glaze, Ogee**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 190".**Rough Opening:** 29 - 1/8" X 68 - 1/4"

Customer Notes: MO = 31.375 X 69.75 / 69.25 / 69.25

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass


3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 & 7/14/20 - revised size & REMOVED OBSCURE TEMP glass - - price with Annealed Cardinal Low E 272 / clear glass - NZ

Line #	Location:	Attributes
--------	-----------	------------

298 A3 E Din-B



Viewed From Exterior

PK #
2066**Special Pella® Reserve, Traditional, Double Hung, 38.75 X 66.375**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 3/4 X 66 3/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** No Screen**Performance Information:** U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00255-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local requirements**Grille:** ILT, No Custom Grille, 7/8", Traditional (3W2H / 0W0H), Putty Glaze, Ogee**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 211".**Rough Opening:** 39 - 1/2" X 68 - 1/4"

Customer Notes: MO = 42.125 X 69.375

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

3/9/20: new line/size - price w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 & 7/14/20 - revised size & REMOVED OBSCURE TEMP glass - - price with Annealed Cardinal Low E 272 / clear glass - NZ

Line #	Location:	Attributes
--------	-----------	------------

300 A S Din-B

Special Pella® Reserve, Traditional, Single Hung, 38.5 X 64.5Qty

1



Viewed From Exterior

PK #
2066**1: Traditional, 38.564.5 Single Hung, Custom Split (30.6139)****Frame Size:** 38 1/2 X 64 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Custom, Arch Head Glass, 3.5, Custom Width, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** No Screen**Performance Information:** U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00255-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** ILT, Yes (Arch Services drawing required), 7/8", Custom Process Grille, Putty Glaze, Ogee**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 206".**Rough Opening:** 39 - 1/4" X 66 - 3/8"

Customer Notes: TO BE ORDERED AFTER RECTANGULAR DH'S -- SIZE TO BE CONFIRMED BUT PRICE HELD

Custom Product Instructions: ***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***
 *** PASS Installation Details are recommended for proper unit sizing. ***

Quote with Cardinal Low E 272 / clear glass 3-6-19

Squareback w/blindstop - REVISED SIZE, SCREEN (none), LOCK STYLE, SASH LIFT, LOH, NO JE & JAMB INSERT TYPE 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

4-29-2020

Please adjust brickmould to the standard wood 1-7/8. All brickmould should be consistent throughout and currently we're showing two(2) different types. Please advise if there are any questions or if anything else is needed to complete. Thank you.


7/14/20 - deleted screen NZ

Line #	Location:	Attributes
--------	-----------	------------

305 T S Ktch-B

Special Architect, Traditional, Double Hung, 28.5 X 47.125**Qty**

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 28 1/2 X 47 1/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 152".**Rough Opening:** 29 - 1/4" X 49"

Customer Notes: MO = 31.5 X 50.125

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH- 1/15/20


3/9/20: reprice w/ Std Ext Half Screen & NO LOH - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

310 P S Bath-B



Viewed From Exterior

PK #
2066**Special Architect, Traditional, Double Hung, 24.25 X 47.125**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 24 1/4 X 47 1/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 143".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 25" X 49"

Customer Notes: MO = 27.5 X 50

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20


3/9/20: reprice w/ Std Ext Half Screen & NO LOH - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

315 L S BR-B

PK #
2066

Viewed From Exterior

Special Architect, Traditional, 2-Wide Double Hung, 62 X 66.75Qty

1

1: Traditional, 29,566.75 Double Hung, Equal**Frame Size:** 29 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 29,566.75 Double Hung, Equal****Frame Size:** 29 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 258".**Rough Opening:** 62 - 3/4" X 68 - 5/8"

Customer Notes: MO = 65.125 X 69.625

LOH

Custom Product Instructions:

Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z


***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Revised Mull. Please adjust drawings to account for change.

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White & changed to LOH - NZ

Line #	Location:	Attributes
--------	-----------	------------

320 L S BR1-C

PK #
2066

Viewed From Exterior

Special Architect, Traditional, 2-Wide Double Hung, 70 X 66.75Qty

1

1: Traditional, 33,566.75 Double Hung, Equal**Frame Size:** 33 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 33,566.75 Double Hung, Equal****Frame Size:** 33 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 274".**Rough Opening:** 70 - 3/4" X 68 - 5/8"

Customer Notes: MO = 73.375 X 69.625

LOH

Custom Product Instructions:

Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, WOCD - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Revised Mull. Please adjust drawings to account for change.

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White & changed to LOH - NZ

Line #	Location:	Attributes
--------	-----------	------------

325 R S Bth1-C

Special Architect, Traditional, Double Hung, 24.25 X 46.75**Qty**

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 24 1/4 X 46 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 142".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 25" X 48.625"

Customer Notes: MO = 27.375 X 49.75

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH + TEMPERED- 1/15/20


3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

330 Q S BR2-C

PK #
2066

Viewed From Exterior

Special Architect, Traditional, 2-Wide Double Hung, 62 X 66.75Qty

1

1: Traditional, 29,566.75 Double Hung, Equal**Frame Size:** 29 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 29,566.75 Double Hung, Equal****Frame Size:** 29 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 258".**Rough Opening:** 62 - 3/4" X 68 - 5/8"

Customer Notes: MO = 65.125 X 69.75

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, WOOD
- 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z


***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Revised Mull. Please adjust drawings to account for change.

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White & changed to LOH - NZ

Line #	Location:	Attributes
--------	-----------	------------

335 P S Bth2-C



Viewed From Exterior

PK #
2066**Special Architect, Traditional, Double Hung, 24.25 X 47.125**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 24 1/4 X 47 1/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 143".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 25" X 49"

Customer Notes: MO = 27.5 X 50.25

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH + TEMPERED- 1/15/20


3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

340 P S Ktch-C



Viewed From Exterior

PK #
2066**Special Architect, Traditional, Double Hung, 28.25 X 47.125**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 28 1/4 X 47 1/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 151".**Rough Opening:** 29" X 49"

Customer Notes: MO = 31,375 X 50

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

345 O S Din-C

Special Architect, Traditional, Double Hung, 28.5 X 66.75Qty

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 28 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 191".**Rough Opening:** 29 - 1/4" X 68 - 5/8"

Customer Notes: MO = 31.875 X 69.875

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE. LOH - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

350 A2 W Din-C

Special Architect, Traditional, Double Hung, 28.5 X 66.75Qty

1



PK #

2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 28 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 191".**Rough Opening:** 29 - 1/4" X 68 - 5/8"

Customer Notes: MO = 31.875 X 70.125

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20


3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

355 L W Liv-C

PK #
2066

Viewed From Exterior

Special Architect, Traditional, 2-Wide Double Hung, 70 X 66.75Qty

1

1: Traditional, 33,566.75 Double Hung, Equal**Frame Size:** 33 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 33,566.75 Double Hung, Equal****Frame Size:** 33 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 274".**Rough Opening:** 70 - 3/4" X 68 - 5/8"

Customer Notes: MO = 73.125 X 69.625

LOH

Custom Product Instructions:

Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z


***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Revised Mull. Please adjust drawings to account for change.

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

360 N W Stair



Viewed From Exterior

PK #
2066**Special Architect, Traditional, Double Hung, 38.25 X 67.5**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 1/4 X 67 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Almond, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 212".**Rough Opening:** 39" X 69.375"

Customer Notes: MO = 41.375 X 70.5

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE N+ TEMPERED, LOH - 1/15/20


3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Almond - NZ

Line #	Location:	Attributes
--------	-----------	------------

365 L W Liv-D

PK #
2066

Viewed From Exterior

Special Architect, Traditional, 2-Wide Double Hung, 70 X 66.75Qty

1

1: Traditional, 33,566.75 Double Hung, Equal**Frame Size:** 33 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 33,566.75 Double Hung, Equal****Frame Size:** 33 1/2 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 274".**Rough Opening:** 70 - 3/4" X 68 - 5/8"

Customer Notes: MO = 73.125 X 69.875

LOH

Custom Product Instructions:

Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z


***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Revised Mull. Please adjust drawings to account for change.

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

370 A2 W Din-D



Viewed From Exterior

PK #
2066**Special Architect, Traditional, Double Hung, 38.25 X 66.75**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 1/4 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 210".**Rough Opening:** 39" X 68.625"

Customer Notes: MO = 41.375 X 69.75

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20


3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Almond - NZ

Line #	Location:	Attributes
--------	-----------	------------

375 G E BR2-D



Viewed From Exterior

PK #
2066**Special Architect, Traditional, Double Hung, 38.25 X 66.875**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 1/4 X 66 7/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 211".**Rough Opening:** 39" X 68.75"

Customer Notes: MO = 41.5 X 69.875

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, WOCD - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White & changed to LOH - NZ

Line #	Location:	Attributes
--------	-----------	------------

380 T E Bth2-D

Special Architect, Traditional, Double Hung, 22.125 X 54.875Qty

1



PK #

2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 22 1/8 X 54 7/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 154".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 22 - 7/8" X 56 - 3/4"

Customer Notes: MO = 25.375 X 58

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH - 1/15/20


3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size & removed LOH - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

385 I N BR1-D



PK #

2066

Viewed From Exterior

Special Architect, Traditional, 2-Wide Double Hung, 69.75 X 66.875Qty

1

1: Traditional, 33.37566.875 Double Hung, Equal**Frame Size:** 33 3/8 X 66 7/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, 3" x 4 3/8" Wood, Mull Design Pressure- 20**2: Traditional, 33.37566.875 Double Hung, Equal****Frame Size:** 33 3/8 X 66 7/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 274".**Rough Opening:** 70 - 1/2" X 68 - 3/4"

Customer Notes: MO = 73.125 X 70.125

LOH

Custom Product Instructions:

Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, WOCD - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z


***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

Revised Mull. Please adjust drawings to account for change.

7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White & changed to LOH - NZ

Line #	Location:	Attributes
--------	-----------	------------

390 H N Bth1-D



Viewed From Exterior

PK #
2066**Special Architect, Traditional, Double Hung, 24.5 X 47.125**Qty

1

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 24 1/2 X 47 1/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 144".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 25 - 1/4" X 49"

Customer Notes: MO = 27.5 X 50.125

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH + TEMPERED - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 - revised size & removed LOH - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

391 G N BR1-A

Special Architect, Traditional, Double Hung, 38.375 X 66.75**Qty**

1



PK #

2066

Viewed From Exterior

1: Traditional, 38.37566.75 Double Hung, Equal**Frame Size:** 38 3/8 X 66 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 211".**Rough Opening:** 39 - 1/8" X 68 - 5/8"

Customer Notes: MO = 41.5 X 69.625

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, WOCD - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

7/10/20 - revised size & change to Annealed Cardinal LowE 272/clear glass - NZ 7/16/20 - revised screen to Poplar White & chanded to LOH - NZ

Line #	Location:	Attributes
--------	-----------	------------

392 T W Bth1-A

Special Architect, Traditional, Double Hung, 22.125 X 54.875Qty

1



PK #

2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 22 1/8 X 54 7/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Tempered Obscure Low-E Obscure Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, No Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00257-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 154".**Obscure Glass Style:** Pattern62(Standard)**Rough Opening:** 22 - 7/8" X 56 - 3/4"

Customer Notes: MO = 25.5 X 57.75

TEMPERED OBSCURED

Custom Product Instructions: Quote with Cardinal Low E 272 , OBSCURED & TEMPERED (PER CHANGE ON 4/6/20) - NANCY Z

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYLE, LOH + TEMPERED - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 - revised size & removed LOH - NZ 7/16/20 - revised screen to Poplar White - NZ

Line #	Location:	Attributes
--------	-----------	------------

393 G W BR2-A

Special Architect, Traditional, Double Hung, 38.375 X 66.625Qty

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Double Hung, Equal**Frame Size:** 38 3/8 X 66 5/8**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Standard, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** Half Screen, Standard EnduraClad, Poplar White, Standard, InView™**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.53, CPD PEL-N-234-00253-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** No Grille,**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 210".**Rough Opening:** 39 - 1/8" X 68 - 1/2"

Customer Notes: MO = 41.5 X 69.375

LOH

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass

REVISED SIZE, WALL DEPTH, JAMB INSERT, LOCK STYL, WOCDE - 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

***No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


7/10/20 - revised size only - NZ 7/16/20 - revised screen to Poplar White & changed to LOH - NZ

Line #	Location:	Attributes
--------	-----------	------------

394 A E Din-A

Special Pella® Reserve, Traditional, Single Hung, 38.375 X 64.5Qty

1

PK #
2066

Viewed From Exterior

1: Traditional, Non-Standard Size Non-Standard Size Single Hung, Custom Split (30.6139)**Frame Size:** 38 3/8 X 64 1/2**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Custom, Arch Head Glass, 3.5, Custom Width, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** No Screen**Performance Information:** U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00255-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** ILT, Yes (Arch Services drawing required), 7/8", Custom Process Grille, Putty Glaze, Ogee**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 206".**Rough Opening:** 39 - 1/8" X 66 - 3/8"

Customer Notes: TO BE ORDERED AFTER RECTANGULAR DH'S -- SIZE TO BE CONFIRMED BUT PRICE HELD

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass 3-6-19

Squareback w/blindstop - REVISED SIZE, SCREEN (none), LOCK STYLE, SASH LIFT, LOH, NO JE & JAMB INSERT
TYPE 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

*** No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

*** PASS Installation Details are recommended for proper unit sizing. ***

4-29-2020


Please adjust brickmould to the standard wood 1-7/8. All brickmould should be consistent throughout and currently we're showing two(2) different types. Please advise if there are any questions or if anything else is needed to complete. Thank you.

Line #	Location:	Attributes
--------	-----------	------------

395 B E Liv-A

Special Pella® Reserve, Traditional, Single Hung, 28.25 X 64.75Qty

3

PK #
2066

Viewed From Exterior

1: Traditional, 28.2564.75 Single Hung, Custom Split (30.6139)**Frame Size:** 28 1/4 X 64 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Custom, Arch Head Glass, 3.5, Custom Width, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** No Screen**Performance Information:** U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00255-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** ILT, Yes (Arch Services drawing required), 7/8", Custom Process Grille, Putty Glaze, Ogee**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 186".**Rough Opening:** 29" X 66.625"

Customer Notes: TO BE ORDERED AFTER RECTANGULAR DH'S -- SIZE TO BE CONFIRMED BUT PRICE HELD

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass 3-6-19

Squareback w/blindstop - REVISED SIZE, SCREEN (none), LOCK STYLE, SASH LIFT, LOH, NO JE & JAMB INSERT
TYPE 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

*** No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***


*** PASS Installation Details are recommended for proper unit sizing. ***

4-29-2020

Please adjust brickmould to the standard wood 1-7/8. All brickmould should be consistent throughout and currently we're showing two(2) different types. Please advise if there are any questions or if anything else is needed to complete. Thank you.

Line #	Location:	Attributes
--------	-----------	------------

396 C E Stair



Viewed From Exterior

PK #
2066

Special Pella® Reserve, Traditional, Monumental Hung Simulated Hung, 38.25 X 103.875

Qty

1

1: Traditional, 38.25103.875 Simulated Hung, Custom Split (49.8707)

Frame Size: 38 1/4 X 103 7/8

General Information: Standard, Luxury, Wood, Pine, 5 5/8", 5 7/16"

Exterior Color / Finish: Primed

Interior Color / Finish: Prefinished White Paint Interior

Sash / Panel: Putty Glaze, Ogee, Custom, Arch Head Glass, 3.5, Custom Width, No Sash Lugs

Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude

Hardware Options: Upgraded Balance, Cam-Action Lock, Champagne, No Sash Lift

Performance Information: U-Factor 0.29, SHGC 0.23, VLT 0.43, CPD PEL-N-236-00623-00001, Performance Class CW, PG 30, Calculated Positive DP Rating 30, Calculated Negative DP Rating 30, Year Rated 08|11

Grille: ILT, Yes (Arch Services drawing required), 7/8", Custom Process Grille, Putty Glaze, Ogee

Wrapping Information: Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 5 7/16", 5 5/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 285".

Rough Opening: 39" X 105.75"

Customer Notes: TO BE ORDERED AFTER RECTANGULAR DH'S -- SIZE TO BE CONFIRMED BUT PRICE HELD

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass 3-6-19

Squareback w/blindstop - REVISED SIZE, JAMB INSERT TYPE & LOCK -- MAKE LOWER IG TEMPERED (upper tempered only if required - in stairwell) -- ELIMINATE Simulated Lock -- we are going with Spoon Style on all other units and don't want Cam-Action simulated here! - 1/15/20

*** No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

*** PASS Installation Details are recommended for proper unit sizing. ***


4-29-2020

Please adjust brickmould to the standard wood 1-7/8. All brickmould should be consistent throughout and currently we're showing two(2) different types. Please advise if there are any questions or if anything else is needed to complete. Thank you.

7/10/20 & 7/14/20 - revised to champagne hardware, only if simulated lock is required. Would prefer no simulated lock at all -- need this to have a primed wood jameliner if possible, NOT the primed aluminum one (not sure what is priced) - Tempered symbol is not showing on graphic; can it be added? - NZ

Line #	Location:	Attributes
--------	-----------	------------

397 B E Liv1B



Viewed From Exterior

PK #
2066**Special Pella® Reserve, Traditional, Single Hung, 28.875 X 64.75**Qty

3

1: Traditional, 28.87564.75 Single Hung, Custom Split (30.6139)**Frame Size:** 28 7/8 X 64 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Custom, Arch Head Glass, 3.5, Custom Width, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** No Screen**Performance Information:** U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00255-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** ILT, Yes (Arch Services drawing required), 7/8", Custom Process Grille, Putty Glaze, Ogee**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 188".**Rough Opening:** 29 - 5/8" X 66 - 5/8"

Customer Notes: TO BE ORDERED AFTER RECTANGULAR DH'S -- SIZE TO BE CONFIRMED BUT PRICE HELD

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass 3-6-19

Squareback w/blindstop - REVISED SIZE, SCREEN (none), LOCK STYLE, SASH LIFT, LOH, NO JE & JAMB INSERT
TYPE 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

*** No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

*** PASS Installation Details are recommended for proper unit sizing. ***

4-29-2020


Please adjust brickmould to the standard wood 1-7/8. All brickmould should be consistent throughout and currently we're showing two(2) different types. Please advise if there are any questions or if anything else is needed to complete. Thank you.

Line #	Location:	Attributes
--------	-----------	------------

398 B E Liv2B

Special Pella® Reserve, Traditional, Single Hung, 28.5 X 64.75Qty

1

PK #
2066

Viewed From Exterior

1: Traditional, 28.564.75 Single Hung, Custom Split (30.6139)**Frame Size:** 28 1/2 X 64 3/4**General Information:** Standard, Luxury, Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed, Primed Wood**Interior Color / Finish:** Prefinished White Paint Interior**Sash / Panel:** Putty Glaze, Ogee, Custom, Arch Head Glass, 3.5, Custom Width, No Sash Lugs**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Hardware Options:** Spoon-Style Lock, Champagne, No Window Opening Control Device, Limited Opening Hardware, Order Sash Lift, No Integrated Sensor**Screen:** No Screen**Performance Information:** U-Factor 0.29, SHGC 0.25, VLT 0.47, CPD PEL-N-234-00255-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, Year Rated 08|11, Egress Does not meet typical United States egress, but may comply with local code requirements**Grille:** ILT, Yes (Arch Services drawing required), 7/8", Custom Process Grille, Putty Glaze, Ogee**Wrapping Information:** Wood Brickmould, 1 7/8", Factory Applied, 1 1/8" Wood Subsill, Factory Applied, No Exterior Trim, 4 3/16", 4 3/8", Factory Applied, Pella Recommended Clearance, Perimeter Length = 187".**Rough Opening:** 29 - 1/4" X 66 - 5/8"

Customer Notes: TO BE ORDERED AFTER RECTANGULAR DH'S -- SIZE TO BE CONFIRMED BUT PRICE HELD

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass 3-6-19

Squareback w/blindstop - REVISED SIZE, SCREEN (none), LOCK STYLE, SASH LIFT, LOH, NO JE & JAMB INSERT
TYPE 1/15/20

3/9/20: reprice w/ Std Ext Half Screen - Thanks, Nancy Z

*** No NFRC or Hallmark labels will be supplied for this unit. To print an accurate acknowledgement for this line only, please choose the Proposal-Detailed report with the Exclude Performance box chosen. ***

*** PASS Installation Details are recommended for proper unit sizing. ***

4-29-2020

Please adjust brickmould to the standard wood 1-7/8. All brickmould should be consistent throughout and currently we're showing two(2) different types. Please advise if there are any questions or if anything else is needed to complete. Thank you.

Line #	Location:	Attributes
--------	-----------	------------

400 A S Din-B

Special Wood Brickmould, 38.5 X 64.5Qty

1

PK #
2066**1: Traditional, 38.564.5 Single Hung, Equal****Frame Size:** 38 1/2 X 64 1/2**General Information:** Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed**Wrapping Information:** Attachment Options, Wood Brickmould, 1 7/8", With Rabbet (For Windows), 4 3/8", Factory Applied, Perimeter Length = 206", Glazing Pressure = 75.

Viewed From Exterior

Rough Opening: 39 - 1/4" X 65 - 1/4"

Customer Notes: BRICKMOULD FOR LINE ITEM 300:
TO BE ORDERED AFTER RECTANGULAR DH'S -- SIZE TO BE CONFIRMED BUT PRICE HELD

Custom Product Instructions: *** Line 505 is the set up fee for the Brickmould ***

Quote with Cardinal Low E 272 / clear glass 3-6-19

Squareback w/blindstop - REVISED SIZE, SCREEN (none), LOCK STYLE, SASH LIFT, LOH, NO JE & JAMB INSERT
TYPE 1/15/20

4-29-2020


Please adjust brickmould to the standard wood 1-7/8. All brickmould should be consistent throughout and currently we're showing two(2) different types. Please advise if there are any questions or if anything else is needed to complete. Thank you.

Line #	Location:	Attributes
--------	-----------	------------

494 A E Din-A

Special Wood Brickmould, 38.375 X 64.5Qty

1



PK #

2066

1: Traditional, 38.37564.5 Single Hung, Equal**Frame Size:** 38 3/8 X 64 1/2**General Information:** Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed**Wrapping Information:** Attachment Options, Wood Brickmould, 1 7/8", With Rabbet (For Windows), 4 3/8", Factory Applied, Perimeter Length = 206", Glazing Pressure = 75.

Viewed From Exterior

Rough Opening: 39 - 1/8" X 65 - 1/4"

Customer Notes: BRICKMOULD FOR LINE ITEM 394:
TO BE ORDERED AFTER RECTANGULAR DH'S -- SIZE TO BE CONFIRMED BUT PRICE HELD

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass 3-6-19

Squareback w/blindstop - REVISED SIZE, SCREEN (none), LOCK STYLE, SASH LIFT, LOH, NO JE & JAMB INSERT
TYPE 1/15/20

*** Line 505 is the set up ***

Note: Per engineering, profile is standard
4-29-2020


Please adjust brickmould to the standard wood 1-7/8. All brickmould should be consistent throughout and currently we're showing two(2) different types. Please advise if there are any questions or if anything else is needed to complete. Thank you.

Line #	Location:	Attributes
--------	-----------	------------

495 B E Liv1-A

Special Wood Brickmould, 28.25 X 64.75Qty

3



PK #

2066

1: Traditional, 28.2564.75 Single Hung, Equal**Frame Size:** 28 1/4 X 64 3/4**General Information:** Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed**Wrapping Information:** Attachment Options, Wood Brickmould, 1 7/8", With Rabbet (For Windows), 4 3/8", Factory Applied, Perimeter Length = 186", Glazing Pressure = 100.

Viewed From Exterior

Rough Opening: 29" X 65.5"

Customer Notes: BRICKMOULD FOR LINE ITEM 395:
TO BE ORDERED AFTER RECTANGULAR DH'S -- SIZE TO BE CONFIRMED BUT PRICE HELD

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass 3-6-19

Squareback w/blindstop - REVISED SIZE, SCREEN (none), LOCK STYLE, SASH LIFT, LOH, NO JE & JAMB INSERT
TYPE 1/15/20

*** Line 505 is the set up fee for the Brickmould ***

Note: Per engineering, profile is standard

4-29-2020

Please adjust brickmould to the standard wood 1-7/8. All brickmould should be consistent throughout and currently we're showing two(2) different types. Please advise if there are any questions or if anything else is needed to complete. Thank you.

Line #	Location:	Attributes
--------	-----------	------------

496 C E Stair

Special Wood Brickmould, 38.25 X 103.875Qty

1



PK #

2066

1: Traditional, 38.25103.875 Simulated Hung, Equal**Frame Size:** 38 1/4 X 103 7/8**General Information:** Wood, Pine, 5 5/8", 5 7/16"**Exterior Color / Finish:** Primed**Wrapping Information:** Attachment Options, Wood Brickmould, 1 7/8", With Rabbet (For Windows), Perimeter Length = 285", Glazing Pressure = 205.

Viewed From Exterior

Rough Opening: 39" X 104.625"

Customer Notes: BRICKMOULD FOR LINE ITEM 396:
TO BE ORDERED AFTER RECTANGULAR DH'S -- SIZE TO BE CONFIRMED BUT PRICE HELD

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass 3-6-19

Squareback w/blindstop - REVISED SIZE, JAMB INSERT TYPE & LOCK - - MAKE LOWER IG TEMPERED (upper tempered only if required - in stairwell) - - ELIMINATE Simulated Lock - - we are going with Spoon Style on all other units and don't want Cam-Action simulated here! - 1/15/20

*** Line 505 is the set up fee for the Brickmould ***

Note: Per engineering, profile is standard

4-29-2020


Please adjust brickmould to the standard wood 1-7/8. All brickmould should be consistent throughout and currently we're showing two(2) different types. Please advise if there are any questions or if anything else is needed to complete. Thank you.

Line #	Location:	Attributes
--------	-----------	------------

497 B E Liv1B

Special Wood Brickmould, 28.875 X 64.75Qty

3



PK #

2066

1: Traditional, 28.87564.75 Single Hung, Equal**Frame Size:** 28 7/8 X 64 3/4**General Information:** Wood, Pine, 4 3/8", 4 3/16"**Exterior Color / Finish:** Primed**Wrapping Information:** Attachment Options, Wood Brickmould, 1 7/8", With Rabbet (For Windows), 4 3/8", Factory Applied, Perimeter Length = 188", Glazing Pressure = 100.

Viewed From Exterior

Rough Opening: 29 - 5/8" X 65 - 1/2"

Customer Notes: BRICKMOULD FOR LINE ITEM 397:
TO BE ORDERED AFTER RECTANGULAR DH'S -- SIZE TO BE CONFIRMED BUT PRICE HELD

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass 3-6-19


Squareback w/blindstop - REVISED SIZE, SCREEN (none), LOCK STYLE, SASH LIFT, LOH, NO JE & JAMB INSERT
TYPE 1/15/20

*** Line 505 is the set up fee for the Brickmould ***

Note: Per engineering, profile is standard

4-29-2020

Please adjust brickmould to the standard wood 1-7/8. All brickmould should be consistent throughout and currently we're showing two(2) different types. Please advise if there are any questions or if anything else is needed to complete. Thank you.

Line #	Location:	Attributes		Qty
498	B E Liv2B	Special Wood Brickmould, 28.5 X 64.75		1
		PK # 2066	1: Traditional, 28,564.75 Single Hung, Equal Frame Size: 28 1/2 X 64 3/4 General Information: Wood, Pine, 4 3/8", 4 3/16" Exterior Color / Finish: Primed Wrapping Information: Attachment Options, Wood Brickmould, 1 7/8", With Rabbet (For Windows), 4 3/8", Factory Applied, Perimeter Length = 187", Glazing Pressure = 100.	
	Viewed From Exterior			

Rough Opening: 29 - 1/4" X 65 - 1/2"

Customer Notes: BRICKMOULD FOR LINE ITEM 398:
TO BE ORDERED AFTER RECTANGULAR DH'S -- SIZE TO BE CONFIRMED BUT PRICE HELD

Custom Product Instructions: Quote with Cardinal Low E 272 / clear glass 3-6-19

Squareback w/blindstop - REVISED SIZE, SCREEN (none), LOCK STYLE, SASH LIFT, LOH, NO JE & JAMB INSERT
TYPE 1/15/20

*** Line 505 is the set up fee for the Brickmould ***
 Note: Per engineering, profile is standard
 4-29-2020

Please adjust brickmould to the standard wood 1-7/8. All brickmould should be consistent throughout and currently we're showing two(2) different types. Please advise if there are any questions or if anything else is needed to complete. Thank you.

Line #	Location:	Attributes		Qty
500	C E Stair	0CSMD000 - AS (Model 3, 5, 6) Spoon Lock/Strike, Champagne		1

Customer Notes: Use to replace the cam-action lock that is standard on the monumental simulated hung unit.

Line #	Location:	Attributes	Qty
505	None Assigned	SPSETUPSHEN Custom Setup Charge A	1

Thank You For Purchasing Pella® Products

PELLA WARRANTY:

Pella products are covered by Pella's limited warranties in effect at the time of sale. All applicable product warranties are incorporated into and become a part of this contract. Please see the warranties for complete details, taking special note of the two important notice sections regarding installation of Pella products and proper management of moisture within the wall system. Neither Pella Corporation nor the Seller will be bound by any other warranty unless specifically set out in this contract. However, Pella Corporation will not be liable for branch warranties which create obligations in addition to or obligations which are inconsistent with Pella written warranties.

Clear opening (egress) information does not take into consideration the addition of a Rolscreen [or any other accessory] to the product. You should consult your local building code to ensure your Pella products meet local egress requirements.

Per the manufacturer's limited warranty, unfinished mahogany exterior windows and doors must be finished upon receipt prior to installing and refinished annually, thereafter. Variations in wood grain, color, texture or natural characteristics are not covered under the limited warranty.

INSYNCTIVE PRODUCTS: In addition, Pella Insynctive Products are covered by the Pella Insynctive Products Software License Agreement and Pella Insynctive Products Privacy Policy in effect at the time of sale, which can be found at [Insynctive.pella.com](https://www.pella.com). By installing or using Your Insynctive Products you are acknowledging the Insynctive Software Agreement and Privacy Policy are part of the terms of sale.

Notice of Collection of Personal Information: We may collect your personal information when you interact with us. Under the California Consumer Privacy Act (CCPA), California residents have specific rights to request this information, request to delete this information, and opt out of the sharing or sale of this information to third parties. To learn more about our collection practices and your rights under the CCPA please visit our link <https://www.pella.com/california-rights-policy/> at [pella.com](https://www.pella.com).

ARBITRATION AND CLASS ACTION WAIVER ("ARBITRATION AGREEMENT")

YOU and Pella and its subsidiaries and the Pella Branded Distributor AGREE TO ARBITRATE DISPUTES ARISING OUT OF OR RELATING TO YOUR PELLA PRODUCTS (INCLUDES PELLA GOODS AND PELLA SERVICES) AND WAIVE THE RIGHT TO HAVE A COURT OR JURY DECIDE DISPUTES. YOU WAIVE ALL RIGHTS TO PROCEED AS A MEMBER OR REPRESENTATIVE OF A CLASS ACTION, INCLUDING CLASS ARBITRATION, REGARDING DISPUTES ARISING OUT OF OR RELATING TO YOUR PELLA PRODUCTS. You may opt out of this Arbitration Agreement by providing notice to Pella no later than ninety (90) calendar days from the date You purchased or otherwise took ownership of Your Pella Goods. To opt out, You must send notice by e-mail to pellawebsupport@pella.com, with the subject line: "Arbitration Opt Out" or by calling (877) 473-5527. Opting out of the Arbitration Agreement will not affect the coverage provided by any applicable limited warranty pertaining to Your Pella Products. For complete information, including the full terms and conditions of this Arbitration Agreement, which are incorporated herein by reference, please visit www.pella.com/arbitration or e-mail to pellawebsupport@pella.com, with the subject line: "Arbitration Details" or call (877) 473-5527. D'ARBITRAGE ET RENONCIATION AU RECOURS COLLECTIF ("convention d'arbitrage") EN FRANÇAIS SEE PELLA.COM/ARBITRATION. DE ARBITRAJE Y RENUNCIA COLECTIVA ("acuerdo de arbitraje") EN ESPAÑOL VER PELLA.COM/ARBITRATION.

Seller shall not be held liable for failure or delay in the performance of its obligations under this Agreement, if such performance is hindered or delayed by the occurrence of an act or event beyond the Seller's reasonable control (force majeure event), including but not limited to earthquakes, unusually severe weather and other Acts of God, fire, strikes and labor unrest, epidemics, riots, war, civil unrest, and government interventions. Seller shall give timely notice of a force majeure event and take such reasonable action to mitigate the impacts of such an event.

Product Performance Information:

U-Factor, Solar Heat Gain Coefficient (SHGC), and Visible Light Transmittance (VLT) are certified by the National Fenestration Rating Council (NFRC).

For more information regarding the finishing, maintenance, service and warranty of all Pella® products, visit the Pella® website at www.pella.com

Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any products and does not warrant the suitability of any product for any specific use.

Design Pressure (DP), Performance Class, and Performance Grade (PG) are certified by a third party organization, in many cases the Window and Door Manufacturers Association (WDMA). The certification requires the performance of at least one product of the product line to be tested in accordance with the applicable performance standards and verified by an independent party. The certification indicates that the product(s) of the product line passed the applicable tests. The certification does not apply to mulled and/or product combinations unless noted. Actual product results will vary and change over the products life.

For more performance information along with information on Florida Product Approval System (FPAS) Number and Texas Dept. of Insurance (TDI) number go to www.pella.com/performance.

Pella products are covered by Pella's limited warranties in effect at the time of sale. All applicable product warranties are incorporated into and become a part of this contract. Please see the warranties for complete details, taking special note of the two important notice sections regarding installation of Pella products and proper management of moisture within the wall system. Neither Pella Corporation nor PWD, LLC ("Pella Windows and Doors") will be bound by any other warranty unless specifically set out in this contract. However, Pella Corporation will not be liable for branch warranties which create obligations in addition to or obligations which are inconsistent with Pella written warranties.

Clear opening (egress) information does not take into consideration the addition of a Rolscreen [or any other accessory] to the product. You should consult your local building code to ensure your Pella products meet local egress requirements.

Per the manufacturer's limited warranty, unfinished mahogany exterior windows and doors must be finished upon receipt prior to installing and refinished annually, thereafter. Variations in wood grain, color, texture or natural characteristics are not covered under the limited warranty.

GENERAL TERMS AND CONDITIONS: ACCEPTANCE: This order is subject to acceptance by an authorized agent of PWD, LLC. PRICING: All quote pricing is valid for a period of 30 days, at which time an adjustment may be made for product offering changes or transportation costs. CHANGES: Product manufactured or in process of manufacturing in accordance with the specifications, as outlined herein, cannot be returned or cancelled. Additional materials or services will be billed at the price prevailing at the time of order. INSPECTION: Buyer should carefully check material upon delivery and report any claim for product shortages or damages within 3 days. TERMS: Payment required with order unless upon approved credit. Net 30 Days on approved credit. Accounts not paid within terms are subject to finance charge of 1 1/2% per month which is an annual percentage rate of 18%. LIENS: Claim of Lien is automatically filed on delinquent jobs as required by law. Waivers of Lien (partial, full or conditional) are furnished upon request after payment. PERFORMANCE: Seller shall not be liable for any consequences of delay regardless of cause. INSTALLATION: Products purchased from and installed by seller under the "Retail" program are covered by a two-year limited installation warranty. With the exception of the "Retail" program, seller shall not be liable to buyer for any damages or problems resulting from installation of Pella products. In the event that buyer has been referred to an independent contractor, including a Certified Pella Contractor, buyer assumes full responsibility for all installation matters, including the selection of the contractor. WARRANTY: Pella products are covered by Pella's limited warranties in effect at the time of sale. All applicable product warranties are incorporated into and become a part of this contract. Please see the warranties for complete details. Neither Pella Corporation nor PWD, LLC will be bound by any other warranty.

Order Checklist

PWD, LLC

Our #1 Priority is Your Satisfaction!

Pella products are made to your specifications, carefully review the details of this contract as we have a NO Return Policy.

Initial below ALL items that have been verified

_____ Brand: _____	_____ Brand: _____
_____ Brand: _____	_____ Brand: _____
_____ Exterior Color: _____	_____ Grilles: (Exterior/Interior) _____
_____ Interior Stain/Finish: _____	_____ Glazing/Glass: _____
_____ Blinds/Shades: _____	_____ Wall Condition: _____

Check below ALL items that have been verified/reviewed

Other Product Attributes:

Reviewed Sizes on Contract _____ Window Hardware Color _____

For more information regarding the finishing, maintenance, service and warranty of all Pella® products, visit the Pella® website at www.pella.com

- Window Screens _____ Door Hardware/Key Cylinder _____
- Door Screens _____ Trim/Casing/Mull Covers _____
- Hinging/Sliding (exterior) _____ Tape/Foam/Caulk/Coil/Etc _____
- Handing (exterior) _____ Line Items Initialed _____

Other Items Special to this order:

- Item #1 _____ Item #3 _____
- Item #2 _____ Item #4 _____

Other Information:

- Customer Satisfaction! _____ Product Warranty Reviewed _____
- No Return Policy _____ I Have Received Interior Finish Disclaimer _____
- Delivery Date & Special Instructions _____ Sales & Service Contact Information Reviewed _____
- Delivery Confirmation Process & Expectations Reviewed Service Contact Information #866-647-0570
- Delivery Cancellation Fee \$150 if order rejected at job site Accessory Hold Items Reviewed & Date Set _____
- Reschedule Fee \$75 if Cancelled within 24 hours of Scheduled Delivery Other _____

I hereby authorize Pella Corporation, its affiliates and/or subsidiaries to use, reproduce, and/or publish photographs and/or video that may pertain to me and my project, including materials described below, without compensation. I understand that this material may be used in various communications (e.g. Website, e-newsletters, promotional materials, etc).

Consequently, the Corporation may publish materials, photographs, and/or make reference to the project in a manner that the Corporation or project sponsor deems appropriate.

Comments: _____

Project Checklist has been reviewed shop drawings to be approved replace checklist

X Marques King
 Customer Name (Please print)

X *Marques G. King*
 Customer Signature

X 8/11/2020
 Date

DANA REEVES
 Pella Sales Rep Name (Please print)

[Signature]
 Pella Sales Rep Signature

7/30/2020
 Date

Order Totals	
Taxable Subtotal	\$157,645.00
Sales Tax @ 0%	\$0.00
Non-taxable Subtotal	\$0.00
Total	\$157,645.00
Deposit Received	\$0.00
Amount Due	\$157,645.00

~~Credit Card Approval Signature~~