

MG450 | 21.9L | 450 kW
INDUSTRIAL SPARK-IGNITED GENERATOR SET

EPA Certified Stationary Emergency and Non-Emergency

**GENERATOR
 SCREENED IN AT GROUND LEVEL - EAST SIDE OF BUILDING A**

DEMAND RESPONSE READY

Standby Power Rating

450 kW, 562 kVA, 60 Hz

Demand Response Rating

450 kW, 562 kVA, 60 Hz

Prime Power Rating

360 kW, 450 kVA, 60 Hz




Image used for illustration purposes only



Codes and Standards

Not all codes and standards apply to all configurations. Contact factory for details.

-   UL2200, UL6200, UL1236, UL489
-  CSA C22.2, B149
-   BS5514 and DIN 6271
-  SAE J1349
-  NFPA 37, 70, 99, 110
-  NEC700, 701, 702, 708
-  ISO 3046, 7637, 8528, 9001
-  NEMA ICS10, MG1, 250, ICS6, AB1
-  ANSI C62.41
-  IBC 2009, CBC 2010, IBC 2012, ASCE 7-05, ASCE 7-10, ICC-ES AC-156 (2012)

Powering Ahead

Generac ensures superior quality by designing and manufacturing most of its generator components, such as alternators, enclosures, control systems and communications software. Generac also makes its own spark-ignited engines, and you'll find them on every Generac gaseous-fueled generator. We engineer and manufacture them from the block up — all at our facilities throughout Wisconsin. Applying natural gas and LP-fueled engines to generators requires advanced engineering expertise to ensure reliability, durability and necessary performance. By designing specifically for these dry, hotter-burning fuels, the engines last longer and require less maintenance. Building our own engines also means we control every step of the supply chain and delivery process, so you benefit from single-source responsibility.

Plus, Generac Industrial Power's distribution network provides all parts and service so you don't have to deal with third-party suppliers. It all leads to a positive owner experience and higher confidence level. Generac spark-ignited engines give you more options in commercial and industrial generator applications as well as extended run time from utility-supplied natural gas.

EPA Certified Stationary Emergency and Non-Emergency

STANDARD FEATURES **GENERATOR SCREENED IN AT GROUND LEVEL - EAST SIDE OF BUILDING A** **DEMAND RESPONSE READY**

ENGINE SYSTEM

- Oil Drain Extension
- Air Cleaner
- Stainless Steel Flexible Exhaust Connection
- Factory Filled Oil and Coolant
- Radiator Duct Adapter (Open Set Only)
- Critical Silencer

Fuel System

- NPT Fuel Connection on Frame
- Primary and Secondary Fuel Shutoff

Cooling System

- Closed Coolant Recovery System
- UV/Ozone Resistant Hoses
- Factory-Installed Radiator
- 50/50 Ethylene Glycol Antifreeze
- Radiator Drain Extension

Electrical System

- Battery Charging Alternator
- Battery Cables
- Battery Tray
- Rubber-Booted Engine Electrical Connections
- Solenoid Activated Starter Motor

ALTERNATOR SYSTEM

- UL2200 GENprotect™
- Class H Insulation Material
- 2/3 Pitch
- Skewed Stator
- Permanent Magnet Excitation
- Sealed Bearing
- Amortisseur Winding
- Full Load Capacity Alternator

GENERATOR SET

- Internal Genset Vibration Isolation
- Separation of Circuits - High/Low Voltage
- Separation of Circuits - Multiple Breakers

- Wrapped Exhaust Piping
- Standard Factory Testing
- 2 Year Limited Warranty (Standby and Demand Response Rated Units)
- 1 Year Limited Warranty (Prime Rated Units)
- Silencer Mounted in the Discharge Hood (Enclosed Units Only)

ENCLOSURE (If Selected)

- Rust-Proof Fasteners with Nylon Washers to Protect Finish
- High Performance Sound-Absorbing Material (Sound Attenuated Enclosures)
- Gasketed Doors
- Upward Facing Discharge Hood (Radiator and Exhaust)
- Stainless Steel Lift Off Door Hinges
- Stainless Steel Lockable Handles
- RhinoCoat™ - Textured Polyester Powder Coat Paint

CONTROL SYSTEM



Power Zone® Pro Sync Controller

Program Functions

- NFPA 110 Level 1 Compliant
- Engine Protective Functions
- Alternator Protective Functions
- Digital Engine Governor Control
- Digital Voltage Regulator
- Multiple Programmable Inputs and Outputs
- Remote Display Capability
- Remote Communication via Modbus® RTU, Modbus TCP/IP, and Ethernet 10/100
- Alarm and Event Logging with Real Time Stamping
- Expandable Analog and Digital Inputs and Outputs

- Remote Wireless Software Update Capable
- Wi-Fi, Bluetooth, BMS and Remote Telemetry
- Built-In Programmable Logic Eliminates the Need for External Controllers Under Most Conditions
- Ethernet Based Communications Between Generators
- Programmable I/O Channel Properties
- Built-In Diagnostics

Protections

- Low Oil Pressure
- Low Coolant Level
- High/Low Coolant Temperature
- Sensor Failure
- Oil Temperature
- Over/Under Speed
- Over/Under Voltage
- Over/Under Frequency
- Over/Under Current
- Over Load
- High/Low Battery Voltage
- Battery Charger Current
- Phase to Phase and Phase to Neutral Short Circuits (I²T Algorithm)

7 Inch Color Touch Screen Display

- Resistive Color Touch Screen
- Sunlight Readable (1400 NITS)
- Easily Identifiable Icons
- Multi-Lingual
- On Screen Editable Parameters
- Key Function Monitoring
- Three Phase Voltage, Amperage, kW, kVA, and kVAR
- Selectable Line to Line or Line to Neutral Measurements
- Frequency
- Engine Speed
- Engine Coolant Temperature
- Engine Oil Pressure
- Engine Oil Temperature
- Battery Voltage
- Hourmeter
- Warning and Alarm Indication
- Diagnostics
- Maintenance Events/Information

PARALLELING CONTROLS

- Auto-Synchronization Process
- Isochronous Load Sharing
- Reverse Power Protection

- Maximum Power Protection
- Electrically Operated, Mechanically Held Paralleling Switch
- Sync Check System
- Independent On-Board Paralleling

- Optional Programmable Logic Full Auto Back-Up Controls (PLS)
- Shunt Trip and Auxiliary Contact

MG450 | 21.9L | 450 kW

INDUSTRIAL SPARK-IGNITED GENERATOR SET

EPA Certified Stationary Emergency and Non-Emergency

CONFIGURABLE OPTIONS

DEMAND RESPONSE READY

ENGINE SYSTEM

- Baseframe Cover/Rodent Guard
- Oil Heater
- Air Filter Restriction Indicator
- Radiator Stone Guard (Open Set Only)
- Level 1 Fan and Belt Guards (Enclosed Units Only)

FUEL SYSTEM

- NPT Flexible Fuel Line

ELECTRICAL SYSTEM

- 10A UL Listed Battery Charger
- Battery Warmer

ALTERNATOR SYSTEM

- Alternator Upsizing
- Anti-Condensation Heater
- Tropical Coating

CIRCUIT BREAKER OPTIONS

- Main Line Circuit Breaker
- Electronic Trip Breakers

ENGINEERED OPTIONS

ENGINE SYSTEM

- Coolant Heater Ball Valves
- Fluid Containment Pans

CONTROL SYSTEM

- Battery Disconnect Switch

GENERATOR SET

- Demand Response Rating
- Extended Factory Testing (3-Phase Only)
- 12 Position Load Center

ENCLOSURE

- Weather Protected Enclosure
- Level 1 Sound Attenuated
- Level 2 Sound Attenuated
- Level 2 Sound Attenuated with Motorized Dampers
- Level 3 Sound Attenuated (Steel Only)
- Steel Enclosure
- Aluminum Enclosure
- Damper Alarm (Motorized Dampers Only)
- Up to 200 MPH Wind Load Rating (Contact Factory for Availability)
- AC/DC Enclosure Lighting Kit
- Enclosure Heaters
- Door Open Alarm Switch

CONTROL SYSTEM

- Oil Temperature Sender with Indication Alarm
- Remote E-Stop (Break Glass-Type, Surface Mount)
- Remote E-Stop (Red Mushroom-Type, Surface Mount)
- Remote E-Stop (Red Mushroom-Type, Flush Mount)
- 10A Engine Run Relay
- Ground Fault Annunciator
- 100 dB Alarm Horn
- 120V GFCI and 240V Outlets

WARRANTY (Standby Gensets Only)

- 2 Year Extended Limited Warranty
- 5 Year Limited Warranty
- 5 Year Extended Limited Warranty
- 7 Year Extended Limited Warranty
- 10 Year Extended Limited Warranty

GENERATOR SET

- Special Testing
- Battery Box

**GENERATOR
SCREENED IN AT GROUND LEVEL - EAST SIDE OF BUILDING A**

MG450 | 21.9L | 450 kW

INDUSTRIAL SPARK-IGNITED GENERATOR SET

EPA Certified Stationary Emergency and Non-Emergency

APPLICATION AND ENGINEERING DATA

DEMAND RESPONSE READY

ENGINE SPECIFICATIONS

General

| | |
|------------------------------------|--------------------------|
| Make | Generac |
| Cylinder # | 12 |
| Type | V12 |
| Displacement - In ³ (L) | 1,336.4 (21.9) |
| Bore - in (mm) | 5.03 (128) |
| Stroke - in (mm) | 5.6 (142) |
| Compression Ratio | 10.0:1 |
| Intake Air Method | Turbocharged/Aftercooled |
| Number of Main Bearings | 7 |
| Connecting Rods | Steel Alloy |
| Cylinder Head | Cast Iron |
| Cylinder Liners | Cast Steel Alloy |
| Ignition | Electronic |
| Piston Type | Cast Aluminum Alloy |
| Crankshaft Type | Steel |
| Lifter Type | Solid |
| Intake Valve Material | High Temp Steel Alloy |
| Exhaust Valve Material | High Temp Steel Alloy |
| Hardened Valve Seats | Proprietary Alloy |

Engine Governing

| | |
|-------------------------------------|------------|
| Governor | Electronic |
| Frequency Regulation (Steady State) | ±0.25% |

Lubrication System

| | |
|-----------------------------|-----------------------------|
| Oil Pump Type | Gear |
| Oil Filter Type | Full-Flow Spin-On Cartridge |
| Crankcase Capacity - qt (L) | 31.7 (30) |

Cooling System

| | |
|------------------------|-----------------------------|
| Cooling System Type | Pressurized Closed Recovery |
| Fan Type | Pusher |
| Fan Speed - RPM | 1,404 |
| Fan Diameter - in (mm) | 44 (1,118) |

Fuel System

| | |
|--|---------------------|
| Fuel Type | Natural Gas |
| Carburetor | Down Draft |
| Secondary Fuel Regulator | Standard |
| Fuel Shut Off Solenoid | Standard |
| Operating Fuel Pressure - in H ₂ O (kPa) | 11 - 14 (2.7 - 3.5) |
| Optional Operating Fuel Pressure - in H ₂ O (kPa) | 7 - 11 (1.7 - 2.7) |

Engine Electrical System

| | |
|----------------------------|------------------------------|
| System Voltage | 24 VDC |
| Battery Charger Alternator | 57 A |
| Battery Size | See Battery Index 0161970SBY |
| Battery Voltage | (2) - 12 VDC |
| Ground Polarity | Negative |

ALTERNATOR SPECIFICATIONS

| | |
|-------------------------------------|---------------|
| Standard Model | K0500124Y23 |
| Poles | 4 |
| Field Type | Revolving |
| Insulation Class - Rotor | H |
| Insulation Class - Stator | H |
| Total Harmonic Distortion | <5% (3-Phase) |
| Telephone Interference Factor (TIF) | <52 |

| | |
|------------------------------------|--------------------------|
| Standard Excitation | Permanent Magnet |
| Bearings | Sealed Ball |
| Coupling | Direct via Flexible Disc |
| Prototype Short Circuit Test | Yes |
| Voltage Regulator Type | Full Digital |
| Number of Sensed Phases | All |
| Regulation Accuracy (Steady State) | ±0.25% |

**GENERATOR
SCREENED IN AT GROUND LEVEL - EAST SIDE OF BUILDING A**

MG450 | 21.9L | 450 kW

INDUSTRIAL SPARK-IGNITED GENERATOR SET

EPA Certified Stationary Emergency and Non-Emergency

OPERATING DATA

DEMAND RESPONSE READY

POWER RATINGS

| | Standby/Demand Response | | Prime | |
|--------------------------------|-------------------------|-----------|----------------|-----------|
| Three-Phase 277/480 VAC @0.8pf | 450 kW/563 kVA | Amps: 677 | 405 kW/506 kVA | Amps: 610 |
| Three-Phase 346/600 VAC @0.8pf | 450 kW/563 kVA | Amps: 542 | 405 kW/506 kVA | Amps: 488 |

MOTOR STARTING CAPABILITIES (skVA)

| skVA vs. Voltage Dip | |
|----------------------|-------|
| 277/480 VAC | 30% |
| K0500124Y23 | 1,020 |
| K0600124Y23 | 1,560 |

FUEL CONSUMPTION RATES*

| Natural Gas – scfh (m³/hr) | | |
|----------------------------|-------------------------|---------------|
| Percent Load | Standby/Demand Response | Prime |
| 25% | 1,800 (51.0) | 1,740 (49.3) |
| 50% | 2,880 (81.6) | 2,640 (74.8) |
| 75% | 3,960 (112.1) | 3,600 (101.9) |
| 100% | 5,040 (142.7) | 4,620 (130.8) |

* Fuel supply installation must accommodate fuel consumption rates at 100% load.

COOLING

| | | Standby/Demand Response | Prime |
|---|---------------------------|-----------------------------|--------------|
| Air Flow (Fan Air Flow Across Radiator) | scfm (m³/min) | 28,004 (793) | 28,004 (793) |
| Coolant Flow | gpm (Lpm) | 211 (799) | 211 (799) |
| Coolant System Capacity | gal (L) | 15.5 (58.7) | 15.5 (58.7) |
| Maximum Operating Ambient Temperature | °F (°C) | 122 (50) | 122 (50) |
| Maximum Operating Ambient Temperature (Before Derate) | | See Bulletin No. 0199270SSD | |
| Maximum Radiator Backpressure | in H ₂ O (kPa) | 0.5 (0.12) | 0.5 (0.12) |

COMBUSTION AIR REQUIREMENTS

| | Standby/Demand Response | Prime |
|-------------------------------------|-------------------------|------------|
| Flow at Rated Power - scfm (m³/min) | 801 (22.7) | 733 (20.8) |

ENGINE

| | | Standby/Demand Response | Prime |
|--------------------------|----------------|-------------------------|-------------|
| Rated Engine Speed | RPM | 1,800 | 1,800 |
| Horsepower at Rated kW** | hp | 656 | 590 |
| Piston Speed | ft/min (m/min) | 1,680 (512) | 1,680 (512) |
| BMEP | psi (kPa) | 216 (1,489) | 194 (1,340) |

EXHAUST

| | | Standby/Demand Response | Prime |
|---|---------------|-------------------------|--------------|
| Exhaust Flow (Rated Output) | scfm (m³/min) | 2,685 (76.0) | 2,385 (67.5) |
| Max. Backpressure (Post Silencer) | inHg (kPa) | 0.75 (2.54) | 0.75 (2.54) |
| Exhaust Temp (Rated Output - Post Silencer) | °F (°C) | 1,350 (732) | 1,297 (703) |

** Refer to "Emissions Data Sheet" for maximum bHP for EPA and SCAQMD permitting purposes.

Deration – Operational characteristics consider maximum ambient conditions. Derate factors may apply under atypical site conditions. Please contact a Generac Power Systems Industrial Dealer for additional details. All performance ratings in accordance with ISO3046, BS5514, ISO8528, and DIN6271 standards.
 Standby - See Bulletin 0187500SSB
 Demand Response - See Bulletin 10000018250
 Prime - See Bulletin 0187510SSB



GENERATOR
SCREENED IN AT GROUND LEVEL - EAST SIDE OF BUILDING A

MG450 | 21.9L | 450 kW
INDUSTRIAL SPARK-IGNITED GENERATOR SET

EPA Certified Stationary Emergency and Non-Emergency



DIMENSIONS AND WEIGHTS*

DEMAND RESPONSE READY





OPEN SET (Includes Exhaust Flex)

| | |
|---------------------|---|
| L x W x H - in (mm) | 154.4 (3,922) x 71.0 (1,803) x 66.5 (1,689) |
| Weight - lbs (kg) | 8,257 - 8,650 (3,745 - 3,923) |





WEATHER PROTECTED ENCLOSURE

| | |
|---------------------|---|
| L x W x H - in (mm) | 207.4 (5,268) x 71.0 (1,803) x 80.0 (2,032) |
| Weight - lbs (kg) | Steel: 10,055 - 10,840 (4,560 - 4,916) Aluminum: 9,357 - 9,753 (4,244 - 4,423) |



LEVEL 1 SOUND ATTENUATED ENCLOSURE

| | |
|---------------------|--|
| L x W x H - in (mm) | 247.5 (6,287) x 71.0 (1,803) x 80.0 (2,032) |
| Weight - lbs (kg) | Steel: 11,155 - 11,847 (5,059 - 5,373) Aluminum: 9,788 - 10,185 (4,439 - 4,619) |



LEVEL 2 SOUND ATTENUATED ENCLOSURE

| | |
|---------------------|--|
| L x W x H - in (mm) | 207.4 (5,268) x 71.0 (1,803) x 114.1 (2,898) |
| Weight - lbs (kg) | Steel: 10,836 - 12,185 (4,914 - 5,526) Aluminum: 8,963 - 10,330 (4,065 - 4,685) |

LEVEL 3 SOUND ATTENUATED ENCLOSURE

| | |
|---------------------|--|
| L x W x H - in (mm) | 232.0 (5,893) x 76.9 (1,953) x 129.2 (3,282) |
| Weight - lbs (kg) | 13,224 - 14,285 (5,997 - 6,478) |

* All measurements are approximate and for estimation purposes only.

YOUR FACTORY RECOGNIZED GENERAC INDUSTRIAL DEALER

GENERATOR
 SCREENED IN AT GROUND LEVEL - EAST SIDE OF BUILDING A

Specification characteristics may change without notice. Please contact a Generac Power Systems Industrial Dealer for detailed installation drawings.

MG250 | 14.2L | 250 kW
INDUSTRIAL SPARK-IGNITED GENERATOR SET

EPA Certified Stationary Emergency and Non-Emergency

GENERATOR
SCREENED IN AT GROUND LEVEL - EAST SIDE OF BUILDING A

DEMAND RESPONSE READY

Standby Power Rating

250 kW, 313 kVA, 60 Hz

Demand Response Rating

250 kW, 313 kVA, 60 Hz

Prime Power Rating

225 kW, 281 kVA, 60 Hz




Image used for illustration purposes only



Codes and Standards

Not all codes and standards apply to all configurations. Contact factory for details.

-   UL2200, UL6200, UL1236, UL489
-  CSA C22.2, B149
-   BS5514 and DIN 6271
-  SAE J1349
-  NFPA 37, 70, 99, 110
-  NEC700, 701, 702, 708
-  ISO 3046, 7637, 8528, 9001
-  NEMA ICS10, MG1, 250, ICS6, AB1
-  ANSI C62.41
-   IBC 2009, CBC 2010, IBC 2012, ASCE 7-05, ASCE 7-10, ICC-ES AC-156 (2012)

Powering Ahead

Generac ensures superior quality by designing and manufacturing most of its generator components, such as alternators, enclosures, control systems and communications software. Generac also makes its own spark-ignited engines, and you'll find them on every Generac gaseous-fueled generator. We engineer and manufacture them from the block up — all at our facilities throughout Wisconsin. Applying natural gas and LP-fueled engines to generators requires advanced engineering expertise to ensure reliability, durability and necessary performance. By designing specifically for these dry, hotter-burning fuels, the engines last longer and require less maintenance. Building our own engines also means we control every step of the supply chain and delivery process, so you benefit from single-source responsibility.

Plus, Generac Industrial Power's distribution network provides all parts and service so you don't have to deal with third-party suppliers. It all leads to a positive owner experience and higher confidence level. Generac spark-ignited engines give you more options in commercial and industrial generator applications as well as extended run time from utility-supplied natural gas.

MG250 | 14.2L | 250 kW

INDUSTRIAL SPARK-IGNITED GENERATOR SET

EPA Certified Stationary Emergency and Non-Emergency

STANDARD FEATURES

GENERATOR
SCREENED IN AT GROUND LEVEL - EAST SIDE OF BUILDING A

DEMAND RESPONSE READY

ENGINE SYSTEM

- Oil Drain Extension
- Air Cleaner
- Fan Guard (Open Set Only)
- Stainless Steel Flexible Exhaust Connection
- Factory Filled Oil and Coolant
- Radiator Duct Adapter (Open Set Only)
- Critical Silencer (Open Set Only)
- Oil Temperature Indication and Alarm

Fuel System

- NPT Fuel Connection on Frame
- Primary and Secondary Fuel Shutoff

Cooling System

- Closed Coolant Recovery System
- UV/Ozone Resistant Hoses
- Factory-Installed Radiator
- 50/50 Ethylene Glycol Antifreeze
- Radiator Drain Extension

Electrical System

- Battery Charging Alternator
- Battery Cables
- Battery Tray
- Rubber-Booted Engine Electrical Connections
- Solenoid Activated Starter Motor

ALTERNATOR SYSTEM

- UL2200 GENprotect™
- Motorized Main Line Circuit Breaker
- Class H Insulation Material
- 2/3 Pitch
- Skewed Stator
- Permanent Magnet Excitation
- Sealed Bearing
- Amortisseur Winding
- Full Load Capacity Alternator

GENERATOR SET

- Internal Genset Vibration Isolation
- Separation of Circuits - High/Low Voltage
- Separation of Circuits - Multiple Breakers
- Wrapped Exhaust Piping
- Standard Factory Testing
- 2 Year Limited Warranty (Standby and Demand Response Rated Units)
- 1 Year Limited Warranty (Prime Rated Units)
- Silencer Mounted in the Discharge Hood (Enclosed Units Only)

ENCLOSURE (If Selected)

- Rust-Proof Fasteners with Nylon Washers to Protect Finish
- High Performance Sound-Absorbing Material (Sound Attenuated Enclosures)
- Gasketed Doors
- Upward Facing Discharge Hood (Radiator and Exhaust)
- Stainless Steel Lift Off Door Hinges
- Stainless Steel Lockable Handles
- RhinoCoat™ - Textured Polyester Powder Coat Paint

CONTROL SYSTEM



Power Zone® Pro Sync Controller

Program Functions

- NFPA 110 Level 1 Compliant
- Engine Protective Functions
- Alternator Protective Functions
- Digital Engine Governor Control
- Digital Voltage Regulator
- Multiple Programmable Inputs and Outputs
- Remote Display Capability
- Remote Communication via Modbus® RTU, Modbus TCP/IP, and Ethernet 10/100
- Alarm and Event Logging with Real Time Stamping
- Expandable Analog and Digital Inputs and Outputs

- Remote Wireless Software Update Capable
- Wi-Fi®, Bluetooth®, BMS and Remote Telemetry
- Built-In Programmable Logic Eliminates the Need for External Controllers Under Most Conditions
- Ethernet Based Communications Between Generators
- Programmable I/O Channel Properties
- Built-In Diagnostics

Protections

- Low Oil Pressure
- Low Coolant Level
- High/Low Coolant Temperature
- Sensor Failure
- Oil Temperature
- Over/Under Speed
- Over/Under Voltage
- Over/Under Frequency
- Over/Under Current
- Over Load
- High/Low Battery Voltage
- Battery Charger Current
- Phase to Phase and Phase to Neutral Short Circuits (I²T Algorithm)

7 Inch Color Touch Screen Display

- Resistive Color Touch Screen
- Sunlight Readable (1400 NITS)
- Easily Identifiable Icons
- Multi-Lingual
- On Screen Editable Parameters
- Key Function Monitoring
- Three Phase Voltage, Amperage, kW, kVA, and kVAh
- Selectable Line to Line or Line to Neutral Measurements
- Frequency
- Engine Speed
- Engine Coolant Temperature
- Engine Oil Pressure
- Engine Oil Temperature
- Battery Voltage
- Hourmeter
- Warning and Alarm Indication
- Diagnostics
- Maintenance Events/Information

PARALLELING CONTROL FEATURES

- Paralleling Control (Synchronizing)
- Reverse Power
- Loss of Synchronization Between Gensets
- Load and VAR Sharing

CONFIGURABLE OPTIONS

DEMAND RESPONSE READY

ENGINE SYSTEM

- Engine Coolant Heater
- Baseframe Cover/Rodent Guard
- 2 Stage Air Cleaner
- Oil Heater
- Air Filter Restriction Indicator
- Radiator Stone Guard (Open Set Only)
- Level 1 Fan and Belt Guards (Enclosed Units Only)

FUEL SYSTEM

- NPT Flexible Fuel Line

ELECTRICAL SYSTEM

- 10A UL Listed Battery Charger
- Battery Warmer

ALTERNATOR SYSTEM

- Alternator Upsizing
- Anti-Condensation Heater
- Tropical Coating

CIRCUIT BREAKER OPTIONS

- Shunt Trip and Auxiliary Contact
- Electronic Trip Breakers

ENGINEERED OPTIONS

ENGINE SYSTEM

- Fluid Containment Pan

ALTERNATOR SYSTEM

- 2nd Breaker System

GENERATOR SET

- Demand Response Rating
- Extended Factory Testing
- 12 Position Load Center
- Vapor Recovery Heater

ENCLOSURE

- Weather Protected Enclosure
- Level 1 Sound Attenuated
- Level 2 Sound Attenuated
- Level 2 Sound Attenuated with Motorized Dampers
- Level 3 Sound Attenuated (Steel Only)
- Steel Enclosure
- Aluminum Enclosure
- Up to 200 MPH Wind Load Rating (Contact Factory for Availability)
- AC/DC Enclosure Lighting Kit
- Enclosure Heaters (with Motorized Dampers Only)
- IBC Certification
- Door Open Alarm Switch

CONTROL SYSTEM

- NFPA 110 Level 1 Compliant 21-Light Remote Annunciator
- Remote Relay Assembly (8 or 16)
- Remote E-Stop (Break Glass-Type, Surface Mount)
- Remote E-Stop (Red Mushroom-Type, Surface Mount)
- Remote E-Stop (Red Mushroom-Type, Flush Mount)
- 10A Engine Run Relay
- Ground Fault Annunciator
- 120V GFCI and 240V Outlets
- Damper Alarm Contacts (with Motorized Dampers Only)
- 100 dB Alarm Horn
- Permissive/Load Shed Module

WARRANTY (Standby Gensets Only)

- 2 Year Extended Limited Warranty
- 5 Year Limited Warranty
- 5 Year Extended Limited Warranty
- 7 Year Extended Limited Warranty
- 10 Year Extended Limited Warranty

GENERATOR
SCREENED IN AT GROUND LEVEL - EAST SIDE OF BUILDING A

CONTROL SYSTEM

- Battery Disconnect Switch

GENERATOR SET

- Special Testing
- Battery Box

MG250 | 14.2L | 250 kW

INDUSTRIAL SPARK-IGNITED GENERATOR SET

EPA Certified Stationary Emergency and Non-Emergency

APPLICATION AND ENGINEERING DATA

DEMAND RESPONSE READY

ENGINE SPECIFICATIONS

General

| | |
|------------------------------------|------------------------------|
| Make | Generac |
| Cylinder # | 6 |
| Type | In-line |
| Displacement - in ³ (L) | 864.71 (14.2) |
| Bore - in (mm) | 5.31 (135) |
| Stroke - in (mm) | 6.50 (165) |
| Compression Ratio | 9.5:1 |
| Intake Air Method | Turbocharged/Aftercooled |
| Number of Main Bearings | 7 |
| Connecting Rods | Steel Alloy |
| Cylinder Head | Cast Iron |
| Cylinder Liners | Ductile Iron |
| Ignition | Electronic |
| Piston Type | Aluminum |
| Crankshaft Type | Ductile Iron |
| Lifter Type | Solid |
| Intake Valve Material | Special Heat-Resistant Steel |
| Exhaust Valve Material | High Temp Steel Alloy |
| Hardened Valve Seats | High Temp Steel Alloy |

Engine Governing

| | |
|-------------------------------------|------------|
| Governor | Electronic |
| Frequency Regulation (Steady State) | ±0.25% |

Lubrication System

| | |
|-----------------------------|---------------------|
| Oil Pump Type | Gear |
| Oil Filter Type | Full-Flow Cartridge |
| Crankcase Capacity - qt (L) | 36.2 (34.3) |

Cooling System

| | |
|------------------------|-----------------------------|
| Cooling System Type | Pressurized Closed Recovery |
| Fan Type | Pusher |
| Fan Speed - RPM | 1,894 |
| Fan Diameter - in (mm) | 30 (762) |

Fuel System

| | |
|---|--------------------|
| Fuel Type | Natural Gas |
| Carburetor | Down Draft |
| Secondary Fuel Regulator | Standard |
| Fuel Shut Off Solenoid | Standard |
| Operating Fuel Pressure - in H ₂ O (kPa) | 7 - 11 (1.7 - 2.7) |

Engine Electrical System

| | |
|----------------------------|------------------------------|
| System Voltage | 24 VDC |
| Battery Charger Alternator | 57.5 A |
| Battery Size | See Battery Index 0161970SBY |
| Battery Voltage | (2) - 12 VDC |
| Ground Polarity | Negative |

ALTERNATOR SPECIFICATIONS

| | |
|-------------------------------------|-------------|
| Standard Model | K0250124Y21 |
| Poles | 4 |
| Field Type | Revolving |
| Insulation Class - Rotor | H |
| Insulation Class - Stator | H |
| Total Harmonic Distortion | <5% |
| Telephone Interference Factor (TIF) | <50 |

| | |
|------------------------------------|--------------------------|
| Standard Excitation | Permanent Magnet |
| Bearings | Single Sealed Ball |
| Coupling | Direct via Flexible Disc |
| Prototype Short Circuit Test | Yes |
| Voltage Regulator Type | Full Digital |
| Number of Sensed Phases | All |
| Regulation Accuracy (Steady State) | ±0.25% |

**GENERATOR
SCREENED IN AT GROUND LEVEL - EAST SIDE OF BUILDING A**

MG250 | 14.2L | 250 kW

INDUSTRIAL SPARK-IGNITED GENERATOR SET

EPA Certified Stationary Emergency and Non-Emergency

OPERATING DATA

DEMAND RESPONSE READY

POWER RATINGS - NATURAL GAS

| | Standby/Demand Response | | Prime | |
|--------------------------------|-------------------------|-----------|----------------|-----------|
| Three-Phase 120/208 VAC @0.8pf | 250 kW/313 kVA | Amps: 868 | 225 kW/281 kVA | Amps: 782 |
| Three-Phase 277/480 VAC @0.8pf | 250 kW/313 kVA | Amps: 376 | 225 kW/281 kVA | Amps: 339 |
| Three-Phase 346/600 VAC @0.8pf | 250 kW/313 kVA | Amps: 301 | 225 kW/281 kVA | Amps: 271 |

MOTOR STARTING CAPABILITIES (skVA)

| skVA vs. Voltage Dip | | | |
|----------------------|-----|-------------|-----|
| 277/480 VAC | 30% | 120/208 VAC | 30% |
| K0250124Y21 | 630 | K0250124Y21 | 506 |
| K0300124Y21 | 790 | K0300124Y21 | 609 |

FUEL CONSUMPTION RATES*

| Natural Gas – scfh (m³/hr) | | |
|----------------------------|-------------------------|--------------|
| Percent Load | Standby/Demand Response | Prime |
| 25% | 1,020 (28.9) | 990 (28.0) |
| 50% | 1,620 (45.9) | 1,260 (35.7) |
| 75% | 2,520 (71.4) | 1,980 (56.1) |
| 100% | 3,180 (90.0) | 2,700 (76.5) |

* Fuel supply installation must accommodate fuel consumption rates at 100% load.

COOLING

| | | Standby/Demand Response | Prime |
|---|---------------------------|-----------------------------|----------------|
| Air Flow (Fan Air Flow Across Radiator) | scfm (m³/min) | 10,078 (285.4) | 10,078 (285.4) |
| Coolant Flow | gpm (Lpm) | 90 (340.7) | 90 (340.7) |
| Coolant System Capacity | gal (L) | 15 (54.9) | 15 (54.9) |
| Maximum Operating Ambient Temperature | °F (°C) | 122 (50) | 122 (50) |
| Maximum Operating Ambient Temperature (Before Derate) | | See Bulletin No. 0199270SSD | |
| Maximum Radiator Backpressure | in H ₂ O (kPa) | 0.5 (0.12) | 0.5 (0.12) |

COMBUSTION AIR REQUIREMENTS

| | Standby/Demand Response | Prime |
|-------------------------------------|-------------------------|------------|
| Flow at Rated Power - scfm (m³/min) | 506 (14.3) | 455 (12.9) |

ENGINE

| | | Standby/Demand Response | Prime |
|--------------------------|----------------|-------------------------|-------------|
| Rated Engine Speed | RPM | 1,800 | 1,800 |
| Horsepower at Rated kW** | hp | 375 | 337 |
| Piston Speed | ft/min (m/min) | 1,950 (594) | 1,950 (594) |
| BMEP | psi (kPa) | 190 (1,313) | 171 (1,182) |

EXHAUST

| | | Standby/Demand Response | Prime |
|---|---------------|-------------------------|-------------|
| Exhaust Flow (Rated Output) | scfm (m³/min) | 1,703 (48) | 1,517 (43) |
| Max. Backpressure (Post Silencer) | inHg (kPa) | 0.75 (2.54) | 0.75 (2.54) |
| Exhaust Temp (Rated Output - Post Silencer) | °F (°C) | 1,357 (736) | 1,340 (727) |

** Refer to "Emissions Data Sheet" for maximum bHP for EPA and SCAQMD permitting purposes.

Deration – Operational characteristics consider maximum ambient conditions. Derate factors may apply under atypical site conditions. Please contact a Generac Power Systems Industrial Dealer for additional details. All performance ratings in accordance with ISO3046, BS5514, ISO8528, and DIN6271 standards.
 Standby - See Bulletin 0187500SSB
 Demand Response - See Bulletin 10000018250
 Prime - See Bulletin 0187510SSB


GENERATOR
SCREENED IN AT GROUND LEVEL - EAST SIDE OF BUILDING A

MG250 | 14.2L | 250 kW
INDUSTRIAL SPARK-IGNITED GENERATOR SET

EPA Certified Stationary Emergency and Non-Emergency


DIMENSIONS AND WEIGHTS*

DEMAND RESPONSE READY




OPEN SET (Includes Exhaust Flex)

| | |
|---------------------|---|
| L x W x H - in (mm) | 136.0 (3,454) x 57.1 (1,450) x 67.9 (1,725) |
| Weight - lbs (kg) | 5,883 - 6,031 (2,668 - 2,735) |




WEATHER PROTECTED ENCLOSURE

| | |
|---------------------|---|
| L x W x H - in (mm) | 174.7 (4,437) x 57.5 (1,461) x 77.8 (1,976) |
| Weight - lbs (kg) | Steel: 7,448 - 7,596 (3,378 - 3,445) Aluminum: 6,654 - 6,801 (3,018 - 3,084) |




LEVEL 1 SOUND ATTENUATED ENCLOSURE

| | |
|---------------------|---|
| L x W x H - in (mm) | 200.2 (5,085) x 57.5 (1,461) x 77.8 (1,976) |
| Weight - lbs (kg) | Steel: 7,911 - 8,059 (3,588 - 3,655) Aluminum: 6,853 - 7,000 (3,108 - 3,175) |



LEVEL 2 SOUND ATTENUATED ENCLOSURE

| | |
|---------------------|---|
| L x W x H - in (mm) | 180.6 (4,587) x 57.5 (1,461) x 111.3 (2,827) |
| Weight - lbs (kg) | Steel: 8,484 - 8,632 (3,848 - 3,915) Aluminum: 7,099 - 7,247 (3,220 - 3,287) |



LEVEL 3 SOUND ATTENUATED ENCLOSURE

| | |
|---------------------|--|
| L x W x H - in (mm) | 207.3 (5,265) x 63.7 (1,618) x 128.9 (3,274) |
| Weight - lbs (kg) | Steel: 10,840 - 10,990 (4,916 - 4,984) |

* All measurements are approximate and for estimation purposes only.

YOUR FACTORY RECOGNIZED GENERAC INDUSTRIAL DEALER



GENERATOR
 SCREENED IN AT GROUND LEVEL - EAST SIDE OF BUILDING A

Specification characteristics may change without notice. Please contact a Generac Power Systems Industrial Dealer for detailed installation drawings.

| REL NO | LTR | NO | REVISION | OWN | CAD | APVD | DATE |
|------------|-----|----|--------------------|-----|-----|-------------|---------|
| ECO-152551 | A | 1 | PRODUCTION RELEASE | CG | NK | M. WICKMANN | 14MAY15 |
| | | | | | | | |




**GENERATOR
SCREENED IN AT GROUND LEVEL - EAST SIDE OF BUILDING A**

- NOTES:
- DIM [] IN INCHES
 - WHEN THE HOUSING INSTALLED ON AN OPEN GENERATOR SET, THE TOTAL WEIGHT WILL INCREASE BY 131.5 KG (290 LBS). THIS INCLUDES THE MUFFLER.
 - THE CENTER OF GRAVITY (CG) OF THE GENERATOR SET WHEN EQUIPPED WITH THIS HOUSING SHIFTS APPROXIMATELY 65mm (2.55 inch) TOWARDS THE AIR DISCHARGE END OF THE HOUSING AND 42MM (1.66 INCH) HIGHER FROM THE GROUND, COMPARED TO THE EQUIVALENT NON-HOUSED PRODUCT WITH THE F179 SKID. SEE HOUSING READY SKID BASE OUTLINE DRAWING FOR CG LOCATION OF NON HOUSED PRODUCT.



DISTANCE REQUIRED TO OPEN DOORS

TOP VIEW



RIGHT SIDE VIEW

OUTLET VIEW

LEFT SIDE VIEW

F231-2 ENCLOSURE CONFIGURATION


| | | | | | | |
|---|------------|-------------------------|-------------------|-------|--------------------------|--------------|
| UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MILLIMETERS | | SIM 10 NONE | OWN C. GADE | | CUMMINS POWER GENERATION | |
| DO NOT SCALE PRINT | | DO NOT SCALE PRINT | CAD N. KASIBHOTLA | | OUTLINE, ENCLOSURE | |
| CH | X ± 1 | 0.00- 4.99 +0.15/-0.08 | APVD M. WICKMANN | | SITE CODE | SHEET 1 OF 2 |
| | .X ± 0.8 | 5.00- 9.99 +0.20/-0.10 | DATE 14MAY15 | | | |
| | .XX ± 0.38 | 10.00-17.49 +0.25/-0.13 | | ARROW | | |
| | | 17.50-24.99 +0.30/-0.13 | | | | |
| ANG TOL: | ± 1.0° | SCALE: ~3/32 | | | | |

| REL NO | LTR | NO | REVISION | DWN | CAD | APVD | DATE |
|------------|-----|----|--------------------|-----|-----|-------------|---------|
| ECO-152551 | A | 1 | PRODUCTION RELEASE | CG | NK | M. WICKMANN | 14MAY15 |
| | | | | | | | |
| | | | | | | | |

GENERATOR
SCREENED IN AT GROUND LEVEL - EAST SIDE OF BUILDING A



AIR INTAKE AREA



3456
 [136.06]

AIR INTAKE AREA

AIR INTAKE AREA

440.1
 [17.33]

F217-2 ENCLOSURE CONFIGURATION

REFER TO PAGE 1 (F231-2 ENCLOSURE FOR OTHER F217-2 ENCLOSURE DIMENSIONS.)

| | | | | | | | | | | | | | |
|--|-------------------------|--|---------------------|------------------------|--------------------------|-------------------------|--|-------------------------|--------------|------------------|-----------|--|--|
| UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MILLIMETERS | | SIM TO NONE | DWN C. GADE | | CUMMINS POWER GENERATION | | | | | | | | |
| DO NOT SCALE PRINT | | | CAD N. KASIBHOTLA | | OUTLINE, ENCLOSURE | | | | | | | | |
| <table border="1"> <tr> <td>X ± 1</td> <td>0.00- 4.99 +0.15/-0.08</td> </tr> <tr> <td>.X ± 0.8</td> <td>5.00- 9.99 +0.20/-0.10</td> </tr> <tr> <td>.XX ± 0.38</td> <td>10.00-17.49 +0.25/-0.13</td> </tr> <tr> <td></td> <td>17.50-24.99 +0.30/-0.13</td> </tr> </table> | X ± 1 | 0.00- 4.99 +0.15/-0.08 | .X ± 0.8 | 5.00- 9.99 +0.20/-0.10 | .XX ± 0.38 | 10.00-17.49 +0.25/-0.13 | | 17.50-24.99 +0.30/-0.13 | DATE 14MAY15 | APVD M. WICKMANN | SITE CODE | | |
| X ± 1 | 0.00- 4.99 +0.15/-0.08 | | | | | | | | | | | | |
| .X ± 0.8 | 5.00- 9.99 +0.20/-0.10 | | | | | | | | | | | | |
| .XX ± 0.38 | 10.00-17.49 +0.25/-0.13 | | | | | | | | | | | | |
| | 17.50-24.99 +0.30/-0.13 | | | | | | | | | | | | |
| ANG TOL: ± 1.0° | SCALE: ~3/32 | <p>CONFIDENTIAL</p> <p>FOR INTERPRETATION OF DIMENSIONS AND TOLERANCING, SEE ASME Y14.5M-1994</p> | FIRST USED ON ARROW | PGF | D | A051P365 | | | | | | | |
| | | | | | | SHEET 2 OF 2 | | | | | | | |

Part A051P365 A

| Description | Legacy Name | External Regulations | Application Status | Release Phase Code | Security Classification | Alternates |
|-------------------|-------------|----------------------|--------------------|--------------------|-------------------------|------------|
| OUTLINE,ENCLOSURE | A051P365 | None | Production Only | Production | Public | |

Part Specifications :A051P365 A

| Name | Description | Legacy Name |
|----------|------------------------|-------------|
| A030B356 | SPECIFICATION,MATERIAL | CES10903 |
| A051P366 | DRAWING,ENGINEERING | A051P366 |

**GENERATOR
SCREENED IN AT GROUND LEVEL - EAST SIDE OF BUILDING A**

DOAS/RTU FAN SCHEDULE - Job#4122613

| FAN UNIT NO. | TAG | DOAS/RTU MODEL # | BLOWER | RETURN AIR CFM | MAX OUTSIDE AIR CFM | TOTAL CFM | ESP. | RPM | H.P. | B.H.P. | Ø | VOLT | MCA | MOCP | WEIGHT (LBS.) | SDNES |
|--------------|-----|-----------------------------|--------|----------------|---------------------|-----------|-------|------|-------|--------|---|------|-------|------|---------------|-------|
| 1 | | CASRTU3-1.300-15-12.5T-DDAS | 15P-3 | 0 | 2400 | 2400 | 0.500 | 1420 | 2.000 | 1.0910 | 3 | 208 | 65.2A | 100A | 2495 | 11 |

DOAS/RTU COOLING SCHEDULE

| FAN UNIT NO. | TAG | COMPRESSOR | | | OUTDOOR FAN | | | | INDOOR COIL | | OUTSIDE AIR DB TEMP. | OUTSIDE AIR WB TEMP. | MIXED AIR DB TEMP. | MIXED AIR WB TEMP. | LEAVING DB TEMP. | LEAVING WB TEMP. | LEAVING DP TEMP. | TOTAL CAPACITY | SENSIBLE CAPACITY | LATENT CAPACITY | REHEAT LEAVING DB TEMP. | REHEAT LEAVING WB TEMP. | DESIRED REHEAT CAPACITY | MAX REHEAT CAPACITY | REHEAT LEAVING RELATIVE HUMIDITY | MOISTURE REMOVAL RATE | IEER |
|--------------|-----|------------|---------|---|---------------|---------|-----------------|-----------|-------------|------------|----------------------|----------------------|--------------------|--------------------|------------------|------------------|------------------|----------------|-------------------|-----------------|-------------------------|-------------------------|-------------------------|---------------------|----------------------------------|-----------------------|------|
| | | TONNAGE | VOLTAGE | Ø | MOTOR VOLTAGE | MOTOR Ø | MOTOR FREQUENCY | MOTOR QTY | ROWS | FACE AREA | | | | | | | | | | | | | | | | | |
| 1 | | 12.5 | 190-240 | 3 | 200-240 | 3 | 60 | 2 | 6 | 11.9 SQFT. | 90.0°F | 74.0°F | 90.0°F | 74.0°F | 54.9°F | 53.8°F | 53.1°F | 154.0 MBH | 89.0 MBH | 65.0 MBH | 70.0°F | 62.7°F | 40.7 MBH | 101 MBH | 67 | 59.1 LBS/HR | 21.3 |

DOAS/RTU HEATING SCHEDULE

| FAN UNIT NO. | TAG | INPUT BTUS | OUTPUT BTUS | TEMP. RISE | REQUIRED INPUT GAS PRESSURE | GAS TYPE | BURNER EFFICIENCY(%) |
|--------------|-----|------------|-------------|------------|-----------------------------|----------|----------------------|
| 1 | | 300000 | 240000 | 79 deg F | 7 in. w.c. - 14 in. w.c. | Natural | 80 |

FAN OPTIONS

| FAN UNIT NO. | TAG | OPTION (Qty. - Descr.) |
|--------------|--|--|
| 1 | | 1 - Single Point Electrical Connection for RTU. QNTY 1 750va Transformer Used. If a Non-DCV Prewire controls this unit, the #28, #47, 'MA', or 'E2' Option Prewire must be selected. Do not provide supply starter in prewire. |
| | | 1 - CASLink Building Monitoring System - Internet or Cellular Connection Required |
| | | 1 - RTU Size 3 Down Discharge |
| | | 1 - 2" MERV 13 Filters for Size 3 RTU. Qty 4. |
| | | 1 - 2" MERV 8 Filters for Size 3 RTU. Qty 4. |
| | | 1 - Overheat Stat |
| | | 1 - VFD factory mounted and wired in commercial control vestibule for RTU |
| | | 1 - 12.5 Ton Modulating Cooling Option, 208/230V. R410A Refrigerant, Variable Speed Compressor, ECM Condensing Fan(s). |
| | | 1 - RTU Fixed 100% OA Intake Control |
| | | 1 - RTU Size 3 No Return |
| | | 1 - Inlet Pressure Gauge, 0-35" |
| | | 1 - Manifold Pressure Gauge, 0 to 10" wc, 1 Furnace |
| | | 1 - Control Panel Enclosure Heater. Recommended for winter design temperature less than 0°F. PCB Controls |
| | | 1 - Size 3 RTU Curb Duct Hanger |
| | | 1 - 12.5 Ton Modulating Reheat Option. Discharge Relative Humidity Control. |
| | 1 - Commercial Smoke Detector/Alarm Interlock (Supplied by Others) | |
| | 1 - Exhaust Contactor After Airflow Switch-Field Wired | |
| | 1 - Occupied Scheduling | |
| | 1 - VAV Package w/ Manual/DDC Control (571 VFD Included) | |

CURB ASSEMBLIES


| NO. | DN FAN | WEIGHT | ITEM | SIZE |
|-----|--------|---------|------|--|
| 1 | # 1 | 100 LBS | Curb | 59.500"W x 91.000"L x 20.000"H Insulated |

FAN SOUND DATA

| FAN UNIT NO. | TAG | MOTOR | RPM | SOUND DATA | | | OCTAVE BAND SOUND DATA | | | | | | | | |
|--------------|-----|--------|------|------------|--------------|------------|------------------------|-------|--------|--------|--------|-------|-------|-------|-------|
| | | | | LWA | SDNES @ 5 ft | DBA @ 5 ft | DISTANCE (ft) | 63 Hz | 125 Hz | 250 Hz | 500 Hz | 1 kHz | 2 kHz | 4 kHz | 8 kHz |
| 1 | | Supply | 1420 | 73.5 | 11 | 62 | 5 | 71.3 | 69.4 | 73.7 | 70.6 | 66.7 | 66 | 62.8 | 58.1 |

FAN#1 - HEATER PERFORMANCE CURVES.

2400 CFM, 0.77 SP @ 1420 RPM and 1.091 BHP at 0 feet and -10 deg F
 * Please note that these curves were adjusted for job specific temperature and altitude.



REVISIONS

| DESCRIPTION | DATE |
|-------------|------|
| | |
| | |
| | |
| | |

DETROIT MECHANICAL

PO Box 924, Royal Oak, MI, 48068 PHONE: (248) 658-0509 FAX: EMAIL: reg12@captive.com

ACD, 0

DATE: 12/16/2019

DWG.#: 4122613

DRAWN BY:

SCALE: 3/4" = 1'-0"

MASTER DRAWING

SHEET NO. 1

Model: CASRTU Specifications

SECTION 23 74 23
FACTORY FABRICATED PACKAGED, 100% OUTDOOR, HEATING AND COOLING
MAKEUP AIR UNITS

SPECIFICATIONS
TAG: DDAS-1
PART 1 - GENERAL

- 11. SUMMARY
A. This Section includes packaged heating and cooling units capable of supplying up to 100 percent outdoor air.
12. SUBMITTALS
A. The manufacturer assumes no liability for the use or conflicts of use of this document. This specification is to be reviewed by the engineer to confirm requirements of the project and building codes are met.
B. As the manufacturer continues product development, it reserves the right to change design and specifications without notice.
13. SEISMIC DESIGN
A. Should project be located within a seismic zone requiring special provisions for support and restraint of equipment, components, and piping, see Section 23 01 01 - Seismic, Wind, and Flood Load Design for additional requirements.
14. WIND LOAD DESIGN
A. Refer to Section 23 00 01, Seismic, Wind, Flood Load Design for additional requirements.
B. Main Damp rated up to #150psf per TAS 201, 202 & 203 paired with 20' curb or shorter.
15. QUALITY ASSURANCE
A. All models shall be ETL listed and comply with safety standards UL 1995, and CSA Std. C222, No. 236-11. Units outfitted with indirect fired heaters shall also comply with ANSI Z83.9-2013, and CSA 246-2012.
16. Warranty
A. All units shall be provided with the following standard warranties:
1. 10-Year (non-prorated) parts warranty covering the entire unit when accompanied by a company provided service plan. 5-Year (non-prorated) parts warranty covering the entire unit otherwise.
2. 25-Year (non-prorated) parts warranty for SS heat exchanger on indirect fired units.
This warranty shall not apply if:
1. The equipment is not installed by a qualified installer per the manufacturer's installation instructions shipped with the product.
2. The equipment is not installed in accordance with Federal, state and local codes and regulations.
3. The equipment is abused or neglected, or not maintained per the manufacturer's maintenance instructions.
4. The equipment is not operated within its published capacity.
5. The invoice is not paid within the terms of the sales agreement.
C. The manufacturer shall not be liable for incidental and consequential losses and damages potentially attributable to manufacturing equipment. Should any part of the equipment prove to be defective in material or workmanship within the 10 year period upon examination by the manufacturer, such part will be repaired or replaced by manufacturer at no charge. The buyer shall pay all labor costs incurred in connection with such repair or replacement. Equipment shall not be returned without manufacturer's prior authorization and all returned equipment shall be shipped by the buyer. Freight prepaid to a destination determined by the manufacturer.

PART 2 - PRODUCTS
21. GENERAL
A. Supply single zone one piece packaged units that are complete as per the following specification, deliver all capacities scheduled, and conform to design indicated herein. Alternate layouts or dimensional changes will not be accepted.
22. CABINET
A. Units shall be constructed of minimum 20ga. G-90 galvanized steel riveted together via structural pop-rivets. All metal shall be CMC bent for precise assembly.
1. Rigging Provisions The unit shall have a structural base constructed of minimum 14ga. G-90 galvanized steel, and include full sized fork pockets and lifting points on all four sides.
2. Roof Construction The lids shall be fabricated by forming a double-standing, self-locking seon that requires no additional support. Roof shall be pitched to allow for proper drainage.
3. Exterior Wall Construction All exterior walls shall consist of a double wall, G-90 galvanized steel construction insulated with 2in. thick, foil-faced, R13 closed cell foam.
4. Service Access Doors All door joints shall be gasketed around their perimeter, and allow for doors to be mounted via removable, spring actuated, stainless steel hinges with stainless steel rivets, and self-compressing latches. Each compartment shall have removable access panels to allow for ease of service and maintainability. Electrical cabinet access doors shall have a door hold installed to prop doors open. All doors shall have stainless steel latches which are pad lockable. Electrical cabinet doors shall be outfitted with schematic/manual pouches formed into the door, along with wiring diagram attached to the interior of the door from the factory.
B. Entire interior and exterior casing shall be constructed of minimum 20 GA G90 galvanized steel with no painting, and shall have surpassed a salt spray corrosion test as per ASTM B 117.
C. Entire unit shall be Mini-Blade wind rated up to #150psf per TAS 201, 202 & 203 on any units utilizing a 20' or shorter factory provided roof curb.
23. Air-Flow Configuration
A. Unit shall be configurable for both down (vertical) discharge through base of unit, or side discharge through the cabinet. Unit shall also be configurable to both down (vertical) return or side return into the cabinet.
B. Unit intake air-flow configuration shall be through use of a Fresh/Outdoor and return air damper.
1. Damper Shall exceed AMCA Class 1A standard for low leakage. Damper assembly shall be a single assembly, and outfitted with an integral bird screen and lower/gutter system to divert any drainage through the base of the unit - intake air hood not required.
2. Actuator A single direct drive damper actuator shall be used with spring return to ensure that the outdoor air section closes when not powered.
24. SUPPLY AIR BLOWER AND MOTOR
A. All supply fans shall be direct drive (belt-driven not acceptable) variable speed plenum fans.
B. Blower Motor: Motor shall be a premium efficiency motor available as:
1. Open Drip Proof (ODP) or Totally Enclosed Fan Cooled (TEFC) motor driven by a Variable Frequency Drive.
2. Electronically Commutated Motor (ECM).
C. Fans to be selected at or near efficiency peak. (Submit fan curves)
D. Blower and motor assembly shall be dynamically balanced. The entire blower and motor assembly shall be mounted on rubber vibration isolators. Wheels balanced as per AMCA 204/96, Balance Quality and Vibration Levels For Fans.
25. REFRIGERATION SYSTEM
A. Unit shall utilize a variable speed inverter duty scroll compressor with the following features:
1. Modulation Compressor shall be capable of compressor speed modulation from 15%-100% on 8, 10, & 12.5 Ton units, and 25%-100% on 15, 20, 25, 25 & 30 Ton units.
2. Refrigerant Unit shall be factory charged with R410A refrigerant.
3. Vibration Isolation Compressor shall be mounted on rubber vibration isolators to reduce transmission of vibration to the building structure.
4. Internal Overload Protection Compressor shall include internal thermal overload protection to protect against excessive motor temperatures.
5. Crankcase Heater Compressor shall include a crankcase heater to protect against liquid flood-back and elimination of oil foaming on startup. The crankcase heater must remain powered when compressor is not in operation.
6. Oil Management Unit shall utilize both passive and active oil return management using Oil Level Sensor and scheduled oil boosts.
7. Motorized Envelope Unit shall monitor all critical refrigeration points to ensure compressor does not operate outside of safe operating envelope.
8. Throttling Logic Unit shall allow for high head pressure monitoring throttle mode for high ambient operation, and low suction pressure throttle mode for low capacity operation or any conditions resulting in low suction pressure.
9. Pump-Down Active pump-down mode with discharge line check valve to protect against liquid migration into compressor during idle times.
10. Defrost mode in optional Heat Pump: When outdoor coils are deemed at risk of freezing, the unit shall simultaneously turn on auxiliary heat while running the heat pump in 'cooling' mode to help defrost outdoor coils as needed while still maintain desired leaving air temperatures.
B. The unit shall be outfitted with the following:
1. Indoor Coil: Indoor coil shall be a high efficiency 5-7 row coil design with aluminum fins mechanically bonded to copper tubes. Coil is staggered to increase turbulence, reduce the coil bypass factor, and ultimately the time the air stays within the coil.
2. Electronic Expansion Valve: Each refrigeration circuit will be outfitted with an electronic expansion valve metering device which can be throttled from 0-100% open to allow for precise superheat control.
3. Indoor Coil Drain Pan: The indoor coil shall be outfitted with a sloped stainless steel drain pan. This pan shall be insulated along the entire base to prevent condensation, and outfitted with a safety overflow switch which will automatically shut down cooling operation prior to water overflowing the drain pan in the event of a drain clog. The drain pan shall be 20 GA Stainless Steel construction and wrap beneath the entire coil with flashing on entering side of coil to ensure capture of all condensate. Drain pan discharge tee shall be stainless steel construction. Drain pan shall be pitched to exceed ASHRAE 62.1 standard.
4. Base of the condensing coil cabinet shall be pitched away from the unit as a safety to ensure all draining exits away from the curb.

- 5. Optional Hot Gas Reheat Coil: The unit shall include an optional copper tube and aluminum fin hot gas reheat coil mounted downstream of the indoor coil. The coil shall be controlled via fully modulating hot gas reheat valve to provide precise reheat temperature control. This coil shall include the addition of an evaporator coil leaving condensation sensor to maintain a coil dew point. This also prevents operation of a dehumidification coil when intake dew point conditions are found to be below space dew point conditions, preventing wasted energy.
6. Outdoor (Condenser) Coil: Outdoor coil shall be a high efficiency coil design with aluminum fins mechanically bonded to copper tubes. The coil shall be downward sloped to protect coil from hail damage. Optional hail guards may also be outfitted to the outdoor coil for added protection from hail bouncing off of the roof of the unit up the coil.
7. Outdoor Fans: The outdoor coil shall have a vertical discharge outfitted with quiet, efficient, fully modulating Electronically Commutated Motor (ECM) condensing fans. These fans shall modulate to maintain a temperature differential between outside air and the outdoor coil.
C. To help mitigate any long-term potential for leaks or hardware failures, the unit shall be outfitted with the following protection measures:
1. Suction line accumulator for added protection against liquid entering suction line of compressor
2. Bi-flow, low pressure drop, filter drier.
3. Electronic Expansion Valve (EEV) for precise superheat control. EEV shall open partially allowing system pressure equalization prior to activation of the compressor.
4. On optional heat pump units, use of a single 3-way reheat valve to prevent obstructions due to valve failure.
5. Protective rubber sleeves installed on all distribution lines of indoor coil to prevent wear from rubbing.
6. All refrigeration parts shall be short-stroke assembly and any access port with a transducer or switch is mounted vertically to mitigate risk of bent/cracked stub joints.
7. Refrigeration circuit shall be mechanically CNC pre-bent tubing wherever possible with minimal brazed joints to minimize points for potential refrigeration leaks.
8. Factory tested for leaks via high pressure nitrogen decay and helium tracer gas testing.
9. Suction line temperature sensor failure detection.
10. Preventative failure alerts through a manufacturer provided, cloud based, cellular remote monitoring system.


26. HEATING SYSTEM
A. The gas burner shall be an indirect-fired, push-through type, using natural (LP) gas at an inlet-supply pressure to the unit of 7"wc. minimum Nat. Gas, (11"wc. minimum LP Gas). Burner shall be a tubular-in-shot three design capable of using natural or LP type gas. Each burner ignition shall be of the direct-spark design with remote flame sensing at inlet of the last firing tube of the gas manifold.
B. Direct-sparking sequence shall last throughout the complete duration of the trial for combustion period for guaranteed light-off. Burner shall always lit at maximum gas flow and ignition air flow for guaranteed light-off. Each burner ignition module shall have LED indicators for troubleshooting and a set of exposed prongs for testing flame induction signal.
C. All furnaces shall be controlled by an electronic Verner-type fully modulating control system capable of achieving 80% combustion efficiency over the entire gas firing range of the unit.
D. Each furnace shall have:
1. A minimum burnout ratio of 6:1 for natural gas and 5:1 for LP gas with maintaining a constant 80% efficiency (90% for high efficiency furnace option). No cold air bypass of the heat exchanger is allowed.
2. Each furnace heat exchanger shall be a bent-tube style design made entirely of type 409 stainless steel.
3. Stainless steel Quick Seal Connection for gas connection.
4. Manifold and input gas pressure gauging.
5. Factory piped condensate drain to exterior of cabinet.
6. A combustion flue to be installed on adjacent side as combustion intake with integrated high velocity wind cap.
7. A blocked vent safety air-flow switch with high temperature silicone tubing operating off of absolute pressure measured inside of the power-vent blower housing.
8. A high temperature auto-recycling limit with a maximum non-adjustable set point.
9. A manual reset high temperature flame roll out switch with a non-adjustable set point.
10. Each furnace compartment shall have a removable port and panel that allows the furnace to be easily removed for service and maintainability.
11. A power-vent assembly for exhausting flue gases with a PSC or ECM type motor that is securely mounted and easily accessible/removable for service.
12. A 0-10"wc. gas pressure gauge installed on the gas manifold.

27. FILTERS
A. Provide filters as part of unit. All filters shall be furnished and installed to meet the performance requirements set forth in the schedule and as specified under another section of this work.
B. All filters shall be installed on tracks for easy removal from the unit.
C. Unit up to 3 layers of outdoor air filtration installed Unit shall ship with a 2" washable metal mesh outdoor air filter. Most air shall have optional 2" MERV-8 and 4" MERV-13 Filters , 4" MERV-15 or 4" MERV-17 HEPA filter banks factory installed.
D. Unit shall have an optional adjustable pressure differential sensor for the filter bank to alert in the event of a clogged filter.
28. Electrical
A. All controls shall be pre-wired and housed in an insulated electrical cabinet within the unit to protect against risk of condensation.
B. All direct fired and cooling only units shall be provided with single point electrical connection.
C. Unit shall be provided with a door safety switch that de-energizes the supply fan when the door is opened.
D. Unit shall be provided with a factory mounted averaging supply air temperature sensor to allow for accurate discharge temperature readings within unit when a downstream sensor is not installed. Field mounted and wired discharge air temperature sensors will not be accepted.
E. Unit shall be provided with a factory mounted averaging intake air temperature sensor to allow for accurate intake temperature reading regardless of how the DA/BA sensors are positioned.
F. The electrical cabinet shall be outfitted with the following:
1. LED electrical cabinet service light with automatic activation upon door switch.
2. Color wiring schematics, laminated to the interior wall of the cabinet doors.
3. Factory mounted disconnect with unit lockout knockouts.
4. A LED backlit, LED Human-Machine Interface (HMI) shall be mounted within the unit's control cabinet to allow for all set points configuration and refrigeration system monitoring at the unit.
5. Up to 4 additional space mounted HMI's available. Additional HMI's shall allow for full programming capabilities and are outfitted with integral temperature and humidity sensors. Additional HMI's shall be capable of being individually averaged for space temperature/humidity readings. All HMI's shall be wired using standard CAT5e cables.
6. Optional 120V, 15A unit powered or unpowered convenience outlet.
G. All sensors shall be wired back to the main control board that continuously monitors all critical components and makes decisions based on pre-determined logic to accurately control the following:
1. PID logic to control heater modulation ensuring precise discharge/space temperature control.
2. PID logic to control compressor speed to provide precise control over evaporative coil temperatures, leaving dew point, and discharge/space temperatures.
3. PID logic for Outdoor Fan modulation to maintain an optimal outdoor coil temperature.
4. PID logic for Electronic Expansion Valve (EEV) position to maintain a precise superheat temperature.
5. PID logic for Modulating Reheat valve to limit supply air temperature and relative humidity based off of space or discharge conditions.
29. CONTROLS
A. Unit shall be outfitted with a control board to allow for full control of the entire unit.
B. Provide air flow switch on the supply fan system to sense air flow with available set of contacts for connection to BMS for airflow alerts.
C. All unit controls shall be compatible with BACnet and LonWorks based building management systems.
D. All units shall be outfitted with CASLink cloud based monitoring, which monitors every point of operation. Provides configurable automated fault alert e-mails, and remote control capabilities.
E. Integrated cellular module to provide remote connection to monitoring services to view both real time and historical unit operation. Data shall be stored a minimum of 3 years on the cloud. Data sample rate shall be a maximum of 60 seconds.
F. Temperature Control System
1. Low-Ambient Cooling Unit is factory outfitted with logic allowing for low-ambient operation of the DX system down to 15F outdoor temperatures purely through software utilizing the standard factory modulating components.
2. Discharge Temp Control (Heating)
Unit modulates the burner flame (current supply in the case of electric heating) to accurately maintain the desired discharge temperature set point and compensate for fluctuations in entering air temperature, air volume and % of DA using heating PID controls designed specifically for the IDAS. Minimum and maximum discharge set points can be set to limit the temperature entering the space. When ambient temperatures drop below a user configurable minimum outdoor air temperature set point, or the unit is not able to maintain a user configurable minimum discharge temp for 5 minutes time, the heat pump will initiate its backup heat source. Initiation of backup heater operation shall ensure discharge temps are maintained prior to disabling heat pump to make sure discharge temps are never impacted during changeover. An optional additional HMI or room thermostat can be used to determine the space temperature. In the case that no temperature sensor is available in the space, the unit will use an internal return temperature sensor.
3. Discharge Humidity Control (Dehumidification)
Unit modulates the compressor frequency to accurately maintain a desired evaporative coil dew point measured via a coil mounted temperature sensor between the evaporative and hot gas reheat coils. A fully modulating hot gas reheat valve shall utilize excess waste heat from the condensing section to reheat the hot gas reheat coil with the precise amount of heat needed to accurately reheat the airstream in order to maintain a desired discharge temperature compensating for fluctuations in entering air temperature, air volume and % of DA using proprietary dehumidification PID controls designed specifically for the IDAS.
4. Space Temp Control (Heating)
Unit modulates the burner flame (current supply in the case of electric heating) to accurately maintain the desired space temperature set point and compensate for fluctuations in entering air temperature, air volume and % of DA using heating PID controls designed specifically for the IDAS. Minimum and maximum discharge set points can be set to limit the temperature entering the space. An optional additional HMI or room thermostat can be used to determine the space temperature. In the case that no temperature sensor is available in the space, the unit will use an internal return temperature sensor.
5. Space Temp Control (Cooling)
Unit modulates the compressor frequency to accurately maintain the desired space temperature set point and compensate for fluctuations in entering air temperature, air volume and % of DA using cooling PID controls designed specifically for the IDAS. Minimum and maximum discharge set points can be set to limit the temperature entering the space. An optional additional HMI or room thermostat can be used to determine the space temperature. In the case that no temperature sensor is available in the space, the unit will use an internal return temperature sensor.
6. Space Temp Control (Heat Pump)
Unit modulates the compressor frequency to accurately maintain the desired space temperature set point and compensate for fluctuations in entering air temperature, air volume and % of DA using heating PID controls designed specifically for the IDAS. Minimum and maximum discharge set points can be set to limit the temperature entering the space. When ambient temperatures drop below a user configurable minimum outdoor air temperature set point, or the unit is not able to maintain a user configurable minimum discharge temp for 5 minutes time, the heat pump will initiate its backup heat source. Initiation of backup heater operation shall ensure discharge temps are maintained prior to disabling heat pump to make sure discharge temps are never impacted during changeover. An optional additional HMI or room thermostat can be used to determine the space temperature. In the case that no temperature sensor is available in the space, the unit will use an internal return temperature sensor.
7. Space Humidity Control (Dehumidification)
Unit modulates the compressor frequency to accurately maintain a desired evaporative coil dew point measured via a coil mounted temperature sensor between the evaporative and hot gas reheat coils. A fully modulating hot gas reheat valve shall utilize excess waste heat from the condensing section to reheat the hot gas reheat coil with the precise amount of heat needed to accurately reheat the airstream in order to maintain a desired space temperature compensating for fluctuations in entering air temperature, air volume and % of DA using proprietary dehumidification PID controls designed specifically for the IDAS.
8. Advanced Total Unit Economizer: The control system is outfitted standard, without need for any additional hardware, with an Advanced Total Unit Economizer which will take maximum advantage of as much energy available in the outdoor air conditions as possible to run the compressor the minimum amount required at any given incoming air conditions. If the outdoor ambient temperature and relative humidity permits, the unit will be capable of completely modulating and shutting off compressor to provide free cooling and dehumidification as the outdoor conditions allow.

- 9. Space Humidity Control (Dehumidification)
Unit modulates the compressor frequency to accurately maintain a desired evaporative coil dew point measured via a coil mounted temperature sensor between the evaporative and hot gas reheat coils. A fully modulating hot gas reheat valve shall utilize excess waste heat from the condensing section to reheat the hot gas reheat coil with the precise amount of heat needed to accurately reheat the airstream in order to maintain a desired space temperature compensating for fluctuations in entering air temperature, air volume and % of DA using proprietary dehumidification PID controls designed specifically for the IDAS.
10. Advanced Total Unit Economizer: The control system is outfitted standard, without need for any additional hardware, with an Advanced Total Unit Economizer which will take maximum advantage of as much energy available in the outdoor air conditions as possible to run the compressor the minimum amount required at any given incoming air conditions. If the outdoor ambient temperature and relative humidity permits, the unit will be capable of completely modulating and shutting off compressor to provide free cooling and dehumidification as the outdoor conditions allow.
G. Activation Controls
1. Activate Based on Intake (Heating)
Unit will activate heating when the intake temperature drops below the desired set point.
2. Activate Based on Intake (Cooling)
Unit will activate cooling when the intake temperature rises above the desired set point.
3. Activate Based on Intake (Dehumidification)
Unit will activate dehumidification when the intake conditions rise above the desired intake set point, with activation set points configured to a Dew Point, Relative Humidity or a combination of Dew Point/Relative Humidity.
4. Activate Based on Space (Heating)
Unit will activate heating when the space temperature drops below the desired set point.
5. Activate Based on Space (Cooling)
Unit will activate cooling when the space temperature rises above the desired set point.
6. Activate Based on Space (Dehumidification)
Unit will activate dehumidification when the space set point rises above the desired space set point, with activation set points configured to a Dew Point, Relative Humidity or a combination of Dew Point/Relative Humidity.
7. Activate Based on Both (Heating)
Unit will activate heating when the space AND intake temperature drop below the desired set point.
8. Activate Based on Both (Cooling)
Unit will activate cooling when the space AND intake temperature rise above the desired set point.
9. Activate Based on Both (Dehumidification)
Unit will activate dehumidification when the space and intake set point rises above the desired space and intake set point, with activation set points configured to a Dew Point, Relative Humidity or a combination of Dew Point/Relative Humidity.
10. Activate Based on Either (Heating)
Unit will activate heating when the space OR intake temperature drops below the desired set point.
11. Activate Based on Either (Cooling)
Unit will activate cooling when the space OR intake temperature rises above the desired set point.
12. Activate Based on Either (Dehumidification)
Unit will activate dehumidification when the space or intake set point rises above the desired space or intake set point, with activation set points configured to a Dew Point, Relative Humidity or a combination of Dew Point/Relative Humidity.
13. Activate Based on Stat (Heating)
Unit will activate heating when the space thermostat sends a 24V signal to W and G on the main control board. Unit will modulate to maintain a constant discharge cool set point.
14. Activate Based on Stat (Cooling)
Unit will activate cooling when the space thermostat sends a 24V signal to Y and G on the main control board. Unit will modulate to maintain a constant discharge cool set point.
210. ROOF CURB
A. Unit shall be factory assembled, and constructed of 18GA galvanized steel, with optional 16GA available.
B. Curb shall be fully insulated with 1" acoustic and thermal insulation.
C. Curb shall be factory outfitted with duct support hangers.
211. VARIABLE FREQUENCY DRIVES
A. Provide Variable Frequency Drive for the compressor as part of the AC unit. VFD shall be furnished and installed to meet the performance set forth in the schedule and as specified under another section of this work.
1. Accessories to be furnished and mounted by the drive manufacturer and contained in a single enclosure. (The use of more than one enclosure is not acceptable).
B. Provide Variable Frequency Drive for speed control on all non-ECM direct drive supply fans.
C. All VFD's shall provide the following inherent protections:
1. Phase protection
2. Breakout protection
3. Overload/Overheat protection
4. Soft starts to protect bearings/hardware.
5. Low & High voltage & over-torque protections.
34. SYSTEM START-UP
A. System start-up is performed by a factory trained Service Technician
END DF SECTION 23 74 23
Fan shall be model CASRTU as manufactured by CaptiveAir® Systems.
Rev #1, 5-28-19 MAP

REVISIONS

Table with columns: DESCRIPTION, DATE. Contains revision symbols (triangles) and empty rows for recording changes.



Detroit Mechanical
www.captiveair.com
www.captiveair.com
EMAIL: reg12@captiveair.com
PHONE: (248) 658-0509
FAX: (248) 658-0509



PO Box 924, Royal Oak, MI, 48068

DATE: 12/16/2019

DWG.#: 4122613

DRAWN BY:


SCALE: 3/4" = 1'-0"

MASTER DRAWING

SHEET NO. 2

TYPICAL DOAS/RTU ROOF MOUNTING INSTALLATION INSTRUCTIONS

1. Secure the curb to the roof framing members by drilling 1/4" pilot holes in the curb flanges at locations shown in the diagram below. Using 3/8" x 2" zinc plated steel lag bolts, and zinc plated washers, screw through the curb flanges and into the roof framing members. A minimum of (5) lag bolts on each short side, and (7) lag bolts on each long side is required.
2. Secure the unit base to the side walls of the curb using (24) 1/4"-14 x 2" self-drilling, steel zinc plated screws. Pre-punched holes have been provided for each screw location.



**ROOF TOP FRESH AIR UNIT
SCREENED-IN ON ROOF TOP ALL BUILDINGS**

| REVISIONS | |
|-------------|-------|
| DESCRIPTION | DATE: |
| | |
| | |
| | |
| | |



CAPTIVE MECHANICAL

 Detroit Mechanical

 www.captiveaire.com

 PO Box 924, Royal Oak, MI, 48068 PHONE: (248) 658-0509 FAX: EMAIL: reg123@captiveaire.com

ACD , 0

DATE: 12/16/2019

DWG.#: 4122613

DRAWN BY:

SCALE: 3/4" = 1'-0"


MASTER DRAWING

SHEET NO. 3

NOTES:

- DO NOT OBSTRUCT OUTSIDE AIR INLET, OUTSIDE AIR COIL OR OUTSIDE AIR FAN.
-  DENOTES CORNER WEIGHT.
- ROOF OPENING MUST BE 2" SMALLER THAN CURB DIMENSIONS IN BOTH DIRECTIONS.

*NOTE: SUPPLY DUCT MUST BE INSTALLED TO MEET SMACNA STANDARDS. A MINIMUM STRAIGHT DUCT LENGTH MUST BE MAINTAINED DOWNSTREAM OF UNIT DISCHARGE AS OUTLINED IN AMCA PUBLICATION 201. DO NOT RELY ON UNIT TO SUPPORT DUCT IN ANY WAY. FAILURE TO PROPERLY SIZE DUCTWORK MAY CAUSE SYSTEM EFFECTS AND REDUCE PERFORMANCE OF THE EQUIPMENT. SUGGESTED STRAIGHT DUCT SIZE IS 21.5" x 39"



**ROOF TOP UNIT
SCREENED-IN ON ROOF TOP ALL BUILDINGS**

OPTIONS

- SINGLE POINT ELECTRICAL CONNECTION FOR RTU. QNTY 1 750VA TRANSFORMER USED. IF A NON-DCV PREWIRE CONTROLS THIS UNIT, THE #28, #47, "MA", OR "E2" OPTION PREWIRE MUST BE SELECTED. DO NOT PROVIDE SUPPLY STARTER IN PREWIRE.
- CASLINK BUILDING MONITORING SYSTEM - INTERNET OR CELLULAR CONNECTION REQUIRED
- RTU SIZE 3 DOWN DISCHARGE
- 2" MERV 13 FILTERS FOR SIZE 3 RTU. QTY 4.
- 2" MERV 8 FILTERS FOR SIZE 3 RTU. QTY 4.
- OVERHEAT STAT
- VFD FACTORY MOUNTED AND WIRED IN COMMERCIAL CONTROL VESTIBULE FOR RTU
- 12.5 TON MODULATING COOLING OPTION, 208/230V. R410A REFRIGERANT, VARIABLE SPEED COMPRESSOR, ECM CONDENSING FAN(S).
- RTU FIXED 100% DA INTAKE CONTROL
- RTU SIZE 3 NO RETURN
- INLET PRESSURE GAUGE, 0-35"
- MANIFOLD PRESSURE GAUGE, 0 TO 10" WC, 1 FURNACE
- CONTROL PANEL ENCLOSURE HEATER. RECOMMENDED FOR WINTER DESIGN TEMPERATURE LESS THAN 0°F. PCB CONTROLS
- SIZE 3 RTU CURB DUCT HANGER
- 12.5 TON MODULATING REHEAT OPTION. DISCHARGE RELATIVE HUMIDITY CONTROL.
- COMMERCIAL SMOKE DETECTOR/ALARM INTERLOCK (SUPPLIED BY OTHERS)
- EXHAUST CONTACTOR AFTER AIRFLOW SWITCH-FIELD WIRED
- OCCUPIED SCHEDULING
- VAV PACKAGE W/ MANUAL/DDC CONTROL (571 VFD INCLUDED)

| REVISIONS | |
|-------------|-------|
| DESCRIPTION | DATE: |
| | |
| | |
| | |
| | |

www.captiveair.com

CAPTIVE AIR

Detroit Mechanical

PO Box 924, Royal Oak, MI, 48068 PHONE: (248) 658-0509 FAX: EMAIL: reg123@captiveair.com

ACD , 0

DATE: 12/16/2019


DWG.#: 4122613

DRAWN BY:



SCALE: 1/2" = 1'-0"

MASTER DRAWING

SHEET NO.
4




FOR EACH CABINET



NOTES:

1. BIND THE CONCENTRIC NEUTRAL OF EACH CABLE AT A HEIGHT OF 8" (MAX) FROM THE BOTTOM OF THE CABINET.

2. USE FEED THROUGH RATED 8 3/4 KV FD. NO. 761-0515 SEE



Pad-Mounted Transformers

Contents

Pad-Mounted Transformers

- General Description 17.0-2
- Introduction 17.0-2
- Application. 17.0-2
- Industry Standards 17.0-2
- Ratings 17.0-2
- Design Impedances. 17.0-2
- Application Limitations. 17.0-2
- Standard Features 17.0-3
- Options. 17.0-3
- Transformer Cooling Classes 17.0-4
- NEC Requirement Guidelines. 17.0-5
- Seismic Qualification 17.0-5
- Primary Protection Options 17.0-6
- Primary Switching Options. 17.0-10
- PEAK Transformers 17.0-12
- Load-break Wells and Inserts 17.0-15
- Primary Fuse Details. 17.0-17
- Layout Data 75–2500 kVA 17.0-18
- Technical Data 75–2500 kVA 17.0-19
- Layout Dimensions 3000–5000 kVA 17.0-20
- Technical Data 3000–5000 kVA 17.0-21

Specifications

See Eaton's *Product Specification Guide*, available on CD or on the Web.

| | | |
|----------------------|----------------------|-------------------------|
| CSI Format | 1995 | 2010 |
| | Section 16321 | Section 26 12 19 |



Typical Pad-Mounted Transformer

GROUND-MOUNTED
TRANSFORMER BY DTE

General Description

Three-Phase Pad-Mounted Transformers



Typical Pad-Mounted Transformer

Introduction

Eaton's three-phase pad-mounted transformer is offered in a variety of designs and configurations. The following pages describe the standard designs and the common options that are available.

Some special designs and options may require additional engineering, factory coordination, unusual application requirements or special manufacturing needs.

Higher impedances limit secondary fault currents such that coordination with secondary low voltage molded-case circuit breakers is usually possible. (Low impedances are also available if required for paralleling, and so on.)

Standard color is pad-mounted green [Munsell® Green (#7GY3.29/1.5)]. ANSI #24, 61 and 70 are available as options.

Application

Liquid-filled, three-phase, commercial pad-mounted distribution transformers are designed for servicing such underground distribution loads as shopping centers, schools, institutions, data centers, and industrial plants. They are also heavily utilized for step-up applications in renewable energy installations. They are available in both deadfront and livefront and construction, for radial or loop-feed applications, with or without taps.

Industry Standards

Pad-mounted transformers meet industry standards: IEEE® C57.12.00, IEEE C57.12.34, IEEE C57.12.28, IEEE C57.12.29, IEEE C57.12.70,

IEEE C57.12.80, IEEE C57.12.90, IEEE C57.91, DOE 10 CFR Part 431 and NEMA®.

Ratings

- 45–10,000 kVA
- High voltages (primary):

| | |
|------------------|---------|
| 4160 Grd. Y/2400 | 2400Δ |
| through | through |
| 43,800 GY/25,300 | 46,000Δ |
| Grd. Y/19,920 | |
- HV Taps: 2–2-1/2% above and below normal, or 4–2-1/2% below normal
- Standard BIL levels:

| | |
|------------------|-----------------|
| kV Class | BIL (kV) |
| 1.2 | 30 |
| 2.5 | 45 |
| 5.0 | 60 |
| 8.7 | 75 |
| 15.0 | 95 |
| 25.0 Grd. Y Only | 125 |
| 25.0 | 150 |
| 34.5 Grd. Y Only | 150 |
| 34.5 | 150 |
| 46 | 250 |
- Low voltages (secondary). All voltages through 15 kV class
- UL listing and/or classification available
- Factory Mutual Approval available

Design Impedances

Impedances are supplied to meet IEEE C57.12.34 standards. Customer-specified impedances are available. (Subject to IEEE/ANSI ±7.5% impedance tolerance.)

- Nominal impedance per IEEE C57.12.34:

| | |
|-------------|-----------|
| kVA | %Z |
| 45 | 2.70–5.75 |
| 75 | 2.7–5.75 |
| 112-1/2 | 3.1–5.75 |
| 150 | 3.1–5.75 |
| 225 | 3.1–5.75 |
| 300 | 3.1–5.75 |
| 500 | 4.35–5.75 |
| 750 | 5.75 |
| 1000 | 5.75 |
| 1500 | 5.75 |
| 2000 | 5.75 |
| 2500 | 5.75 |
| 3000 | 5.75 |
| 3750 | 5.75 |
| 5000–10,000 | 6.0–6.5 |

Note: Subject to NEMA/IEEE ±7.5% impedance tolerance.

Note: Non-standard design impedance may be obtained by contacting Eaton.

Application Limitations

The transformers described herein are designed for the application conditions normally encountered on electric power distribution systems. As such, they are suitable for use under the “usual service

conditions” described in IEEE Standard C57.12.00 general requirements for liquid-immersed distribution, power and regulating transformers. Transformers required for step-up applications should be specified as such.

Consult Eaton for unusual service conditions such as:

- Abnormal environmental conditions
- Unusual transient voltages present on the source voltage
- Frequent or planned through-fault duty
- Planned overloading unless in strict accordance with the IEEE loading guide (C57.91)
- Motors whose horsepower rating is greater than half the transformer kVA rating
- Unusual frequency of impact loading may occur when supplying welding apparatus, electric arc furnaces or motors with cyclical loads
- Loads involving abnormal harmonic or DC current that may result where appreciable load currents are controlled by solid-state or similar devices

These lists do not purport to cover all unusual conditions and applicable limitations. Other “unusual service conditions” are described in IEEE Standard C57.12.00.

Table 17.0-1. Temperature Guarantees

| Description | Ambient ① | Rise ②③ |
|-------------|-----------|---------|
| Standard | 30 °C | 65 °C |
| Optional | 30 °C | 55 °C |
| Optional | 30 °C | 75 °C ④ |

- ① 30 °C average ambient temperature of cooling air not to exceed 40 °C maximum over any 24-hour period.
- ② Degree rise is the average winding temperature rise by resistance.
- ③ A dual temperature rating of 55 °C/65 °C or 65 °C/75 °C adds 12% additional continuous capacity to the base kVA rating of the transformer. 55 °C/75 °C adds 22%.
- ④ Requires transformer to be filled with Envirotemp™ FR3™ fluid.

Note: Altitudes not to exceed 3300 ft (1006 m). Unit deration or special designs are required above 3300 ft (1006 m).

Fluids—Liquid Dielectric

The choice of fluid, mineral oil or less flammable natural ester fluid (Envirotemp FR3) is made based upon site conditions and proximity to facility walls, windows and flammable structures, environmentally sensitive areas, and when considering extended transformer insulation life.

Note: For additional information about transformer applications and types of insulating fluids, see Tab 14.

General Description

PEAK Transformers (Continued)

The example below illustrates the potential footprint change in three-phase pad-mounted transformers.




Table 17.0-12. PEAK Transformer Comparison

| Description | Mineral Oil | PEAK 75 °C | PEAK 65/75 °C | PEAK 55/75 °C |
|----------------------------|-------------------------------|-------------------------------|---|---|
| Three-phase load capacity | IEEE Std C57.91-2011 standard | IEEE Std C57.91-2011 standard | +12% continuous (above base kVA rating) | +22% continuous (above base kVA rating) |
| Life extension | 1x | 3-4x | 8x (when operating at base kVA rating) | 8x (when operating at base kVA rating) |
| Enhanced fire safety | — | ■ | ■ | ■ |
| Environmentally preferred | — | ■ | ■ | ■ |
| First price | Lowest | Lower | Low | Low |
| Lifetime cost of ownership | Low | Lower | Lowest | Lower |
| Bioremediation cost | High | Moderate | Moderate | Moderate |

Note: All values are design dependent.



Layout Dimensions




Figure 17.0-12. Pad-Mounted Transformer—Dimensions in Inches (mm)

Table 17.0-13. Dimensions with DOE Efficiency at 65 Degree AWR

| kVA | A | B | C | D | E | F | I | Gallons | Approximate Weight | DOE 2016 Efficiency |
|-------|----|-----|----|----|----|----|----|---------|--------------------|---------------------|
| 45 | 50 | 68 | 39 | 42 | 26 | 68 | 20 | 115 | 2150 | 98.92% |
| 75 | 50 | 68 | 39 | 42 | 26 | 68 | 20 | 125 | 2350 | 99.03% |
| 112.5 | 50 | 68 | 39 | 42 | 26 | 68 | 20 | 135 | 2600 | 99.11% |
| 150 | 50 | 68 | 49 | 42 | 26 | 68 | 20 | 150 | 2900 | 99.16% |
| 225 | 50 | 72 | 53 | 42 | 30 | 72 | 20 | 170 | 3400 | 99.23% |
| 300 | 50 | 72 | 55 | 42 | 30 | 72 | 20 | 190 | 3950 | 99.27% |
| 500 | 50 | 72 | 61 | 42 | 30 | 72 | 20 | 240 | 5300 | 99.35% |
| 750 | 64 | 72 | 63 | 42 | 30 | 72 | 20 | 300 | 7150 | 99.40% |
| 1000 | 64 | 72 | 64 | 42 | 30 | 72 | 20 | 350 | 8950 | 99.43% |
| 1500 | 73 | 89 | 71 | 42 | 30 | 72 | 24 | 400 | 11,450 | 99.48% |
| 2000 | 73 | 101 | 75 | 42 | 30 | 72 | 24 | 525 | 13,800 | 99.51% |
| 2500 | 73 | 101 | 99 | 42 | 30 | 72 | 24 | 600 | 16,750 | 99.53% |

Note: The reference dimensions in this table cover the following: livefront and deadfront configurations, loop feed and radial feed, mineral oil and FR3 filled units.

Dimensional Variations

Height Variations

1. Add 9.00 inches (228.6 mm) to the height when using bayonet fusing on all kVA ratings.
2. Less flammable natural ester fluid requires deeper tanks on some transformer ratings.
 - a. Add 2.00 inches (50.8 mm) to the depth of kVA ratings 75–1500. Add 8.00 inches (203.2 mm) to the depth of kVA ratings 2000 and 2500.



*Dimensions are approximate—
not for construction.*

Layout Dimensions/Technical Data

Technical Data

Table 17.0-14. Liquid Filled <34.5 kV Primary 55 °C Temp. Rise

| kVA | No Load at 75 °C Ref. Temp. (Watts) | Load Loss at 100% Load and 75 °C Ref. Temp. (Watts) | Total Losses at 100% Load and 85 °C (Watts) | 60–150 kV HV BIL Total Losses at 50% Load and 55 °C LL Ref. Temp. and 20 °C NL Ref. Temp. per DOE (Watts) |
|-------|-------------------------------------|---|---|---|
| 75 | 175 | 960 | 1135 | 413 |
| 112.5 | 250 | 1250 | 1500 | 562 |
| 150 | 300 | 1630 | 1930 | 696 |
| 225 | 330 | 2500 | 2830 | 942 |
| 300 | 520 | 2600 | 3120 | 1164 |
| 500 | 730 | 4900 | 5630 | 1889 |
| 750 | 1100 | 6200 | 7300 | 2567 |
| 1000 | 1500 | 6700 | 8200 | 3221 |
| 1500 | 1900 | 10,000 | 11,900 | 4375 |
| 2000 | 2600 | 12,000 | 14,600 | 5429 |
| 2500 | 2800 | 15,000 | 17,800 | 6408 |
| 3000 | 3800 | 16,000 | 19,800 | — |

Note: Losses offered are typical only, not guaranteed.

Table 17.0-15. Liquid Filled <34.5 kV Primary 65 °C Temp. Rise

| kVA | No Load at 85 °C Ref. Temp. (Watts) | Load Loss at 100% Load and 85 °C Ref. Temp. (Watts) | Total Losses at 100% Load and 85 °C (Watts) | 60–150 kV HV BIL Total Losses at 50% Load and 55 °C LL Ref. Temp. and 20 °C NL Ref. Temp. per DOE (Watts) |
|-------|-------------------------------------|---|---|---|
| 75 | 190 | 950 | 1140 | 413 |
| 112.5 | 260 | 1300 | 1560 | 562 |
| 150 | 320 | 1600 | 1920 | 696 |
| 225 | 400 | 2300 | 2700 | 942 |
| 300 | 500 | 3000 | 3500 | 1164 |
| 500 | 700 | 5000 | 5700 | 1889 |
| 750 | 1000 | 6500 | 7500 | 2567 |
| 1000 | 1300 | 8500 | 9800 | 3221 |
| 1500 | 1900 | 10,500 | 12,400 | 4375 |
| 2000 | 2100 | 14,500 | 16,600 | 5429 |
| 2500 | 2700 | 15,500 | 18,200 | 6408 |
| 3000 | 4000 | 18,000 | 22,000 | — |

Note: Losses offered are typical only, not guaranteed.

Table 17.0-16. Envirotemp FR3 <34.5 kV Primary 55 °C Temp. Rise

| kVA | No Load at 75 °C Ref. Temp. (Watts) | Load Loss at 100% Load and 75 °C Ref. Temp. (Watts) | Total Losses at 100% Load and 85 °C (Watts) | 60–150 kV HV BIL Total Losses at 50% Load and 55 °C LL Ref. Temp. and 20 °C NL Ref. Temp. per DOE (Watts) |
|-------|-------------------------------------|---|---|---|
| 75 | 175 | 960 | 1135 | 413 |
| 112.5 | 250 | 1250 | 1500 | 562 |
| 150 | 300 | 1630 | 1930 | 696 |
| 225 | 330 | 2500 | 2830 | 942 |
| 300 | 520 | 2600 | 3120 | 1164 |
| 500 | 730 | 4900 | 5630 | 1889 |
| 750 | 1100 | 6200 | 7300 | 2567 |
| 1000 | 1500 | 6700 | 8200 | 3221 |
| 1500 | 1900 | 10,000 | 11,900 | 4375 |
| 2000 | 2600 | 12,000 | 14,600 | 5429 |
| 2500 | 2800 | 15,000 | 17,800 | 6408 |
| 3000 | 3800 | 16,000 | 19,800 | — |

Note: Losses offered are typical only, not guaranteed.

Table 17.0-17. Envirotemp FR3 <34.5 kV Primary 65 °C Temp. Rise

| kVA | No Load at 85 °C Ref. Temp. (Watts) | Load Loss at 100% Load and 85 °C Ref. Temp. (Watts) | Total Losses at 100% Load and 85 °C (Watts) | 60–150 kV HV BIL Total Losses at 50% Load and 55 °C LL Ref. Temp. and 20 °C NL Ref. Temp. per DOE (Watts) |
|-------|-------------------------------------|---|---|---|
| 75 | 190 | 950 | 1140 | 413 |
| 112.5 | 260 | 1300 | 1560 | 562 |
| 150 | 320 | 1600 | 1920 | 696 |
| 225 | 400 | 2300 | 2700 | 942 |
| 300 | 500 | 3000 | 3500 | 1164 |
| 500 | 700 | 5000 | 5700 | 1889 |
| 750 | 1000 | 6500 | 7500 | 2567 |
| 1000 | 1300 | 8500 | 9800 | 3221 |
| 1500 | 1900 | 10,500 | 12,400 | 4375 |
| 2000 | 2100 | 14,500 | 16,600 | 5429 |
| 2500 | 2700 | 15,500 | 18,200 | 6408 |
| 3000 | 4000 | 18,000 | 22,000 | — |

Note: Losses offered are typical only, not guaranteed.

Table 17.0-18. DOE 2016 Transformer Efficiencies Three-Phase Liquid Filled Transformers

| Three-Phase kVA | % Efficiency ^① |
|-----------------|---------------------------|
| 15 | 98.65 |
| 30 | 98.83 |
| 45 | 98.92 |
| 75 | 99.03 |
| 112.5 | 99.11 |
| 150 | 99.16 |
| 225 | 99.23 |
| 300 | 99.27 |
| 500 | 99.35 |
| 750 | 99.40 |
| 1000 | 99.43 |
| 1500 | 99.48 |
| 2000 | 99.51 |
| 2500 | 99.53 |

^① Based on transformer operating at 50% of nameplate base kVA.



Layout Dimensions




Figure 17.0-13. Pad-Mounted Transformer (3000–5000 kVA)—Dimensions in Inches (mm)

Table 17.0-19. Standard Unit, Oil-Immersed Rated 65 °C Rise, 3000–5000 kVA—Dimensions in Inches (mm)

| kVA | Transformer | | | Pad | | | Approximate Weight Lb (kg) | Gallons (Liters) of Oil |
|--|-----------------|-----------------|-----------------|-----------------|----------------|----------------|----------------------------|-------------------------|
| | A | B | C ① | D | E ② | F | | |
| 15 kV Class, Delta Connected HV-HV 95 kV BIL, LV 30 kV BIL ③ | | | | | | | | |
| 3000 | 76.00 (1930.4) | 119.00 (3022.6) | 100.00 (2540.0) | 74.00 (1879.6) | 72.00 (1828.8) | 58.00 (1473.2) | 12,900 (5851) | 385 (1457) |
| 3750 | 80.00 (2032.0) | 82.00 (2082.8) | 111.00 (2819.4) | 79.00 (2006.6) | 83.00 (2108.2) | 63.00 (1600.2) | 20,000 (9072) | 540 (2044) |
| 5000 | 78.00 (1981.2) | 137.00 (3479.8) | 108.00 (2743.2) | 76.00 (1930.4) | 80.00 (2032.0) | 60.00 (1524.0) | 21,500 (9752) | 565 (2139) |
| 15 kV Class, Wye Connected HV-HV 95 kV BIL, LV 30 kV BIL ③ | | | | | | | | |
| 3000 | 74.00 (1879.6) | 117.00 (2971.8) | 102.00 (2590.8) | 78.00 (1981.2) | 74.00 (1879.6) | 62.00 (1574.8) | 15,000 (6804) | 390 (1476) |
| 3750 | 97.00 (2463.8) | 81.00 (2057.4) | 101.00 (2565.4) | 81.00 (2057.4) | 77.00 (1955.8) | 65.00 (1651.0) | 21,800 (9888) | 550 (2082) |
| 5000 | 91.00 (2311.4) | 119.00 (3022.6) | 108.00 (2743.2) | 84.00 (2133.6) | 80.00 (2032.0) | 68.00 (1727.2) | 22,000 (9979) | 585 (2214) |
| 25 kV Class, Delta Connected HV-HV 150 kV BIL, LV 30 kV BIL ③ | | | | | | | | |
| 3000 | 83.00 (2108.2) | 84.00 (2133.6) | 101.00 (2565.4) | 86.00 (2184.4) | 74.00 (1879.6) | 70.00 (1778.0) | 15,400 (6985) | 515 (1949) |
| 3750 | 96.00 (2438.4) | 84.00 (2133.6) | 98.00 (2489.2) | 86.00 (2184.4) | 78.00 (1981.2) | 70.00 (1778.0) | 20,100 (9117) | 650 (2461) |
| 5000 | 101.00 (2565.4) | 101.00 (2565.4) | 107.00 (2717.8) | 84.00 (2133.6) | 79.00 (2006.6) | 68.00 (1727.2) | 22,900 (10,387) | 670 (2536) |
| 25 kV Class, Wye Connected HV-HV 125 kV BIL, LV 30 kV BIL ③ | | | | | | | | |
| 3000 | 84.00 (2133.6) | 80.00 (2032.0) | 102.00 (2590.8) | 80.00 (2032.0) | 74.00 (1879.6) | 64.00 (1625.6) | 16,300 (7394) | 450 (1703) |
| 3750 | 93.00 (2362.2) | 85.00 (2159.0) | 99.00 (2514.6) | 84.00 (2133.6) | 78.00 (1981.2) | 68.00 (1727.2) | 21,200 (9616) | 575 (2177) |
| 5000 | 90.00 (2286.0) | 110.00 (2794.0) | 108.00 (2743.2) | 84.00 (2133.6) | 80.00 (2032.0) | 68.00 (1727.2) | 23,100 (10,478) | 605 (2290) |
| 35 kV Class, Delta Connected HV-HV 200 kV BIL, LV 30 kV BIL | | | | | | | | |
| 3000 | 86.00 (2184.4) | 86.00 (2184.4) | 101.00 (2565.4) | 78.00 (1981.2) | 73.00 (1854.2) | 62.00 (1574.8) | 15,700 (7121) | 420 (1590) |
| 3750 | 86.00 (2184.4) | 82.00 (2082.8) | 102.00 (2590.8) | 82.00 (2082.8) | 76.00 (1930.4) | 66.00 (1676.4) | 19,800 (8981) | 525 (1987) |
| 5000 | 102.00 (2590.8) | 122.00 (3098.8) | 106.00 (2692.4) | 83.00 (2108.2) | 78.00 (1981.2) | 67.00 (1701.8) | 22,600 (10,251) | 580 (2196) |
| 35 kV Class, Wye Connected HV-HV 125 kV BIL, LV 30 kV BIL | | | | | | | | |
| 3000 | 82.00 (2082.8) | 86.00 (2184.4) | 101.00 (2565.4) | 78.00 (1981.2) | 73.00 (1854.2) | 62.00 (1574.8) | 15,700 (7121) | 420 (1590) |
| 3750 | 91.00 (2311.4) | 82.00 (2082.8) | 102.00 (2590.8) | 82.00 (2082.8) | 76.00 (1930.4) | 66.00 (1676.4) | 19,800 (8981) | 525 (1987) |
| 5000 | 92.00 (2336.8) | 122.00 (3098.8) | 106.00 (2692.4) | 83.00 (2108.2) | 78.00 (1981.2) | 67.00 (1701.8) | 22,600 (10,251) | 580 (2196) |
| 35 kV Class, Delta Connected HV-HV 150 kV BIL, LV 30 kV BIL | | | | | | | | |
| 3000 | 84.00 (2133.6) | 84.00 (2133.6) | 100.00 (2540.0) | 86.00 (2184.4) | 74.00 (1879.6) | 70.00 (1778.0) | 15,400 (6985) | 530 (2006) |
| 3750 | 84.00 (2133.6) | 84.00 (2133.6) | 101.00 (2565.4) | 86.00 (2184.4) | 77.00 (1955.8) | 70.00 (1778.0) | 19,300 (8754) | 630 (2385) |
| 5000 | 92.00 (2336.8) | 122.00 (3098.8) | 106.00 (2692.4) | 81.00 (2057.4) | 78.00 (1981.2) | 65.00 (1651.0) | 20,500 (9299) | 600 (2271) |
| 35 kV Class, Wye Connected HV-HV 150 kV BIL, LV 30 kV BIL | | | | | | | | |
| 3000 | 80.00 (2032.0) | 84.00 (2133.6) | 104.00 (2641.6) | 86.00 (2184.4) | 76.00 (1930.4) | 70.00 (1778.0) | 17,100 (7756) | 500 (1893) |
| 3750 | 86.00 (2184.4) | 87.00 (2209.8) | 107.00 (2717.8) | 86.00 (2184.4) | 79.00 (2006.6) | 70.00 (1778.0) | 20,600 (9344) | 560 (2120) |
| 5000 | 95.00 (2413.0) | 105.00 (2667.0) | 107.00 (2717.8) | 85.00 (2159.0) | 79.00 (2006.6) | 69.00 (1752.6) | 23,800 (10,795) | 625 (2366) |
| 35 kV Class, Wye Connected HV-HV 200 kV BIL, LV 30 kV BIL | | | | | | | | |
| 3000 | 88.00 (2235.2) | 104.00 (2641.6) | 99.00 (2514.6) | 107.00 (2717.8) | 83.00 (2108.2) | 91.00 (2311.4) | 19,800 (8981) | 720 (2725) |
| 3750 | 90.00 (2286.0) | 104.00 (2641.6) | 104.00 (2641.6) | 107.00 (2717.8) | 90.00 (2286.0) | 91.00 (2311.4) | 24,400 (11,068) | 840 (3180) |
| 5000 | 101.00 (2565.4) | 102.00 (2590.8) | 106.00 (2692.4) | 107.00 (2717.8) | 90.00 (2286.0) | 89.00 (2260.6) | 28,600 (12,973) | 920 (3483) |

① Standard compartment depth is 22.00 inches (558.8 mm) except 200 kV BIL has a depth of 30.00 inches (762.0 mm). Depth may be altered by the addition of switching and fusing.

② Extends under base of transformer only. Does not include rear coolers.

③ Standard low voltages are 480Y and 480 delta (through 3750 kVA only). Low voltage above 3750 kVA must be 2400 V or above.

Dimensions are approximate—not for construction.




Installation, Operation and Maintenance Manual

Please read and save these instructions for future reference. Read carefully before attempting to assemble, install, operate or maintain the product described. Protect yourself and others by observing all safety information. Failure to comply with these instructions will result in voiding of the product warranty and may result in personal injury and/or property damage.

Direct Drive Downblast Centrifugal Exhaust

These fans are specifically designed for roof mounted applications exhausting relatively clean air. The maximum continuous operating temperature is 130°F (54°C). Direct drive models are made with nominal wheel diameter ranging from 8 to 30 inches (203 to 762 mm) (060-300 unit sizes). Each fan shall bear a permanently affixed manufacturer's embossed metal nameplate containing the model number and individual serial number. All fans are UL/cUL Listed Standard 705.



Belt Drive Downblast Centrifugal Exhaust

These fans are specifically designed for roof mounted applications exhausting relatively clean air. The maximum continuous operating temperature is 180°F (82°C). Belt drive models are made with nominal wheel diameters ranging from 11 to 54 inches (279 to 1372 mm) (097-540 unit sizes). Each fan shall bear a permanently affixed manufacturer's embossed metal nameplate containing the model number and individual serial number. All fans are UL/cUL Listed Standard 705.

General Safety Information

Only qualified personnel should install this fan. Personnel should have a clear understanding of these instructions and should be aware of general safety precautions. Improper installation can result in electric shock, possible injury due to coming in contact with moving parts, as well as other potential hazards. Other considerations may be required if high winds or seismic activity is present. If more information is needed, contact a licensed professional engineer before moving forward.

1. Follow all local electrical and safety codes, as well as the National Electrical Code (NEC) and the National Fire Protection Agency (NFPA), where applicable. Follow the Canadian Electric Code (CEC) in Canada.
2. The rotation of the wheel is critical. It must be free to rotate without striking or rubbing any stationary objects.
3. Motor must be securely and adequately grounded.
4. Do not spin fan wheel faster than max cataloged fan RPM. Adjustments to fan speed significantly affects motor load. If the fan RPM is changed, the motor current should be checked to make sure it is not exceeding the motor nameplate amps.
5. Do not allow the power cable to kink or come in contact with oil, grease, hot surfaces or chemicals. Replace cord immediately if damaged.
6. Verify that the power source is compatible with the equipment.

7. Never open access doors to a duct while the fan is running.

DANGER

Always disconnect, lock and tag power source before installing or servicing. Failure to disconnect power source can result in fire, shock or serious injury.

CAUTION

When servicing the fan, motor may be hot enough to cause pain or injury. Allow motor to cool before servicing.

CAUTION

Precaution should be taken in explosive atmospheres.

DANGER

Pour écarter les risques d'incendie, de choc électrique ou de blessure grave, veiller à toujours débrancher, verrouiller et étiqueter la source de courant avant l'installation ou l'entretien.

ATTENTION

Lors de toute intervention sur la soufflante, le moteur peut être suffisamment chaud pour provoquer une douleur voire une blessure. Laisser le moteur refroidir avant toute maintenance.

ATTENTION

Faire preuve de précaution dans les atmosphères explosives.

Receiving

Upon receiving the product, check to ensure all items are accounted for by referencing the delivery receipt or packing list. Inspect each crate or carton for shipping damage before accepting delivery. Alert the carrier of any damage detected. The customer will make notification of damage (or shortage of items) on the delivery receipt and all copies of the bill of lading which is countersigned by the delivering carrier. If damaged, immediately contact your representative. Any physical damage to the unit after acceptance is not the responsibility of the manufacturer.


Unpacking

Verify that all required parts and the correct quantity of each item have been received. If any items are missing, report shortages to your local representative to arrange for obtaining missing parts. Sometimes it is not possible that all items for the unit be shipped together due to availability of transportation and truck space. Confirmation of shipment(s) must be limited to only items on the bill of lading.

Handling

Belt and Direct Drive Units



Lift Direct Drive unit on to the roof utilizing hooks under the lip of the shroud. Evenly space the hooks around the shroud using a minimum of four lifting straps. Use a spreader bar to ensure the straps do not come in contact with the unit (see Figure 1).



When lifting a belt drive unit on to the roof, use either the four lifting points on the drive frame or the two lifting points on the bearing plate if present (see Figure 2 for lifting points). Access to the drive frame is accomplished by removing the screws identified in Figure 3. The cover can then be removed and placed on a flat surface in an area protected from strong winds.

When direct and/or belt drive unit is on the roof, move fan to desired location using lifting points and fasten securely through mounting holes in base. Shims may be necessary depending upon roofing material thickness.

The motor amperage and voltage ratings must be checked for compatibility to supply voltage prior to final electrical connection. For direct and/or belt drive installations, the electrical supply should be routed through the conduit chase located between the curb cap and the bottom of the motor compartment. Wiring must conform to local and national codes.



Storage

Fans are protected against damage during shipment. If the unit cannot be installed and operated immediately, precautions need to be taken to prevent deterioration of the unit during storage. The user assumes responsibility of the fan and accessories while in storage. The manufacturer will not be responsible for damage during storage. These suggestions are provided solely as a convenience to the user.

Indoor - The ideal environment for the storage of fans and accessories is indoors, above grade, in a low humidity atmosphere which is sealed to prevent the entry of blowing dust, rain or snow. Temperatures should be evenly maintained between 30° to 110°F (-1° to 43°C) (wide temperature swings may cause condensation and “sweating” of metal parts). All accessories must be stored indoors in a clean, dry atmosphere.

Remove any accumulations of dirt, water, ice or snow and wipe dry before moving to indoor storage. To avoid “sweating” of metal parts, allow cold parts to reach room temperature. To dry parts and packages, use a portable electric heater to get rid of any moisture buildup. Leave coverings loose to permit air circulation and to allow for periodic inspection.

The unit should be stored at least 3½ inches (89 mm) off the floor on wooden blocks covered with moisture proof paper or polyethylene sheathing. Aisles between parts and along all walls should be provided to permit air circulation and space for inspection.

Outdoor - Fans designed for outdoor applications may be stored outdoors, if absolutely necessary. Roads or aisles for portable cranes and hauling equipment are needed.

The fan should be placed on a level surface to prevent water from leaking into the fan. The fan should be elevated on an adequate number of wooden blocks so that it is above water and snow levels and has enough blocking to prevent it from settling into soft ground. Locate parts far enough apart to permit air circulation, sunlight and space for periodic inspection. To minimize water accumulation, place all fan parts on blocking supports so that rain water will run off.

Do not cover parts with plastic film or tarps as these cause condensation of moisture from the air passing through heating and cooling cycles.

Fan wheels should be blocked to prevent spinning caused by strong winds.

Inspection and Maintenance During Storage

While in storage, inspect fans once per month. Keep a record of inspection and maintenance performed.

If moisture or dirt accumulations are found on parts, the source should be located and eliminated. At each inspection, rotate the wheel by hand ten to fifteen revolutions to distribute lubricant in motor. If paint deterioration begins, consideration should be given to touch-up or repainting. Fans with special coatings may require special techniques for touch-up or repair.

Machined parts coated with rust preventive should be restored to good condition promptly if signs of rust occur. Immediately remove the original rust preventive coating with petroleum solvent and clean with lint-free cloths. Polish any remaining rust from surface with crocus cloth or fine emery paper and oil. Do not destroy the continuity of the surfaces. Thoroughly wipe clean with Tectyl® 506 (Ashland Inc.) or the equivalent. For hard to reach internal surfaces or for occasional use, consider using Tectyl® 511M Rust Preventive, WD-40® or the equivalent.


Removing From Storage

As fans are removed from storage to be installed in their final location, they should be protected and maintained in a similar fashion until the fan equipment goes into operation.

Dimensional Data


Direct Drive

Figure 4 - Typical Roof Mounting Installation



Belt Drive

Figure 5 - Typical Roof Mounting Installation



| Model Size | Curb Cap | Damper | Roof Opening | **Approx. Weight |
|--------------------------|-----------|----------|--------------|------------------|
| 060, 070 | 17 (432) | 8 (203) | 10½ (267) | 18 (8) |
| 080, 090, 095 | 17 (432) | 10 (254) | 12½ (318) | 26 (12) |
| 097, 098, 099 | 19 (483) | 12 (305) | 14½ (368) | 57 (26) |
| 100, 103*, 100HP, 103HP* | 19 (483) | 12 (305) | 14½ (368) | 62 (28) |
| 120, 123* | 19 (483) | 12 (305) | 14½ (368) | 65 (30) |
| 130, 133* | 19 (483) | 12 (305) | 14½ (368) | 66 (30) |
| 140, 143*, 140HP, 143HP* | 22 (559) | 16 (406) | 18½ (470) | 76 (35) |
| 160, 163* | 22 (559) | 16 (406) | 18½ (470) | 80 (36) |
| 180, 183* | 30 (762) | 18 (457) | 20½ (521) | 119 (54) |
| 200, 203*, 200HP | 30 (762) | 18 (457) | 20½ (521) | 130 (59) |
| 240 | 34 (864) | 24 (610) | 26½ (673) | 158 (72) |
| 300 | 40 (1016) | 30 (762) | 32½ (826) | 320 (145) |

- All dimensions are in inches (*millimeters*).
- * Previous size, no physical product change with new size
- ** Approximate weight shown in pounds (*kilograms*) is the largest cataloged open drip proof motor.
- “Curb Cap” is the inside dimension of the curb cap.
- The roof curb should be 1½ in. (38 mm) less than the curb cap to allow for roofing and flashing.
- Roof opening is a square dimension

| Model Size | Curb Cap | Damper | Roof Opening | **Approx. Weight |
|---------------------------------|-----------|-----------|--------------|------------------|
| 071*, 097, 081*, 098, 091*, 099 | 19 (483) | 12 (305) | 14½ (368) | 58 (26) |
| 100, 101*, 100HP, 101HP* | 19 (483) | 12 (305) | 14½ (368) | 63 (29) |
| 120, 121* | 19 (483) | 12 (305) | 14½ (368) | 66 (30) |
| 130, 131* | 19 (483) | 12 (305) | 14½ (368) | 67 (30) |
| 140, 141*, 140HP, 141HP* | 22 (559) | 16 (406) | 18½ (470) | 83 (38) |
| 160, 161*, 160HP, 161HP* | 22 (559) | 16 (406) | 18½ (470) | 89 (40) |
| 180, 180HP | 30 (762) | 18 (457) | 20½ (521) | 125 (57) |
| 200, 200HP | 30 (762) | 18 (457) | 20½ (521) | 138 (63) |
| 220, 220HP, 240, 240HP | 34 (864) | 24 (610) | 26½ (673) | 158 (72) |
| 260 | 40 (1016) | 30 (762) | 32½ (826) | 305 (138) |
| 300, 300HP | 40 (1016) | 30 (762) | 32½ (826) | 320 (145) |
| 330 | 46 (1168) | 36 (914) | 38½ (978) | 385 (175) |
| 360, 360HP | 46 (1168) | 36 (914) | 38½ (978) | 403 (183) |
| 420 | 52 (1321) | 42 (1067) | 44½ (1130) | 495 (225) |
| 480 | 52 (1321) | 48 (1219) | 50½ (1283) | 623 (283) |
| 500 | 64 (1626) | 54 (1372) | 56½ (1435) | 687 (312) |
| 540 | 64 (1626) | 54 (1372) | 56½ (1435) | 748 (339) |

- All dimensions are in inches (*millimeters*).
- * Previous size, no physical product change with new size
- ** Approximate weight shown in pounds (*kilograms*) is the largest cataloged open drip proof motor.
- “Curb Cap” is the inside dimension of the curb cap.
- The roof curb should be 1½ in. (38 mm) less than the curb cap to allow for roofing and flashing.
- Roof opening is a square dimension




Installation

Typical Roof Mounting Installation


1. On the roof surface, cut an appropriate sized hole and follow manufacturer's instructions on curb installation. Caulk and flash the curb to ensure a water tight seal.

Roof Curb Installation



2. If unit is equipped with a backdraft damper, it should be installed now.
3. Remove motor cover. Access to the motor compartment is accomplished by removing the screws as shown in Figure 3, page 2.
4. On **belt drive** fans, use the lifting lugs on the drive frame or bearing plate to lift and place the unit on top of roof curb. Refer to Figure 2, page 2.
5. On **direct drive** fans, lift and place the unit on top of roof curb using hooks under the lip of the shroud. Refer to Figure 1, page 2.
6. Secure fan to curb using a minimum of eight lag screws, metal screws or other suitable fasteners. Shims may be required depending upon curb installation and roofing material.
7. Verify power line wiring is de-energized before connecting fan motor to power source.
8. Connect power supply wiring to the motor as indicated on the motor nameplate or terminal box cover. Check the power source for compatibility with the requirements of your equipment.
9. Check fan wheel for free rotation, recenter if necessary. Check setscrew(s) for tightness.
10. Check all fasteners for tightness.

11. Mount and wire safety disconnect switch under motor cover. Wire control switches at ground level, refer to Figure 6.
12. Replace motor cover.



Vari-Green Wiring

For Vari-Green wiring, refer to the Vari-Green Motor and Controls Installation, Operation and Maintenance Manual for complete wiring and operation instructions.

IMPORTANT

Installation, troubleshooting and parts replacement are to be performed only by qualified personnel. Consult and follow all applicable national, state and local codes. They will supercede this document.

Pre-Starting Checks

1. Check all fasteners and setscrews for tightness. The wheel should rotate freely and be aligned as shown in Figure 7.




Figure 7

| Model Type | | Size | Overlap in. (mm) | Gap in. (mm) |
|------------|------|---------|------------------|--------------|
| Direct | Belt | | | |
| X | — | 060-095 | — | 3/32 (2) |
| X | — | 097-163 | 1/4 (6) | — |
| — | X | 071-161 | 1/4 (6) | — |
| X | X | 180-240 | 3/8 (10) | — |
| X | — | 300 | 1/2 (13) | — |
| — | X | 260-540 | 1/2 (13) | — |

2. Wheel position is preset and the unit is test run at the factory. Movement may occur during shipment and realignment may be necessary.
3. **Belt Drive:** Centering wheel across the inlet can be accomplished by loosening the bolts holding the drive frame to the vibration isolators and repositioning the drive frame.


Direct and Belt Drive: If further alignment is needed, loosen shroud bolts and move shroud and motor to align wheel over inlet properly.

Wheel and inlet cone overlap can be adjusted by loosening the setscrews in the wheel hub and moving the wheel to the desired position. For both **direct and belt drive** models with wheel hubs and shaft pulleys utilizing a tapered bushing interface, reference page 8 for the tapered bushing removal and move the wheel to the desired position.

Fan RPM should be checked and verified with a tachometer.

4. Check wheel rotation (viewing from the shaft side) by momentarily energizing the unit. Rotation should be clockwise as shown in Figure 8 and correspond to rotation decal on the unit.

If wheel rotation is incorrect, reverse two of the wiring leads or check motor wiring for single phase. Fan RPM should be checked and verified with a tachometer.



Clockwise Rotation

Figure 8

WARNING

Correct direction of wheel rotation is critical. Reversed rotation will result in poor air performance, motor overloading and possible motor burnout.

AVERTISSEMENT

La turbine doit impérativement tourner dans le bon sens. Une rotation en sens inverse entraînerait de mauvaises performances de soufflage, une surcharge du moteur voire un grillage du moteur.

IMPORTANT

The fan has been checked for mechanical noises at the factory prior to shipment. If mechanical noise should develop, suggested corrective actions are offered in the Troubleshooting section.

IMPORTANT

Over tightening belts will cause excessive bearing wear and noise. Too little tension will cause slippage at startup and uneven wear.

Belt Drive Pre-Starting Belt Tension Checks

5. Always loosen tension enough to install belts without stretching. Do not force belt(s) see Figure 9. Forcing belts will break the cords and cause belt failure.




Figure 9

6. For units with two groove pulleys, adjust so the tension is equal in both belts.
7. If adjustments are made, it is very important to check the pulleys for proper alignment. Misaligned pulleys lead to excessive belt wear, vibration, noise and power loss, see Figure 10.




Figure 10

- Belt tension can be adjusted by loosening four fasteners on the drive frame, see Figure 11. The motor plate slides on the slotted adjusting arms and drive frame angles in the same manner.

Four (4) fasteners in total.

Identical fasteners on opposing side must also be loosened.




Figure 11

- Sizes 097-160:** Belts should be tensioned just enough to prevent slippage at full load. Belts should have a slight bow on the slack side while running at full load, see Figure 12a.




Figure 12a




Figure 12b

Sizes 180-540: Belt tension should be adjusted to allow 1/64 in. (0.397 mm) of deflection per inch of belt span. For example, a 15 in. (381 mm) belt span should have 15/64 in. (5.95 mm) (or about 1/4 in. (6 mm)) of deflection with moderate thumb pressure at mid-point between pulleys, see Figure 12b.

- The adjustable motor pulley is factory set for the RPM specified. Speed can be increased by closing or decreased by opening the adjustable motor pulley.
- Any increase in speed represents a substantial increase in the horsepower required by the unit.
- Motor amperage should always be checked to avoid serious damage to the motor when speed is varied.

Operation

- Before starting up or operating fan, check all fasteners for tightness. In particular, check the setscrews in the wheel hub (or the tapered bushing and pulleys if applicable).
- While in the OFF position or before connecting the fan to power, turn the fan wheel by hand to be sure it is not striking the venturi or any obstacle.
- Start the fan and shut it off immediately to check rotation of the wheel with directional arrow in the motor compartment, see Figure 8.
- When the fan is started, observe the operation and check for any unusual noises.
- With the system in full operation and all ductwork attached, measure current input to the motor and compare with the nameplate rating to determine if the motor is operating under safe load conditions.
- Keep inlets and approaches to fan clean and free from obstruction.

IMPORTANT

Adjust (tighten) belt tension after the first 24-48 hours of operation.

Inspection

Inspection of the fan should be conducted at the first 30 minute and 24 hour intervals of satisfactory operation.

30 Minute Interval: Inspect bolts, setscrews and motor mounting bolts. Adjust and tighten as necessary.

24 Hour Interval: Check all internal components. On belt drive units only, inspect belt alignment and tension. Adjust and tighten as necessary.

Maintenance

DANGER

Disconnect and secure to the "off" position all electrical power to the fan prior to inspection or servicing. Failure to comply with this safety precaution could result in serious injury or death.

DANGER

Pour écarter les risques de blessure grave ou de mort, débrancher et verrouiller l'alimentation électrique en position « Arrêt » avant tout contrôle ou entretien.

WARNING

This unit should be made non-functional when cleaning the wheel or housing (fuses removed, disconnect locked off).

AVERTISSEMENT

L'appareil doit être rendu non opérationnel lors du nettoyage de la turbine ou du caisson (fusibles retirés, sectionneur verrouillé).

IMPORTANT

Uneven cleaning of the wheel will produce an out of balance condition that will cause vibration in the fan.

Installation and maintenance are to be performed only by qualified personnel who are familiar with local codes and regulations and who are experienced with this type of equipment.

Motor maintenance is generally limited to cleaning and lubrication (where applicable). Cleaning should be limited to exterior surfaces only. Removing dust buildup on motor housing ensures proper motor cooling.

Greasing of motors is only intended when fittings are provided. Many fractional horsepower motors are permanently lubricated and should not be lubricated after installation. Motors supplied with grease fittings should be greased in accordance with manufacturer's recommendations. Where motor temperatures do not exceed 104°F (40°C), the grease should be replaced after 2,000 hours of running time as a general rule.

Wheels require very little attention when moving clean air. Occasionally, oil and dust may accumulate causing imbalance. When this occurs, the wheel and housing should be cleaned to ensure smooth and safe operation.

All fasteners should be checked for tightness each time maintenance checks are performed prior to restarting unit.


A proper maintenance program will help these units deliver years of dependable service.

Tapered Bushing Hub Installation and Removal

For wheel hubs and shaft pulleys utilizing a tapered bushing interface, follow this procedure for installation and removal. There are two possible setups for the tapered bushing, both have the same procedure, but orientation of the hub varies.

Tapered Bushing Removal:

1. If present, loosen the setscrew holding the bushing and shaft key in place.
2. Loosen and remove the socket head cap screws which fasten the bushing to the hub as shown in the section views and examples of Figures 13-16.



3. **Standard Mounting:** Take the two socket head cap screws that were removed and install them into the visibly threaded holes on the wheel hub.
Reverse Mounting: Install the two socket head cap screws into the visibly threaded holes of the bushing flange.
4. Once both socket head cap screws are installed, tighten them an eighth of a turn at a time, alternating between the two until the hub comes loose from the bushing.

Bushing Installation:

1. Clean all surfaces of hub and bushing to remove any oil or residue present. Do not use any lubricant to install bushing into the hub. For both standard and reverse mounting styles, the socket head cap screws are adjustable from the inlet of the fan.
2. **Standard Mounting:** Slide the bushing and shaft key onto the fan shaft followed by the wheel and hub assembly. If present, use the keyway setscrew to hold the shaft key and bushing in place but DO NOT overtighten as this can damage the bushing. Align the unthreaded holes of the hub with the threaded holes of the tapered bushing.
Reverse Mounting: Slide the wheel and hub assembly on to the fan shaft followed by the bushing and shaft key. If present, use the keyway setscrew to hold the shaft key and bushing in place but DO NOT overtighten as this can damage the bushing. Align the unthreaded holes of the tapered bushing with the threaded holes of the hub.
3. Install the two bushing socket head cap screws into the aligned holes by hand (or without excessive torque) until the heads of the socket head cap screws are seated against the mating surface.
4. Adjust the height of the wheel in the fan relative to the inlet venturi then tighten the two socket head cap screws an eighth turn at a time in an alternating fashion and reach a torque of 10 ft-lbs.

Belt and Bearing Maintenance

1. Belts tend to stretch after a period of time. They should be checked periodically for wear and tightness. When replacing belts, use the same type as supplied with the unit.
2. Matched belts should always be used on units with multi-groove pulleys.
3. For belt replacement, loosen the tensioning device enough to allow removal of the belt by hand.
4. Once installed, adjust belts as shown in “Pre-Starting Checks.”
5. To ensure tightness, check pulley setscrews. Proper keys must be in keyways.
6. Fan RPM should not be readjusted. Only use pulleys of identical size and type when replacing pulleys.
7. Shaft bearings can be classified in two groups: relubricating and non-relubricating. All non-relubricating bearings on belt drive fans are factory lubricated and require no further lubrication under normal use (between -20° to 180°F (-29° to 82°C) in a relatively clean environment).

8. On belt drive fans, the standard cast pillow block bearings are factory lubricated and are provided with external grease fittings. Annual lubrication is recommended, or more frequently if needed. See Table 2. Do not over-grease. Use only one or two shots of lubricant with a hand gun. Maximum hand gun rating is 40 psi. Rotate bearings during lubrication where good safety practice permits. Caution should be employed to prevent over packing or contamination.
9. Units installed in hot, humid or dirty locations should be equipped with special bearings. These bearings will require frequent lubrication. Caution should be employed to prevent over packing or contamination.
10. Grease fittings should be wiped clean. The unit should be in operation while lubricating bearings. Extreme care should be used around moving parts.
11. Grease should be pumped in very slowly until a slight bead forms around the seal. A high grade lithium base grease should be used. See Table 3.
12. During the first few months of operation, check bearing setscrews periodically to ensure tightness.
13. If unit is to be left idle for an extended period, remove belts and store in a cool, dry place to avoid premature belt failure.

Bearing Lubrication Schedule

NOTE: If unusual environment conditions exist (extreme temperature, moisture or contaminants) more frequent lubrication is required.

A good quality lithium base grease, conforming to NLGI Grade 2 consistency, such as those listed in Table 3 may be used.

Table 2: Suggested Fan Bearing Lubrication Intervals


| Interval (months) | Type of Service |
|-------------------|--|
| 1 to 3 | Heavy duty in dirty, dusty locations; high ambient temperatures; moisture laden atmosphere; vibration. |
| 3 to 6 | 12 to 24 hours per day, heavy duty, or if moisture is present |
| 6 to 12 | 8 to 16 hours per day in clean, relatively dry atmosphere |
| 12 to 18 | Infrequent operation or light duty in clean atmosphere |

Table 3: Grease Manufacturers


| Manufacturer | Grease (NLGI #2) |
|-----------------------|-----------------------|
| U.S. Electric Motors | Grease No. 83343 |
| Chevron U.S.A. Inc | Chevron SRI Grease #2 |
| Mobil Oil Corporation | Mobilith |
| | Mobil 532 |
| Texaco, Inc. | Premium BRB #2 |
| | Texaco Multifak #2 |
| Amoco Oil Co. | Rykon Premium #2 |
| Exxon | Unirex N2 |
| Shell | B Shell Alvania #2 |

Fan Inlet Connections


In order to ensure proper fan performance, caution must be exercised in fan placement and connection to the ventilation system. Obstructions, transitions, poorly designed elbows, improperly selected dampers, etc., can cause reduced performance, excessive noise and increased mechanical stress. For performance to be as published, the system must provide uniform and stable airflow into the fan.




Dampers must open fully. Use motorized dampers in low airflow applications to reduce losses.



Avoid sharp turns or entrance conditions which cause uneven flow. Use turning vanes in elbows to reduce adverse effects.



Provide uniform airflow at fan inlet and through the damper to ensure optimum performance. Curb cap should be three wheel diameters from the radius. Use turning vanes in duct when possible.



Provide uniform airflow at fan inlet to ensure optimum performance.

Parts List

Each fan bears a manufacturer's nameplate with model number and serial number. This information will assist the local representative and the factory in providing service and replacement parts. Before taking any corrective action, make certain unit is not capable of operation during repairs.


CAUTION

A fan manufactured with an explosion resistant motor does not certify the entire unit to be explosion proof. Refer to UL Listing mark for the fans approved usage.


CAUTION

La présence d'un moteur antidéflagrant sur un ventilateur ne garantit pas que tout l'appareil est antidéflagrant. Pour connaître les emplois autorisés de l'appareil, voir son marquage de conformité UL.

Direct Drive



Belt Drive



Troubleshooting

WARNING

Before taking any corrective action, make certain unit is not capable of operation during repairs.


AVERTISSEMENT

Avant d'entreprendre toute action corrective, s'assurer que l'appareil ne pourra pas fonctionner durant les réparations.


| PROBLEM | CAUSE | CORRECTIVE ACTION |
|------------------------------|--------------------------------------|---|
| Excessive noise or vibration | Wheel rubbing inlet | Adjust wheel and/or inlet cone. Tighten wheel hub or bearing collars on shaft. |
| | V-belt drive | Tighten pulleys on motor/fan shaft. Adjust belt tension. Align pulleys properly, see page 6, Figures 9 and 10. Replace worn belts or pulleys. |
| | Bearings | Replace defective bearing(s). Lubricate bearings. Tighten collars and fasteners. |
| | Wheel unbalance | Clean all dirt off wheel. Check wheel balance, rebalance in place if necessary. |
| | Belts too tight or too loose | Adjust tension, see page 7, Figure 12a-b. |
| | Wheel improperly aligned and rubbing | Center wheel on inlet, see page 6, Figure 7. |
| | Loose drive or motor pulleys | Align and tighten. See "Pre-Starting Checks", see page 6 and 7. |
| | Foreign objects in wheel or housing | Remove objects, check for damage or unbalance. |
| | Fan base not securely anchored | Secure properly. |
| | Motor hood loose and rattling | Tighten fasteners to secure the motor hood. |
| | Defective or loose motor bearings | Replace motor with same frame size, RPM-HP. |
| High horsepower | Fan | Check rotation of wheel, see page 6, Figure 8. Reduce fan speed. |
| | Duct system | Resize ductwork. Check proper operation of face and bypass dampers. Check filters and access doors. |
| Fan does not operate | Electrical supply | Check fuses/circuit breakers. Check for switches off. Check for correct supply voltage. |
| | Drive | Check for broken belts. Tighten loose pulleys or belts. |
| | Motor | Ensure motor is correct horsepower and not tripping overload protector. |
| Motor overloads or overheats | Lubrication | Check for excessive or insufficient grease in the bearing. |
| | Mechanical | Replace damaged bearing. Relieve excessive belt tension. Align bearings. Check for bent shaft. |
| | Belt slippage | Adjust tension or replace bad belts, see pages 6 and 7. |
| | Over/Under line voltage | Contact power company. |
| | Incorrect wheel rotation | Check motor wiring, see page 5, Figure 4. Confirm wheel rotation, see page 6, Figure 8. |
| | Wheel RPM too high | Check drives or slow down fan by opening variable pitch pulley on motor shaft. |
| | Undersized motor | Check motor ratings with catalog speed and air capacity chart. |
| | Motor wired incorrectly | Check motor wiring to wiring diagram located on fan motor. |
| Reduced airflow | System resistance too high | Check system: Proper operation of backdraft or control dampers, obstruction in ductwork, clean dirty filters. |
| | Unit running backwards | Correct as shown on page 6, Figure 8. |
| | Excessive dirt buildup on wheels | Clean wheel. |
| | Improper wheel alignment | Center wheel on inlet, see "Pre-Starting Checks" on page 6. |
| | Dampers closed | Inspect and repair. |
| | Blocked duct/clogged filter | Clean or replace. |
| | Belt slippage | Replace and adjust tension. |
| | Speed too slow | Check for correct drives. |

Mounting for Severe Duty Installations

Fan to Curb Mounting: 5/16-inch self-drilling fasteners are to be installed on each side of fan with one fastener 4 inches from each edge and one fastener in the center. Fasteners are to be equally spaced.





| Fan Size | Fasteners Per Side |
|------------|--------------------|
| ≤ 163 | 3 |
| 180 to 240 | 5 |
| ≥ 260 | 9 |



Roof Curb
Model GPF, GPFHL, GPFHD or Equivalent
18 ga. min.
High wind ratings – 42 in. Tall Max
Seismic ratings – 24 in. Tall Max
Steel Welded Construction

Curb to Deck Mounting: Fasteners need to be located on all four sides of the curb.



Timber Anchoring

| High Wind Ratings | | | | | Seismic Ratings | | |
|-------------------|------------------------------------|--------------------------|-----------|-------|-----------------|-----------|-------|
| Fan Size | Curb Cap Size | Self-Drilling Screw Size | Fasteners | | Fan Size | Fasteners | |
| | | | Per Side | Total | | Per Side | Total |
| Concrete | ≤ 143 (432x432 to 559x559 mm) | 3/8" | 3 | 12 | 060-300 | 2 | 8 |
| | > 143 (660x660 to 1016x1016 mm) | | 3 | 12 | 330-540 | 3 | 12 |
| Steel | ≤ 143 (432x432 to 559x559 mm) | 1/4" - 14 | 3 | 12 | 060-300 | 2 | 8 |
| | > 143 (660x660 to 1016x1016 mm) | | 4 | 16 | 330-540 | 3 | 12 |
| Timber | ≤ 143 (432x432 to 559x559 mm) | 3/8" | 3 | 12 | 060-300 | 2 | 8 |
| | > 143 (660x660 to 1016x1016 mm) | | 4 | 16 | 330-540 | 3 | 12 |

All dimensions are in inches (millimeters).

NOTE: Installation instructions for seismic ratings are only recommendations.

Final design must be determined by Structural Engineer of Record (SEOR) including requirements for curb construction, mounting of unit to curb and mounting of curb to structure.

Our Commitment

As a result of our commitment to continuous improvement, Greenheck reserves the right to change specifications without notice.

Specific Greenheck product warranties are located on greenheck.com within the product area tabs and in the Library under Warranties.

Greenheck Centrifugal Roof Downblast Exhaust Fans catalog provides additional information describing the equipment, fan performance, available accessories, and specification data.

AMCA Publication 410-96, Safety Practices for Users and Installers of Industrial and Commercial Fans, provides additional safety information. This publication can be obtained from AMCA International, Inc. at www.amca.org.



Job Name/Location

Tag #:

| | | |
|--------------------------|----------------------------------|----------|
| Date: | For: File | Resubmit |
| PO No.: | Approval | Other |
| Architect: | GC: | |
| Engr: | Mech: | |
| Rep: | | |
| <small>(Company)</small> | <small>(Project Manager)</small> | |



ARUN024GSS4
Multi V™ S Heat Pump
2.0 Ton Outdoor Unit

Performance:

Cooling Mode:

| | |
|-------------------------------|--------|
| Rated Capacity (Btu/h) | 24,000 |
| Power Input ¹ (kW) | 1.52 |

Heating Mode:

| | |
|-------------------------------|--------|
| Rated Capacity (Btu/h) | 27,000 |
| Power Input ¹ (kW) | 2.02 |

Rated Capacity is based on the following conditions:

| | |
|---------------------------|----------------------------|
| Cooling | Heating: |
| Indoor: 80°F DB / 67°F WB | Indoor: 70°F DB |
| Outdoor: 95°F DB | Outdoor: 47°F DB / 43°F WB |

Electrical:

| | |
|-----------------------|-------------------|
| Power Supply (V/Hz/Ø) | 208-230V / 60 / 1 |
| MOP (A) | 30 |
| MCA (A) | 19.6 |
| Rated Amps (A) | |
| Compressor (A) | 15.3 |
| Fan (A) x Qty. | 0.5 x 1 |

Piping:

| | |
|--------------------------|------------|
| Refrigerant Charge (lbs) | 4 |
| Liquid Line (in, OD) | Ø3/8 Flare |
| Vapor Line (in, OD) | Ø5/8 Flare |

Standard Features:

- Night Quiet Operation
- Fault Detection and Diagnosis

Optional Accessories:

- Low Ambient Baffle Kit - ZLABGP04A (1 required)
- Drain Pan Heater - PQSH1200

***Installation of an optional Low Ambient Wind Baffle Kit will allow operation down to -9.9°F in cooling mode.**

Operating Range:

| | |
|------------------|-----------|
| Cooling (°F DB)* | 23 - 122 |
| Heating (°F WB) | -4 to +61 |

Unit Data:

| | |
|---|----------|
| Refrigerant Type | R410A |
| Refrigerant Control | EEV |
| Max Number of Indoor Units ² | 4 |
| Sound Pressure ³ dB(A) | 50 |
| Net Unit Weight (lbs) | 159 |
| Shipping Weight (lbs) | 176 |
| Communication Cable ⁴ (No x AWG) | 2 x 18 |
| Heat Exchanger Coating | GoldFin™ |

Compressor:

| | |
|------------|----------------------|
| Type | DC Inverter Starting |
| Quantity | 1 |
| Oil / Type | PVE/FVC68D |

Fan:

| | |
|---------------------|---------------------------------------|
| Type | Axial Flow Fan |
| Quantity | 1 |
| Motor / Drive | Brushless Digitally Controlled/Direct |
| Air Flow Rate (CFM) | 2,119 |

Notes:

1. For AHRI rating, refer to the AHRI website <http://www.ahridirectory.org>.
2. The combination ratio must be between 50 – 130%.
3. Sound Pressure levels are tested in an anechoic chamber under ISO Standard 3745.
4. Communication cable between ODU, IDU(s), and Central Controller must be a minimum of 2-conductor, 18 AWG, twisted, stranded, and shielded. Ensure the communication cable shield is properly grounded to the ODU chassis only. Do not ground the communication cable at any other point. Wiring must comply with all applicable local and national codes.
5. Nominal data is rated 0 ft above sea level, with 25 ft of refrigerant line per indoor unit and a 0 ft level difference between outdoor and indoor units. All capacities are net with a combination ratio between 95-105%.
6. Power wiring cable size must comply with the applicable local and national codes.
7. The voltage tolerance is ± 10%.

**ROOF TOP CONDENSER
SCREENED-IN ON ROOF TOP ALL BUILDINGS**



ARUN024GSS4

Multi V™ S Heat Pump


2.0 Ton Outdoor Unit



Tag No.: _____

Date: _____

PO No.: _____



| Symbols | | Note | |
|---------|------------------------------------|------|--|
| ▶ | Piping Direction | 1. | Unit should be installed in compliance with the installation manual in the product box. |
| ◀ | Datum line | 2. | Unit should be grounded in accordance with the local regulations or applicable national codes. |
| □ | Datum line | 3. | All electrical components and materials to be supplied from the site must comply with the local regulations or international codes. |
| | | 4. | Electric characteristics chapter should be considered for electrical work and design. Especially the power cable and circuit breaker should be selected in accordance with that. |
| 5 | Handle | | |
| 4 | Liquid Pipe Connection | | |
| 3 | Gas Pipe Connection | | |
| 2 | Power and communication cable Hole | | |
| 1 | Air Outlet | | |
| No. | Part Name | | Description |

[Unit: inch]

**ROOF TOP CONDENSER
SCREENED-IN ON ROOF TOP ALL BUILDINGS**

Job Name/Location: _____

ARUN024GSS4

Multi V™ S Heat Pump

2.0 Ton Outdoor Unit



Tag No.: _____

Date: _____

PO No.: _____

AHRI Data:

| AHRI Certified Reference Number | Indoor Type | AHRI Certified Ratings - Cooling Capacity (95°F) | AHRI Certified Ratings - EER (95°F) | AHRI Certified Ratings - SEER | AHRI Certified Ratings - High Heating Capacity (47°F) | AHRI Certified Ratings - Low Heating Capacity (17°F) | AHRI Certified Ratings - HSPF |
|---------------------------------|--|--|-------------------------------------|-------------------------------|---|--|-------------------------------|
| 10070562 | Non-Ducted Indoor Units | 24,000 | 10.70 | 17.00 | 27,000 | 18,000 | 10.00 |
| 10070563 | Ducted Indoor Units | 24,000 | 12.20 | 15.80 | 27,000 | 17,000 | 8.60 |
| 10271658 | Mixed Ducted and Non-Ducted Indoor Units | 24,000 | 11.45 | 16.40 | 27,000 | 17,500 | 9.30 |

**ROOF TOP CONDENSER
SCREENED-IN ON ROOF TOP ALL BUILDINGS**



Trane Precedent Gas/Electric Packaged Rooftop

Unit Overview - YSC036G3*M***P0B0A1B000A0000000000000000

| Application | Unit Size | Supply Fan | | External Dimensions (in.) | | | Weight | | EER | IEER/SEER | Elevation |
|-------------------------|-------------|------------|--------------------------|---------------------------|---------|---------|----------|----------|----------|-----------|-----------|
| DX cooling, gas heat | 3 Ton (036) | Airflow | External Static Pressure | Height | Width | Length | Minimum | Maximum | 12.0 EER | 14.00 | |
| | | 1200 cfm | 0.726 in H2O | 3.41 ft | 3.69 ft | 5.82 ft | 472.0 lb | 747.0 lb | | | |

Unit Features

Fresh Air Selection Low Leak Econ-comp enthalpy 0-100%/BR 3p



Unit Electrical

Voltage/phase/hertz 208-230/60/3
MCA 20.00 A
MOP 30.00 A

**ROOF TOP UNIT
 SCREENED-IN ON ROOF TOP ALL BUILDINGS**

Cooling Section

| Cooling Section | | Capacity | |
|-------------------------------------|---------|--------------------------------|-----------|
| Entering Dry Bulb | 77.80 F | Gross Total | 37.50 MBh |
| Entering Wet Bulb | 67.60 F | Gross Sensible | 25.96 MBh |
| Ambient Temp | 95.00 F | Net Total | 35.80 MBh |
| Leaving Coil Dry Bulb | 57.80 F | Net Sensible | 24.26 MBh |
| Leaving Coil Wet Bulb | 57.80 F | Fan Motor Heat | 1.70 MBh |
| Leaving Unit Dry Bulb | 60.08 F | Refrig Charge-circuit 1 | 3.2 lb |
| Leaving Unit Wet Bulb | 58.67 F | | |
| Refrigeration System Options | | | |
| Leaving Dew Point | 57.81 F | | |

Heating Section

| | |
|---|-----------|
| Heat Type | Gas Heat |
| Heating Stages | 2 |
| Output Heating Capacity | 81.00 MBh |
| Output Heating Capacity with Fan | 82.71 MBh |
| Heating EAT | 60.00 F |
| Heating LAT | 122.70 F |
| Heating Temp Rise | 62.70 F |

Fan Section

| Indoor Fan Data | | Outdoor Fan Data | |
|-------------------------------------|----------------|--------------------------------|-----------|
| Type | FC Centrifugal | Type | Propeller |
| Drive Type | Direct | Fan Quantity | 1 |
| Evap Fan FLA | 5.70 A | Drive Type | Direct |
| Indoor Fan Performance | | Outdoor Fan Performance | |
| Airflow | 1200 cfm | Condenser Fan FLA | 1.10 A |
| Design ESP | 0.726 in H2O | | |
| Component SP | 0.210 in H2O | | |
| Total SP | 0.952 in H2O | | |
| Supply Motor Horsepower | 0.750 hp | | |
| Indoor Motor Operating Power | 0.57 bhp | | |
| Indoor Motor Power | 0.42 kW | | |
| Indoor RPM | 1061 rpm | | |
| Indoor Fan FLA | 1.10 A | | |

Compressor Section

| | |
|----------------------|---------|
| Power | 2.45 kW |
| Circuit 1 RLA | 10.40 A |
| Circuit 2 RLA | 0.00 A |

Accessories

Roof curb yes



Acoustics

| Sound Path | 63 Hz | 125 Hz | 250 Hz | 500 Hz | 1 kHz | 2 kHz | 4 kHz | 8 kHz |
|------------------|-------|--------|--------|--------|-------|-------|-------|-------|
| Ducted Discharge | 90 dB | 73 dB | 68 dB | 61 dB | 59 dB | 55 dB | 52 dB | 45 dB |
| Ducted Inlet | 89 dB | 73 dB | 62 dB | 54 dB | 50 dB | 47 dB | 45 dB | 39 dB |
| Outdoor Noise | 79 dB | 85 dB | 79 dB | 79 dB | 77 dB | 71 dB | 67 dB | 58 dB |



Note: Ducted Inlet and Ducted Discharge Sound Power Levels are in accordance with AHRI 260.

Note: Outdoor Sound Power Levels are in accordance with AHRI 270.

Warranty

| | |
|--------------------|-------------------------|
| Labor (first year) | 1st Year Labor warranty |
|--------------------|-------------------------|



**ROOF TOP UNIT
SCREENED-IN ON ROOF TOP ALL BUILDINGS**



- NOTES:
 1. THRU -THE -BASE GAS AND ELECTRICAL IS NOT STANDARD ON ALL UNITS.
 2. VERIFY WEIGHT, CONNECTION, AND ALL DIMENSION WITH INSTALLER DOCUMENTS BEFORE INSTALLATION

**ROOF TOP UNIT
 SCREENED-IN ON ROOF TOP ALL BUILDINGS**

PLAN VIEW UNIT
 DIMENSION DRAWING




HORIZONTAL
 AIR FLOW

PACKAGED GAS / ELECTRICAL
 DIMENSION DRAWING




**ROOF TOP UNIT
SCREENED-IN ON ROOF TOP ALL BUILDINGS**




ISOMETRIC-PACKAGED COOLING

**ROOF TOP UNIT
 SCREENED-IN ON ROOF TOP ALL BUILDINGS**



PANEL
ACCESS SIDE

CONDENSER
COIL SIDE



PANEL
ACCESS SIDE

- NOTES:
1. THRU -THE -BASE GAS AND ELECTRICAL IS NOT STANDARD. VERIFY OPTION IN PRODUCT DATA IN THIS DOCUMENT.
 2. VERIFY WEIGHT, CONNECTION, OPTION CONFIGURATION AND ALL DIMENSION WITH INSTALLER DOCUMENTS BEFORE INSTALLATION

THRU THE BASE ELECTRICAL
 PLAN / ISO VIEW DRAWING



ELECTRICAL / GENERAL DATA

| | | | |
|--|--|---|--|
| GENERAL (2)(4)(6) Model: YSC036G Oversized Motor Unit Operating Voltage: 187-253 Unit Primary Voltage: 208 Unit Secondary Voltage: 230 Unit Hertz: 60 Unit Phase: 3 EER/SEER: 12.0/14.0 Standard Motor MCA: 20.0 MFS: 30.0 MCB: 30.0 | | HEATING PERFORMANCE HEATING - GENERAL DATA Heating Model: Medium Heating Input (BTU): 100,000/70,000 Heating Output (BTU): 81,000/56,700 No. Burners: 3 No. Stages: 2 Gas Inlet Pressure Natural Gas (Min/Mix): 4 1/2"/14" LP (Min/Max): 11"/14" Gas Pipe Connection Size: 1/2" | |
| INDOOR MOTOR Standard Motor Number: 1 Horsepower: 0.75 Motor Speed (RPM): -- Phase: 1 Full Load Amps: 5.7 | | Oversized Motor Number: N/A Horsepower: N/A Motor Speed (RPM): N/A Phase: N/A Full Load Amps: N/A | |
| COMPRESSOR Circuit 1/2 Number: 1 Horsepower: 2.8 Phase: 3 Rated Load Amps: 10.4 73.0 | | OUTDOOR MOTOR Number: 1 Horsepower: 0.25 Motor Speed (RPM): 1100 Phase: 3 Full Load Amps: 1.1 3.6 | |
| POWER EXHAUST ACCESSORY (3,7) (Field Installed Power Exhaust) Phase: N/A Horsepower: N/A Motor Speed (RPM): N/A Full Load Amps: N/A Locked Rotor Amps: N/A | | FILTERS Type: Throwaway Furnished: Yes Number: 2 Recommended: 20"x35"x2" | |
| | | REFRIGERANT (2) Type Factory Charge Circuit #1: 3.2 lb Circuit #2: N/A | |


NOTES:

1. Maximum (HACR) Circuit Breaker sizing is for installations in the United States only.
2. Refrigerant charge is an approximate value. For a more precise value, see unit nameplate and service instructions.
3. Value does not include Power Exhaust Accessory.
4. Value includes oversized motor.
5. Value does not include Power Exhaust Accessory.
6. EER is rated at AHRI conditions and in accordance with DOE test procedures.
7. Installation of this power exhaust kit will affect unit level MCA and could affect MOP sizing having a direct impact on existing field wiring and unit protection devices. The change in MCA/MOP is the sole responsibility of the field installing party. Trane will not issue new nameplates as a result of this power exhaust accessory installation. FLA of the power exhaust kit option must be added to the MCA of the unit for building supply conductor sizing determination.

ROOF TOP UNIT
 SCREENED-IN ON ROOF TOP ALL BUILDINGS




CLEARANCE FROM TOP OF UNIT 72"



PACKAGED GAS / ELECTRIC

CLEARANCE








PACKAGED GAS / ELECTRIC

DOWNFLOW TYPICAL ROOF OPENING

**ROOF TOP UNIT
SCREENED-IN ON ROOF TOP ALL BUILDINGS**



NOTES:
1. VERIFY WEIGHT, CONNECTION, AND ALL DIMENSION WITH INSTALLER DOCUMENTS BEFORE INSTALLATION




ROOF TOP CURB (BAYCURB042)
ACCESSORY

**ROOF TOP UNIT
SCREENED-IN ON ROOF TOP ALL BUILDINGS**




Downflow Duct Connections - Field Fabricated
All Flanges - 1 1/4"




**ROOF TOP UNIT
SCREENED-IN ON ROOF TOP ALL BUILDINGS**

DUCT CONNECTIONS
ACCESSORY



**ROOF TOP UNIT
 SCREENED-IN ON ROOF TOP ALL BUILDINGS**



LOW LEAK ECONOMIZER HOOD
 ACCESSORY



Trane Precedent Gas/Electric Packaged Rooftop

Unit Overview - YSC120H3*H***P7B0A1B000A0000000000000000

| Application | Unit Size | Supply Fan | | External Dimensions (in.) | | | Weight | | EER | IEER/SEER | Elevation |
|-------------------------|-----------|------------|--------------------------|---------------------------|---------|---------|-----------|-----------|----------|-----------|-----------|
| DX cooling, gas heat | 10 Ton | Airflow | External Static Pressure | Height | Width | Length | Minimum | Maximum | 11.2 EER | 12.70 | |
| | | 3850 cfm | 1.080 in H2O | 3.91 ft | 4.44 ft | 7.39 ft | 1058.0 lb | 1384.0 lb | | | |

Unit Features

| | |
|-----------------------------------|--|
| Fresh Air Selection | Low Leak Econ-comp enthalpy 0-100%/BR 3p |
| SupplyFan/Drive/ MotorType | Multi speed fan |

Unit Electrical

| | |
|----------------------------|--------------|
| Voltage/phase/hertz | 208-230/60/3 |
| MCA | 49.00 A |
| MOP | 60.00 A |



ROOF TOP UNIT
 SCREENED-IN ON ROOF TOP ALL BUILDINGS

Cooling Section

| Cooling Section | | Capacity | |
|-------------------------------------|---------|--------------------------------|------------|
| Entering Dry Bulb | 77.40 F | Gross Total | 116.81 MBh |
| Entering Wet Bulb | 67.70 F | Gross Sensible | 80.26 MBh |
| Ambient Temp | 95.00 F | Net Total | 109.28 MBh |
| Leaving Coil Dry Bulb | 58.10 F | Net Sensible | 72.72 MBh |
| Leaving Coil Wet Bulb | 58.09 F | Fan Motor Heat | 7.53 MBh |
| Leaving Unit Dry Bulb | 60.20 F | Refrig Charge-circuit 1 | 5.6 lb |
| Leaving Unit Wet Bulb | 58.88 F | Refrig Charge-circuit 2 | 4.4 lb |
| Refrigeration System Options | | | |
| Leaving Dew Point | 58.08 F | | |

Heating Section

| | |
|---|------------|
| Heat Type | Gas Heat |
| Heating Stages | 2 |
| Output Heating Capacity | 200.00 MBh |
| Output Heating Capacity with Fan | 207.53 MBh |
| Heating EAT | 61.90 F |
| Heating LAT | 110.20 F |
| Heating Temp Rise | 48.30 F |

Fan Section

| Indoor Fan Data | | Outdoor Fan Data | |
|-------------------------------------|-----------------|--------------------------------|-----------|
| Type | BC Plenum | Type | Propeller |
| Drive Type | Variable Direct | Fan Quantity | 1 |
| Evap Fan FLA | 7.30 A | Drive Type | Direct |
| Indoor Fan Performance | | Outdoor Fan Performance | |
| Airflow | 3850 cfm | Outdoor Motor Power | 0.65 kW |
| Design ESP | 1.080 in H2O | Condenser Fan FLA | 3.30 A |
| Component SP | 0.731 in H2O | | |
| Total SP | 1.842 in H2O | | |
| Supply Motor Horsepower | 2.750 hp | | |
| Indoor Motor Operating Power | 2.65 bhp | | |
| Indoor Motor Power | 1.97 kW | | |
| Indoor RPM | 1594 rpm | | |
| Indoor Fan FLA | 3.30 A | | |

Compressor Section

| | |
|----------------------|---------|
| Power | 8.55 kW |
| Circuit 1 RLA | 19.60 A |
| Circuit 2 RLA | 13.10 A |

Accessories

| | |
|------------------|-----|
| Roof curb | yes |
|------------------|-----|



Acoustics

| Sound Path | 63 Hz | 125 Hz | 250 Hz | 500 Hz | 1 kHz | 2 kHz | 4 kHz | 8 kHz |
|------------------|-------|--------|--------|--------|-------|-------|-------|-------|
| Ducted Discharge | 85 dB | 87 dB | 85 dB | 79 dB | 75 dB | 71 dB | 71 dB | 65 dB |
| Ducted Inlet | 83 dB | 79 dB | 83 dB | 68 dB | 60 dB | 63 dB | 64 dB | 54 dB |
| Outdoor Noise | 91 dB | 86 dB | 90 dB | 86 dB | 82 dB | 78 dB | 73 dB | 67 dB |


Note: Ducted Inlet and Ducted Discharge Sound Power Levels are in accordance with AHRI 260.

Note: Outdoor Sound Power Levels are in accordance with AHRI 270.


Warranty

| | |
|--------------------|-------------------------|
| Labor (first year) | 1st Year Labor warranty |
|--------------------|-------------------------|

**ROOF TOP UNIT
SCREENED-IN ON ROOF TOP ALL BUILDINGS**





PACKAGED GAS / ELECTRICAL



- NOTES:
1. THRU -THE -BASE ELECTRICAL IS NOT STANDARD ON ALL UNITS.
 2. VERIFY ALL DIMENSIONS WITH INSTALLER DOCUMENTS BEFORE INSTALLATION.

PLAN VIEW UNIT
 DIMENSION DRAWING



PACKAGED GAS / ELECTRICAL
 DIMENSION DRAWING

**ROOF TOP UNIT
 SCREENED-IN ON ROOF TOP ALL BUILDINGS**



ELECTRICAL / GENERAL DATA

| | | | |
|--|---|---|--|
| GENERAL (2)(4)(6) Model: YSC120H Oversized Motor Unit Operating Voltage: 187-253 Unit Primary Voltage: 208 Unit Secondary Voltage: 230 Unit Hertz: 60 Unit Phase: 3 EER: 11.3 Standard Motor MCA: 49.0 MFS: 60.0 MCB: 60.0 | | HEATING PERFORMANCE HEATING - GENERAL DATA Heating Model: High Heating Input (BTU): 235000 / 164500 Heating Output (BTU): 188000 / 131000 No. Burners: 5 No. Stages: 2 Gas Inlet Pressure Natural Gas (Min/Mix): 4 1/2"/14" LP (Min/Max): 11"/14" Gas Pipe Connection Size: 3/4" | |
| INDOOR MOTOR Standard Motor Number: Horsepower: Motor Speed (RPM): Phase: Full Load Amps: | | Oversized Motor Number: N/A Horsepower: N/A Motor Speed (RPM): N/A Phase: N/A Full Load Amps: N/A | |
| COMPRESSOR Circuit 1/2 Number: 2 Horsepower: 4.8/3.7 Phase: 3 Rated Load Amps: 19.6 / 13.1 136.0/83.1 | | OUTDOOR MOTOR Number: 1 Horsepower: 0.75 Motor Speed (RPM): 1100 Phase: 1 Full Load Amps: 3.3 12.3 | |
| POWER EXHAUST ACCESSORY (3,7) (Field Installed Power Exhaust) Phase: N/A Horsepower: N/A Motor Speed (RPM): N/A Full Load Amps: N/A Locked Rotor Amps: N/A | FILTERS Type: Furnished: Number: Recommended | | REFRIGERANT (2) Type Factory Charge Circuit #1 5.6 lb Circuit #2 4.4 lb |
| | | Throwaway Yes 4 20"x25"x2" | |






NOTES:

1. Maximum (HACR) Circuit Breaker sizing is for installations in the United States only.
2. Refrigerant charge is an approximate value. For a more precise value, see unit nameplate and service instructions.
3. Value does not include Power Exhaust Accessory.
4. Value includes oversized motor.
5. Value does not include Power Exhaust Accessory.
6. EER is rated at AHRI conditions and in accordance with DOE test procedures.
7. Installation of this power exhaust kit will affect unit level MCA and could affect MOP sizing having a direct impact on existing field wiring and unit protection devices. The change in MCA/MOP is the sole responsibility of the field installing party. Trane will not issue new nameplates as a result of this power exhaust accessory installation. FLA of the power exhaust kit option must be added to the MCA of the unit for building supply conductor sizing determination.

ROOF TOP UNIT
 SCREENED-IN ON ROOF TOP ALL BUILDINGS




NOTES:
1. VERIFY WEIGHT, CONNECTION, AND ALL DIMENSION WITH INSTALLER DOCUMENTS BEFORE INSTALLATION





ROOF TOP CURB (BAYCURB043)
ACCESSORY

**ROOF TOP UNIT
SCREENED-IN ON ROOF TOP ALL BUILDINGS**



**ROOF TOP UNIT
SCREENED-IN ON ROOF TOP ALL BUILDINGS**

ACCESSORY - DUCT CONNECTIONS



LOW LEAK ECONOMIZER HOOD
ACCESSORY

**ROOF TOP UNIT
SCREENED-IN ON ROOF TOP ALL BUILDINGS**

Assembly Instructions

Please read and save these instructions for future reference. Read carefully before attempting to assemble, install, operate or maintain the product described. Protect yourself and others by observing all safety information. Failure to comply with these instructions will result in voiding of the product warranty and may result in personal injury and/or property damage.

Standard Assembly

IMPORTANT: For high wind rated hoods, follow assembly instructions starting on page 5.




Figure 1

Step 1 – Open crates and separate parts

Open the shipping crates and separate the parts according to the size of the unit, refer to Figure 1.

Step 2 – Place BASE ENDS and BASE SIDES

Place the two base ends and the two base sides in their approximate relationship to each other, see Figure 2. Fasten together using three 1/4-20 fasteners per corner for 5 inch high base and four 1/4-20 fasteners per corner for 12 inch high base.

NOTE: Fasteners should be hand tightened only until Step 4.

On some units where the difference between the hood width and throat width is greater than 32 inches, a reinforcing plate is required in the corners of the base, refer to Figure 2, Detail A.




Figure 2

Step 3 – Attach HOOD BASE ENDS to HOOD BASE SIDES

Attach the hood support angle to the base assembly, using four 1/4-20 fasteners per angle, see Figure 3, Detail B.

On some units, two diagonal braces come pre-attached to the hood support angle. Fasten the loose end of the diagonal braces to the base assembly, using one 1/4-20 fastener per diagonal brace. See Figure 3, Detail C.




Figure 3

Step 4 – Tighten fasteners and caulk all inside corners

Tighten all fasteners. Caulk all inside corners where the base sections come together. At this point, the base may be lifted onto the roof curb before proceeding with further assembly.

Step 5 – Attach SIDE BIRDSCREEN ASSEMBLY to HOOD SUPPORT ANGLE

Attach the side bird screen assembly to the hood support angle and base assembly using four 1/4-20 x 1 inch fasteners per screen assembly, see Figure 4.




Figure 4

Step 6 – Install END BIRDSCREEN ASSEMBLY

Install the end birdscreen assembly, refer to Figure 5. Turn the birdscreen clips (which are pre-assembled to the end birdscreen assembly) so that two are under the side birdscreen frame extension and the other two are under the hood support angle. See Figure 5, Detail D.

NOTE: Loosen and tighten the birdscreen clip as necessary.




Figure 5

Step 7 – Attach HOOD RAIL ASSEMBLY to HOOD SUPPORT ANGLES

Attach the hood rail assembly to the hood support angles, using 3/8 x 3/4 inch bolt with 3/8 inch Nyloc nut at each attachment point, see Figure 6.

NOTE: Fasteners should be hand tightened only until Step 9.




Figure 6

Step 8 – Assemble HOOD PANELS to HOOD RAIL ASSEMBLY

Assemble hood panels to hood rail assembly. The hood end assembly with the “male rib” is to be installed first, see Figure 7, Detail E. Place the remaining hood panels in place, interlocking panels as you go, see Detail E. Secure each hood panel to the hood rail assembly as it is put in place, using four 12 x 3/8 inch sheet metal screws with sealing washers per hood panel. The hood end assembly with the “female rib” is to be installed last.

NOTE: Hoods over 9 feet wide are supplied with special hood clips. See Detail F. hood panels have predrilled holes for hood clip installation. Install clips as hood panels are being put in place, using one 12 x 5/8 inch sheet metal screw with sealing washer per hood clip. To install clips in the last panel, leave the end birdscreen assembly out to provide access to the underside of the hood. The end birdscreen assembly can be easily replaced after the hood is completely assembled.




Figure 7

DETAIL F

Step 9 – Tighten fasteners

Tighten all pivot bracket fasteners. **NOTE:** There may be extra fasteners.

High Wind Assembly

NOTE: Depending on the size of the hood it may be easier to assemble unit on the ground and lift to the roof assembled. This is due to the self tapping screws that need to be fastened down the center of the hood.

IMPORTANT: Do not climb on top of hood to fasten screws in the center of the hood.

Step 1 – Open crates and separate parts


Open the shipping crates and separate the parts according to the size of the unit, refer back to Figure 1, page 1.

Step 2 – Place BASE ENDS and BASE SIDES

Place the two base ends and the two base sides in their approximate relationship to each other, see Figure 2. Fasten together using three 1/4-20 fasteners per corner for 5 inch high base and four 1/4-20 fasteners per corner for 12 inch high base.

NOTE: Fasteners should be hand tightened only until Step 4.


On some units where the difference between the hood width and throat width is greater than 32 inches, a reinforcing plate is required in the corners of the base. Refer to Figure 2, Detail A.



Step 3 – Attach HOOD BASE ENDS to HOOD BASE SIDES

Attach the hood support angle to the base assembly, using four 1/4-20 fasteners per angle, see Figure 3, Detail B.

On some units, two diagonal braces come pre-attached to the hood support angle. Fasten the loose end of the diagonal braces to the base assembly, using one 1/4-20 fastener per diagonal brace. See Figure 3, Detail C.



Step 4 – Tighten fasteners and caulk all inside corners

Tighten all fasteners. Caulk all inside corners where the base sections come together.

Step 5 – Attach SIDE BIRDSCREEN ASSEMBLY TO HOOD SUPPORT ANGLE

Attach the side bird screen assembly to the hood support angle and base assembly using four 1/4-20 x 1 inch fasteners per screen assembly, see Figure 4.




Figure 4

Step – 6 Install END BIRDSCREEN ASSEMBLY

Install the end birdscreen assembly, refer to Figure 5. Turn the birdscreen clips (which are pre-assembled to the end birdscreen assembly) so that two are under the side birdscreen frame extension and the other two are under the hood support angle. See Figure 5, Detail D.

NOTE: Loosen and tighten the birdscreen clip as necessary.




Figure 5

Step – 7 HOOD RAIL ASSEMBLY

NOTE: For easier assembly and lifting elevate hood rail assembly on blocks.

Lay out hood rail assembly and hood end angles, see Figure 6. Install thread cutters (hardware kit # 415041 - 5/16-18 x 1 in.) from underneath, first through hood end angles and second hood rail assembly.

NOTE: Use a builders square to ensure the corners of the frame are as close to 90° as possible.




Figure 6

Step 8 – Install HAT CHANNEL

Place diagonal end panel supports with the formed angle running the length of the part facing out and slots next to hat channel. Fasten diagonals with whiz nut (hardware kit # 415456). Leave whiz nuts snug and DO NOT tighten. Lift hat channel into place. The diagonals will support the hat channel as it is being installed. Use thread cutters (hardware kit # 415456) to attach the hat channel to the diagonal end panel supports. Tighten whiz nuts.




Figure 7

NOTE: Adjustment of the hat channel may be needed. Ensure there is no more than an 1/8 inch gap between the hat channel and hood panel.

Step 9 – Install HOOD END PANEL (MALE RIB)

Lift the hood end panel (male rib) into place. Use the 1/4-20 x 1 thread rolling screws with washer (hardware kit # 417119) to attach hood end panel to the diagonal end panel supports at the holes in the hood end panel that line up with holes in the diagonal end panel supports.

Use four #12-14 x 1 inch self-tapping screws (hardware kit # 415450) to attach the hood panel to the hat channel. Use four #12-11 x 5/8 sheet metal screws (hardware kit # 417467) to attach the hood panel to the hood rail assembly.

USE PROVIDED HARDWARE KIT
415180 AND 415450




Figure 8

Step 10 – Install HOOD PANELS to HOOD RAIL ASSEMBLY

Place the next hood panel by interlocking each panel as shown in Figure 7, Detail E. Secure each hood panel to the hood rail assembly as it is put in place, using four #12-14 x 1 inch self-tapping screws (hardware kit # 415450) to attach the hood panel to the hat channel. Use four #12-11 x 5/8 sheet metal screws (hardware kit # 417467) to attach the hood panel to the hood rail assembly. Using quantity 10 sheet metal screws (hardware kit # 416900) with sealing washers per hood panel. Place the remaining hood panels in place with the hood end assembly with the female rib is to be installed last as shown in step 9.

IMPORTANT: Do not drive sheet metal screws all the way through both sides of the ribs as this could allow water to leak through the hood. Screws are to fasten only the first 2 layers of the rib joint.




Figure 9

Step 11 – Lift HOOD ASSEMBLY onto HOOD BASE

Lift completed hood assembly onto the hood base and attach the hood assembly to the hood support angles, using 3/8 x 3/4 inch bolt with 3/8 inch Nyloc nut at each attachment point.

Step 12 – Tighten fasteners

Tighten all pivot bracket fasteners.

NOTE: There may be extra fasteners.





Phone: 715.359.6171 • Fax: 715.355.2399 • Parts: 800.355.5354 • E-mail: gfcinfo@greenheck.com • Website: www.greenheck.com