



MISTA RANDOM

DESCRIPTION: Paver TEXTURE: Multi-textured

PALLET OVERVIEW



Permeable pavers allow for storm water drainage and manage excess runoff. The use of permeable pavers also facilitates LEED® certification easier to obtain.

NOTES


See page 62 to 64 for more technical information. When used in a permeable pavement application, see page 33 and 101 for more technical information.

See page 30 for more information about applications.


JOINT WIDTH: 3/16" TO 9/16" (4 TO 14 mm)
% OF SURFACE OPENING: 6.3 %
INFILTRATION RATE: 610 in./hr (15 505 mm/hr)

Specifications per pallet	Imperial	Metric
Cubing	116.20 ft²	10.80 m ²
Approx. Weight	3 356 lbs	1 522 kg
Number of rows	10	
Coverage per row	11.62 ft ²	1.08 m ²
Linear coverage per row	17.71 lin. ft	5.40 lin. m

	Unit dimensions	in	mm	Units/pallet
A		Height 2 3/16	65	80 units
		Width 7 3/8	200	
		Length 3 13/16	100	
B		Height 2 3/16	65	100 units
		Width 7 3/8	200	
		Length 7 3/8	200	
C		Height 2 3/16	65	90 units
		Width 7 3/8	200	
		Length 11 13/16	300	



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.



MISTA

techo-bloc.com

