

GENERAL NOTES

A REFER TO A600 SERIES FOR WINDOW AND DOOR SCHEDULE AND DETAILS.

B REFER TO REFLECTED CEILING PLANS FOR EXTERIOR SOFFIT INFORMATION. C REFER TO ROOF PLAN FOR PARAPET AND OVERHAND INFORMATION.

D SEE ELECTRICAL DRAWINGS FOR ADDITIONAL LIGHTING REQUIREMENTS AND FIXTURE TYPES. E SEE ELEVATIONS AND STRUCTURAL DRAWINGS FOR LOCATIONS OF EXPANSION AND CONTROL JOINTS. CONTRACTOR SHALL PROVIDE ADDITIONAL INTERIOR CONTROL JOINTS AS REQUIRED TO COMPLY WITH MAXIMUM SPACING REQUIREMENTS IN SPECIFICATIONS AND NATIONAL MASONRY INSTITUTE. PROVIDE CONTROL JOINTS AT ALL MASONRY REENTRANT CORNERS.

F PROVIDE BACKING AND/OR STRUCTURAL SUPPORT AS REQUIRED FOR SIGNAGE AND LIGHTING.

G EXPOSED STRUCTURAL STEEL SHALL BE GALVANIZED AND PAINTED UNLESS NOTED OTHERWISE.

RESTORATION GENERAL NOTES

H APPLY SEALANT WHENEVER DISSIMILAR MATERIALS MEET.

A. MASONRY/STONE RESTORATION CONTRACTOR ("SUBCONTRACTOR") TO PROVIDE ALL LABOR, MATERIAL, EQUIPMENT, SUPERVISION, PERMITS AND ANY OTHER COSTS OR EXPENSES NECESSARY TO COMPLETE THE WORK. SUBCONTRACTOR JOB MOBILIZATION SHALL INCLUDE, BUT NOT BE LIMITED TO, ANY NECESSARY WORK STATION AND JOB TRAILER, MAST CLIMBING PLATFORMS, AERIAL LIFTS, SWING STAGES, BARRICADES AND WALK THRU SCAFFOLD AS NEEDED.

BUILDING RESTORATION TO INCLUDE ALL TERMS, CONDITIONS AND SPECIFICATIONS OF ORIGINAL CONTRACT AND ANY ADDITIONAL WORK NECESSARY TO MEET THE SECRETARY OF THE INTERIOR STANDARDS FOR THE REHABILITATION OF HISTORIC PROPERTIES. THIS INCLUDES ALL WORK NECESSARY OVER AND ABOVE THAT SPECIFIED IN THE ARCHITECTURAL DRAWINGS AND OTHER CONSTRUCTION DOCUMENTS, INCLUDING ALL NOTES REGARDLESS OF TIME AND MATERIAL NECESSARY TO EXECUTE THIS WORK. ANY AREAS INDICATED WITHIN DRAWINGS ARE ONLY SUGGESTIVE IN NATURE . MASON TO MEET WITH ARCHITECT AND OWNER TO CONFIRM THE

C. RESTORATION CONTRACTOR SHALL INSPECT ALL EXISTING MASONRY, INCLUDING BOTH SIDES OF PARAPET FULL HEIGHT, FOR STRUCTURAL STABILITY PRIOR TO BID. REINSPECT AFTER INITIAL CLEANING OF MASONRY.

D. ALL ELEVATIONS SHALL UNDERGO COMPLETE BRICK AND CONCRETE CLEANING FROM PARAPET TO GRADE. SEE MASONRY CLEANING SPECIFICATION SECTIONS FOR DETAILS ON APPROVED CLEANING PROCEDURES, PRODUCTS, AND MANUFACTURERS.

E. CLEAN FACADE USING GENTLEST MEANS POSSIBLE TO ACHIEVE SATISFACTORY RESULTS WITHOUT CHANGING THE SURFACE OF THE MASONRY. PAY SPECIAL ATTENTION TO AREAS OF EXCESSIVE SOILING. CONTRACTOR SHALL CONDUCT TEST PATCHES TO ENSURE THE BEST AND MOST ECONOMICAL MEANS OF CLEANING. ALL MASONRY AND CONCRETE CLEANING SHALL MEET THE SECRETARY OF INTERIOR STANDARDS FOR REHABILITATION AS WELL AS ALL APPLICABLE NATIONAL PARK SERVICE TECHNICAL BRIEFS.

SURFACES TO BE PRE-WET WITH CLEAN WATER. CLEANING SOLUTIONS TO NOT REMAIN ON SURFACES FOR MORE THAN 5 MINUTES FOLLOWED IMMEDIATELY BY LOW-PRESSURE FLOOD RINSE, UNLESS NOTED OTHERWISE IN MASONRY CLEANING SPECIFICATION. CLEANING IS TO BRING MASONRY / STONE UNIT AS CLOSE AS POSSIBLE TO ORIGINAL COLOR WITHOUT BURNING OR

G CLEAN ALL STONE THAT IS TO REMAIN & LET WEATHER FOR TWO WEEKS BEFORE ANY REPLACEMENT OR PATCHING IS TO OCCUR - REPLACEMENT STONE & PATCHED AREAS TO MATCH

H. 100% OF MORTAR JOINTS TO BE VISUALLY INSPECTED. ALL MORTAR JOINTS DETERIORATED IN EXCESS OF 3/8 INCH BEYOND FACE OF MASONRY/STONE UNIT, OR EVIDENCING UNSOUNDNESS OF CRACKING WHETHER STRUCTURAL OR OTHERWISE SHALL BE REMOVED TO A DEPTH OF 1/2" MINIMUM. WRITTEN APPROVAL BY OWNER SHALL BE REQUIRED PRIOR TO COMMENCEMENT OF REPAIR BY SATISFACTORY SUBMISSION OF MOCK-UP OF PROPOSED MORTAR JOINT.

NEW MORTAR APPLIED TO ALL OPEN JOINTS SHALL BE OF NO GREATER STRENGTH THAN ORIGINAL MORTAR OR MASONRY UNITS. MORTAR COLOR, TEXTURE, CONSISTENCY AND JOINT PROFILE WILL MATCH EXISTING AS CLOSE AS POSSIBLE. APPLY NEW, TWO COMPONENT URETHANE SEALANT AT ALL JOINTS WHERE DISSIMILAR MATERIALS MEET, AND ALL SKYWARD FACING JOINTS. BACKER ROD TO BE INSTALLED IN OPEN

NO ACCELERATORS OR OTHER ADMIXTURES SHALL BE USED WITHOUT PRIOR WRITTEN OWNER APPROVAL. ENCLOSURES AND HEAT SUFFICIENT TO PROTECT MORTAR FROM FREEZING PRIOR TO

SET SHALL BE THE SOLE RESPONSIBILITY OF SUBCONTRACTOR. REPLACE/RESET LOOSE MASONRY UNITS AND REPOINT DAMAGED MORTAR JOINTS AS REQUIRED. IF NECESSARY, RECOMMEND FURTHER REHABILITATION TO ENSURE STABILITY OF EXTERIOR WALL AND PARAPET CONSTRUCTION. SEE MASONRY RESTORATION SPECIFICATIONS FOR DETAILS ON APPROVED RESTORATION PROCEDURES, PRODUCTS, AND MANUFACTURERS. ALL MASONRY

AS WELL AS ALL APPLICABLE NATIONAL PARK SERVICE TECHNICAL BRIEFS. M. ALL MASONRY/ STONE UNIT SHALL BE REPLACED WITH OWNER APPROVED MATERIAL WHEREIN SPALLING OR OTHER DETERIORATION ELIMINATED MORE THAN 5% OF THE MASONRY/ STONE UNIT (MEASURED BY ORIGINAL BRICK OR STONE FACE AREA).

RESTORATION WORK SHALL MEET THE SECRETARY OF INTERIOR STANDARDS FOR REHABILITATION

CONSTRUCTION KEYNOTES

204 DOOR

208 COPING - SEE ROOF PLAN

JOINT PRIOR TO SEALANT APPLICATION.

209 EXISTING STONE COPING - SEE ROOF PLAN 212 EXTERIOR STAIR

213 AWNING - OWNER FURNISHED 214 SCUPPER - SEE ROOF PLAN; EXISTING OVERFLOW LOCATION

217 BLADE SIGN -

218 BUILDING DIRECTORY

220 BOLLARD

224 EXTERIOR LIGHT 236 BRICK INFILL FLUSH WITH EXISTING MASONRY INDICATED BY HATCH

237 BRICK INFILL HELD BACK FROM HISTORIC MASONRY OPENING 1" MINIMUM. 238 BRICK INFILL 2 HR RATED, HELD BACK FROM HISTORIC MASONRY OPENING 1"

MINIMUM, INDICATED BY HATCH 239 PROTECTED OPENING, REFER TO LIFE SAFETY PLANS, WINDOW SCHEDULE, AND

SPECIFICATIONS

240 CONCRETE SILL TYP, REFER TO STRUCT FOR DETAIL

241 OVERHEAD DOOR 242 HISTORIC STEEL BUMPER

243 VECHICLE DRIVE THROUGH, OPEN TO BEYOND

244 TRASH CHUTE EXHAUST

245 EXISTING WATER TOWER, PNT-##

246 INFILL HISTORIC OVERFLOW 247 VECHICLE GATE - MANUALLY OPERATED

248 MAN GATE - MANUALLY OPERATED 249 CARD READER


EXTERIOR ELEVATION MATERIAL LEGEND

CONC-1 CONCRETE - GRAY

BRK-1 BRICK - EXISTING

BRK-2 ORANGE BRICK - EXISTING









THIS DOCUMENT AND THE IDEAS AND DESIGNS INCORPORATED HEREIN, AS AN DESIGN GROUP, LLC AND ARE NOT TO BE USED IN WHOLE OR IN PART FOR ANY REASON WITHOUT THE WRITTEN AUTHORIZATION OF KRAEMER DESIGN

02-21-22 SPR AND SLU SUBMISSIONS 01-31-22 **ARCH DESIGN** DEVELOPMENT PROGRESS PRINT 12-15-21

SCOPE DOCUMENTS Revision

PERMIT DATE

Project Number Sheet Title

EXTERIOR ELEVATIONS

Sheet Number

SCALE: 3/32" = 1'-0"
REFERENCE LOCATIONS: A101