

CLOPAY COMMERCIAL – MODELS 904, 904U architectural series



ALUMINUM FULL-VIEW DOORS

Clopay's Model 904 showcases a sleek design with fewer lines and angles to its appearance. With equal stile spacing, rail and stile profiles are more proportional to each other. This design provides an aesthetically pleasing appearance making it ideal in applications such as restaurants, auto dealerships and fire stations. In addition to these features, Model 904U features Intellicore® polyurethane insulated rails and stiles.

clopaycommercial.com




Frame Detail



Section Joint Seal



Reinforcing Fin (where applicable)



Model 904U*

Model 904

*Model 904U R-value 3.8 with clear insulated glass.

OPTIONS

PANEL OPTIONS




Aluminum Full-View



Solid Aluminum

FRAME/SOLID PANEL COLOR OPTIONS



*Additional cost and lead time may apply. The use of "Bronze (Painted)" is recommended due to slight color variation that may occur during the anodizing process.

CUSTOM PAINT OPTIONS


Color Blast® finish paint system or RAL Powder Coating give you thousands of color options for endless upgrades. See your Clopay Dealer for details.



Model 904U not available with RAL Powder Coat finish.



GLASS/PANEL OPTIONS



*Glass/acrylic panels may be combined with aluminum panels. Custom glass and colors available.
 †5/16" clear laminate impact rated glass is available only on 904W8/904UW8.

PERFORMANCE OPTIONS

HEAVY-DUTY HARDWARE



Double-end Hinge 3" Track High Performance Hardware

SPECIALTY PRODUCTS



Center Mullions Exhaust Port

OPTIONAL WARRANTY

Extended 8-year hardware warranty includes upgraded industrial hardware. Upgraded hardware includes 3" track and rollers, 11 gauge hinges, heavy duty brackets, solid shaft and more.



WINDCODE®



Design pressures (DP) up to 52 PSF depending on configuration. Models tested 50% greater than DP.

STANDARD SPECIFICATIONS

Max Width	24'2" (Maximum width for Model 904U is 20'2")
Max Height	20'0"
Exterior/Interior Panel Thickness	2-1/8"
Insulation	Intellicore® polyurethane (Model 904U)
R-Value*	3.8 (Model 904U with clear insulated glass)
U-Factor	0.86 (Model 904U with clear insulated glass)
Air Infiltration Rate	0.15cfm/ft²
End Stile Thickness	4.5" wide single up to 14'2" 6.5" wide double over 14'2"
Emboss	Recessed panel with smooth surface
Panel Style	Full-view or solid aluminum panel
Section Construction	6063-T5 extruded aluminum alloy

Window Style	Full-view
Glass	DSB glass, tempered glass, acrylic, thicknesses of 1/8", 1/4" and 1/2"
Solid Panels	Insulated and non-insulated aluminum panels
Wind Load	Impact rated (W8 only)
Joint Seal	Yes
Springs	10,000 cycle springs Galvanized aircraft cable with minimum 7:1 safety factor
Tracks	2" angle mount track with standard lift 3" track where applicable
Hardware	TPE astragal in corrosion-resistant retainer Commercial 10-ball steel rollers Steel step plate and lift handle 14 gauge hinges Inside slide lock for increased security
Warranty	Standard Paint – 5 Years Color Blast® finish – 5 Years Material and Workmanship – 1 Year Hardware – 1 Year

*Calculated door section R-value is in accordance with DASMA TDS-163.



For more information on these and other Clopay products, visit clopaycommercial.com. Architects and specifiers, visit architectdoorhelp.com.



©2022 Clopay Corporation. All rights reserved.



CMDC-904-19_REV1122