

AXIS P3265-LVE Dome Camera

Outdoor 2 MP dome with IR and deep learning

Featuring Lightfinder 2.0, Forensic WDR, and OptimizedIR, AXIS P3265-LVE delivers excellent image quality under any light conditions. Based on the latest Axis system-on-chip (SoC), it includes a deep learning processing unit enabling advanced features and powerful analytics based on deep learning on the edge. Thanks to AXIS Object Analytics, it offers detection and classification of humans, vehicles, and types of vehicles – all tailored to your specific needs. Featuring audio and I/O connectivity, you can integrate equipment and extend the value of your system. Furthermore, this robust, IK10-rated, outdoor-ready camera includes built-in cybersecurity to help prevent unauthorized access and safeguard your system.

- > **Excellent image quality in 2 MP**
- > **Lightfinder 2.0, Forensic WDR, OptimizedIR**
- > **Analytics with deep learning**
- > **Available with wide or tele lens**
- > **Built-in cybersecurity features**



AXIS P3265-LVE Dome Camera

Models	AXIS P3265-LVE 9 mm AXIS P3265-LVE 22 mm	Network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS ^a , HTTP/2, TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, DHCPv4/v6, ARP, SSH, SIP, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)
Camera			
Image sensor	1/2.8" progressive scan RGB CMOS	System integration	
Lens	9 mm: Varifocal, 3.4–8.9 mm, F1.8 Horizontal field of view: 100°–36° Vertical field of view: 53°–20° Minimum focus distance: 50 cm (20 in) 22 mm: Varifocal, 9–22 mm, F1.6 Horizontal field of view: 35°–15° Vertical field of view: 19°–9° Minimum focus distance: 3 m (9.84 ft) 9 mm and 22 mm: IR corrected, remote zoom and focus, P-Iris control	Application Programming Interface	Open API for software integration, including VAPIX [®] , metadata, and AXIS Camera Application Platform (ACAP); specifications at axis.com/developer-community . ACAP includes Native SDK and Computer Vision SDK. One-click cloud connection ONVIF [®] Profile G, ONVIF [®] Profile M, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX.
Day and night	Automatically removable infrared-cut filter	Onscreen controls	Day/night shift Defogging Wide dynamic range Video streaming indicator IR illumination
Minimum illumination	With Forensic WDR and Lightfinder 2.0: Color: 0.1 lux at 50 IRE, F1.8/F1.6 (9 mm/22 mm) B/W: 0 lux at 50 IRE, F1.8/F1.6 (9 mm/22 mm)	Event conditions	Analytics, external input, supervised external input, virtual inputs through API Audio: audio clip playing, audio clip currently playing Call: state, state change Device status: above operating temperature, above or below operating temperature, below operating temperature, within operating temperature, IP address removed, new IP address, network lost, system ready, ring power overcurrent protection, live stream active, 22 mm: casing open Digital audio: digital signal contains Axis metadata, digital signal has invalid sample rate, digital signal missing, digital signal okay Edge storage: recording ongoing, storage disruption, storage health issues detected I/O: digital input, manual trigger, virtual input MQTT: subscribe Scheduled and recurring: schedule Video: average bitrate degradation, day-night mode, live stream open, tampering
Shutter speed	1/66500 s to 2 s	Event actions	Overlay text, external output activation, play audio clip, zoom preset, day/night mode, flash status LED, use lights, set defog mode, set WDR mode Calls: end SIP call, make SIP call, answer call I/O: toggle I/O once, toggle I/O while the rule is active MQTT: publish Notification: email, HTTP, HTTPS, TCP, and SNMP trap Pre- and post-alarm video or image buffering for recording or upload Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email
Camera angle adjustment	9 mm: Pan ±180°, tilt ±75°, rotation ±175° 22 mm: Pan ±190°, tilt -10 to +80°, rotation ±190°	Built-in installation aids	Remote zoom and focus, straighten image, pixel counter, level grid
System on chip (SoC)			
Model	ARTPEC-8	Analytics	
Memory	1024 MB RAM, 8192 MB Flash	AXIS Object Analytics	Object classes: humans, vehicles (types: cars, buses, trucks, bikes) Features: line crossing, object in area, crossline counting ^{BETA} , occupancy in area ^{BETA} , time in area ^{BETA} Up to 10 scenarios Metadata visualized with trajectories, color-coded bounding boxes and tables Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event
Compute capabilities	Deep learning processing unit (DLPU)	Metadata	Object data: Classes: humans, faces, vehicles (types: cars, buses, trucks, bikes), license plates Confidence, position Event data: Producer reference, scenarios, trigger conditions
Video			
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main, and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	Applications	Included AXIS Object Analytics AXIS Video Motion Detection, active tampering alarm, audio detection
Resolution	1920x1080 to 160x90		
Frame rate	With WDR: 25/30 fps with power line frequency 50/60 Hz Without WDR: 50/60 fps with power line frequency 50/60 Hz		
Video streaming	Multiple, individually configurable streams in H.264, H.265, and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Low latency mode Video streaming indicator		
Multi-view streaming	Up to 2 individually cropped out view areas in full frame rate streaming		
Image settings	Saturation, contrast, brightness, sharpness, Forensic WDR: up to 120 dB depending on scene, white balance, day/night threshold, local contrast, tone mapping, exposure mode, exposure zones, defogging, barrel distortion correction, compression, rotation: 0°, 90°, 180°, 270° including Corridor Format, mirroring, dynamic text and image overlay, privacy masks, polygon privacy mask		
Pan/Tilt/Zoom	Digital PTZ, preset positions		
Audio			
Audio streaming	9 mm: Two-way, full duplex 22 mm: Audio in, simplex, two-way audio via edge-to-edge technology		
Audio encoding	24bit LPCM, AAC-LC 8/16/32/44.1/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate		
Audio input/output	9 mm: External microphone input, line input, digital input with ring power, line output, automatic gain control 22 mm: External microphone input, line input, digital input with ring power, automatic gain control, network speaker pairing		
Network			
Security	IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, user access log, centralized certificate management		

Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap

Cybersecurity	
Edge security	<p>Software: Signed firmware, brute force delay protection, digest authentication, password protection, AES-XTS-Plain64 256bit SD card encryption</p> <p>Hardware: Axis Edge Vault cybersecurity platform Secure element (CC EAL 6+), system-on-chip security (TEE), Axis device ID, secure keystore, signed video, secure boot, encrypted filesystem (AES-XTS-Plain64 256bit)</p>
Network security	IEEE 802.1X (EAP-TLS) ^a , IEEE 802.1AR, HTTPS/HSTS ^a , TLS v1.2/v1.3 ^a , Network Time Security (NTS), X.509 Certificate PKI, IP address filtering
Documentation	<p><i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM)</p> <p>To download documents, go to axis.com/support/cybersecurity/resources</p> <p>To read more about Axis cybersecurity support, go to axis.com/cybersecurity</p>
General	
Casing	<p>IP66-, NEMA 4X- and IK10-rated Polycarbonate hard coated dome Polycarbonate casing and weathershield</p> <p>Color: white NCS S 1002-B</p> <p>For repainting instructions, go to the product's support page. For information about the impact on warranty, go to axis.com/warranty-implication-when-repainting.</p>
Mounting	Mounting bracket with junction box holes (double-gang, single-gang, and 4" octagon) and for wall or ceiling mount 9 mm: 1/4"-20 UNC tripod screw thread
Sustainability	<p>9 mm: PVC free, 4.1% recycled plastics</p> <p>22 mm: PVC free, BFR/CFR free, 6.5% bioplastics</p>
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 4.8 W, max 10.7 W
Connectors	<p>RJ45 10BASE-T/100BASE-TX PoE</p> <p>I/O: 4-pin 2.5 mm (0.098 in) terminal block for 1 supervised digital input and 1 digital output (12 V DC output, max. load 25 mA)</p> <p>Audio 9 mm: 4-pin 2.5 mm (0.098 in) terminal block for audio in and out, 22 mm: 3.5 mm mic/line in</p>
IR illumination	OptimizedIR with power-efficient, long-life 850 nm IR LEDs Range of reach 40 m (130 ft)/45 m (148 ft) (9 mm/22 mm) or more depending on the scene
Storage	<p>Support for microSD/microSDHC/microSDXC card</p> <p>Support for SD card encryption (AES-XTS-Plain64 256bit)</p> <p>Recording to network-attached storage (NAS)</p> <p>For SD card and NAS recommendations see axis.com</p>
Operating conditions	<p>-40 °C to 50 °C (-40 °F to 122 °F)</p> <p>Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F)</p>

Start-up temperature: -30 °C to 50 °C (-22 °F to 122 °F)
 Humidity 10–100% RH (condensing)

Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Approvals	<p>EMC</p> <p>EN 50121-4, EN 55032 Class A, EN 55035, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), IEC 62236-4, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A</p> <p>Safety</p> <p>CAN/CSA-C22.2 No. 60950-22, CAN/CSA C22.2 No. 62368-1, IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IEC/EN 62471, IS 13252</p> <p>Environment</p> <p>IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78</p> <p>IEC/EN 60529 IP66, IEC/EN 62262 IK10, NEMA 250 Type 4X, NEMA TS2 (2.2.7-2.2.9)</p> <p>Network</p> <p>NIST SP500-267</p>
Dimensions	<p>Without weathershield:</p> <p>Height: 104 mm (4.09 in)/107 mm (4.21 in) (9 mm/22 mm) ø 149 mm (5.87 in)</p>
Weight	<p>With weathershield:</p> <p>800 g (1.8 lb)/900 g (2.0 lb) (9 mm/22 mm)</p>
Included accessories	Installation guide, Windows® decoder 1-user license, drill template, RESISTORX® T20 L-key (9 mm), RESISTORX® T20 screw bit (22 mm), terminal block connectors, cable gaskets, connector guard, weathershield
Optional accessories	<p>AXIS TP3201-E Recessed Mount, AXIS TP3103-E Pendant Kit, AXIS T94K01D Pendant Kit, AXIS T8355 Digital Microphone 3.5 mm, AXIS Surveillance Cards</p> <p>9 mm: AXIS Dome Intrusion Switch C, AXIS TP3804-E Metal Casing White, AXIS TP3802-E Clear/Smoked Dome, AXIS TP3820-E Casing Black/White</p> <p>22 mm: AXIS TP3824-E Dome Clear/Smoked, AXIS TP3821-E Casing Black/White</p> <p>For more accessories, see axis.com</p>
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese
Warranty	5-year warranty, see axis.com/warranty

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).