PREPARED BY: A. DYE

STAFF REPORT: 10-14-2020 MEETING APPLICATION NUMBER: 20-6882 ADDRESS: 1055 CLARK HISTORIC DISTRICT: HUBBARD FARMS APPLICANT: LOGESH RAJENDRAN, DMC CONSULTANTS; CITY OF DETROIT BRIDGING NEIGHBORHOODS PROGRAM PROPERTY OWNER: MONICA VEGA GRANADAS DATE OF PROVISIONALLY COMPLETE APPLICATION: 9/24/2020 DATE OF STAFF SITE VISIT: 10/02/2020


SCOPE: REPLACE EXISTING VINYL WINDOWS WITH NEW WOOD WINDOWS

EXISTING CONDITIONS

The 2-1/2 story Queen Anne structure at 1055 Clark was constructed in 1913. Sited high on the property, steps lead from the sidewalk to a raised entry porch constructed of rusticated concrete block painted gray. Cultured stone faces the walls surrounding the front entrance. Aluminum siding covers the remainder of the house, its installation covered the window casings and brick mould. Bay windows protrude from the first and second story. A front facing gable and hip roof dormer echo the roof lines of the house's hip roof. Vinyl windows are present within all of the existing window openings. A single story rear extension, whose footprint was from the date of construction, spans the width of the house.



Above photo: HDC staff, October 2, 2020. Photo on right: Applicant, date unknown.






Sanborn Map Company, Vol. 1, 1921 - Oct 1950, Sec. 102

Google Maps

The house is located within the Bridging Neighborhoods Program. Per the City of Detroit's website: The Bridging Neighborhoods I-75 Environmental Mitigation Program offers home mitigations to address noise and air quality impacts from increased truck traffic related to the Gordie Howe International Bridge Project. Eligible homes may receive some or all of the following mitigations: updated windows, updated HVAC systems, air filters, and insulation.

- Must live in either the YELLOW or GREEN zone on the <u>map</u> AND
- Must own a property that is within 300 feet of the planned I-75 Service Drive AND
- Must not have been acquired by the Michigan Department of Transportation to facilitate construction of the bridge



PROPOSAL

The applicant proposes to remove all of the existing windows within the house and install replacement windows as allowed by the Bridging Neighborhoods 1-75 Mitigation Program. Specifically, the applicant is seeking the Commission's approval to remove all existing window sash and window jambs and replace with new wood, aluminum-clad window sash as per the submitted window quote. The applicant confirmed with HDC staff the existing casings, inner stop, and brick mould will be retained/will remain in their current condition.

The dominant window style is double-hung, one-over-one, vinyl sash. The one exception is a first floor, rear elevation, sliding window.

According to the applicant's window replacement order, all the vinyl double-hung windows will be replaced with one-overone wood, aluminum-clad double-hung windows. A new wood, aluminum-clad sliding window is proposed to replace the existing sliding vinyl window.

STAFF OBSERVATIONS AND RESEARCH

- The Hubbard Farms Historic District was established in 1992.
- It is staff's opinion the aluminum siding was likely in place at the time of local historic district designation as vinyl siding did not surpass aluminum siding in popularity until the 1980s-1990s.
- It is staff's understanding the aluminum siding installation caused the wood brick mould (and window casings) to be covered in order to keep water away from the house. If the brick mould had been left exposed, water would run down the wood, travel behind the siding, and become trapped between the siding and the house.
- The HDC approved the installation of vinyl windows in 2004.
- A window opening on the rear (west) elevation appears to have been reduced in size to accommodate a sliding window. The original window opening is evident as the vinyl siding does not extend to the sliding window frame.

ISSUES

- The applicant proposes to install Weather Shield Windows, Weather Shield series. These are wood-framed units with exterior aluminum cladding.
- The applicant has not identified the exterior aluminum-cladding color.
- The applicant did not provide dimensions of the existing vinyl window frames. As the Commission would not approve vinyl windows today, staff did not request the dimensions of the existing windows. The date of construction and architectural style of the house makes it likely wood windows were present at the time of construction. Therefore, staff listed the comparison frames of the adjacent houses with wood windows (1041 and 1035 Clark) for use with this application.

Existing Wood Frames-1035 & 1041 Clark		Proposed Wood Frames		Percentage Increase	
Width of frame	2"	Width of frame	3-3/16"	62%	
Depth of frame	1-3/8"	Depth of frame	4-9/16"	200%	
Height of meeting rail	1-3/8"	Height of meeting rail	2-7/8"	100%	
Depth of meeting rail	1-3/8"	Depth of meeting rail	3-3/16"	133%	

- The window replacement includes not just the operable sash but also the window jambs. The applicant confirmed with HDC staff the casings, inner stop, and brick mould will be retained and the windows will remain covered with aluminum trim.
- The Weather Shield, wood aluminum-clad windows have substantially thicker window frames. The dimensional increase is too large and is not compatible with the scale and architectural features of the house. Therefore, it is staff's opinion the proposed windows do not meet the Secretary of the Interior Standards.

RECOMMENDATION

Staff recommends the Commission consider issuing a NOTICE TO PROCEED for the window replacement at 1055 Clark Avenue. As this property falls within the service area of the Bridging Neighborhoods I-75 Environmental Mitigation Program, the Notice to Proceed may fall under the following Condition:

2) The resource is a deterrent to a major improvement program that will be of substantial benefit to the community. Substantial benefit shall be found only if the applicant proposing the work has obtained all necessary planning and zoning approvals, financing, and environmental clearances, and the improvement program is otherwise feasible;

If a Notice to Proceed is issued, staff recommends the Commission include the following conditions:

• The existing windows will remain in place until the replacement windows are approved by Commission staff.

- The new window frame dimensions shall not increase more than ¹/₄-inch (from the existing frame dimensions).
- The operation and glass within each new window unit will match the existing window.
- Existing wood mullions, if present, will remain in place. New, single window units will be inserted into existing window openings.
- The new windows will be solid wood (exterior to be painted) **or** solid wood, aluminum-clad units. The exterior frame color will be submitted for review.
- The existing exterior wood brick mould will be retained and will remain covered with aluminum.

If any of the above conditions not be met, HDC staff will require the applicant to submit a revised proposal for the Commission's review at an upcoming meeting.







THIS IS A 3-PAGE FORM - ALL INFORMATION IS REQUIRED FOR PROJECT REVIEW

HISTORIC DISTRICT COMMISSION PROJECT REVIEW REQUEST

City of Detroit - Planning & Development Department 2 Woodward Avenue, Suite 808 Detroit, Michigan 48226

Date: 8/20/2020

PR	OPERTY INFORMATION							
ADD	DRESS: 1055 Clark Street		AKA:					
нізт	TORIC DISTRICT: Hubbard Farms							
		oof/Gutters/ himney	Porch/ Deck	Landscape Tree/Park	/Fence/	General Rehab		
	New	emolition	Addition	Other:				
AP	PLICANT IDENTIFICATION		探索和自己					
	Property Owner/ Homeowner Contractor		enant or usiness Occuj	pant	Archited	t/Engineer/ ant		
NAM	_{1E} Logesh Rajendran	_ COMPANY	NAME:	mc cor	1Sult	ads, Inc		
ADD	RESS: 13500 Foley	_ CITY:Detro	it s	TATE: MI	_ ZIP:482	209		
РНО	NE:(313) 491-1815 MOBILE:		E	MAIL: logeshr	@dmcgr	oupusa.com		
DR(OJECT REVIEW REQUEST CHE	CKLIST						
	se attach the following documentation t		:t:					
	ASE KEEP FILE SIZE OF ENTIRE SUBMIS					,		
х	x Completed Building Permit Application (highlighted portions only) Based on the scope of work,							
	ePLANS Permit Number (only applicable if you've already applied for permits through ePLANS)							
	1				See www.detroitmi.gov/hdc for scope-specific requirements.			
х	Photographs of ALL sides of existing b	building or site				irements.		
V	Detailed photographs of location of p (photographs to show existing condition	roposed work I(s), design, col	or, & material)				
x	Description of existing conditions (ir	ncluding mate	rials and desi	gn)				
x	Description of project (if replacing any existing material(s), include an explanation as to why							

replacement--rather than repair--of existing and/or construction of new is required)

Detailed scope of work (formatted as bulleted list)

Brochure/cut sheets for proposed replacement material(s) and/or product(s), as applicable

Upon receipt of this documentation, staff will review and inform you of the next steps toward obtaining your building permit from the Buildings, Safety Engineering and Environmental Department (BSEED) to perform the work.

SUBMIT COMPLETED REQUESTS TO HDC@DETROITMI.GOV

1055 Clark

City of Detroit Bridging Neighborhoods I-75 Environmental Mitigation Program



Description of Project

The Bridging Neighborhoods Program was created by City Council Resolution and approved by the Mayor on July 26, 2017.

The home for which this application was created falls within the service area of the I-75 Environmental Mitigation Program which, per Exhibit A Item H. of the resolution is required to provide a "retrofit package designed to protects occupants of the Retrofit-Eligible Home from air pollution and noise pollution.... Retrofit packages may include new windows; air filters; insulation; and/or heating, ventilation, and air conditioning systems."

Because of the requirement to provide new windows, we seek permission to replace the existing windows.

Scope of Work

 Replacing existing vinyl windows with new STC 27 wood windows. Interior casings and stops will be retained.
Exterior is covered with white aluminum trim outside (refer to the pictures attached).

Description of Existing Conditions

The property at 1055 Clark street has existing single pane, double hung vinyl windows.


As you review the provided images, you will see that these windows are in various states of repair.

The windows all have white exteriors.

Brochure/Cut Sheet

Weather Shield®


Weather Shield Series™




WEATHER SHIELD DOUBLE HUNG WINDOW (610) Horizontal Section

Double Hung Windows

CROSS SECTION DETAILS




WEATHER SHIELD DOUBLE HUNG WINDOW Horizontal Stack Section - Transom Stack over DH



WEATHER SHIELD DOUBLE HUNG WINDOW Vertical Mull Section - DH / DH

Note: All dimensions are approximate. Weather Shield reserves the right to change specifications without notice.



www.weathershield.com

REV 7/17



EXTERIOR COLOR OPTIONS

To help you get the exact look you desire, we offer an ever-expanding palette of durable and distinct exterior color options rated to the highest industry standards (AAMA 2605) for color retention. Our Premium windows and doors are available in 12 standard and 45 designer colors, 8 anodized and 4 radiant metallic colors, with unlimited custom color match aluminum finishes.



Designer Exterior Colors (AAMA 2605 premium paint)







Textured Exterior Aluminum Finishes



Finishes and colors shown may not be actual representations. Please visit an authorized Weather Shield dealer for color samples.



INTERIOR WOOD OPTIONS

Every home is different. So we give you choices to add your own special touch. Choose the wood grain and color that complement your design. Then add warmth and beauty with our factory finishes. Whether subtle or stunning, you'll find options to make a lasting impression.

Rich Wood Interiors

With eight wood species to choose from, there's sure to be one perfect for your home. For a truly unique look, other wood species are available upon request.





Durable Factory Finishes

Save time and money with our factory finishing. The wood is stained and sealed on all surfaces to repel moisture and includes two Clear Satin top coats for durability and easy cleaning.



Designer Stains

Explore our new furniture-grade stain offering created in partnership with leading paint and coatings manufacturer Sherwin-Williams®. These new stains provide clean, vivid colors with high pigmentation for excellent clarity and uniformity.

SHERWIN-WILLIAMS.

PROUDLY FINISHED WITH

7 Step Process

Our intensive seven step process creates a long-lasting premium finish that will protect and enhance the beauty of your windows and doors for years to come.

FINE SANDING WASH COAT STAIN COAT SEALER COAT BUTFING TONER COAT. CLEAR COAT COMPLETED FINISH Prepares wood to A toned wood Primary color Builds a smooth 5.rfsces are buffed This step is used to A specially formulated 2K Polyurethane accept coatings. conditioner that cost, designed to surface that looks to create an ultraeven out the color to pocat dasigned to protect from UV and fills wood pores. highlight the natural down the color and amonth surface. and add depth and scratching. beauty of the wood. provides chemical and creates an richness to the final even finish. andmosture co icr. resistance.

7 STEPS TO CREATE A FURNITURE GRADE STAIN

Finishes and colors shown may not be actual representations. Please visit an authorized Weather Shield dealer for color samples. All finishes not available on all wood spacies. Please visit an authorized Weather Shield dealer for catalis.

30

31

DOUBLE HUNG WINDOWS

Glass: Insulated Low-E with Argon

ARCHITECTURALLY INSPIRED, TECHNOLOGICALLY ADVANCED

Our double hung windows represent a one-of-a-kind approach to a popular choice in home design. With the versatility to open from the top or bottom, a breath of fresh air is never out of reach. From robust ventilation to energy efficiency and ease of use, double hung windows are a timeless classic.



Natural Finish A wood jambliner covers all mechanical balance systems to create a tailored aesthetic

Tilt and Release With concealed tilt release latches. nothing comes between you and the view. Recessed into the lock rail, this design element leaves the sash clear of all visible latch hardware.



Single Handed Ease The single dual action lock allows the sash to be unlocked and tilted easily with one hand - so you can save your energy for the things that really matter.

High Quality Exteriors

Our aluminum exterior-ciad wood products feature commercial-grade premium AAMA 2605 paint that resists fading and chalking. Extruded aluminum resists dents, dings and scratches and is backed by Weather Shield's 20-year limited warranty.

The 3-1/2" bottom rail creates clean lines and ideal architectural proportions.

The Beauty is in the Details

The rigid integral nailing fin makes installation simple and provides more durability than flimsy snap-in or fold-out fins found with other windows.

Butt jointed dadding accurately mimics traditional wood windows for a familiar aesthetic.






OUTSTANDING PERFORMANCE, EXCEPTIONAL EFFICIENCY

Selecting the right windows is crucial in determining the style and elegance of your home. We offer only top-of-the-line design and construction, so you can choose among the industry's most innovative options. State-of-the-art windows like these are an investment that pays for itself in a lifetime of reduced costs.

The Perfect Grille

Personalize your home with windows featuring a selection of bar widths and profiles, as well as traditional grille patterns and custom designs. For even greater **creativity and design** flexibility, most grilles can be manufactured from Weather Shield's custom wood interiors collection.

COTTAGE T



RECTINUUAR



ORE.




SINGLE HORZONTAL BAR

PRAIDE



PRAFIE W/ VERTICAL BAR

SMULATED DOUBLE HUNG





Innovative Design; Classic Appeal The best of modern energy efficiency meets old-world charm in Simulated Divided Lite (SDL) grilles. While minicking the look of classic single-pane windows, SDL grilles offer exterior and interior grille bars either with or without an aluminum spacer bar — translating to powerful insulation and innovation.

Framed With You in Mind

Square Interior Wood Profile

Featuring a unique **perimeter grille frame design** that rests on the inside of the unit, Weather Shield windows employ a concealed pin system to snap the perimeter grille frame securely into place. These grilles can be easily removed in order to clean the entire interior glass surface.





Grilles Between the Glass Airspace Grilles seal aluminum grille bars in either a sculpted or flat design between

two panes of glass. Resulting in a classic

aesthetic that is easy to clean and maintain.





11/16* SCULPTURED

TURED 5/8* FLAT

COTTAGE



REFLECTIONS OF QUALITY

From specialty glass to high-end glazing, our windows are truly a cut above the rest. Add color and texture options to the glass in your home while enjoying the energy efficiency and quality for which we're known best.

Gold Standard

Weather Shield Premium Series products are certified and labeled according to the highest standards, set by the Window and Door Manufacturers Association (WDMAI/National Fenestration Ratings Council (NFRC) Certification Program. Al WDMA/NFRC certified products must pass performance tests conducted by an independent lab for resistance to air leakage, water penetration and wind pressures.

Specialty Glass Options

Add color or texture - or privacy and modesty - to your palette of design options. Special finishes and tint can give a project distinction. Specialty glass includes bronze, gray, rain and obscure.



High Quality Glaze

Maximize your windows' energy efficiency with the exclusive Zo-e-shield's glazing system. With powerful layers of Low-E coating, optional EasyCare® surface costing, inert gas-filled insulating airspace, and Real Warm-Edge® spacers, our glazing options represent the ultimate in energy efficiency for any climate.

Glazing Options



Insulated Low-E

All Climate · Minimizes the sun's heat

and damaging UV rays in warmer months. · Reflects the sun's heat back into room during cooler months

· Excellent protection against damaging UV rays.

· Excellent

· Maintains great clarity

Zo-e-shield 5

Ultimate Solar Control

· Strong resistance to the

san's glating heat.

insulating value.

Zo-e-shield

Zo-e-shield Zo-e-shield 5 Plus

Laminated Interior

- · Best resistance available
- to the sun's heat
- visible light transmittance

Energy Star

As a proud ENERGY STAR® partner, Weather Shield products are rated, certified and labeled for U-Value and Solar Heat Gain by the National Fenestration Rating Council (NFRC). Many of Weather Shield® windows not only meet, but exceed ENERGY STAR® standards for energy efficient windows and doors. Using ENERGY STAR® windows can also help you save money through various tax rebates and incentives.

Plus Room Side Low-E

· Compination of two

energy off clency

· Significantly incroved

· Complies with northern

interior LoE i89 coating


Energy Star guidelinas with

los-e cortings





The ENERGY STAR® criteria for residential windows and doors are tailored to four Climate Zones. A product's energy efficiency for a given climate is based on its impact on heat gain and loss in cold weather and heat gain in warm weather. Check to see what ENERGY STAR® climate zone you live in utilizing the climate map above.



Zo-e-shield

· Controls glare and

blocks the sun's heat

in warmer months

Triple Glazed with 5 Coats of Low-E · Great insulating value

- Minimizes glare and

Superior sound control

· Excellent for use in all climate regions and UV protection



SCREEN AND TRIM OPTIONS

Weather Shield's high-visibility screen options maximize your view and allow more light to flow in. Then add unparalleled design flexibility and customization with our wood interior and aluminum exterior trim options. Available for curved and angle-shaped windows and doors, adding distinctive architectural detail.

Screen Options

Screens allow you to enjoy fresh air flow throughout your home all while keeping out pesky insects. Our High-Visibility, No See-um screen doth utilizes a much finer mesh that offers more air flow along with better optical clarity. Also available in aluminum, non-glare mesh.

Retractable and Wood Screen

Our retractable screen offers unmatched operation with a fully concealed screen channel that maximizes your viewing area. Engineered brake system allows for hands free operation and smooth screen retraction with fully concealed screen components creating a tailored upscale aesthetic.

Hinged from the side, and easily removed for repairs or maintenance, our wood hinged screen option welcomes the natural wood character into your home.

NO SEE UN WESH



AUMINUMINON-GLARE MESH

Exterior Trim Options

Our exterior trim accessories allow for a clean and finished exterior look. Available in any of our standard, designer, radiant metallic, or anodized aluminum finishes, these exterior casings add an ideal finishing touch.







AUMINUM **GIUGNOORB**

3.112 ALLWINLEY FLAT CASING

ALUMINUM HISTORICAL BRORNOULD





7/8* ALUMINUM

BRCKWOULD

2" BULL NOSE





Interior Trim Options

Available in any of our rich wood interiors and finishes, these trims are expertly dried, milled and jointed together reflecting the quality you expect.











WM327 (2-1/4*)

WM356(2-1/47)

WM/376-(2-1/4-) WVB66 (2-1/45)

WM351 (2-1/21)



WNDSDR CASINS (3-1/2*)

FLAT CASINS (3-1/21)



Commercial Custom Design Solutions

Weather Shield specializes in engineering the perfect solution for your unique window and door challenges. From the replication of historical trim to the creation of custom aluminum extrusions, Weather Shield has the expertise to ensure the success of your next commercial project:

- · Custom aluminum extrusions
- · Specialized paint and anodized finishing











A1 Interior



A2 Interior



A3 Interior



A4 Interior




A5 Interior



A6 Interior



A7 Interior



A8 Interior




A9 Interior



A10 Interior







B2 Interior








B4 Interior






C1 Interior




C2 Interior



C3 Interior



C4 Interior






D1 Interior



D2 Interior





WEATHER SH WINDOWS & DO P.O. Box 309 Medford, WI weathershield.com	DORS	QUOTE	P	Project Da Qu	2020 04:49 PM ate: 08/03/2020 ote #: 2387745 ate: 08/03/2020
Sold To: 59377 DMC GROUP 13500 FOLEY ST DETROIT, MI 48227		Ship To: 59377 DMC GROUP		WS	OneSource 1.0
Delivery Instructions:		Deliver To:			
LINE # QUANTITY	ATTRIBUTES			UNIT	EXTENDED
1 6	Complete Mfg I Fram See weat Sizing Me R/O : Jamt Venting F Glas: Operating Poly W Exter - Factory Stan Stan Stan Stan Stan Stan Stan White Insulated W/O Glazing E W/O Glazing E W/O Silve Silve White - S White - S	Shield Double Hung Tilt Rectangle 610 1 Wide 9 Unit 2 Jate 8/8/2008 to Present 1 we Style Double Hung 1 hershield.com for PG/DP information 1 ethod Jb to Jb/Frame Size - Even 1 Size 28 3/4" X 66" 2 Size 27 3/4" X 65 1/2" 1 X0 - Top 33" Venting R/O - Btm 33" 5 Size - Top 22 5/16" X 27 7/8" - Bottom 22 5/16" X 27 2 Code - Operating 2 /hite 1 or Panel/Sash Color White Applied 1 dard Sillnose - " Installation Clips - Factory Applied amb Depth - efinished White a Vinyl Jamb Liner Low E 1 Neat Clean Glass 1 Seacr ert Airspace Gas 1 ingle Lock - amb Jack Screws rcen - White - NO-SEE-UM Mesh - Shipped Loose Unit	A9 , A10, B4 & A6	A8, B2	9
(Viewed from Exterior) Rough Opening 28-3/4" x 66" Overall Jamb 27-3/4" x 65-1/2"	Lead Time	e: 5 Weeks			

-	EATHER S WINDOWS & D P.O. Box 309 Medford, W weathershield.com	OORS // 54451	QUOTE	Project E Q Quote E	5/2020 04:49 PM Date: 08/03/2020 uote #: 2387745 Date: 08/03/2020 SOneSource 1.0
LINE #	QUANTITY	ATTRIBUTES		UNIT	EXTENDED
2	2	Complete Mfg] Fran See weal Sizing Mu R/O Jaml Venting F Glas Operating Poly V Exte - Factory Stan Stan Stan Stan Stan Whit Insulated W/O Glazing E W/O Silve W/In 1 Lite - White - D	Date 8/8/2008 to Present ne Style Double Hung thershield.com for PG/DP information sthod Jb to Jb/Frame Size - Even Size 34 3/4" X 66" to Size 33 3/4" X 65 1/2" X/O - Top 33" Venting R/O - Btm 33" s Size - Top 28 5/16" X 27 7/8" - Bottom 28 5/16" X 27 7/8" g Code - Operating Vhite rior Panel/Sash Color White Applied dard Sillnose - " Installation Clips - Factory Applied amb Depth - efinished White e Vinyl Jamb Liner Low E ut Neat Clean Glass 3ead Type - Colonial ut Protective Film rr Spacer ert Airspace Gas Vouble Locks - amb Jack Screws zreen - White - NO-SEE-UM Mesh - Shipped Loose Unit	A7 & B3	

(Viewed from Exterior) Rough Opening 34-3/4" x 66" Overall Jamb 33-3/4" x 65-1/2"

_	EATHER S		QUOTE		5/2020 04:49 PM Date: 08/03/2020
	P.O. Box 309 Medford, W weathershield.cor			Quote [Quote #: 2387745 Date: 08/03/2020 SOneSource 1.0
LINE #	QUANTITY	ATTRIBUTES		UNIT	EXTENDED
3	2	P.O.: Location: BEDROOM Job: 1055 CLARK Weather Complete Mfg I Fram See weat Sizing Mu R/O Jamt Venting F Glas Operating Poly W Stan Stan Stan Stan Stan Stan Stan Stan Whit Insulated W/O Glazing E W/O Stan	Shield Double Hung Tilt Rectangle 610 1 Wide e Unit Date 8/8/2008 to Present hershield.com for PG/DP information ethod Jb to Jb/Frame Size - Even Size 30 3/4" X 62" o Size 29 3/4" X 61 1/2" R/O - Top 31" Venting R/O - Btm 31" s Size - Top 24 5/16" X 25 7/8" - Bottom 24 5/16" X 25 7/8" g Code - Operating Vhite rior Panel/Sash Color White Applied dard Sillnose - "Installation Clips - Factory Applied amb Depth - efinished White e Vinyl Jamb Liner Low E ut Neat Clean Glass Bead Type - Colonial ut Protective Film r Spacer	B1 & C2	
		1 Lite - White - D No J			

(Viewed from Exterior) Rough Opening 30-3/4" x 62" Overall Jamb 29-3/4" x 61-1/2"

WI P.0	ATHER S NDOWS & I D. Box 309 Medford, weathershield.cc	DOORS WI 54451 om	QUOTE	Project I C Quote I W	5/2020 04:49 PM Date: 08/03/2020 Quote #: 2387745 Date: 08/03/2020 SOneSource 1.0
LINE #	QUANTITY	ATTRIBUTES		UNIT	EXTENDED
4	1 I 26	Complet Mfg Frar See wea Sizing M Glas Poly V Star Star Star Star W/C Glazing W/C W/C W/C Silve Silve W/I 1 Lite - Standard	Shield Direct Set Rectangle 630 Direct Set 1 Wide e Unit Date 12/1/1988 to Present ne Style Double Hung thershield.com for PG/DP information ethod Jb to Jb/Frame Size Size 27" X 15 1/4" b Size 26" X 14" ss Size 24 1/2" X 12 1/2" White rior Panel/Sash Color White Applied dard Subsill - 2" Installation Clips - Factory Applied lamb Depth - refinished White 1 Low E tut Neat Clean Glass Bead Type - Colonial tut Protective Film cure pered Glass er Spacer nert Airspace Gas	C3	

(Viewed from Exterior) Rough Opening 27" x 15-1/4" Overall Jamb 26" x 14"

-	EATHER S		QUOTE			5/2020 04:49 PM Date: 08/03/2020
	P.O. Box 309 Medford, W weathershield.com				Quote I	Quote #: 2387745 Date: 08/03/2020 SOneSource 1.0
LINE #	QUANTITY	ATTRIBUTES			UNIT	EXTENDED
5	1	Complete Mfg Fram See weai Sizing Mi R/O Jam Venting F Glas Operating Poly V Exte - Factory Stan 	Shield Double Hung Tilt Rectangle 610 1 Wide a Unit Date 8/8/2008 to Present he Style Double Hung thershield.com for PG/DP information ethod Jb to Jb/Frame Size - Even Size 34 3/4" X 66" to Size 33 3/4" X 65 1/2" R/O - Top 33" Venting R/O - Btm 33" s Size - Top 28 5/16" X 27 7/8" - Bottom 28 5/16" X 27 7/8" g Code - Operating Vhite rior Panel/Sash Color White Applied dard Silnose - I" Installation Clips - Factory Applied amb Depth - efinished White e Vinyl Jamb Liner Low E ut Neat Clean Glass Bead Type - Colonial ut Protective Film rr Spacer ert Airspace Gas Nouble Locks - amb Jack Screws creen - White - NO-SEE-UM Mesh - Shipped Loose Unit	C4		

(Viewed from Exterior) Rough Opening 34-3/4" x 66" Overall Jamb 33-3/4" x 65-1/2"

	EATHER SI		QUOTE			5/2020 04:49 PM Date: 08/03/2020
	P.O. Box 309 Medford, W weathershield.com	54451			Quote [Quote #: 2387745 Date: 08/03/2020 SOneSource 1.0
LINE #	QUANTITY	ATTRIBUTES		l	UNIT	EXTENDED
6	1	P.O.: Location: STAIRCAS Job: 1055 CLARK Weather Complete	Shield Double Hung Tilt Rectangle 610 1 Wide			
	* T T T	Mfg Fran See wea Sizing M R/O Jam Venting F Glas Operatin Poly V Exte - Factory Stan 5 1/2 4 9/16" J Pine - Pr Whit Insulated W/O Glazing E W/O Glazing E W/O Tem Silve Silve Whit 1 Lite - White - E	Date 8/8/2008 to Present te Style Double Hung thershield.com for PG/DP information ethod Jb to Jb/Frame Size - Even Size 30 3/4" X 62" b Size 29 3/4" X 61 1/2" R/O - Top 31" Venting R/O - Btm 31" s Size - Top 24 5/16" X 25 7/8" - Bottom 24 5/16" X 25 7/8" g Code - Operating Vhite rior Panel/Sash Color White Applied dard Sillnose - "Installation Clips - Factory Applied amb Depth - efinished White e Vinyl Jamb Liner I Low E ut Neat Clean Glass Bead Type - Colonial ut Protective Film pered All Sash rr Spacer ert Airspace Gas Double Locks - amb Jack Screws Creen - White - NO-SEE-UM Mesh - Shipped Loose I Unit	D2		

(Viewed from Exterior) Rough Opening 30-3/4" x 62" Overall Jamb 29-3/4" x 61-1/2"

	EATHER S		QUOTE		08/05/2020 04:49 PM bject Date: 08/03/2020
	P.O. Box 309 Medford, weathershield.co			Q	Quote #: 2387745 uote Date: 08/03/2020 WSOneSource 1.0
LINE #	QUANTITY	ATTRIBUTES		UN	IT EXTENDED
7	1	Complete Mfg Fran See wea Sizing Mu R/O Jam Venting F Glas Operating Poly V Exte - Factory Stan Stan Stan Stan Stan Stan Stan Stan Stan Whit Insulated W/O Glazing F W/O Glazing F Silve Silve Silve W/In 1 Lite - S	Shield Double Hung Tilt Rectangle 610 1 Wide e Unit Date 8/8/2008 to Present he Style Double Hung thershield.com for PG/DP information ethod Jb to Jb/Frame Size - Even Size 28 3/4" X 62" b Size 27 3/4" X 61 1/2" R/O - Top 31" Venting R/O - Btm 31" s Size - Top 22 5/16" X 25 7/8" - Bottom 22 5/16" X 25 7/8" g Code - Operating Vhite rior Panel/Sash Color White Applied dard Sillnose - "Installation Clips - Factory Applied amb Depth - efinished White e Vinyl Jamb Liner I Low E ut Neat Clean Glass Bead Type - Colonial ut Protective Film pered All Sash	C1	
			creen - White - NO-SEE-UM Mesh - Shipped Loose I Unit		

(Viewed from Exterior)

Rough Opening 28-3/4" x 62" Overall Jamb 27-3/4" x 61-1/2"

v	P.O. Box 309 Medford, weathershield.cc	DOORS WI 54451 m	QUOTE	Project D Qi Quote D WS	/2020 04:49 PM ate: 08/03/2020 uote #: 2387745 ate: 08/03/2020 GOneSource 1.0
LINE #	QUANTITY	ATTRIBUTES		UNIT	EXTENDED
8		Complete Mfg I Fram See wead Sizing Me R/O Jam Venting F Glas Operating Poly W Exte - Factory Stan 	Shield Double Hung Tilt Rectangle 610 1 Wide a Unit Date 8/8/2008 to Present the Style Double Hung thershield.com for PG/DP information ethod Jb to Jb/Frame Size - Even Size 28 3/4" X 62" b Size 27 3/4" X 61 1/2" R/O - Top 31" Venting R/O - Btm 31" s Size - Top 22 5/16" X 25 7/8" - Bottom 22 5/16" X 25 7/8" g Code - Operating Vhite rior Panel/Sash Color White Applied dard Sillnose - "Installation Clips - Shipped Loose amb Depth - efinished White e Vinyl Jamb Liner I Low E ut Neat Clean Glass Bead Type - Colonial ut Protective Film er Spacer ert Airspace Gas single Lock - amb Jack Screws creen - White - NO-SEE-UM Mesh - Shipped Loose	A1 & A3	

(Viewed from Exterior) Rough Opening 28-3/4" x 62" Overall Jamb 27-3/4" x 61-1/2"

WEATHER	SHIELD.

WINDOWS & DOORS

P.O. Box 309 Medford, WI 54451 weathershield.com

QUOTE

Quote #: 2387745 Quote Date: 08/03/2020 WSOneSource 1.0

LINE # QUANTITY ATTRIBUTES UNIT EXTENDED 9 2 P.O.: Location: BATHROOM Job: 1055 CLARK Location: BATHROOM Job: 1055 CLARK Weather Shield Double Hung Tilt Rectangle 610 1 Wide Complete Unit 						SOneSource 1.0
Location: BATHROOM Job: 1055 CLARK Weather Shield Double Hung Tilt Rectangle 610 1 Wide Complete Unit "Mig Date 8/4/2008 to Present	LINE #	QUANTITY	ATTRIBUTES	·		
White Vinyl Jamb Liner Insulated Low E W/Out Neat Clean Glass Glazing Bead Type - Colonial W/Out Protective Film Obscure Tempered All Sash Time Clean		2	P.O.: Location: BATHROO Job: 1055 CLARK Weather Complet Mfg Fran See wea Sizing M R/O Jan Venting Glas Operatin Poly V Exte - Factory Stan Stan Stan Stan Stan	Shield Double Hung Tilt Rectangle 610 1 Wide e Unit Date 8/8/2008 to Present me Style Double Hung athershield.com for PG/DP information lethod Jb to Jb/Frame Size - Even Size 24 3/4" X 37 1/2" ab Size 23 3/4" X 37" R/O - Top 18 3/4" Venting R/O - Btm 18 3/4" ss Size - Top 18 5/16" X 13 5/8" - Bottom 18 5/16" X 13 5/8" g Code - Operating White erior Panel/Sash Color White / Applied ndard Sillnose - 2" Installation Clips - Shipped Loose Jamb Depth -	D1	
(Viewed from Exterior) Rough Opening 24-3/4" x 37-1/2" Lead Time: 5 Weeks Overall Jamb 23-3/4" x 37"	Rough Opei	, ning 24-3/4" x 37-1	Pine - Pi Whi Insulated W/C Glazing W/C Obs Ten Silv W/Ir 1 Lite - White - S No W/Full S Standard No Field	refinished White te Vinyl Jamb Liner d Low E Jut Neat Clean Glass Bead Type - Colonial Dut Protective Film iccure spered All Sash er Spacer nert Airspace Gas Single Lock - Jamb Jack Screws icreen - White - NO-SEE-UM Mesh - Shipped Loose d Unit Prepping		

	R SHIELD. s & doors	QUOTE		5/2020 04:49 PM Date: 08/03/2020
	Medford, WI 54451 rshield.com		Quote E	uote #: 2387745 Date: 08/03/2020 SOneSource 1.0
LINE # QUANTI	TY ATTRIBUTES		UNIT	EXTENDED
10	1 P.O.: Location: BEDROOD Job: 1055 CLARK			
	Complet Mfg Fra See wea Sizing M R/O Jam Venting Gla: Operatir Poly N Extta Extta Stat 	I Date 8/8/2008 to Present me Style Double Hung athershield.com for PG/DP information Alethod Jb to Jb/Frame Size - Even) Size 34 3/4" X 62" nb Size 33 3/4" X 61 1/2" R/O - Top 31" Venting R/O - Btm 31" ss Size - Top 28 5/16" X 25 7/8" - Bottom 28 5/16" X 25 7/8" ng Code - Operating White erior Panel/Sash Color White y Applied ndard Sillnose - '2" Installation Clips - Shipped Loose Jamb Depth - refinished White ite Vinyl Jamb Liner d Low E Dut Neat Clean Glass Bead Type - Colonial Dut Protective Film npered All Sash ter Spacer nert Airspace Gas Double Locks - Jamb Jack Screws Screen - White - NO-SEE-UM Mesh - Shipped Loose	A2	

(Viewed from Exterior)

Rough Opening 34-3/4" x 62" Overall Jamb 33-3/4" x 61-1/2"

WEATHER	SHIEL	D.
---------	-------	----

WINDOWS & DOORS

P.O. Box 309 Medford, WI 54451 weathershield.com

QUOTE

Quote #: 2387745 Quote Date: 08/03/2020 WSOneSource 1.0

				WSOneSource 1.0	
LINE #	QUANTITY	ATTRIBUTES	•	UNIT	EXTENDED
11	2		Shield Double Hung Tilt Rectangle 610 1 Wide		
		Fran See wea Sizing M Jam Venting I Glas Operatin Poly V Exte - Factory Stan 5 1/2 4 9/16" J Pine - Pr Whit Insulatec W/O Glazing I W/O Silve W/O Silve W/I 1 Lite - L White - L No J	Date 8/8/2008 to Present ne Style Double Hung thershield.com for PG/DP information ethod. Jb to Jb/Frame Size - Even Size 30 3/4" X 62" b Size 29 3/4" X 61 1/2" R/O - Top 31" Venting R/O - Btm 31" is Size - Top 24 5/16" X 25 7/8" - Bottom 24 5/16" X 25 7/8" g Code - Operating Vhite rior Panel/Sash Color White Applied dard Sillnose - 2" Installation Clips - Shipped Loose amb Depth - efinished White e Vinyl Jamb Liner I Low E ut Neat Clean Glass Bead Type - Colonial ut Protective Film er Spacer lert Airspace Gas Double Locks - lamb Jack Screws creen - White - NO-SEE-UM Mesh - Shipped Loose I Unit	A4 & A	15

(Viewed from Exterior)

Rough Opening 30-3/4" x 62"

Overall Jamb 29-3/4" x 61-1/2" Miscellaneous Charges Lead Time: 5 Weeks

Thank you for choosing Weather Shield Windows & Doors



WINDOWS & DOORS

P.O. Box 309 Medford, WI 54451 weathershield.com

Message Summary

Printed: 08/05/2020 04:49 PM Project Date: 08/03/2020

> Quote #: 2387745 Quote Date: 08/03/2020 WSOneSource 1.0

Message # Line Item/s <u>Message</u>