1411 Iroquois Ave.

Roofing Specification

CERTAINTEED LANDMARK SHINGLE COLOR: "HEATHER BLEND"



LANDMARK®

For homeowners seeking true peace of mind, Landmark[®] shingles are the high-quality, reliable choice for beautifying and protecting a home. With a dual-layered design that emulates the dimensionality of true wood shake, Landmark asphalt shingles offer the heaviest weight and widest array of color options in their class, allowing you to create or re-create the ideal look for your home with confidence. Backed by a 100+ year legacy of trusted manufacturing performance, all Landmark shingles include CertainTeed's industry-leading, lifetime-limited warranty.

- Certified as meeting the industry's toughest third-party
- (UL) manufacturing quality standards
- Dual-layered construction provides extra protection from the elements
- Ten year StreakFighter® algae-resistance warranty
- Class A fire-resistance rating




Technical Data Sheet

Landmark[®], Landmark[®] Premium, Landmark[®] Pro Shingles, Landmark[®] Pro/Architect 80 (NW Region Only) Shingles

PRODUCT INFORMATION

Landmark shingles reflect the same high manufacturing standards and superior warranty protection as the rest of CertainTeed's line of roofing products. Landmark Premium (and Algae Resistant-AR), Landmark PRO (and AR) and Landmark (and AR) are built with the industry's toughest fiber glass mat base, and their strict dimensional tolerance assures consistency. Complex granule color blends and



subtle shadow lines produce a distinctive color selection. Landmark is produced with the unique NailTrak[®] nailing feature. *Please see the installation instruction section below for important information regarding NailTrak.*

In the Northwest Region Landmark PRO (AR) is double-branded as Landmark PRO/Architect 80 (AR).

Landmark algae-resistant (AR) shingles are algae-resistant and help protect against dark or black discoloration, sometimes called staining or streaking, caused by blue-green algae. AR shingles are not available in all regions.

Colors: Please refer to the product brochure or CertainTeed website for the colors available in your region.

Limitations: Use on roofs with slopes greater than 2" per foot. Low-slope applications (2:12 to < 4:12) require additional underlayment. In areas where icing along eaves can cause the back-up of water, apply CertainTeed WinterGuard[®] Waterproofing Shingle Underlayment, or its equivalent, according to application instructions provided with the product and on the shingle package.

Product Composition: Landmark Series shingles are composed of a fiber glass mat base. Ceramiccoated mineral granules are tightly embedded in carefully refined, water-resistant asphalt. Two pieces of the shingle are firmly laminated together in a special, tough asphaltic cement. All Landmark shingles have self-sealing adhesive strips.

Applicable Standards

ASTM D3018 Type I ASTM D3462 ASTM E108 Class A Fire Resistance ASTM D3161 Class F Wind Resistance ASTM D7158 Class H Wind Resistance UL 790 Class A Fire Resistance ICC-ES ESR-1389 and ESR-3537 CSA Standard A123.5 (Regional) Miami-Dade Product Control Approved Florida Product Approval # FL5444 Meets TDI Windstorm Requirements

Technical Data:

	Landmark (and AR)
Weight/Square (approx.)	219 to 238 lb **
Dimensions (overall)	13 1/4" x 38 3/4"
Shingles/Square (approx.)	66
Weather Exposure	5 5/8"

Landmark PRO* (and AR) 240 to 267 lb ** 13 1/4" x 38 3/4" 66 5 5/8"

Landmark Premium (and AR) 300 lb 13 1/4" x 38 3/4" 66 5 5/8"

*Includes Landmark PRO AR/Architect 80 **Dependent on manufacturing location

Technical Data Sheet Landmark[®] Series Shingles

INSTALLATION

Detailed installation instructions are supplied on each bundle of Landmark shingles and must be followed. Separate application sheets may also be obtained from CertainTeed.

Hips and Ridges: For capping hip and ridge apply CertainTeed Shadow Ridge[®], Cedar Crest[®] or Mountain Ridge[®] shingles of a like color.

MAINTENANCE

These shingles do not require maintenance when installed according to manufacturer's application instructions. However, to protect the investment, any roof should be routinely inspected at least once a year. Older roofs should be looked at more frequently.

WARRANTY

Landmark Premium (and AR), Landmark PRO/Architect 80 AR, Landmark PRO (and AR), and Landmark (and AR) shingles carry a lifetime limited, transferable warranty to the consumer against manufacturing defects when applied to stated CertainTeed application instructions for this product. In addition, Landmark Premium (and AR), Landmark PRO (and AR), Landmark PRO/Architect 80 AR, and Landmark (and AR) carry 10-years of SureStart[™] Protection. Landmark AR shingles carry a 10-year algae resistance warranty. Landmark Premium AR, Landmark PRO AR, and Landmark PRO/Architect 80 AR shingles carry a 15-year algae resistance warranty. For specific warranty details and limitations, refer to the warranty itself (available from the local supplier, roofing contractor or on-line at <u>www.certainteed.com</u>).

FOR MORE INFORMATION

Sales Support Group: 800-233-8990 Web site: <u>www.certainteed.com</u> See us at our on-line specification writing tool, CertaSpec[®], at <u>www.certainteed.com/certaspec</u>.

CertainTeed 20 Moores Road Malvern, PA 19355



© 01/20 CertainTeed