

**Owens Corning® WeatherLock® G Granulated Self-Sealing Ice and Water Barrier 3' x 66.7' (200 sq. ft.)**  
Model Number: 1511827 | Menards® SKU: 1511827



EVERYDAY LOW PRICE \$65.99  
11% MAIL-IN REBATE Good Through 7/11/20 \$7.26  
**FINAL PRICE** **\$58<sup>73</sup>** each

**\$0.29 /sq.ft**  
You Save \$7.26 After Mail-In Rebate

**285** People have purchased this product in the past 30 days

\* Mail-in Rebate is in the form of merchandise credit check, valid in-store only. Merchandise credit check is not valid towards purchases made on MENARDS.COM®.



**Pick Up At Store**  
21 In-Stock at **LIVONIA**  
[Check Another Store for Availability.](#)



**Shipping & Delivery**  
Available

**Description & Documents** ^

Owens Corning® WeatherLock® G granulated self-sealing barrier acts as a waterproof barrier in the most vulnerable sections of the roof to create a second line of defense. It allows for proper water flow, preventing damage from ice dams and ultimately protecting interiors under applied areas. WeatherLock® G is engineered with a tri-layer construction to provide excellent performance and peak protection.



**Dimensions:** 3' W x 66.7' L

Brand Name: **Owens Corning**



**Features**

- Ideal for all underlayment applications such as full roof deck coverage, eaves, rakes, and valleys
- Constructed with a top layer of granules to enable better traction for the installer
- Manufactured with a durable Fiberglas™ mat to increase the tear strength
- Resists cracking and breaking during installation
- Features an easy-to-remove split-release liner for easy application and positioning on the roof deck
- When top shingles are applied, barrier will seal around the nail penetration, creating a water tight construction

**Specifications** ^

Product Type	Ice and Water Barrier	Coverage Area	200 square foot
Overall Width	3 foot	Overall Length	66.7 foot
Resistance Features	Secondary Waterproof Barrier, UL 790 (Class A Fire Resistance), Tear Resistance, Slip-Resistant	Listing Agency Standards	ASTM D1970, ASTM E108, ICC-ESR 1783, UL 790
<a href="#">View Return Policy.</a>			

