

Mastercraft® 20-Minute 36"W x 80"H Primed Steel 6 Panel Fire Door System - Left Inswing

Model Number: 4140403 | Menards® SKU: 4140403



EVERYDAY LOW PRICE

11% MAIL-IN REBATE Good Through 4/16/22

FINAL PRICE

\$274.00

\$30.14

\$243.86 each

You Save \$30.14 with Mail-In Rebate

Nominal Size: 36" W x 80" H

Door Swing: Left Hand

Frame Width: 4-9/16"

* Mail-in Rebate is in the form of merchandise credit check, valid in-store only. Merchandise credit check is not valid towards purchases made on MENARDS.COM®.

Need more information?

[VIEW BUYING GUIDE](#)



Pick Up At Store

3 In-Stock at **WIXOM**
[Check Another Store for Availability](#)



Shipping & Delivery

Available

Description & Documents

Built with safety in mind, this steel door from Mastercraft® was designed with 24-gauge steel and a 20-minute fire rating. It offers the safety and security you want for your home while still maintaining beauty and creating a welcoming atmosphere.



Brand Name: **Mastercraft**



Find more information about this product on the [Manufacturer's website](#)

Features

- Left inswing
- Constructed from 24-gauge steel that's primed white and ready to be finished with a 1-3/4" thick, energy-saving, insulating foam core
- Prehung with a 4-9/16", primed, 20-minute fire-rated frame
- No-rot sill with adjustable inswing, 2 spring-loaded hinges, and 1 standard satin nickel hinge
- Prebored with a 2-3/4" backset for easy handle installation and double bored and prepped for deadbolt (handleset and deadbolt sold separately)
- Nominal size of 36" W x 80" H with left inswing
- ENERGY STAR® qualified

Specifications

Color/Finish	Primed	Deadbolt Bore	Yes
Door Construction	Primed Steel	Door Style	6 Panel
Door Swing	Left	Door Thickness	1-3/4 inch
Frame Material	Primed Wood	Frame Width	4-9/16 inch
Glass Caming Finish	None	Hinge Finish	Satin Nickel
Includes	Hinges, Sill, Frame, Preassembled Door Slab, Brickmould	Lockset Bore	Yes
Lockset/Deadbolt Backset Dimension	2-3/4 inch	Manufacturer Warranty	Limited Lifetime
Nominal Door Height	80 inch	Nominal Door Width	36 inch
Obscurity Rating	10	Rough Opening Height	82 inch
Rough Opening Width	38-1/4 inch	Sill Finish	Aluminum
Sill Type	Adjusting	Solar Heat Gain Coefficient	0.01
U-Value	0.12	Air Leakage (AL) Rating	0.3
Energy Star Certified	Yes	Shipping Dimensions	84.88 H x 41.88 W x 5.94 D
Shipping Weight	79.0 lbs	Return Policy	Regular Return (view Return Policy)

Please Note: Prices, promotions, styles and availability may vary by store and online. Inventory is sold and received continuously throughout the day; therefore, the quantity shown may not be available when you get to the store. This inventory may include a store display unit. Online orders and products purchased in-store qualify for rebate redemption. Mail-in Rebate is in the form of merchandise credit check, valid in-store only. Merchandise credit check is not valid towards purchases made on MENARDS.COM®. By submitting this rebate form, you agree to resolve any disputes related to rebate redemption by binding arbitration and you waive any right to file or participate in a class action. Terms and conditions available at www.rebateinternational.com

