

**Downlights  
with partially frosted crystal glass**

Electronic driver location	<b>ceiling box or pan</b>
Delivered lumens	<b>265 · 1375 lm</b>
Luminaire size	<b>Ø 3 1/4 · 4 1/2 · 6 · 7 1/4</b>
Glass	<b>partially frosted crystal glass</b>

**Compact downlights**  
with partially frosted crystal glass

A series of compact downlights with a symmetrical wide beam light distribution. The partially frosted, crystal glass provides glare control while adding visual interest and sparkle to any space.


Die-cast aluminum housing · Stainless steel trim ring  
Partially frosted crystal glass · Reflector made of pure anodized aluminum

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at [www.bega-us.com](http://www.bega-us.com)

Luminaires are provided with a #4 brushed stainless steel trim

NRTL listed to North American standards · Suitable for wet locations  
Protection class IP 65



Downlights				
	LED	A	B	C
<b>55 941</b>	4.7 W	3 1/4	2 3/8	–
<b>55 942</b>	8.7 W	4 1/2	4 1/2	18 1/2
<b>55 943</b>	12.7 W	6	4 1/2	18 1/2
<b>55 944</b>	18.1 W	7 1/4	4 1/2	18 1/2