

AXIS M3058-PLVE

12 MP outdoor-ready dome with 360° panoramic view and IR illumination

AXIS M3058-PLVE Network Camera delivers outstanding video in any light conditions, using Axis-developed Forensic WDR and Lightfinder technologies. With its integrated, automatically adaptable OptimizedIR illumination, this versatile camera even sees in the dark. The camera offers 360° overview as well as dewarped views. AXIS M3058-PLVE is vandal resistant (IK10) and discreetly designed. The optional black skin, which is also easily repaintable, can be used to further blend the camera into its environment. The camera has good capacity for analytics. It comes factory-focused and is designed for easy installation.

- > **12 MP sensor**
- > **OptimizedIR illumination**
- > **Lightfinder technology**
- > **Forensic WDR**
- > **Zipstream for reduced bandwidth and storage**



2992 x 2992
4000 x 3000

AXIS M3058-PLVE

Camera	
Image sensor	12 MP (4000x3000) 1/1.7" progressive scan RGB CMOS
Lens	Fixed iris, fixed focus, 1.2 mm, F2.2 Horizontal field of view: 181° Vertical field of view: 181°
Day and night	Automatically removable infrared-cut filter
Minimum illumination	Color: 0.19 lux at 50 IRE F2.2 B/W: 0.04 lux at 50 IRE F2.2 0 lux with IR illumination on
Shutter time	1/22 500 s to 2 s
Camera angle adjustment	Rotation $n \pm 180^\circ$
Video	
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG
Resolution	Overview: 2992x2992 to 160x160 Panorama: 3584x1344 to 192x72 Double panorama: 3584x2688 to 256x144 Quad view: 3584x2688 to 256x144 View area 1-4, 16:9: 2304x1296 to 256x144, 4:3: 2048x1536 to 320x240 Panorama corner left/right: 3200x1600 to 192x72 Double panorama corner: 2880x2880 to 320x240 Corridor: 2560x1920 to 256x144
Frame rate	360° overview only, up to 2992x2992 without WDR: 25/30 fps @ 50/60 Hz 360° overview and dewarped views up to max resolution with WDR: up to 12.5/15 fps @ 50/60 Hz
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264
Multi-view streaming	360° overview, dewarped panorama, double panorama, corridor and quad views. Up to 4 individually cropped out and dewarped view areas. All different views can be streamed simultaneously. When streaming 4 dewarped view areas and one 360° overview in max resolution: up to 12 fps per stream
HDMI output	HDMI 1080p @ 50/60 fps (50/60 Hz)
Image settings	Compression, color, brightness, sharpness, contrast, local contrast, white balance, exposure control (including automatic gain control) exposure zones, fine tuning of behavior at different light levels, forensic WDR: up to 120 dB depending on scene, dynamic text and image overlay, privacy masks, mirroring of images, rotation: 0°, 180°, including Corridor Format
Pan/Tilt/Zoom	Digital PTZ of view areas, digital PT of panorama, corner, corridor and quad views, preset positions, guard tour
Network	
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, digest authentication, user access log, centralized certificate management
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP ^b , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP, HDMI 1.4b
System integration	
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profile S and ONVIF [®] Profile G, specification at onvif.org
Analytics	Included AXIS Video Motion Detection, active tampering alarm Supported AXIS Motion Guard, AXIS Fence Guard, and AXIS Loitering Guard Support for AXIS Camera Application Platform enabling installation of third-party applications, see www.axis.com/acap

Event triggers	Analytics, supervised external input, virtual inputs through API, edge storage events
Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text, external output activation
Data streaming	Event data
Built-in installation aids	Pixel counter, digital PTZ of view areas, digital PT of panorama, corner, corridor and quad views
General	
Casing	IP66- and NEMA 4X-rated, IK10 impact-resistant casing in polycarbonate and aluminium, with hard-coated dome and dehumidifying membrane Encapsulated electronics and captive screws Color: White NCS S 1002-B For repainting, use the optional skin cover. Contact your Axis partner for instructions.
Sustainability	PVC free
Memory	2 GB RAM, 512 MB Flash
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 7.8 W, max 12.95 W
Connectors	RJ45 10BASE-T/100BASE-TX PoE Terminal block for 1 supervised alarm input and 1 digital output (12 V DC output, max. load 25 mA) HDMI type D ^b
IR illumination	Optimized IR with with power-efficient, long-life 850 nm IR LEDs with adaptable illumination intensity Range of reach 15 m (49 ft) or more depending on scene
Storage	Support for microSD/microSDHC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Operating conditions	-40 °C to 50 °C (-40 °F to 122 °F) Maximum temperature (intermittent): 55 °C (131 °F) Start-up: -30 °C to 50 °C (-22 °F to 122 °F) Humidity 10–100% RH (condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Approvals	EMC EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KC KN35 Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IEC/EN 62471 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC/EN 60529 IP66, IEC/EN 62262 IK10, NEMA 250 Type 4X
Dimensions	Height: 66 mm (2 5/8 in) ø 149 mm (5 7/8 in)
Weight	770 g (1.7 lb)
Included accessories	Installation guide, Windows [®] decoder 1-user license, drill hole template, cable gaskets, connector guard, I/O connector, Resistorx [®] T20 L-key, mounting bracket, cable hole lid, view protector
Optional accessories	AXIS T94T02D Pendant Kit with weathershield, AXIS T94K01D Pendant Kit, AXIS T94S02L Recessed Mount Kit, AXIS M30 Skin Cover A Black, Axis Mounts & Cabinets For more accessories, see www.axis.com
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available on www.axis.com/vms

Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Polish, Portuguese, Traditional Chinese	b. <i>Make sure that the cable has a slim connector plug</i>
Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty	Environmental responsibility: www.axis.com/environmental-responsibility

a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*