


TILT-WASH FULL-FRAME WINDOWS

Table of Tilt-Wash Double-Hung Window Sizes

Scale 1/8" (3) = 1'-0" (305) – 1:96

Window Dimension	1'-9 5/8" (549)	2'-1 5/8" (651)	2'-5 5/8" (752)	2'-7 5/8" (803)	2'-9 5/8" (854)	2'-11 5/8" (905)	3'-1 5/8" (956)	3'-5 5/8" (1057)	3'-9 5/8" (1159)
Minimum Rough Opening	1'-10 1/8" (562)	2'-2 1/8" (664)	2'-6 1/8" (765)	2'-8 1/8" (816)	2'-10 1/8" (867)	3'-0 1/8" (917)	3'-2 1/8" (968)	3'-6 1/8" (1070)	3'-10 1/8" (1172)
Unobstructed Glass (lower sash only)	15" (381)	19" (483)	23" (584)	25" (635)	27" (686)	29" (737)	31" (787)	35" (889)	39" (991)
3'-0 7/8" (937)									
3'-0 7/8" (937)	TW18210	TW20210	TW24210	TW26210	TW28210	TW210210	TW30210	TW34210	TW38210
3'-4 7/8" (1038)									
3'-4 7/8" (1038)	TW1832	TW2032	TW2432	TW2632	TW2832	TW21032	TW3032	TW3432	TW3832
3'-8 7/8" (1140)									
3'-8 7/8" (1140)	TW1836	TW2036	TW2436	TW2636	TW2836	TW21036	TW3036	TW3436	TW3836
4'-0 7/8" (1241)									
4'-0 7/8" (1241)	TW18310	TW20310	TW24310	TW26310	TW28310	TW210310	TW30310	TW34310	TW38310
4'-4 7/8" (1343)									
4'-4 7/8" (1343)	TW1842	TW2042	TW2442	TW2642	TW2842	TW21042	TW3042	TW3442	TW3842
4'-8 7/8" (1445)									
4'-8 7/8" (1445)	TW1846	TW2046	TW2446	TW2646	TW2846	TW21046	TW3046 [◊]	TW3446 [◊]	TW3846 [◊]
5'-0 7/8" (1546)									
5'-0 7/8" (1546)	TW18410	TW20410	TW24410	TW26410	TW28410	TW210410 [◊]	TW30410 [◊]	TW34410 [◊]	TW38410 [◊]
5'-4 7/8" (1648)									
5'-4 7/8" (1648)	TW1852	TW2052	TW2452	TW2652	TW2852 [◊]	TW21052 [◊]	TW3052 [◊]	TW3452 [◊]	TW3852 [◊]
5'-8 7/8" (1749)									
5'-8 7/8" (1749)	TW1856	TW2056	TW2456	TW2656 [◊]	TW2856 [◊]	TW21056 [◊]	TW3056 [◊]	TW3456 [◊]	TW3856 [◊]
6'-0 7/8" (1851)									
6'-0 7/8" (1851)	TW18510	TW20510	TW24510 [◊]	TW26510 [◊]	TW28510 [◊]	TW210510 [◊]	TW30510 [◊]	TW34510 [◊]	TW38510 [◊]
6'-4 7/8" (1953)									
6'-4 7/8" (1953)	TW1862	TW2062	TW2462 [◊]	TW2662 [◊]	TW2862 [◊]	TW21062 [◊]	TW3062 [◊]	TW3462 [◊]	TW3862 [◊]

Cottage and reverse cottage sash available for these heights and in all widths.



- "Window Dimension" always refers to outside frame to frame dimension.
- "Minimum Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.
- Dimensions in parentheses are in millimeters.
- ◊ Meet or exceed clear opening area of 5.7 sq.ft. or 0.53 m², clear opening width of 20" (508) and clear opening height of 24" (610).

continued on next page

Table of Tilt-Wash Double-Hung Window Sizes *(continued)*

Scale 1/8" (3) = 1'-0" (305) – 1:96

Window Dimension	1'-9 5/8"	2'-1 5/8"	2'-5 5/8"	2'-7 5/8"	2'-9 5/8"	2'-11 5/8"	3'-1 5/8"	3'-5 5/8"	3'-9 5/8"
	(549)	(651)	(752)	(803)	(854)	(905)	(956)	(1057)	(1159)
Minimum Rough Opening	1'-10 1/8"	2'-2 1/8"	2'-6 1/8"	2'-8 1/8"	2'-10 1/8"	3'-0 1/8"	3'-2 1/8"	3'-6 1/8"	3'-10 1/8"
	(562)	(664)	(765)	(816)	(867)	(917)	(968)	(1070)	(1172)
Unobstructed Glass (lower sash only)	15"	19"	23"	25"	27"	29"	31"	35"	39"
	(381)	(483)	(584)	(635)	(686)	(737)	(787)	(889)	(991)
7'-4 7/8" (2257)									
	TW1872	TW2072 [◊]	TW2472 [◊]	TW2672 [◊]	TW2872 [◊]	TW21072 [◊]	TW3072 [◊]	TW3472 [◊]	TW3872 [◊]
7'-8 7/8" (2359)									
	TW1876	TW2076 [◊]	TW2476 [◊]	TW2676 [◊]	TW2876 [◊]	TW21076 [◊]	TW3076 [◊]	TW3476 [◊]	TW3876 [◊]

- "Window Dimension" always refers to outside frame to frame dimension.
- **"Minimum Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.**
- Dimensions in parentheses are in millimeters.
- ◊ Meet or exceed clear opening area of 5.7 sq.ft. or 0.53 m², clear opening width of 20" (508) and clear opening height of 24" (610).

Windows 7'-4 7/8" (2257) and 7'-8 7/8" (2359) high have interior and exterior brackets. Interior brackets, located on both sides of the check rail, must be flipped up for proper product performance.

7'-4 7/8" (2257) and 7'-8 7/8" (2359) high windows joined vertically must use Andersen® reinforced joining materials.