

Historic Fort Wayne

Memorandum of Agreement Mitigation Work Plan

Background:

A Memorandum of Agreement (MOA) between the Federal Highway Administration and the Michigan State Historic Preservation Officer (SHPO) regarding the Gordie Howe International Bridge (GHIB) (formerly the Detroit River International Crossing) was signed in December 2008. The MOA identified 13 mitigation measures specific to Historic Fort Wayne (HFW). This memo outlines a work plan for implementing the mitigation measures identified in the MOA.

The following outlines each mitigation measure and how it will be implemented. Coordination meetings regarding these measures were held with the City of Detroit on September 24, 2024, January 15, 2025, and February 24, 2025.

MOA Historic Fort Wayne Mitigation:

Item #1: *MDOT shall pay for an update of the existing Fort Wayne Master Plan to revisit Fort entryway options.*

Work Plan: The City of Detroit (General Services Department (GSD), Parks & Recreation, Historic Fort Wayne Office – “Fort Wayne”) does not intend on updating the existing Fort Wayne Master Plan as it is currently considered a low priority. HFW is prioritizing physical projects that have impacts on landscaping and aesthetic improvements.

Item #2: *MDOT shall conduct videotape documentation and seismic monitoring of structural conditions before, during and after construction for Fort buildings and structures closest to Jefferson Avenue, the north elevation of the Star Fort, and Detroit Historical Society collections stored within the Fort property. MDOT shall implement a protocol to notify the City of Detroit of any damage that may be associated with construction-related vibration.*

Work Plan: Seismic monitoring of structural conditions before and during construction has been completed to date. The results of the monitoring will be coordinated with the Fort once the post construction monitoring is complete.

Item #3: *MDOT shall provide wayfinding signage to assist visitors in accessing the Fort and create and print brochures showing changes in access to the Fort.*

Work Plan: MDOT developed a signage plan that was reviewed and accepted by the City of Detroit. The WDBA communication team will coordinate with Fort Wayne and MDOT to prepare a

map/graphic to show changes in the access to the Fort. This map will be printed as a brochure and also posted on the Fort's website.

Item #4: *MDOT shall construct a direct local access road to and from the plaza to Campbell Street. Campbell Street shall receive pavement, landscaping and lighting improvements from the new I-75 northbound ramp south to West Jefferson Avenue to serve as a gateway to the Fort. Campbell Street will be reconstructed as a narrow boulevard from the railroad tracks to West Jefferson Avenue. MDOT will work with the City of Detroit to investigate the possibility of renaming Campbell Street to Fort Wayne Street or another, similar name that will help identify the street as an access route to the Fort.*

Work Plan: The design to improve Campbell Street including landscaping and lighting is complete and construction is ongoing. The City of Detroit does not want to rename Campbell Street.

Item #5: *MDOT shall install new pavement, landscaping and lighting along West Jefferson Avenue from West End Street to Clark Street as well as along Clark Street from its interchange with I-75 to Jefferson Avenue to provide an attractive route to Fort Wayne.*

Work Plan: The Jurisdictional Transfer Agreement between the City of Detroit and MDOT was entered into in 2017 after extensive negotiations to identify scope of work for various items that took into consideration and complied with all EIS green sheet and MOA mitigation items included the reconstruction of Jefferson Avenue from West End Street to Campbell Boulevard as well as Clark Street intersections with Fort Street and Jefferson Avenue. It also included the reconstruction of the new Green Boulevard and new Campbell Boulevard. New lighting, landscaping, and multiuse path connectivity is currently under construction. These new route connections will act as the main entry way and attractive route to HFW which also provides for safe pedestrian and cyclist use. While the limits originally specified in the 2008 MOA extend beyond the Jurisdictional Transfer agreement, MDOT and the City of Detroit agree that the intent is met and the new connections provide for a more attractive and safer connection to HFW.

Item #6: *MDOT shall construct a new decorative and historically appropriate fence along the West Jefferson property line of the Fort.*

Work Plan: MDOT and HFW agreed on replacing the existing chain link fence with a new wrought iron fence that is aesthetic but also respects the historic nature of the Fort. Initial input from SHPO has been provided to the City. The City of Detroit is working with local vendors to get a quote for the fence. MDOT will transfer funds to the City of Detroit HFW office through a Memorandum of Agreement (MOA) to construct the new fence with MDOT providing the appropriate level of oversight.

Item #7: *MDOT shall construct an entryway treatment for Fort Wayne on Fort's West Jefferson Avenue frontage or on other, adjacent City-owned property to improve wayfinding and visibility as identified in the updated Historic Fort Wayne Master Plan. MDOT shall pay for the reconfiguration of those portions of existing Fort Wayne streets specifically needed to connect the new entryway.*

Work Plan: The City of Detroit HFW office does not contemplate relocating the entrance to Fort Wayne. Improvement to the existing entrance with masonry repairs and additional landscaping will be made by HFW, and MDOT will include funds to cover the work through the MOA agreement.

Item #8: *MDOT shall construct a security wall surrounding the plaza; the wall will receive a surface treatment aesthetically compatible with Historic Fort Wayne along its West Jefferson Avenue perimeter.*

Work Plan: The security wall surrounding the Port of Entry is under construction. The Jefferson barrier wall features an aesthetic treatment that pays tribute to Historic Fort Wayne's unique star fort structure. The barrier is an eight-foot-high security wall with the aesthetic treatment displayed on the public side facing West Jefferson Avenue.

Item #9: *MDOT shall landscape the 100' wide buffer area between the plaza security wall and West Jefferson Avenue, meeting Customs and Border Protection guidelines.*

Work Plan: The buffer area between the plaza security wall and West Jefferson Avenue will be landscaped including native pollinator-positive plantings. The landscaping design was developed with the barrier wall design.

Item #10: *MDOT shall work with Customs and Border Protection to encourage truck anti-idling measures on the plaza.*

Work Plan: This is ongoing. MDOT has held discussions with the Customs and Border Protection to encourage truck anti-idling measures on the plaza.

Item #11: *MDOT shall submit work plans and specifications for all of the above provisions relative to Historic Fort Wayne to the City of Detroit Recreation Department and the SHPO for review and approval.*

Work Plan: This is ongoing. MDOT and the City Detroit will continue to coordinate with SHPO for concurrence on items above.

Item #12: *MDOT shall work with the Fort staff and the Detroit Police Department to develop a traffic management plan for large events. MDOT shall contribute toward consultant services used to create the traffic management plan.*

Work Plan: A traffic management plan is a low priority for the City of Detroit as daily use and specific events have varying and individual traffic control needs. The wayfinding signage plans depict directional traffic flow into and out of the Fort.

Item #13: *MDOT shall construct a surface parking lot to replace legal on-street parking that is eliminated to accommodate the plaza. The lot shall be of a design and construction similar to that used for Park and Ride lots, commonly found adjacent to Interstate Highway interchanges. MDOT and the City of Detroit shall verify the number of legal parking spaces that will be removed from service to the fort. The City of Detroit shall provide a clean site for the parking lot. The parking lot, once constructed, shall become the responsibility of the City of Detroit for any maintenance and policing.*

Work Plan: There are now over 300 additional formalized/protected parking spaces along the reconfigured West Jefferson Avenue which HFW can benefit from for excess parking. MDOT offered an existing parcel adjacent to Green Steet and the RR tracks to use as a parking lot, however, in discussion with HFW, it was rejected do to due to safety, maintenance costs, and distance reasons. The City of Detroit HFW office does not have an adjacent lot for MDOT to construct a new parking lot. The HFW office is satisfied with the additional spaces that can be utilized on West Jefferson Avenue. MDOT and the City of Detroit agree that this item can be considered closed.

GSD - 3/6/2025

GSD - 3/6/2025

NEW SWINGING GATES

PARKING LOT LIGHTING

**ENTRY SIGN
AND 3 FLAG
POLES**

NEW SWINGING GATE

STONE PILLAR REPAIR

NEW GUARD HOUSE

REMOVE SIGNS, FLAG POLES, AND BROKEN CONCRETE

FENCE: REMOVE EXISTING FENCE AND BRUSH. REPLACE WITH ORNAMENTAL IRON FENCE W/ CONCRETE MAINTENANCE STRIP.



NEW SWINGING GATE

CONNECT TO DEL RAY FENCE


1. Lighting work at parking lot
 - a. Based on discussions between GSD and MDOT
2. Fence Replacement
 - a. Remove and dispose of existing fence and any vegetation
 - b. Install new ornamental iron fencing along the entire Northern edge of Fort Wayne. South side of Jefferson Ave, from Campbell St. to Rademacher St. Approximately 2,600 linear feet of fencing
 - c. 6', vertical picket ornamental iron fence, plain bars, with rings and cast spears. Flat capped posts. Finish: Black gloss
 - d. 2' wide concrete maintenance strip installed on grade
3. Entry Gates
 - a. New swinging gates at 4 locations, custom made to match fencing and fit field dimensions. All gates ornamental iron.
 - i. Entrance at Brady
 - ii. Parking lot – east entry
 - iii. Parking lot – west entry
 - iv. Jefferson Field
 - b. Brick work repair as needed on existing pillars and gates.
4. New Guard House
 - a. New prefabricated guard building. 6' x 10' steel structure with added brick facade. To include HVAC and electrical connections.
 - b. New entry gate stop - arms
5. Entrance renovation
 - a. Remove concrete and asphalt as needed to install guard house
 - b. Install new curb around guard house, and edges of roadway
 - c. Mill and resurface asphalt, replace concrete walkways
 - d. Approximately 500 LF Curb, 12,000 SF mill and resurface asphalt, and 3,000 SF concrete walkway.
 - e. Remove existing flag poles, "Historic Fort Wayne" overhead sign, and letter sign.
 - f. Install 3 flag poles. Stainless steel, 30' – 35' flag pole, in ground buried.
 - g. Install 6' GSD park sign




NEW GUARD SHACK




NEW FLAG POLES




NEW FENCE - 6' ORNAMENTAL IRON WITH RINGS AND SPEARS. ON 2' WIDE CONCRETE MAINTENANCE STRIP.




MOUNTING PLATE DETAIL



TOP VIEW - MOUNTING BRACKET



FRONT OF SIGN PANEL DETAIL



2 6' PARK SIGN INSTALLATION
L5.21 NOT TO SCALE



EGIS-BLN

GHIB FORT WAYNE LIGHTING & SITE IMPROVEMENTS

DETROIT, MI

30% DESIGN

APRIL, 2025

SHEET INDEX

LOCATION MAP



GENERAL

G1.0

G1.1

ARCHITECTURE

A1

A1.0

A1.1

A1.2

A1.3

A1.4

A1.5

A1.6

TITLE SHEET

GENERAL NOTES AND INFORMATION

OVERALL SITE PLAN

ENLARGED SITE PLAN @ MAIN ENTRANCE

ENLARGED SITE PLAN @ OPEN PARKING

SITE PLAN DETAILS

SITE PLAN DETAILS

SITE PLAN DETAILS

CLEANING AND WATER-REPELLENT TREATMENTS FOR HISTORIC MASONRY OF THE EXISTING PILLARS AND GATES

REPOINTING MORTAR JOINTS FOR HISTORIC MASONRY OF THE EXISTING PILLARS AND GATES



PROJECT LOCATION

DLZ PROJECT NO. 1641-674700




ARCHITECT/ENGINEER:
DLZ Florida, LLC
NA
NA
Ph: NA
www.dlz.com


EACH SEAL APPLIES TO ITS DESIGNATED DISCIPLINE.

PRINCIPAL ARCHITECT	SITE DEVELOPMENT	CIVIL (STORM)	CIVIL (UTILITIES)	ARCHITECTURAL	STRUCTURAL	MECHANICAL	ELECTRICAL
<div>Eric Beaulieu AIA, LEED AP</div>	<div>LA of Record</div>	<div>Civil Engineer (Drainage) of Record</div>	<div>Civil Engineer (SU) of Record</div>	<div>Architect of Record</div>	<div>Corey A. Van Luchene, PE, SE</div>	<div>Mechanical Engineer (HVAC) of Record</div>	<div>Jeromy Haines, PE</div>

DEDICATION PLAQUE




PROJECT SIGN



PROJECT SIGN MATERIALS:
SINGLE SIDED SIGN PANEL TO BE DIGITALLY PRINTED GRAPHICS AND LETTERING ON 6MM ALUMINUM COMPOSITE BOARD. SUPPORT BY THREE STANDARD 2" SQUARE TUBULAR GALVANIZED POSTS.

- CONTRACTOR SHALL FURNISH AND INSTALL, (1) PROJECT SIGN
- SHOP DRAWING - EXAMPLE OF LOGO COLORS TO BE APPROVED FOR CONTRACTOR'S USE TO MATCH.
- SUBMIT COLOR SIGN PROOF, TO ARCHITECT FOR REVIEW AND APPROVAL PRIOR TO FABRICATION.
- LETTERS SHALL BE THE COLOR "BLACK."
- BACKGROUND SHALL BE THE COLOR "WHITE."

SYMBOLS



GENERAL NOTES

- CONTRACTOR IS RESPONSIBLE TO CONFORM WITH APPLICABLE FEDERAL, STATE, AND LOCAL CODES AND REGULATIONS INCLUDING APPLICABLE ORDINANCES AND REFERENCED STANDARDS.
- CONTRACTOR IS RESPONSIBLE TO FIELD VERIFY ALL DIMENSIONS AND EXISTING CONDITIONS PRIOR TO SUBMITTING A BID OR BEGINNING ANY WORK. CONDITIONS FOUND TO BE IN VARIANCE FROM THE INFORMATION IN THE DRAWINGS OR PROJECT MANUAL SHALL BE SUBMITTED TO THE ARCHITECT IN WRITING FOR CLARIFICATION.
- KEYNOTES ARE MEANT AS A GENERAL GUIDE FOR TYPICAL LOCATIONS. CONTRACTOR TO PERFORM FULL EXTENT OF WORK REQUIRED TO ACCOMPLISH DESIGN INTENT. THE ABSENCE OF A KEYNOTE DOES NOT ABSOLVE THE CONTRACTOR FROM PROVIDING THE FEATURE GRAPHICALLY INDICATED ON THE DRAWINGS.
- SPECIFIC WORK ITEMS SHALL BE COORDINATED AND INTERFACED WITH ALL OTHER TRADES TO ALLOW FOR NEW CONSTRUCTION AND COMPLETE INSTALLATION AS REQUIRED TO ACCOMPLISH DESIGN INTENT.
- REFER TO DRAWINGS OF EACH TRADE OR DISCIPLINE FOR ADDITIONAL GENERAL NOTES AND INFORMATION, INCLUDING CIVIL/SITE DEVELOPMENT, ARCHITECTURAL, STRUCTURAL, MECHANICAL, PLUMBING, FIRE PROTECTION AND ELECTRICAL.
- CONTRACTOR IS RESPONSIBLE FOR ALL WORK IDENTIFIED ON ALL DRAWINGS AND INFORMATION IN THE PROJECT MANUAL, AS A COMPLETE PROJECT. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO DETERMINE THE SPECIFIC SCOPE OF WORK FOR ANY SUBCONTRACTORS FOR THIS PROJECT.
- FIELD VERIFY ACTUAL LOCATIONS OF EXISTING UNDERGROUND UTILITIES, STRUCTURES, WATER LINES, STORM AND SANITARY LINES, GAS LINES, ELECTRICAL CONDUIT, AND OTHER UNDERGROUND UTILITIES PRIOR TO PERFORMING EARTHWORK, EXCAVATION, OR UTILITY WORK. ENGAGE THE SERVICES OF A PRIVATE UTILITY LOCATE COMPANY IF NECESSARY TO COMPLETELY LOCATE EXISTING UNDERGROUND UTILITIES AND STRUCTURES.
- LOCATION OF ALL TEMPORARY FACILITIES SHALL BE COORDINATED WITH OWNER AND ARCHITECT PRIOR TO MOBILIZATION ON-SITE, INCLUDING BUT NOT LIMITED TO TEMPORARY STAGING AREA, MATERIAL STORAGE AREA, ACCESS DRIVE(S), PARKING AREA, TOPSOIL STOCKPILE AREA, WASTE DISPOSAL AREA, FIELD OFFICES AND TEMPORARY FACILITIES, JOB SIGN, AND TEMPORARY FENCING.
- CONTRACTOR IS RESPONSIBLE TO PROVIDE ALL MISCELLANEOUS BLOCKING REQUIRED FOR INSTALLATION OF ALL BUILDING COMPONENTS, INCLUDING BUT NOT LIMITED TO FURNISHINGS, FIXTURES, EQUIPMENT, HARDWARE, BRACKETS, AND OWNER-PROVIDED EQUIPMENT. CONTRACTOR SHALL COORDINATE SPECIFIC REQUIREMENTS ASSOCIATED WITH EACH TRADE AND WITH OWNER'S REPRESENTATIVE.
- CONTRACTOR IS RESPONSIBLE TO PROVIDE ALL MISCELLANEOUS WOOD AND METAL TRIM, FLASHING, CLIP ANGLES, ANCHORS, SUPPORTS, AND CLOSURE TRIM REQUIRED TO PROVIDE A COMPLETE, UNIFORM, AND WEATHERTIGHT ASSEMBLY AS REQUIRED TO ACCOMPLISH THE DESIGN INTENT.
- ALL EQUIPMENT SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURER'S WRITTEN RECOMMENDATIONS. CONTRACTOR SHALL PROVIDE AND INSTALL ALL ACCESSORY COMPONENTS AS REQUIRED TO FULLY COMPLY WITH MANUFACTURER'S RECOMMENDATIONS.
- CONTRACTOR SHALL PROVIDE ACCESS DOORS IN ALL WALLS AND CEILINGS WHERE SERVICE OR ADJUSTMENT TO MECHANICAL, PLUMBING, FIRE PROTECTION OR ELECTRICAL ITEMS MAY BE REQUIRED. ACCESS DOORS SHALL BE OF AN APPROPRIATE SIZE REQUIRED FOR EACH APPLICATION. WHERE APPLICABLE, ACCESS DOORS SHALL MATCH THE FIRE RATING OF THE WALL ASSEMBLY.
- WHERE DISCREPANCIES EXIST IN THE CONTRACT DOCUMENTS INCLUDING DISCREPANCIES BETWEEN DRAWINGS AND PROJECT MANUAL, CONTRACTOR SHALL REQUEST CLARIFICATION IN WRITING FROM ARCHITECT. THE CONTRACTOR SHALL NOT ASSUME ANY ITEM TAKES PRECEDENCE OVER THE OTHER. ANY ACTION THE CONTRACTOR MAKES PRIOR TO NOTIFICATION IN WRITING SHALL BE SOLELY AT THE CONTRACTOR'S RISK.
- CONTRACTOR SHALL SEAL ALL PENETRATIONS IN EXTERIOR WALL AND ROOF ASSEMBLIES WITH APPROPRIATE JOINT SEALANT(S) AND FLASHING(S) TO MAINTAIN A WEATHERTIGHT AND AIRTIGHT BUILDING ENVELOPE. ALL JOINTS AND PENETRATIONS SHALL BE SEALED, GASKETED, OR WEATHER-STRIPPED TO MINIMIZE AIR LEAKAGE, INCLUDING THE FOLLOWING:
 - JOINTS AROUND FENESTRATION AND DOOR FRAMES.
 - JUNCTIONS BETWEEN WALLS AND FOUNDATIONS, BETWEEN WALLS AT BUILDING CORNERS, BETWEEN WALLS AND FLOORS OR ROOFS, AND BETWEEN WALLS AND ROOF OR WALL PANELS.
 - OPENINGS AT PENETRATIONS OF UTILITY SERVICES THROUGH ROOFS, WALLS, AND FLOORS.
 - JOINTS, SEAMS, AND PENETRATIONS OF VAPOR RETARDERS.
 - ALL OTHER OPENINGS IN THE BUILDING ENVELOPE.
- COORDINATE WITH OTHER CONSTRUCTION ACTIVITIES AND CONSTRUCTION SEQUENCING WITH OTHER PROJECT(S) AND WORK BEING PERFORMED CONCURRENTLY ON-SITE.
- BUILDING ELEVATION 100'-0" EQUALS SITE ELEVATION _____.
- CONTRACTOR TO PROTECT ALL ITEMS WITHIN THE CONSTRUCTION LIMITS (INCLUDING SITE ELEMENTS) THAT ARE DESIGNATED TO REMAIN; ITEMS DAMAGED AS A RESULT OF WORK PERFORMED UNDER THIS CONTRACT SHALL BE REPAIRED OR REPLACED TO ORIGINAL CONDITION.
- ALL PENETRATIONS AND JOINTS IN FIRE-RATED WALL ASSEMBLIES AND FLOOR/CEILING ASSEMBLIES SHALL BE SEALED WITH THE FIRESTOPPING SYSTEM OR FIRE-RESISTIVE JOINT SYSTEM WHICH IS THE MOST APPROPRIATE FOR THE SPECIFIC APPLICATION BASED ON THE TYPE OF ASSEMBLY AND TYPE OF PENETRATING ELEMENT. SYSTEMS SHALL BE U.L.-LISTED FOR EACH APPLICATION.
- ALL VERTICAL FENESTRATION (OPERABLE AND FIXED GLAZED ASSEMBLIES) SHALL BE LABELED BY THE MANUFACTURER WITH U-FACTOR, SHGC RATING, SAFETY RATING, AND FIRE-RESISTANCE RATING, WHERE APPLICABLE. WINDOWS AND DOORS SHALL BE CERTIFIED AS MEETING AIR LEAKAGE REQUIREMENTS PER NFRC 400.
- THESE DRAWINGS SHALL NOT BE SCALED TO OBTAIN DIMENSIONS. IF THE DIMENSIONS CANNOT BE DETERMINED BY THE INFORMATION GIVEN, CONTRACTOR SHALL REQUEST CLARIFICATION FROM THE ARCHITECT. ALL DIMENSIONS ARE TO FACE OF STUD, FACE OF CMU, OR FACE OF CONCRETE, UNLESS NOTED OTHERWISE. CEILING HEIGHT DIMENSIONS ARE FROM FINISHED FLOOR TO FACE OF FINISHED CEILING MATERIALS, UNLESS NOTED OTHERWISE.
- CONTRACTOR IS RESPONSIBLE TO PROVIDE ALL NECESSARY DEWATERING ACTIVITIES AS PART OF THE BASE BID AMOUNT.

ABBREVIATIONS

ABBREVIATIONS:

A.B.	ANCHOR BOLT	FWC	FABRIC WALL COVERING	QTY.	QUANTITY
A/C	AIR CONDITIONING	FIN.	FINISH	R.	RIGHT
A.D.	AREA DRAIN	FLR	FLOOR	RA.	RADIUS
ADD.	ADDENDUM	FT	FOOT OR FEET	RA.	RETURN AIR
AFF.	ABOVE FINISHED FLOOR	FTG	FOOTING	RB	RUBBER BASE
AFG	ABOVE FINISHED GRADE			RBR	RUBBER
AFT	ATHLETIC FLOOR TILE	GA	GAUGE	RD.	ROAD
AP	ACCESS PANEL	GC	GENERAL CONTRACTOR	RD.	ROOF DRAIN
APC	ACOUSTICAL PANEL CEILING	GRV	GRAVITY ROOF VENTILATOR	RD.	RECESSED
AV	AUDIO VISUAL	GR	GROUND	REF	REFRIGERATOR
ADMIN.	ADMINISTRATION	GND.	GRADE	REV.	REVISION
AGGR.	AGGREGATE	GR.	GYPSUM WALL BOARD	REM.	REMOVABLE
ALT.	ALTERNATE	GWB		RH	RIGHT HAND
ALUM	ALUMINUM			RHR	RIGHT HAND REVERSE
APPROX	APPROXIMATE	H.	HIGH	RCP	REINFORCED CONCRETE PIPE
ARCH.	ARCHITECT (ARCHITECTURAL)	H.B.	HOSE BIBB	RE:	REFER TO:
ASPH.	ASPHALT	HM	HOLLOW METAL	RECPT	RECEPTACLE
ASSOC.	ASSOCIATE	HOA	HAND-OFF-AUTOMATIC	RECT.	RECTANGLE OR RECTANGULAR
AVG	AVERAGE	HVAC	HEATING VENTILATING & AIR-CONDITIONING	REINF	REINFORCE (D) (ING) (MENT)
		HW	HOT WATER	REQD.	REQUIRED
B/	BOTTOM	HWS	HOT WATER SUPPLY	REV.	REVERSE
BB	BOND BEAM	HWR	HOT WATER RETURN	RFG.	ROOFING
B.F.	BARRIER FREE	HDWD.	HARDWARE	RH	RIGHT HAND
BFP	BACK FLOW PREVENTER	HDWR.	HARDWARE	RHR	RIGHT HAND REVERSE
BL	BUILDING LINE	HT.(HGT.)	HEIGHT	RLG.	RAILING
BM	BENCH MARK	HDP	HIGH DENSITY PARTICALE BOARD	RM	ROOM
BTU	BRITISH THERMAL UNIT	HORIZ.	HORIZONTAL	R.R.	RAIL ROAD
B/U	BUILT UP	HR.	HOUR	RT.	RIGHT
BD	BOARD	HYD.	HYDRAULIC	RVS.	RIGHT OF WAY
BTWN	BETWEEN	ID	INSIDE DIAMETER	RWC	RAIN WATER COLLECTOR
BLDG	BUILDING	IF	INSIDE FACE	RWL	RAIN WATER LEADER
BM	BEAM	IR	INSIDE RADIUS		
BR	BULLET RESISTANT	IN.	INCH	SA	SUPPLY AIR
BRG	BEARING	INFO.	INFORMATION	SC	SEALED CONCRETE
BRZ	BRONZE	INSUL	INSULATION	SFS	STORE FRONT SYSTEM
BSMT	BASEMENT	INT.	INTERIOR	SPS	STAND PIPE
		INV.	INVERT	S.	SOUTH
C.	CONDUIT			SS	STAINLESS STEEL
CAB.	CABINET	JAN.	JANITOR OR JANITORIAL	S. TO S.	STUD TO STUD
C.B.	CATCH BASIN	J.B.	JUNCTION BOX	SHM	SECURITY HOLLOW METAL
C.B.	CORNER BAR	JCT.	JUNCTION	SV	SHEET VINYL
C.C.	CENTER TO CENTER	JT.	JOINT	SAN	SANITARY
CEM.	CEMENT			SCHED	SCHEDULE
CER.	CERAMIC	K.D.	KILN-DRIED	SECT	SECTION
CFM	CUBIC FEET PER MINUTE	KIT.	KITCHEN	SEW	SEWER
CG	CORNER GUARD	KO	KNOCKOUT	SHT	SHEET
C.I.	CAST IRON	KP.	KICK PLATE	SHWR	SHOWER
C.I.P.	CAST-IN-PLACE			SIM.	SIMILAR
CIR.	CIRCLE OR CIRCULAR	L.	LEFT	S.O.	SECTIONAL OVERHEAD
CJ	CONTROL JOINT	LAM.	LAMINATED	SPKS	SPEAKER
CL	CENTERLINE	LAV.	LAVATORY	SQ.	SQUARE
C.L.	CONSTRUCTION LINE	LBS.	POUNDS	ST	STEEL
CLG.	CEILING	LG.	LARGE	STD	STANDARD
CLOS.	CLOSET	LGTH	LENGTH	STOR.	STORAGE
CLR	CLEAR	LH	LEFT HAND	STRUCT	STRUCTURAL
CMU	CONCRETE MASONRY UNIT	LFT.(L.F.)	LINEAR FEET	SUSP.	SUSPENDED
CO	CLEAN OUT	LHR	LEFT HAND REVERSE	SW	SWITCH
COMP.	COMPACTED	L.L.	LIVE LOAD		
CONC.	CONCRETE	L.O.A.	LENGTH OVER ALL		
COND.	CONDENSATE	LIN.	LINEAR		
CONST.	CONSTRUCTION	LTG.	LIGHTING		
CONT.	CONTINUOUS			T	TEMPERED
COORD.	COORDINATE	MDP	MAIN DISTRIBUTION PANEL	T&B	TOP AND BOTTOM
CORR.	CORRIDOR	MATL.	MATERIAL	T&G	TONGUE AND GROOVE
CORG.	CORRUGATED	MAX	MAXIMUM	T/C	TOP CURB
CPT	CARPETING	MECH	MECHANICAL CONTRACTOR	TCC	TEMP. CONTROL CONTRACTOR
CSJ	CONSTRUCTION JOINT	MECH	MECHANICAL	TEMP.	TEMP. CONTROL PANEL
CTB	CERAMIC TILE BASE	MEMB.	MEMBRANE	TP	TEPID WATER
CTF	CERAMIC TILE FLOOR	MEZZ.	MEZZANINE	TWC	TEPID WATER CONTROLLER
CTW	CERAMIC TILE WALL	MFR	MANUFACTURER	TBB	TILE BACKER BOARD
CTR	CENTER OR CENTERING	MH	MAN HOLE	TEL	TELEPHONE
CU	CUBIC	MIN	MINIMUM	TEMP.	TEMPERATURE
CW	COLD WATER	MISC.	MISCELLANEOUS	TERR	TERRAZZO
		MIX.	MIXTURE	THRU	THROUGH
D.	DEEP	ML	MARK	TLT	TOILET
DF	DRINKING FOUNTAIN	MS	MASONRY OPENING	TOL.	TOLERANCE
DL	DOWN SPOUT	MSRY	MASONRY	TYP	TYPICAL
DS	DOUBLE	MTD	MOUNTED		
DBL	DOUBLE	MTL	METAL	U	HEAT TRANSFER COEFFICIENT
DEG.	DEGREE	MTG.	MOUNTING	UFD	UNDER FLOOR DUCT
DEMO	DEMOLISH (ED)			UL	UNDERWRITER'S LABORATORIES
DEPT.	DEPARTMENT			UNO	UNLESS NOTED OTHERWISE
DIA.	DIAMETER	N.	NORTH	UV	UNIT VENTILATOR
DIM.	DIMENSION	NA(N/A)	NOT APPLICABLE	UR	URINAL
DR	DOOR	NIC	NOT IN CONTRACT	UTIL.	UTILITY
DWG	DRAWING	NF	NEAR FACE		
DTL	DETAIL	N.O.P.	NOT OTHERWISE PROVIDED	VVL	VINYL
		NO.	NUMBER	VAP.	VAPOR
E.	EAST	NOM.	NOMINAL	VAR.	VARIES
EA	EXHAUST AIR	NTS	NOT TO SCALE	VCB	VINYL COVE BASE
EC	ELECTRICAL CONTRACTOR			VCP	VITRIFIED CLAY PIPE
EF	EXHAUST FAN	OA	OVERALL	VCT	VINYL COMPOSITION TILE
EFS	EXT. INSULATION FINISH SYSTEM	OA	OUTSIDE AIR	VERT.	VERTICAL
EJ	EXPANSION JOINT	OAI	OUTSIDE AIR INTAKE	VEST.	VESTIBULE
EMER.	EMERGENCY	OC	ON CENTER	VENT.	VENTILATE
E.PAN.	ELECTRICAL PANEL	OD	OUTSIDE DIAMETER	VIF	VERIFY IN FIELD
E.W.	EACH WAY	O.T.O.	OUT TO OUT	VOL.	VOLUME
EWC	ELECTRIC WATER COOLER	OF	OUTSIDE FACE	VP	VENT PIPE
EL	ELEVATION	OR	OVERLOAD	VS	VENT STACK
ELEC.	ELECTRICAL OR ELECTRIC	OL.	OVERLOAD	VWC	VINYL WALL COVERING
ELEV.	ELEVATOR	OFC.	OFFICE		
ENG.	ENGINEER OR ENGINEERING	OH	OVERHEAD	W.	WEST
EQ	EQUAL	OPNG.	OPENING	WC	WATER CLOSET
EQUIP.	EQUIPMENT	OPP.	OPPOSITE	WD	WOOD
ETC.	ET CETERA	OR.	OUTSIDE RADIUS	WF	WASH FOUNTAIN
EXIST.	EXISTING	ORIG.	ORIGINAL	WH	WALL HUNG
EXP	EXPOSED STRUCTURE	OZ	OUNCE	WH	WATER HEATER
EXP.	EXPANSION			WI	WROUGHT IRON
EXT.	EXTERIOR	P.A.	PIPE ANCHOR	WP	WORKING POINT
		P.C.	PLUMBING CONTRACTOR	WL	WIND LOAD
FACP	FIRE ALARM CONTROL PANEL	P.D.	PRESSURE DROP	WM	WALK OFF MAT
FAI	FRESH AIR INTAKE	P.F.	PRESS MOLDED JOINT FILLER	WS	WORK SINK
FAC.	FURNACE	PFRV	PRESSURE REDUCING VALVE	WWF	WROUGHT WIRE FABRIC
FD	FLOOR DRAIN	PASS.	PASSENGER	WT.	WEIGHT
FE	FIRE EXTINGUISHER	PAT.	PATTERN		
FEC	FIRE EXTINGUISHER CABINET	PERP.	PERPENDICULAR	XFMR	TRANSFORMER
FHC	FIRE HOSE CABINET	PF	PRE-FINISHED	XFR	TRANSFER
FLO.	FLOOR MOUNTED	PLAM	PLASTIC LAMINATE		
FR	FIN RADIATION	PLAS	PLASTIC	YD	YARD
F.S.	FOOD SERVICE	PLBG.	PLUMBING	YCO	YARD CLEAN OUT
FV	FIELD VERIFY	PLY	PLYWOOD		
		PNEU.	PNEUMATIC	*	DEGREE
		PNL	PANEL	±	PLUS OR MINUS
		PREFAB	PREFABRICATED	Ø	DIAMETER
		PROJ.	PROJECT		CENTERLINE
		PT	PAINT	P	PLATE
		P.CONC.	PRECAST CONCRETE SLAB	&	AND
		PARTN.	PARTITION	BY	BY
		P.V.	PAVERS	@	PER
		PVC	POLYVINYL CHLORIDE	#	NUMBER
				W/	WITH
		QCV	QUICK COUPLER VALVE		
		QT	QUARRY TILE		
		QUAL.	QUALITY		




DATE	REVISION	NO.

DRAWN: Author	CHK'D: Chkd
DESIGNED: Designer	
APPRVD: Approver	
DATE: APRIL, 2025	
PROJECT NUMBER	1641-674700

EGIS-BLN	GHIB FORT WAYNE LIGHTING & SITE IMPROVEMENTS	GENERAL NOTES AND INFORMATION

DRAWING NUMBER	G1.1	GENERAL



GENERAL NOTES:

- REFER TO G SERIES DRAWINGS FOR ADDITIONAL GENERAL NOTES AND INFORMATION.
1. REFER TO DRAWINGS OF ALL OTHER DISCIPLINES FOR ADDITIONAL REMOVALS AND SELECTIVE DEMOLITION ACTIVITIES.
2. CONTRACTOR SHALL FIELD VERIFY ALL EXISTING CONDITIONS AND DIMENSIONS PRIOR TO SELECTIVE DEMOLITION ACTIVITIES.
3. CONTRACTOR SHALL REMOVE EXISTING ASBESTOS-CONTAINING MATERIALS (ACM) WITHIN THE BUILDING. REFER TO ENVIRONMENTAL SERIES DRAWINGS FOR ADDITIONAL INFORMATION.
4. EXISTING TO REMAIN ITEMS SHALL BE PROTECTED THROUGHOUT.
5. THE DURATION OF THE PROJECT. IF ANY EXISTING ITEM IS DAMAGED DURING CONSTRUCTION, IT SHALL BE REPLACED OR RESTORED TO ITS ORIGINAL CONDITION.
6. CONTRACTOR IS RESPONSIBLE TO PROVIDE ALL TEMPORARY SHORING AND BRACING REQUIRED TO COMPLETE THE WORK.
7. CONTRACTOR IS RESPONSIBLE FOR ALL CUTTING AND PATCHING REQUIRED, INCLUDING ASSOCIATED REPAIR AND FINISHING TO MATCH ADJACENT SURFACES.
8. REMOVE ALL ABANDONED EQUIPMENT, DUCTWORK, PLUMBING, ELECTRICAL, DATA, AND COMMUNICATIONS LINES, DEVICES, AND EQUIPMENT. EXPOSED UTILITIES SHALL BE IDENTIFIED, CAPPED, AND LABELED.
9. CONTRACTOR IS RESPONSIBLE FOR ALL TEMPORARY ENVIRONMENTAL CONTROL MEASURES INCLUDING APPLICABLE AIR QUALITY CONTROL MEASURES, DUST CONTROL, EROSION CONTROL, AND OTHER MEASURES REQUIRED FOR PROTECTION OF OCCUPANTS AND PROPERTY DURING SELECTIVE DEMOLITION AND CONSTRUCTION ACTIVITIES.
10. CONTRACTOR IS SOLELY RESPONSIBLE FOR COORDINATING CONTRACT DOCUMENTS WITH FIELD CONDITIONS AND WITH WORK REQUIRED FOR EACH TRADE.
11. EXISTING CONCRETE SLAB-ON-GRADE SHALL BE SAWCUT AND REMOVED AS REQUIRED TO COMPLETE UNDERGROUND PIPING WORK. REPLACE CONCRETE SLAB-ON-GRADE AND FINISH TO MATCH ADJACENT CONSTRUCTION. ALL CONCRETE REMOVAL AND REPLACEMENT BEYOND THAT SHOWN IS INCIDENTAL TO THE WORK AND SHALL BE INCLUDED IN THE CONTRACTOR'S BID AS REQUIRED TO COMPLETE THE PROJECT.
12. BUILDING TO REMAIN PARTIALLY OCCUPIED DURING CONSTRUCTION. SEQUENCE ALL DEMOLITION ACTIVITIES ACCORDINGLY TO MINIMIZE DISRUPTION OF BUILDING OCCUPANTS. REFER TO PHASING PLANS.
13. CONTRACTOR SHALL COORDINATE DEMOLITION ACTIVITIES WITH NEW WORK TO VERIFY DIMENSIONS AND EXTENT OF REMOVALS PRIOR TO BEGINNING WORK.



NOTE: REFER TO PRESERVATION BRIEFS AND PROJECT SPECIFICATION FOR MORE INFORMATION ON HOW TO REPAIR HISTORIC STONE PILLAR AND BRICK WORK.

1. WALL PREPARATION RESTORATION TO BE CONSISTENT WITH U.S. DEPARTMENT OF INTERIOR PRESERVATION BRIEFS ON "CLEANING AND WATER-REPELLENT TREATMENTS FOR HISTORIC MASONRY" AND "REPOINTING MORTAR JOINTS FOR HISTORIC MASONRY BUILDINGS"
2. 1. REFER TO PROJECT MANUAL FOR ADDITIONAL REQUIREMENTS.
3. 2. CONTRACTOR TO FIELD VERIFY ALL EXISTING CONDITIONS AND DIMENSIONS.
4. 3. REMOVE AND REPOINT ALL FAILED MASONRY MORTAR JOINTS.
5. 4. REMOVE SURFACE RUST AND LOOSE PAINT FROM EXISTING STEEL LINTELS AND RE-PAINT THE STEEL LINTELS.
6. 5. MASONRY SHALL BE RE-TUCK POINTED AS NECESSARY TO STOP AIR AND WATER INFILTRATION.
7. 6. PROVIDE ALL REQUIRED PROJECT DOCUMENTATION, INCLUDING BUT NOT LIMITED TO SUBMITTALS, SHOP DRAWINGS, PRODUCT DATA, SAMPLES, TEST REPORTS, INSPECTION REPORTS, DAILY REPORTS, SCHEDULE UPDATES, PROJECT PHOTOGRAPHS, O&M MANUALS, WARRANTIES, AS-BUILTS, AND OTHER REQUIRED DOCUMENTATION. ALL DOCUMENTS TO BE PROVIDED IN A TIMELY MANNER.
8. 7. PROVIDE ALL REQUIRED FIELD SUPERVISION, QUALITY CONTROL, AND SAFETY PERSONNEL AS REQUIRED. FULL TIME SUPERVISION MUST ALWAYS BE PROVIDED WHEN WORK IS BEING PERFORMED ON-SITE.
9. PATCH AND REPAIR ALL EXISTING WALL, FLOOR AND CEILING CONSTRUCTION DAMAGED BY CONSTRUCTION ACTIVITIES TO MATCH EXISTING ADJACENT FINISH SURFACES.
10. 8. T. REPLACE ALL WINDOW SEALS TO ERA CORRECT MATERIALS.
11. 9. RESTORE WEIGHTS AND COUNTER BALANCE SYSTEM.
12. 10. CONTRACTOR TO TAKE ALL NECESSARY PRECAUTIONS IN HANDLING OF ANY MATERIAL REQUIRING ABATEMENT, SEE SPECIFICATIONS.


KEYNOTES

- 107500 GROUND-SET FLAGPOLES
- 265600 EXTERIOR LIGHTING, LIGHTING POLES AND STANDARDS

LEGEND:

-  EXISTING TO BE REMOVED
 EXISTING CONCRETE & ASPHALT TO BE REMOVED
 EXISTING TO REMAIN

Autodesk Docs/1641-6470-00 GHIB Site Improvements/1641-6470-00 GHIB Site
1/19/2025 12:26:01 PM
4/25/2025 12:26:01 PM



1 ENLARGED SITE PLAN @ OPEN PARKING
SCALE: 1/32" = 1'-0"

GENERAL NOTES:

- A. REFER TO G SERIES DRAWINGS FOR ADDITIONAL GENERAL NOTES AND INFORMATION.
- B. REFER TO DRAWINGS OF ALL OTHER DISCIPLINES FOR ADDITIONAL REMOVALS AND SELECTIVE DEMOLITION ACTIVITIES.
- C. CONTRACTOR SHALL FIELD VERIFY ALL EXISTING CONDITIONS AND DIMENSIONS PRIOR TO SELECTIVE DEMOLITION ACTIVITIES.
- D. CONTRACTOR SHALL REMOVE EXISTING ASBESTOS-CONTAINING MATERIALS (ACM) WITHIN THE BUILDING. REFER TO ENVIRONMENTAL SERIES DRAWINGS FOR ADDITIONAL INFORMATION.
- E. EXISTING TO REMAIN ITEMS SHALL BE PROTECTED THROUGHOUT.
- F. THE DURATION OF THE PROJECT. IF ANY EXISTING ITEM IS DAMAGED DURING CONSTRUCTION, IT SHALL BE REPLACED OR RESTORED TO ITS ORIGINAL CONDITION.
- G. CONTRACTOR IS RESPONSIBLE TO PROVIDE ALL TEMPORARY SHORING AND BRACING REQUIRED TO COMPLETE THE WORK.
- H. CONTRACTOR IS RESPONSIBLE FOR ALL CUTTING AND PATCHING REQUIRED, INCLUDING ASSOCIATED REPAIR AND FINISHING TO MATCH ADJACENT SURFACES.
- I. REMOVE ALL ABANDONED EQUIPMENT, DUCTWORK, PLUMBING, ELECTRICAL, DATA, AND COMMUNICATIONS LINES, DEVICES, AND EQUIPMENT. EXPOSED UTILITIES SHALL BE IDENTIFIED, CAPPED, AND LABELED.
- J. CONTRACTOR IS RESPONSIBLE FOR ALL TEMPORARY ENVIRONMENTAL CONTROL MEASURES INCLUDING APPLICABLE AIR QUALITY CONTROL MEASURES, DUST CONTROL, EROSION CONTROL, AND OTHER MEASURES REQUIRED FOR PROTECTION OF OCCUPANTS AND PROPERTY DURING SELECTIVE DEMOLITION AND CONSTRUCTION ACTIVITIES.
- K. CONTRACTOR IS SOLELY RESPONSIBLE FOR COORDINATING CONTRACT DOCUMENTS WITH FIELD CONDITIONS AND WITH WORK REQUIRED FOR EACH TRADE.
- L. EXISTING CONCRETE SLAB-ON-GRADE SHALL BE SAWCUT AND REMOVED AS REQUIRED TO COMPLETE UNDERGROUND PIPING WORK. REPLACE CONCRETE SLAB-ON-GRADE AND FINISH TO MATCH ADJACENT CONSTRUCTION. ALL CONCRETE REMOVAL AND REPLACEMENT BEYOND THAT SHOWN IS INCIDENTAL TO THE WORK AND SHALL BE INCLUDED IN THE CONTRACTOR'S BID AS REQUIRED TO COMPLETE THE PROJECT.
- M. BUILDING TO REMAIN PARTIALLY OCCUPIED DURING CONSTRUCTION. SEQUENCE ALL DEMOLITION ACTIVITIES ACCORDINGLY TO MINIMIZE DISRUPTION OF BUILDING OCCUPANTS. REFER TO PHASING PLANS.
- N. CONTRACTOR SHALL COORDINATE DEMOLITION ACTIVITIES WITH NEW WORK TO VERIFY DIMENSIONS AND EXTENT OF REMOVALS PRIOR TO BEGINNING WORK.

NOTE: REFER TO PRESERVATION BRIEFS AND PROJECT SPECIFICATION FOR MORE INFORMATION ON HOW TO REPAIR HISTORIC STONE PILLAR AND BRICK WORK.

- A. WALL PREPARATION RESTORATION TO BE CONSISTENT WITH U.S. DEPARTMENT OF INTERIOR PRESERVATION BRIEFS ON "CLEANING AND WATER-REPELLENT TREATMENTS FOR HISTORIC MASONRY" AND "REPOINTING MORTAR JOINTS FOR HISTORIC MASONRY BUILDINGS"
- B. REFER TO PROJECT MANUAL FOR ADDITIONAL REQUIREMENTS.
- C. CONTRACTOR TO FIELD VERIFY ALL EXISTING CONDITIONS AND DIMENSIONS.
- D. REMOVE AND REPOINT ALL FAILED MASONRY MORTAR JOINTS.
- E. REMOVE SURFACE RUST AND LOOSE PAINT FROM EXISTING STEEL LINTELS AND RE-PAINT THE STEEL LINTELS.
- F. MASONRY SHALL BE RE-TUCK POINTED AS NECESSARY TO STOP AIR AND WATER INFILTRATION.
- G. PROVIDE ALL REQUIRED PROJECT DOCUMENTATION, INCLUDING BUT NOT LIMITED TO SUBMITTALS, SHOP DRAWINGS, PRODUCT DATA, SAMPLES, TEST REPORTS, INSPECTION REPORTS, DAILY REPORTS, SCHEDULE UPDATES, PROJECT PHOTOGRAPHS, O&M MANUALS, WARRANTIES, AS-BUILTS, AND OTHER REQUIRED DOCUMENTATION. ALL DOCUMENTS TO BE PROVIDED IN A TIMELY MANNER.
- H. PROVIDE ALL REQUIRED FIELD SUPERVISION, QUALITY CONTROL, AND SAFETY PERSONNEL AS REQUIRED. FULL TIME SUPERVISION MUST ALWAYS BE PROVIDED WHEN WORK IS BEING PERFORMED ON-SITE.
- I. PATCH AND REPAIR ALL EXISTING WALL, FLOOR AND CEILING CONSTRUCTION DAMAGED BY CONSTRUCTION ACTIVITIES TO MATCH EXISTING ADJACENT FINISH SURFACES.
- J. T. REPLACE ALL WINDOW SEALS TO ERA CORRECT MATERIALS.
- K. RESTORE WEIGHTS AND COUNTER BALANCE SYSTEM.
- L. CONTRACTOR TO TAKE ALL NECESSARY PRECAUTIONS IN HANDLING OF ANY MATERIAL REQUIRING ABATEMENT, SEE SPECIFICATIONS.

KEYNOTES

265600 EXTERIOR LIGHTING, LIGHTING POLES AND STANDARDS

LEGEND:

- EXISTING TO BE REMOVED
- EXISTING CONCRETE & ASPHALT TO BE REMOVED
- EXISTING TO REMAIN

DLZ

ARCHITECTURE • ENGINEERING • PLANNING
SURVEYING • CONSTRUCTION SERVICES

DLZ Florida, LLC

DRAWING NUMBER

A1.1

ARCHITECTURE

DETROIT

EGIS-BLN
GHIB FORT WAYNE LIGHTING & SITE IMPROVEMENTS




ENLARGED SITE PLAN @ OPEN PARKING

DATE

APRIL 2025

PROJECT NUMBER

1641-674700



1-1/2" MAXIMUM SHOP GAP
ALLOWED FOR FIELD
FITTING (RAM FOR TIGHT
JOINT)

A. REFER TO G1.1 FOR ADDITIONAL GENERAL NOTES AND INFORMATION.

DRAWN: Author	CHK'D: Chkd
DESIGNED: Designer	
APPRVD: Approver	
DATE: APRIL, 2025	
PROJECT NUMBER	
	1641-674700


GHIB FORT WAYNE LIGHTING & SITE IMPROVEMENTS

SITE PLAN DETAILS


A1.2

ARCHITECTURE

Autodesk Docs/1641-6470-00 GHIB Site Improvements/1641-6470-00 GHIB Site
1/16/2025 12:42 PM
4/25/2025 12:42 PM




1 GUARD HOUSE
SCALE: 3/4" = 1'-0"



- LEGEND:
- 9 - DOOR
 - 10 - ELECTRICAL
 - 11 - LIGHTING (DUAL BULB, FLUORESCENT STRIP LIGHTS)
 - 12 - HEAT (LOCATION OPTIONAL)
 - 13 - COUNTER
 - 14 - A/C (LOCATION OPTIONAL)
 - 15 - ARCHES (OPTIONAL)

- NOTES:
1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
 2. DO NOT SCALE DRAWINGS.
 3. CUSTOM MATCHING: COLORS & SIGNAGE AVAILABLE.
 4. SEE PICTURE # 1 IN AUSTIN MOHAWK BROCHURE.

2 GUARD HOUSE FLOOR PLAN
SCALE: 3/4" = 1'-0"



3 GUARD HOUSE ELEVATIONS
SCALE: 1/2" = 1'-0"


GENERAL NOTES:

- A. REFER TO G1.1 FOR ADDITIONAL GENERAL NOTES AND INFORMATION.


DATE	REVISION	NO.	CHKD:	CHKD:
			Author	Designer
			Appr'd:	Appr'd:
			DATE:	DATE:
			PROJECT NUMBER	PROJECT NUMBER
			1641-674700	1641-674700

DRAWING NUMBER	EGIS-BLN	GHIB FORT WAYNE LIGHTING & SITE IMPROVEMENTS	SITE PLAN DETAILS
A1.3			
ARCHITECTURE			

Autodesk Docs\\1641-6470-00 GHIB Site Improvements\\1641-6470-00 GHIB Site
1/25/2025 1:25:18 PM
1641-6470-00 GHIB Site Improvements\\1641-6470-00 GHIB Site




2 ORNAMENTAL DRIVEWAY SWINGING GATE
SCALE: 3/4" = 1'-0"






- NOTES:**
- 1.) Post size depends on fence height and wind loads.
 - 2.) Panels also available for 6' on center post spacing
 - 3.) Additional heights available on request
 - 4.) Third rail optional (Required with rings, See Detail).

1 ORNAMENTAL IRON FENCE W/ CONCRETE MAINTENANCE STRIP
SCALE: 3/4" = 1'-0"

APPLICABLE HARDWARE



VERSAI RINGS-3D-RES
for Level Installations
(Optional)



- NOTES:**
1. GATE SHOWN WITH OUR CLOSING STANDARD HARDWARE.
 2. OTHER GATE HARDWARE COULD CHANGE LATCH AND HINGE CLEARANCE.
 3. ALL HARDWARE SHIPPED LOOSE AND FIELD INSTALLED.

3 ORNAMENTAL IRON SWING GATE
SCALE: 3/4" = 1'-0"

DATE	REVISION	NO.

DRAWN: Author	CHKD: Chkd
DESIGNED: Designer	APPROVED: Approver
DATE: APRIL 2025	PROJECT NUMBER
1641-674700	


MI	EGIS-BLN	GHIB FORT WAYNE LIGHTING & SITE IMPROVEMENTS
DETROIT		SITE PLAN DETAILS

DRAWING NUMBER	ARCHITECTURE
A1.4	

Autodesk Docs//1641-6470-00 GHIB Site Improvements/1641-6470-00 GHIB Site
1/25/2025 12:32 PM
ghib_sch.dwg



OVERALL SITE
SCALE: 1" = 100'-0"



GENERAL NOTES:

- A. REFER TO G SERIES DRAWINGS FOR ADDITIONAL GENERAL NOTES AND INFORMATION.
- B. REFER TO DRAWINGS OF ALL OTHER DISCIPLINES FOR ADDITIONAL REMOVALS AND SELECTIVE DEMOLITION ACTIVITIES.
- C. CONTRACTOR SHALL FIELD VERIFY ALL EXISTING CONDITIONS AND DIMENSIONS PRIOR TO SELECTIVE DEMOLITION ACTIVITIES.
- D. CONTRACTOR SHALL REMOVE EXISTING ASBESTOS-CONTAINING MATERIALS (ACM) WITHIN THE BUILDING. REFER TO ENVIRONMENTAL SERIES DRAWINGS FOR ADDITIONAL INFORMATION.
- E. EXISTING TO REMAIN ITEMS SHALL BE PROTECTED THROUGHOUT.
- F. THE DURATION OF THE PROJECT, IF ANY EXISTING ITEM IS DAMAGED DURING CONSTRUCTION, IT SHALL BE REPLACED OR RESTORED TO ITS ORIGINAL CONDITION.
- G. CONTRACTOR IS RESPONSIBLE TO PROVIDE ALL TEMPORARY SHORING AND BRACING REQUIRED TO COMPLETE THE WORK.
- H. CONTRACTOR IS RESPONSIBLE FOR ALL CUTTING AND PATCHING REQUIRED, INCLUDING ASSOCIATED REPAIR AND FINISHING TO MATCH ADJACENT SURFACES.
- I. REMOVE ALL ABANDONED EQUIPMENT, DUCTWORK, PLUMBING, ELECTRICAL, DATA, AND COMMUNICATIONS LINES, DEVICES, AND EQUIPMENT. EXPOSED UTILITIES SHALL BE IDENTIFIED, CAPPED, AND LABELED.
- J. CONTRACTOR IS RESPONSIBLE FOR ALL TEMPORARY ENVIRONMENTAL CONTROL MEASURES INCLUDING APPLICABLE AIR QUALITY CONTROL MEASURES, DUST CONTROL, EROSION CONTROL, AND OTHER MEASURES REQUIRED FOR PROTECTION OF OCCUPANTS AND PROPERTY DURING SELECTIVE DEMOLITION AND CONSTRUCTION ACTIVITIES.
- K. CONTRACTOR IS SOLELY RESPONSIBLE FOR COORDINATING CONTRACT DOCUMENTS WITH FIELD CONDITIONS AND WITH WORK REQUIRED FOR EACH TRADE.
- L. EXISTING CONCRETE SLAB-ON-GRADE SHALL BE SAWCUT AND REMOVED AS REQUIRED TO COMPLETE UNDERGROUND PIPING WORK. REPLACE CONCRETE SLAB-ON-GRADE AND FINISH TO MATCH ADJACENT CONSTRUCTION. ALL CONCRETE REMOVAL AND REPLACEMENT BEYOND THAT SHOWN IS INCIDENTAL TO THE WORK AND SHALL BE INCLUDED IN THE CONTRACTOR'S BID AS REQUIRED TO COMPLETE THE PROJECT.
- M. BUILDING TO REMAIN PARTIALLY OCCUPIED DURING CONSTRUCTION. SEQUENCE ALL DEMOLITION ACTIVITIES ACCORDINGLY TO MINIMIZE DISRUPTION OF BUILDING OCCUPANTS. REFER TO PHASING PLANS.
- N. CONTRACTOR SHALL COORDINATE DEMOLITION ACTIVITIES WITH NEW WORK TO VERIFY DIMENSIONS AND EXTENT OF REMOVALS PRIOR TO BEGINNING WORK.

NOTE: REFER TO PRESERVATION BRIEFS AND PROJECT SPECIFICATION FOR MORE INFORMATION ON HOW TO REPAIR HISTORIC STONE PILLAR AND BRICK WORK.














































- A. WALL PREPARATION RESTORATION TO BE CONSISTENT WITH U.S. DEPARTMENT OF INTERIOR PRESERVATION BRIEFS ON "CLEANING AND WATER-REPELLENT TREATMENTS FOR HISTORIC MASONRY" AND "REPOINTING MORTAR JOINTS FOR HISTORIC MASONRY BUILDINGS"
- B. REFER TO PROJECT MANUAL FOR ADDITIONAL REQUIREMENTS.
- C. CONTRACTOR TO FIELD VERIFY ALL EXISTING CONDITIONS AND DIMENSIONS.
- D. REMOVE AND REPOINT ALL FAILED MASONRY MORTAR JOINTS.
- E. REMOVE SURFACE RUST AND LOOSE PAINT FROM EXISTING STEEL LINTELS AND RE-PAINT THE STEEL LINTELS.
- F. MASONRY SHALL BE RE-TUCK POINTED AS NECESSARY TO STOP AIR AND WATER INFILTRATION.
- G. PROVIDE ALL REQUIRED PROJECT DOCUMENTATION, INCLUDING BUT NOT LIMITED TO SUBMITTALS, SHOP DRAWINGS, PRODUCT DATA, SAMPLES, TEST REPORTS, INSPECTION REPORTS, DAILY REPORTS, SCHEDULE UPDATES, PROJECT PHOTOGRAPHS, O&M MANUALS, WARRANTIES, AS-BUILTS, AND OTHER REQUIRED DOCUMENTATION. ALL DOCUMENTS TO BE PROVIDED IN A TIMELY MANNER.
- H. PROVIDE ALL REQUIRED FIELD SUPERVISION, QUALITY CONTROL, AND SAFETY PERSONNEL AS REQUIRED. FULL TIME SUPERVISION MUST ALWAYS BE PROVIDED WHEN WORK IS BEING PERFORMED ON-SITE.
- I. PATCH AND REPAIR ALL EXISTING WALL, FLOOR AND CEILING CONSTRUCTION DAMAGED BY CONSTRUCTION ACTIVITIES TO MATCH EXISTING ADJACENT FINISH SURFACES.
- J. T. REPLACE ALL WINDOW SEALS TO ERA CORRECT MATERIALS.
- K. RESTORE WEIGHTS AND COUNTER BALANCE SYSTEM.
- L. CONTRACTOR TO TAKE ALL NECESSARY PRECAUTIONS IN HANDLING OF ANY MATERIAL REQUIRING ABATEMENT, SEE SPECIFICATIONS.




























LEGEND:

- EXISTING TO BE REMOVED
- EXISTING CONCRETE & ASPHALT TO BE REMOVED
- EXISTING TO REMAIN



DRAWING NUMBER	A1	ARCHITECTURE	DETROIT	EGIS-BLN GHIB FORT WAYNE LIGHTING & SITE IMPROVEMENTS	OVERALL SITE PLAN	MI	NO.	REVISION	DATE	DRAWN: Author	CHKD: Chkd	DESIGNED: Designer	APPRVD: Approver	DATE: APRIL 2025	PROJECT NUMBER	1641-674700	DLZ ARCHITECTURE • ENGINEERING • PLANNING SURVEYING • CONSTRUCTION SERVICES DLZ Florida, LLC

ELECTRICAL SYMBOLS:















	DUPLEX RECEPTACLE, 125V, 20A. INSTALL DEVICE WITH BOTTOM AT +16" A.F.F., U.O.N. ASTERISK INDICATES VANDALPROOF STYLE RECEPTACLE FACEPLATE. VV=VIDEO VISITATION / IPAD CHARGING STATION, OUTLET TO BE LOCATED BEHIND MONITOR, VERIFY EXACT HEIGHT AND LOCATION BEFORE ROUGH-IN. USB = 125V, 20A, USB CHARGING DUPLEX RECEPTACLE. WP = WEATHERPROOF "WHILE-IN-USE" ENCLOSURE. GFCI = GROUND FAULT CIRCUIT INTERRUPTING TYPE DEVICE. U.O.N., COORDINATE EXACT LOCATION BEFORE ROUGH-IN.
	GROUND FAULT CIRCUIT INTERRUPTING TYPE RECEPTACLE, 125V, 20A. INSTALL DEVICE WITH BOTTOM AT +16" A.F.F. U.O.N. WP = WEATHERPROOF "WHILE IN USE" ENCLOSURE.
	GROUND FAULT CIRCUIT INTERRUPTING QUAD RECEPTACLE, 125V, 20A. INSTALL DEVICE WITH BOTTOM AT +16" A.F.F. U.O.N. COORDINATE EXACT LOCATION BEFORE ROUGH-IN.
	DUPLEX RECEPTACLE, 125V, 20A. INSTALL DEVICE WITH TOP AT +40" A.F.F., U.O.N.
	DUPLEX RECEPTACLE ON UNINTERRUPTIBLE POWER SUPPLY CIRCUIT, 125V, 20A. INSTALL DEVICE WITH BOTTOM AT +16", A.F.F., U.O.N. RECEPTACLE TO BE COLOR "ORANGE".
	DUPLEX RECEPTACLE ON UNINTERRUPTIBLE POWER SUPPLY CIRCUIT, 125V, 20A. INSTALL DEVICE WITH TOP AT +40" A.F.F., U.O.N. RECEPTACLE TO BE COLOR "ORANGE".
	DUPLEX RECEPTACLE CEILING MOUNTED 125V, 20A. REFER TO SPECIFICATIONS AND DRAWINGS FOR FURTHER DETAILS.
	DUPLEX RECEPTACLE LIGHTING MOUNTED ON UNINTERRUPTIBLE POWER SUPPLY CIRCUIT 125V, 20A. REFER TO SPECIFICATIONS AND DRAWINGS FOR FURTHER DETAILS. RECEPTACLE TO BE COLOR "ORANGE".
	DUPLEX RECEPTACLE FLOOR BOX 125V, 20A. REFER TO SPECIFICATIONS AND DRAWINGS FOR DETAILED ELECTRICAL REQUIREMENTS.
	QUAD RECEPTACLE, 125V, 20A. INSTALL DEVICE WITH BOTTOM AT +16" A.F.F., U.O.N.
	QUAD RECEPTACLE, 125V, 20A. INSTALL DEVICE WITH TOP AT +40" A.F.F., U.O.N.
	QUAD RECEPTACLE ON UNINTERRUPTIBLE POWER SUPPLY CIRCUIT, 125V, 20A. INSTALL DEVICE WITH BOTTOM AT +16" A.F.F., U.O.N. RECEPTACLE TO BE COLOR "ORANGE".
	QUAD RECEPTACLE ON UNINTERRUPTIBLE POWER SUPPLY CIRCUIT, 125V, 20A. INSTALL DEVICE WITH TOP AT +40" A.F.F., U.O.N. RECEPTACLE TO BE COLOR "ORANGE".
	SPECIAL RECEPTACLE, REFER TO MANUFACTURER REQUIREMENTS. INSTALL DEVICE WITH BOTTOM AT +16" A.F.F., U.O.N.
	SPECIAL RECEPTACLE ON UNINTERRUPTIBLE POWER SUPPLY CIRCUIT, REFER TO MANUFACTURER REQUIREMENTS. INSTALL DEVICE WITH BOTTOM AT +16" A.F.F., U.O.N. RECEPTACLE TO BE COLOR "ORANGE".
	JUNCTION BOX.
	RELAY.
	TOGGLE SWITCH, 120/277V, 1-POLE, 20A. WP=WEATHERPROOF ENCLOSURE, "a" INDICATES SWITCH LEG.
	TOGGLE SWITCH, THREE WAY TYPE, 120/277V, 20A, "a" INDICATES SWITCH LEG.
	TOGGLE SWITCH, FOUR WAY TYPE, 120/277V, 20A, "a" INDICATES SWITCH LEG.
	DIMMABLE SWITCH, 120/277V, 20A, "a" INDICATES SWITCH LEG.
	DUAL TECHNOLOGY OCCUPANCY SENSOR, CEILING OR WALL MOUNT COVERAGE OF SENSOR DEPENDENT ON ROOM SIZE, "a" INDICATES SWITCH LEG. "WG" INDICATES WIRE GUARD INCLUDED. POWER PACKS NOT SHOWN - FIELD LOCATE AND RECORD ON RECORD DRAWINGS.
	PIR HIGH BAY OCCUPANCY SENSOR. PROVIDE POWER PACK(S) AS REQUIRED PER MANUFACTURER'S RECOMMENDATION, "a" INDICATES SWITCH LEG.
	4" SQUARE BOX WITH SINGLE GANG ADAPTER FOR MOUNTING EMERGENCY POWER CONTROL MODULE. MOUNT WHERE INDICATED ON PLANS. PROVIDE PERMANENT LABEL ON MODULE FACEPLATE INDICATING ROOM/AREA(S) WHERE CONTROLLED LIGHTS ARE LOCATED. "C" INDICATES DEVICE FLUSH MOUNTED IN CEILING, "W" INDICATES DEVICE FLUSH MOUNTED IN WALL. COORDINATE EXACT LOCATON WITH OWNER BEFORE ROUGH-IN.
	DISTRIBUTION PANELBOARD, SEE SCHEDULE FOR DETAILED REQUIREMENTS.
	PANELBOARD, SEE SCHEDULE FOR DETAILED REQUIREMENTS.
	NON-FUSED DISCONNECT SWITCH, SEE DRAWINGS FOR DETAILED REQUIREMENTS.
	FUSED DISCONNECT SWITCH, SEE DRAWINGS FOR DETAILED REQUIREMENTS.
	NON-COMBINATION STARTER, SEE DRAWINGS FOR DETAILED REQUIREMENTS.
	COMBINATION STARTER/DISCONNECT, SEE DRAWINGS FOR DETAILED REQUIREMENTS.
	VARIABLE FREQUENCY DRIVE, SEE DRAWINGS FOR DETAILED REQUIREMENTS.
	VARIABLE FREQUENCY DRIVE AND DISCONNECT COMBINATION, SEE DRAWINGS FOR DETAILED REQUIREMENTS.
	NON-COMBINATION MAGNETIC MOTOR STARTER NUMBER INDICATES NEMA RATING, SIZE 1 U.O.N.
	MOTOR.
	SMOKE DAMPER. CONNECT TO LEGALLY REQUIRED 120VAC BRANCH CIRCUIT. DAMPER SHALL OPEN UPON ENERGIZATINO (OR FAIL CLOSED UPON DE-ENERGIZED). POWER TO SMOKE DAMPER(S) ASSOCIATE WITH AHU SHALL BE CONTROLLED BY THE FIRE ALARM CONTROL PANEL UPON DUCT DETECTOR SMOKE DETECTION AT AHU. ASSOCIATED DAMPER(S) SHALL CLOSE (BE DE-ENERGIZED). REFER TO DETAIL #___, ON DRAWING E___ FOR SMOKE DAMPER WIRING DETAIL. REFER TO DRAWING E___ AND E___ FOR LOCATION OF AHU(S) REQUIREING DUCT SMOKE DETECTOR(S)
	PULLBOX
	ADDRESSABLE FIRE ALARM HEAT DETECTOR, CEILING MOUNT COMBINATION RATE-OF-RISE (15° PER MINUTE) AND/OR FIXED (135°) AS NOTED IN SPECIFICATION 284621.11
	ADDRESSABLE FIRE ALARM PHOTOELECTRIC SMOKE DETECTOR. CEILING MOUNT. REFER TO DETAIL #___, DRAWING E___.
	ADDRESSABLE FIRE ALARM PHOTOELECTRIC SMOKE DETECTOR. WALL MOUNT ON RECESSED DEVICE BOX. REFER TO DETAIL #___, DRAWING E___.
	FIRE ALARM DUCT MOUNTED SMOKE DETECTOR, HOUSING, AND SAMPLING TUBE ON RETURN SIDE. INTERLOCK WITH DAMPER/FAN MOTOR CONTROL TO SHUTDOWN UNIT ON DETECTION. PROVIDE AND WIRE AN ILLUMINATED REMOTE TEST SWITCH INTERLOCKED TO THE EQUIPMENT. REFER TO DETAIL #___, DRAWING E___. LOCATION SHALL BE READILY ACCESSIBLE TO FIREMAN FOR SMOKE MANAGEMENT CONTROL.
	ILLUMINATED REMOTE TEST SWITCH INTERLOCKED TO SHUTDOWN AIR HANDLING EQUIPMENT. AS "SIMULATED TEST" OF DUCT SMOKE DETECTOR ACTIVATION AND AHU SHUTDOWN BY IAM INTERLOCK. LOCATION SHALL BE READILY ACCESSIBLE FOR FIREMEN FOR SMOKE MANAGEMENT CONTROL.
	FIRE ALARM HORN WITH VISUAL STROBE. WP = WEATHERPROOF STYLE DEVICE.
	FIRE ALARM VISUAL STROBE ANNUNCIATOR.
	FIRE ALARM MANUAL PULL STATION.
	FIRE ALARM HOLD OPEN DEVICE.

	REMOTE FIRE ALARM ANNUNCIATOR PANEL.
	FIRE ALARM CONTROL PANEL.
	FIRE ALARM MONITOR POINT, BACKFLOW PREVENTOR/PRESSURE INDICATING SWITCH.
	FIRE ALARM MONITOR POINT, TAMPER SWITCH.
	FIRE ALARM MONITOR POINT, FLOW SWITCH.
	FIRE ALARM INTERMEDIATE ADDRESSABLE MODULE.
	GENERATOR ALARM ANNUNCIATOR PANEL.
	OVERHEAD DOOR SAFETY INTERLOCKS. REFER TO SPECIFICATION 083613 FOR MORE INFORMATION.
	LOCAL KEYED OPEN-STOP-CLOSE OVERHEAD DOOR CONTROL STATION. REFER TO SPECIFICATION 083613 FOR MORE INFORMATION.
	2'-0" GROUND BUS BAR. REFER TO DETAIL #___, DRAWING E___.
	COMBINATION TELEPHONE/DATA 2-PORT OUTLET SINGLE GANG. FOR EACH DEVICE 1-DATA/1-TELEPHONE JACK WITHIN THAT RECEPTACLE. INSTALL WITHIN A 4" x 4" EXTRA DEEP BOX. PROVIDE (2) CAT.6 CABLES U.O.N. INSTALL DEVICE WITH BOTTOM AT +16" AFF., U.O.N.
	CAT. 6 DATA OUTLET. SINGLE GANG. INSTALL DEVICE AT +18" AFF., U.O.N. PROVIDE (1) CAT.6 CABLE U.O.N.
	COMBINATION TELEPHONE/DATA 2-PORT OUTLET SINGLE GANG. FOR EACH DEVICE 1-DATA/1-TELEPHONE JACK WITHIN THAT RECEPTACLE. INSTALL WITHIN A 4" x 4" EXTRA DEEP BOX. PROVIDE (2) CAT.6 CABLES U.O.N. INSTALL DEVICE WITH BOTTOM AT +16" AFF., U.O.N. USB INDICATES ONE CAT 6 CABLE/JACK TO BE REPLACED WITH ONE USB CABLE/JACK.
	COMBINATION TELEVISION/DATA 2-PORT OUTLET SINGLE GANG. FOR EACH DEVICE 1-DATA/1-TELEVISION JACK WITHIN THAT RECEPTACLE. INSTALL WITHIN A 4" x 4" EXTRA DEEP BOX. PROVIDE (1) CAT.6 CABLE AND (1) COAX CABLE. INSTALL DEVICE AT +84" AFF., U.O.N
	(1) HDMI INTERFACE OUTLET. PROVIDE 2-GANG BOX WITH ADAPTER RING FOR SINGLE GANG PLATE AND 1-1/4" EMT UP ABOVE CEILING AND STUBBED OUT WITH BUSHING. INSTALL DEVICE AT HEIGHT INDICATED ONPLANS. FURNISH AND INSTALL PRE-TERMINATED HDMI CABLE BETWEEN INTERFACES AS INDICATED ON PLANS. INSTALL DEVICE WITH BOTTOM AT +16" AFF., U.O.N
	PLAIN OLD TELEPHONE SYSTEM OUTLET. PROVIDE (1) CAT 6 CABLE WITH (1) RJ11 JACK. INSTALL DEVICE WITH BOTTOM AT +16" AFF., U.O.N
	CONDUIT CONCEALED IN GROUND OR FLOOR.
	CONDUIT TURN UP AND TURN DOWN RESPECTIVELY.
	FIRE AND SMOKE DAMPER. REFER TO DETAIL #___, ON SHEET E___.
	POWER, DATA, COAX OUTLET FOR TV.
	LIGHT FIXTURE. "A" INDICATES FIXTURE TYPE. "a" INDICATES SWITCH LEG. "L1#" INDICATES CIRUIT NUMBER FIXTURE IS CONNECTED TO. REFER TO LIGHT FIXTURES SCHEDULE ON DRAWING E___.
	LIGHT FIXTURES WITH HALF SOLID SHADING INDICATES FIXTURE IS USED FOR EMERGENCY EGRESS LIGHTING. "A" INDICATES FIXTURE TYPE N.L. = NIGHT LIGHT, CONTINUOUS OPERATION, NON-CONTROLLED. EM = FIXTURE SUPPLIED WITH EMERGENCY POWER CONTROL MODULE, CONTROLLED. REFER TO LIGHT FIXTURE SCHEDULE ON DRAWING E___.
	CEILING MOUNTED PUBLIC ADDRESS SPEAKER, TIED TO TELEPHONE PAGING SYSTEM
	WALL MOUNTED PUBLIC ADDRESS SPEAKER, TIED TO TELEPHONE PAGING SYSTEM
	PHOTOCELL
	WIRELESS ACCESS POINT (WAP). PROVIDE TWO (2) CAT 6 CABLES.
	BRANCH CIRCUIT HOME-RUN SYMBOLOLOGY: SEMI CIRCLE INDICATES GROUND CONDUCTOR LONG LINE INDICATES NEUTRAL CONDUCTOR(S) SHORT LINE INDICATES PHASE CONDUCTOR(S)

SITE ELECTRICAL SYMBOLS:

---- BHV ----	DIRECT BURIED CONDUIT FOR HIGH VOLTAGE CABLE (CABLE BY ELECTRIC UTILITY)
---- BC ----	DIRECT BURIED CONDUIT FOR COMMUNICATIONS CABLES
---- BE ----	DIRECT BURIED CONDUIT FOR ELECTRICAL POWER CABLES
---- BFO ----	DIRECT BURIED CONDUIT FOR SECURITY FIBER OPTIC CABLES
---- G ----	DIRECT BURIED BARE COPPER GROUNDING ELECTRODE CABLE
	ELECTRICAL HANDHOLE "HH-CX" INDICATES ELECTRICAL HANDHOLE #X "HH-CX" INDICATES COMMUNICATION HANDHOLE #X
	3/4" DIAMETER X 10'-0" COPPER CLAD GROUNDING ELECTRODE GROUNDING ROD WITH EXOTHERMIC WELD CABLE CONNECTION

ONE-LINE DIAGRAM SYMBOLS:

	MAIN LUG ONLY PANELBOARD. "PANEL" INDICATES PANEL DESIGNATION. "120/208" INDICATES PANEL OPERATING VOLTAGE. "3Ø, 4W" INDICATES PHASE AND WIRE. "200A 3P" INDICATES 3 POLE MAIN LUGS AND BUS RATED FOR 200A.
	MAIN CIRCUIT BREAKER PANELBOARD. "PANEL" INDICATES PANEL DESIGNATION. "120/208" INDICATES PANEL OPERATING VOLTAGE. "3Ø, 4W" INDICATES PHASE AND WIRE. "200A 3P" INDICATES 3 POLE MAIN LUGS AND BUS RATED FOR 200A.
	FUSED SWITCH. TOP NUMBER INDICATES SWITCH RATING IN AMPERES. BOTTOM NUMBER INDICATES FUSE RATING IN AMPERES.
	THERMAL MAGNETIC CIRCUIT BREAKER. TOP NUMBER INDICATES TRIP RATING IN AMPERES. BOTTOM NUMBER INDICATES FRAME RATING IN AMPERES. "80% RATED" INDICATES BREAKER RATING. "LSIG" INDICATES BREAKER WITH ADJUSTABLE LONG TIME. SHORT TIME, INSTANTANEOUS, AND GROUND FAULT TRIP SETTINGS. "SS" INDICATES SOLID STATE. 3-POLE, U.O.N.
	BUS BAR.
	FEEDER CIRCUIT.
	MOTOR WITH HORSEPOWER INDICATED.
	TRANSFORMER. PRIMARY VOLTAGE, SECONDARY VOLTAGE, RATING IN KVA AS INDICATED. K FACTOR AS INDICATED.
	GROUND.
	NON-FUSED DISCONNECT SWITCH. NUMBER INDICATES RATING IN AMPERES.
	ENCLOSURE OUTLINE.
	CABLE/CONDUIT NUMBER.
	AUTOMATIC TRANSFER SWITCH
	SWITCHBOARD

ABBREVIATIONS:

A.F.	AMPERE FUSE	MFR.	MANUFACTURER
A.F.C.	ABOVE FINISHED COUNTER	MOCP	MAXIMUM OVERCURRENT PROTECTION
A.F.F.	ABOVE FINISHED FLOOR	MTS.	MANUAL TRANSFER SWITCH
A.F.G.	ABOVE FINISHED GRADE	MUTOA	MULTI-USER TELECOMMUNICATIONS OUTLET ASSEMBLY
B.E.	BURIED ELECTRIC		
B.F.G.	BELOW FINISH GRADE	NEC	NATIONAL ELECTRICAL CODE
BFO	BURIED FIBER OPTIC	NL	NON-SWITCHED NIGHT LIGHT
BT	BURIED TELEPHONE	NTRL.	NEUTRAL
C.	CONDUIT	NTS	NOT TO SCALE
CAT	CATEGORY	OC	OVERCURRENT PROTECTIVE DEVICE
DED.	DEDICATED	OL.	OVERLOADS
DFA	DROP FROM ABOVE	P	POLE
DIV.	DIVISION	POTS	PLAIN OLD TELEPHONE SYSTEM
D.S	DISCONNECT SWITCH	Ø	PHASE
E.T.R.	EXISTING TO REMAIN	RCPT.	RECEPTACLE
E	EXISTING	RECEPT.	RECEPTACLE
EC	ELECTRICAL CONTRACTOR	RM.	ROOM
(F)	FUTURE	SE	SERVICE ENTRANCE
FAAP	FIRE ALARM ANNUNCIATOR PANEL	SP.	SPARE
FACP	FIRE ALARM CONTROL PANEL	SPEC	SPECIFICATIONS
G.	GROUND	SS	SOLID STATE (ELECTRONIC) BREAKER
GFI	GROUND FAULT INTERRUPT	SSOL	SOLID STATE OVERLOADS
GRND	GROUND	ST	SAFETY TYPE
H.O.A.	HAND OFF AUTOMATIC	SW.	SWITCH
H.L.O.A.	HIGH LOW OFF AUTOMATIC	T.B.I.	TO BE INSTALLED
HNDLR	HANDLER	TBR	TO BE REMOVED
IDF	INTERMEDIATE DISTRIBUTION FRAME	TWSH.	TWISTED SHIELDED
LSIG	LONG TIME, SHORT TIME, INSTANTANEOUS, GROUND	TYP.	TYPICAL
LTG.	LIGHTING	U.O.N.	UNLESS OTHERWISE NOTED
MC	MECHANICAL CONTRACTOR	V.F.D.	VARIABLE FREQUENCY DRIVE
MCA	MINIMUM CIRCUIT AMPACITY	W	WATT
MCB	MAIN CIRCUIT BREAKER	WG	WIRE GUARD
MDF	MAIN DISTRIBUTION FRAME	WAP	WIRELESS ACCESS POINT
		WP	WEATHERPROOF

GENERAL NOTES:

- DRAWINGS ARE DIAGRAMMATIC. ALL DIMENSIONS SHOWN ARE APPROXIMATE. ALL LOCATIONS SHALL BE FIELD VERIFIED.
- ALL WORK SHALL BE IN CONFORMANCE WITH THE NATIONAL ELECTRICAL CODE LATEST EDITION ADOPTED BY MICHIGAN, THE MICHIGAN ELECTRICAL CODE AMENDMENTS, LOCAL/MUNICIPAL CODES, AND THE AUTHORITY HAVING JURISDICTION.
- ALL CONNECTIONS TO EQUIPMENT SUBJECT TO MOVEMENT OR VIBRATION SHALL BE LIQUID TIGHT FLEXIBLE METAL CONDUIT, NOT LESS THAN 12" IN LENGTH, NOR GREATER THAN 36" IN LENGTH.
- ALL PENETRATIONS THROUGH FIRE RATED WALLS SHALL BE SEALED WITH THE APPROPRIATE FIRE STOPPING MATERIAL TO MAINTAIN WALL FIRE RATING. SEE ARCHITECTURAL DRAWING #A-051 FOR FIRE RATED WALL LOCATIONS.
- SEE MECHANICAL AND PLUMBING SCHEDULES FOR MECHANICAL EQUIPMENT RATINGS AND SIZES.
- ALL POWER AND LIGHTING CIRCUITS SHALL BE MINIMUM (2) #12, AND (1) #12 G, IN 3/4" CONDUIT UNLESS OTHERWISE NOTED. ALL BRANCH CIRCUIT WITH 20A AND BELOW (BREAKER(S)) SHALL USE THE FOLLOWING MINIMUM CABLE SIZE TO ACCOMMODATE VOLTAGE DROP UNLESS OTHER WISE NOTED: LESS THAN 85'-0": #12 AWG; 85'-0" TO 140'-0": #10 AWG; 140'-0" TO 225'-0": #8 AWG.
- ALL CONTROL WIRING SHALL BE NOT LESS THAN (2) #14, (1) #14G, 3/4"C, UON.
- ALL CABLES INSTALLED IN AIR HANDLING PLENUMS SHALL BE PLENUM RATED CABLE.
- HOME RUNS SHALL NOT BE COMBINED IN A RACEWAY UNLESS SHOWN ON THE CONTRACT DRAWINGS. SINGLE PHASE BRANCH CIRCUIT HOME RUNS MAY BE COMBINED AT THE CONTRACTOR'S DISCRETION NOT GREATER THAN (3) PHASE CONDUCTORS, (3) NEUTRAL CONDUCTORS, AND REQUIRED GROUNDING CONDUCTOR(S). CONTRACTOR MUST INCREASE WIRE SIZE AND DERATE CONDUCTOR CAPACITY ACCORDING TO NEC.
- EACH SINGLE PHASE BRANCH CIRCUIT CONDUCTOR SHALL HAVE A DEDICATED NEUTRAL BACK TO THE PANELBOARD.
- SUPPORTING WIRE FOR THE SUSPENDED CEILING GRID SHALL NOT BE USED AS RACEWAY SUPPORT.
- DISCONNECT SWITCH RATINGS SHALL BE AS INDICATED ON THE DRAWINGS.
- MAJOR FEEDERS FROM THE SWITCHBOARD TO PANELBOARDS, TRANSFORMERS, MOTORS AND OTHER LARGE EQUIPMENT ARE NOT SHOWN ON THE FLOOR PLAN DRAWINGS. THESE FEEDERS ARE INCLUDED WITHIN THE SCOPE OF THE ELECTRICAL WORK AND ARE SHOWN ON THE ONE-LINE DIAGRAMS.
- ALL FIRE ALARM CABLING SHALL BE RED, PLENUM RATED, AND INSTALLED IN FACTORY PAINTED "RED" CONDUIT. ALL ASSOCIATED JUNCTION/PULL BOXES SHALL BE FACTORY PAINTED "RED".
- HVAC CONTROL WIRING FURNISHED AND INSTALLED BY OTHERS. PROVIDE POWER TO EACH TEMPERATURE CONTROL PANEL AS SHOWN.
- INDOOR CONTROL EQUIPMENT ENCLOSURES SHALL BE NEMA 1 RATED U.O.N. ALL EXTERIOR ENCLOSURES SHALL BE NEMA 3R UNLESS OTHERWISE NOTED. ALL ENCLOSURES LOCATED IN KITCHEN SHALL BE NEMA 4X STAINLESS STEEL UNLESS OTHERWISE NOTED.
- ALL CONDUITS CROSSING EXPANSION JOINTS SHALL BE INSTALLED WITH EXPANSION JOINTS BELOW THE CONDUIT. UNLESS THE CONDUIT IS BEING COMPACTED GRANULAR FILL. EXPANSION FITTINGS SHALL BE INSTALLED IN ACCORDANCE WITH THE NEC AND MANUFACTURER'S WRITTEN RECOMMENDATIONS. REFER TO STRUCTURAL DRAWINGS FOR EXPANSION JOINT LOCATIONS.
- THE CONTRACTOR SHALL COORDINATE RECEPTACLE HEIGHTS AND LOCATIONS WITH THE CASEWORK SHOP DRAWINGS TO DETERMINE EXACT LOCATIONS AND HEIGHTS FOR OUTLET INSTALLATION.
- CONTROL WIRING FOR HVAC EQUIPMENT FURNISHED AND INSTALLED BY OTHERS. PROVIDE POWER AS INDICATED ON PLANS.
- TO REDUCE NOISE BETWEEN WALLS, CONTRACTOR SHALL:
 - AVOID INSTALLING POWER RECEPTACLES OR DATA OUTLETS LOCATED BACK TO BACK.
 - WHERE OUTLETS ARE REQUIRED TO BE LOCATED BACK TO BACK CONTRACTOR SHALL PROVIDE SOUNDPROOFING MATERIAL BETWEEN JUNCTION BOXES.
- THE WORD "PROVIDE" IS TO BE DEFINED AS "FURNISH AND INSTALL."
- ALL ELECTRICAL DEVICES IN RECREATION ROOMS TO BE PROVIDED WITH WIREGUARD UNLESS INSTALLED IN CUSTOM BOX.
- COORDINATE VIDEO VISITATION POWER REQUIREMENTS WITH OWNER'S VIDEO VISITATION VENDOR BEFORE ROUGH-IN. FURNISH AND INSTALL POWER AS REQUIRED. PROVIDE DEVICES, BOXES, RACEWAYS, CABLING, SUPPORTS, DISCONNECTS, STARTERS, ETC AS REQUIRED.
- THE TRADE CONTRACTOR SHALL COORDINATE LOCATIONS OF ALL PENETRATIONS WITH STRUCTURAL DRAWING REQUIREMENTS. ADDITIONALLY, THE TRADE CONTRACTOR SHALL COORDINATE ALL PENETRATIONS REQUIRED THROUGH PRECAST CONCRETE UNITS WITH THE PRECAST CONCRETE MANUFACTURER TO PRODUCE A SHOP DRAWING SUBMITTAL NOTING ALL PENETRATIONS AND THEIR SIZES. TRADE CONTRACTOR AND PRECAST MANUFACTURER SHALL PROVIDE DOCUMENTATION WITH SHOP DRAWING SUBMITTAL INDICATING THAT ALL TRADES HAVE SIGNED OFF ON ALL AFOREMENTIONED COORDINATION.
- ALL DEVICES SURFACE MOUNTED ON BOTTOM OF PRECAST SHALL BE SUPPLIED FROM ABOVE. NO EXPOSED CONDUITS OR WIREMOLD SHALL BE USED ON BOTTOM OF PRECAST.
- ADJUST DEVICE BOX MOUNTING HEIGHT TO TOP OR BOTTOM OF BLOCK COURSING AS NEEDED SO BOXES DO NOT CROSS A MORTAR JOINT.
- SECURITY CAULKING/SEALANT SHALL BE INSTALLED IN CREVICES IN ALL DETENTION SPACES (I.E. AROUND DEVICE PLATES, LIGHTING FIXTURES, ETC.). REFER TO SPECIFICATION 079200 FOR DETAILED REQUIREMENTS.
- TORX HEAD SCREWS WITH A CENTER PIN SHALL BE INSTALLED IN ALL DETENTION SPACES (I.E. DEVICE FACEPLATES, LIGHTING FIXTURE ACCESS PLATES, ETC.). REFER TO SPECIFICATION 050553 FOR DETAILED REQUIREMENTS.
- CONDUITS SHALL NOT BE ROUTED IN OR THROUGH THE PRECAST HOLLOWCORE CEILING. COORDINATE WITH PRECAST VENDOR TO DETERMINE DROP-IN ANCHOR LOCATIONS FOR MOUNTING OF RACEWAYS OR OTHER ELECTRICAL ITEMS UNDERNEATH THE PRECAST HOLLOWCORE CEILING. REFER TO DRAWING S-500, DETAIL #7.
- REFER TO ARCHITECTURAL DRAWINGS FOR FIRE RATED WALLS AND CEILINGS. INSTALL FIRESTOP AT PENETRATIONS. INSTALL FIRE RATED PUTTY AROUND BOXES INSTALLED IN FIRE RATED WALLS AND OFFSET BACK TO BACK BOXES. REFER TO SPECIFICATION SECTION **078443** "JOINT FIRESTOPPING" FOR DETAILS FIRESTOP REQUIREMENTS.

<div>DRAWING NUMBER</div> <div>E0.1</div>	<div>DETROIT</div> <div>EGIS-BLN</div> <div>GHIB FORT WAYNE LIGHTING & SITE IMPROVEMENTS</div> <div>GENERAL INFORMATION</div>	<div>DLZ</div> <div>ARCHITECTURE • ENGINEERING • PLANNING</div> <div>SURVEYING • CONSTRUCTION SERVICES</div> <div>DLZ Florida, LLC</div>									
		DRAWN: Author		CHKD: Chkd		NO.		REVISION		DATE	
		DESIGNED: Designer									
		APPRVD: Approver									
		DATE: MONTH XX, XXXX									
		PROJECT NUMBER									
		1641-674700									
<div>ELECTRICAL</div>											

Autodesk Docs://1641-6470-00 GHIB Site Improvements/1641-6470-00 GHIB Site
4/23/2025 10:58 PM
1641-6470-00 GHIB Site Improvements/1641-6470-00 GHIB Site



ELECTRICAL SITE PLAN @ OPEN PARKING
SCALE: 1/32" = 1'-0"





GENERAL NOTES:

- REFER TO SHEETS G1.1 AND E0.1 FOR ADDITIONAL GENERAL NOTES AND INFORMATION.
- DASHED LINES INDICATE EXISTING ELECTRICAL EQUIPMENT TO BE REMOVED. REMOVE ASSOCIATED ELECTRICAL ITEMS (E.G. CABLE, CONDUIT, SUPPORTS, DISCONNECTS, ETC.) COMPLETE BACK TO POWER AND/OR SIGNAL SOURCE OR TO NEAREST REMAINING DEVICE(S) U.O.N.
- SHADED LINES INDICATE EXISTING ELECTRICAL ITEMS TO REMAIN.
- E.R. = EXISTING DEVICE TO REMAIN.
- T.B.R. = EXISTING DEVICE TO BE REMOVED.
- ALL EXISTING LIGHTING, POWER, SYSTEMS DEVICES / EQUIPMENT TO REMAIN UNLESS OTHERWISE NOTED.
- NOT ALL KEYNOTES ARE USED ON EVERY SHEET.
- REMOVE EXISTING SYSTEMS, MATERIALS, AND EQUIPMENT WHICH ARE MADE OBSOLETE OR WHICH INTERFERE WITH THE CONSTRUCTION OF THE PROJECT.
 - REINSTALL ANY SUCH SYSTEMS, MATERIALS, AND EQUIPMENT WHICH ARE REQUIRED TO COMPLETE THE PROJECT.
- WHERE EXISTING EQUIPMENT OR MATERIALS ARE REMOVED OR CHANGED, ALL BRANCH CONDUITS, WHICH NO LONGER ARE IN SERVICE, SHALL BE REMOVED AS DIRECTED BY THE ARCHITECT. IF, IN THE COURSE OF THE WORK, OUTLETS ARE COVERED UP OR OTHERWISE RENDERED INACCESSIBLE, ALL WIRING TO SAME SHALL BE REMOVED TO THE SOURCE. IF A CIRCUIT THAT MUST REMAIN IN SERVICE IS INTERRUPTED, IT SHALL BE RECONNECTED BY THE MOST INCONSPICUOUS MEANS SO AS TO REMAIN OPERATIONAL, WITH SAME CAPACITY AS BEFORE. ALL BUILDING SURFACES DAMAGED, AND OPENING LEFT BY REMOVAL OF BOXES, PIPING, OR THEIR EQUIPMENT SHALL BE REPAIRED BY THE CONTRACTOR. ALL HOLES LEFT IN JUNCTION BOXES, SWITCHES, PANELS, ETC. SHALL BE CLOSED.
- WHERE NEW OPENINGS ARE CUT AND CONCEALED CONDUITS, ETC. ARE ENCOUNTERED, THEY SHALL BE REMOVED OR RELOCATED AS REQUIRED. CONDUIT SHALL BE REMOVED TO THE POINT WHERE THE FINISH SURFACES CAN BE PATCHED ADEQUATELY SO THAT NO EVIDENCE OF THE FORMER INSTALLATION REMAINS.
- REFER TO ARCHITECTURAL DRAWINGS WHICH SHOW THE TOTAL DEMOLITION IN SPECIFIC AREAS. E.G. SHALL COORDINATE IN THIS DEMOLITION TO ENSURE THAT POWER IS OFF AND THAT ELECTRICAL EQUIPMENT THAT MUST REMAIN IS PROPERLY PROTECTED.
- ALL REUSABLE DEVICES, FIXTURES, AND EQUIPMENT SHALL BE SALVAGED. SHALL BECOME THE PROPERTY OF THE OWNER, AND SHALL BE STORED BY THE CONTRACTOR IN A ROOM TO BE DESIGNATED BY THE OWNER. ALL OTHER REMOVED ITEMS AND DEBRIS SHALL BE CLEARED FROM THE PREMISES DAILY.

KEYNOTES

- 022603 LIGHTING FIXTURE, POLE, AND POLE BASE TO BE REMOVED. REPLACE WITH HANDHOLE, REWORK CONDUIT AND RECONNECT CONDUCTORS TO MAINTAIN CONTINUITY OF CIRCUIT.
- 022604 REMOVE FIXTURE, POLE, AND POLE BASE IN PREPARATION FOR NEW DIRECT BURY LIGHT POLE IN SAME PLACE. MAINTAIN WIRING FOR NEW POLE. REWORK EXISTING CONDUIT AS REQUIRED FOR NEW POLE.



 <div>ARCHITECTURE • ENGINEERING • PLANNING SURVEYING • CONSTRUCTION SERVICES DLZ Florida, LLC</div>									
DRAWING NUMBER	ED3.1	DETROIT	EGIS-BLN GHIB FORT WAYNE LIGHTING & SITE IMPROVEMENTS	MI	DRAWN: Author	CHKD: Chkd	NO.	REVISION	DATE
					DESIGNED: Designer	APPRVD: Approver			
ELECTRICAL			SITE LIGHTING REMOVAL PLAN		1641-674700				



1

3

FIRST FLOOR POWER PLAN

SCALE: 1" = 100'-0"

GENERAL NOTES

- A. REFER TO SHEETS G1.1 AND E0.1 FOR ADDITIONAL GENERAL NOTES AND INFORMATION.
- B. FIELD VERIFY POWER SOURCE FOR EXTERIOR LIGHTING.

KEYNOTES


DRAWING NUMBER	DETROIT	MI	DRAWN: Author	CHKD: CHKd	NO.	REVISION	DATE
E1.0	GHIB FORT WAYNE LIGHTING & SITE IMPROVEMENTS	EGIS-BLN	DESIGNED: Designer				
			APPRVD: Approver				
			DATE: MONTH XX, XXXX				
			PROJECT NUMBER				
ELECTRICAL	ELECTRICAL SITE PLAN		1641-674700				



Autodesk Docs://1641-6470-00 GHIB Site Improvements/1641-6470-00 GHIB Site
4/25/2025 4:05 PM
1641-6470-00 ELEC.dwg



ELECTRICAL SITE PLAN @ MAIN ENTRANCE
SCALE: 1/32" = 1'-0"



GENERAL NOTES

- A. REFER TO SHEETS G1.1 AND E0.1 FOR ADDITIONAL GENERAL NOTES AND INFORMATION.
B. FIELD VERIFY POWER SOURCE FOR EXTERIOR LIGHTING.

KEYNOTES

- 022606 UTILIZE EXISTING CONDUIT AND FEEDERS TO SUPPLY NEW GUARDHOUSE PANEL.



NO.	REVISION	DATE

DRAWN: Author	CHKD: Chkd
DESIGNED: Designer	
APPRVD: Approver	
DATE: MONTH XX, XXXX	
PROJECT NUMBER	1641-674700

DETROIT	MI
EGIS-BLN	
GHIB FORT WAYNE LIGHTING & SITE IMPROVEMENTS	
ELECTRICAL SITE PLAN ENLARGED	

DRAWING NUMBER	E1.1
	ELECTRICAL

Autodesk Docs://1641-6470-00 GHIB Site Improvements/1641-6470-00 GHIB Site
4/23/2025 4:05 PM
1641-6470-00 GHIB Site Improvements/1641-6470-00 GHIB Site



1

ELECTRICAL SITE PLAN @ OPEN PARKING

SCALE: 1/32" = 1'-0"

GENERAL NOTES

- A. REFER TO SHEETS G1.1 AND E0.1 FOR ADDITIONAL GENERAL NOTES AND INFORMATION.
B. FIELD VERIFY POWER SOURCE FOR EXTERIOR LIGHTING.

KEYNOTES



NO.	REVISION	DATE


DRAWN: Author	CHKD: Chkd
DESIGNED: Designer	APPROVED: Approver
DATE: MONTH XX, XXXX	PROJECT NUMBER
	1641-674700

DETROIT	EGIS-BLN	MI
GHIB FORT WAYNE LIGHTING & SITE IMPROVEMENTS		
ELECTRICAL SITE PLAN ENLARGED @ OPEN PARKING		

DRAWING NUMBER	E1.2
ELECTRICAL	

1 **GUARD HOUSE ELECTRICAL PLAN**

SCALE: 1" = 1'-0"



NOTES:
1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS. GUARD SHACK FURNISHED WITH ELECTRICAL DEVICES BY VENDOR.

DRAWING NUMBER

E1.3

ELECTRICAL

DETROIT

MI

EGIS-BLN
GHIB FORT WAYNE LIGHTING & SITE IMPROVEMENTS

GUARD HOUSE ELECTRICAL PLAN

DRAWN: Author

DESIGNED: Designer

APPROVD: Approver

DATE: MONTH XX, XXXX


PROJECT NUMBER

1641-674700

NO.

REVISION

DATE



 **1 LIGHT POLE CONCRETE FOUNDATION DETAIL**
SCALE: 1/2" = 1'-0"

GENERAL NOTES

- A. REFER TO SHEETS G1.1 AND E0.1 FOR ADDITIONAL GENERAL NOTES AND INFORMATION.
- B. FIELD VERIFY POWER SOURCE FOR EXTERIOR LIGHTING.

DRAWING NUMBER		DETROIT		EGIS-BLN		MI		DRAWN: Author		CHKD: Chkd		NO.		REVISION		DATE	
E5.1		GHIB FORT WAYNE LIGHTING & SITE IMPROVEMENTS		DETAILS - 1		PROJECT NUMBER		APPROVED: Approver									
								DATE: MONTH XX, XXXX									
ELECTRICAL						1641-674700											

LIGHTING FIXTURE SCHEDULE

LIGHTING FIXTURE SCHEDULE						
TYPE	LAMP	WATTAGE	VOLTS	DESCRIPTION	MANUFACTURER 1	TYPE COMMENTS
A	LED	97 W	MVOLT	POLE MOUNTED ARCHITECTURAL AREA LIGHT, DIECAST ALUMINUM HOUSING, ACRYLIC LENS	EVOLVE #EPAM 01 12 A 40 1H A	MOUNT ON WALL WITH BOTTOM AT +12'-0" AFG UNLESS OTHERWISE NOTED.
B	LED	97 W	MVOLT	POLE MOUNTED ARCHITECTURAL AREA LIGHT, DIECAST ALUMINUM HOUSING, ACRYLIC LENS	EVOLVE #EPAM 01 12 B 40 1H A	MOUNT ON WALL WITH BOTTOM AT +12'-0" AFG UNLESS OTHERWISE NOTED.

NOTE: CONTRACTOR TO VERIFY VOLTAGE OF EXISTING LIGHT POLE CIRCUIT

Branch Panel: GUARD SHA...

Location:
Supply From:
Mounting: Surface
Enclosure: 1

Volts: 120/240 Single
Phases: 1
Wires: 3

A.I.C. Rating: 10kA
Mains Type: MLO
Mains Rating: 125 A
MCB Rating: 0 A

Notes:

[illegible]

Total Load:	0 VA	0 VA
Total Amps:	0 A	0 A

Legend:

Load Classification	Connected Load	Demand Factor	Estimated Demand	Panel Totals
				Total Conn. Load: 0 VA
				Total Est. Demand: 0 VA
				Total Conn. Current: 0 A
				Total Est. Demand Current: 0 A

Notes:


GENERAL NOTES

A. REFER TO SHEETS G1.1 AND E0.1 FOR ADDITIONAL GENERAL NOTES AND INFORMATION.




DRAWING NUMBER E6.1	DETROIT	EGIS-BLN GHIB FORT WAYNE LIGHTING & SITE IMPROVEMENTS	MI	DRAWN: Author	CHKD: Cntrl	NO.	REVISION	DATE
				DESIGNED: Designer				
				APPRVD: Approver				
				DATE: MONTH-XX, XXXX				
				PROJECT NUMBER				
ELECTRICAL	SCHEDULES							
	1641-674700							

FINIAL



GLOBE



Weight

- < 20 lbs (9.07 kgs)

Effective Projected Area

- 1.4 sq ft max (0.13 sq M max)

Suggested Mounting Height

- 8-16 ft. (2.5-5 M)

Mounting

- Post top mounting for 2.375 in. (60mm) MIN – 3.5 in. (89mm) MAX diameter by 3.5-inch MIN vertical tenon secured with three square head set screws


Available Finials if ordered separately

MATERIAL DESCRIPTION	COLOR*	MATERIAL
FNLBL-ACN	BLACK	126817
FNLBL-BLS	BLACK	126819
FNLBL-FDL	BLACK	126812
FNLBL-OAK	BLACK	170102
FNLBL-SIL	BLACK	126816
FNLBL-SPK	BLACK	126818

*Contact Factory for different finial colors

Accessories

SAP NUMBER	PART NUMBER	DESCRIPTION
93029237	PED-MV-LED-7	ANSI C136.41 Dimming PE, 120-277V
28299	PEC0TL	Standard 120-277V
73251	SCCL-PECTL	Shorting Cap





EPAM Americana

LED Post Top Lighting

The **Evolve®** LED Americana Post Top offers energy efficiency and quality of light in a classic, Acorn look and style.



Construction

Housing:	Diecast aluminum housing.
Lens:	Acrylic or Polycarbonate Globe
Paint:	Corrosion resistant polyester powder paint, minimum 2.0 mil thickness Standard = Black, Dark Bronze RAL & custom colors available
Weight:	< 20 lbs (9.07 kgs)

Optical System

Lumens:	1,900 – 12,600
Distribution:	Symmetric Asymmetric
Efficacy:	74-155 LPW
CCT:	3000K, 4000K
CRI:	≥70

Electrical

Input Voltage:	120-277V
Input Frequency:	50/60Hz
Power Factor:	≥ 90% at rated watts*
Total Harmonic Distortion:	≤ 20% at rated watts

*PF >0.88 for 1C and 1H globes at 02 Lumen Output above 240V

Surge Protection*

Standard	Optional
10kV/5kA	Secondary 10kV/5kA (R Option) Secondary 20kV/10kA (T Option)

*Per ANSI C136.2-2015

Warranty

5 Year (Standard)

10 Year (Optional)

Luminaire Ambient Temperature Factor (LATF)

Ambient Temp (°C)	Initial Flux Factor	Ambient Temp (°C)	Initial Flux Factor
10	1.02	30	0.99
20	1.01	40	0.98
25	1.00	50	0.97

Operating Temperature

Globe	Min Ambient Temp (°C)	Max Ambient Temp (°C)	Lumen Output
1C & 1H	-40° -40°	50° 40°	02 to 10 12
1D	-40° -40°	50° 45°	02 to 08 10
1M	-40° -40°	50° 45°	02 to 06 07

Ratings

Vibration:	1.5G per ANSI C136.41-2010
LM-79:	Testing in accordance with IES Standards
Environmental:	Complies with the material restrictions of RoHS

Controls

Dimming:	Standard - 0-10V Optional - DALI (Option U)
Sensors:	Photo Electric Sensors (PE) available

Applications

- Local Roadways
- Antique Streetscapes
- Parks and Pathways
- University and Business Campuses



Not all product variations listed on this page are DLC qualified. Visit www.designlights.org/search to confirm qualifications.

Ordering Information

EPAM 01

PROD. ID	GEN	VOLTAGE	LUMEN OUTPUT ⁴	DISTRIBUTION	CCT	CONTROLS	GLOBE	GLOBE MATERIAL	FINIAL READY	FINIAL	COLOR	OPTIONS
E = Evolve	01	0 = 120-277V ³	02	A = Symmetric	30 = 3000K	1 = None	1C = Traditional Standard	A = Acrylic	F = Finial Ready ²	A = Silhouette	BLCK = Black	F = Fusing
P = Post Top		1 = 120V	04	B = Asymmetric ¹⁰	40 = 4000K	A = ANSI C136.41 7-Pin Receptacle (in Base)	1H = Classic	P = Polycarbonate ⁶	X = No Finial Hole or Stud ¹	B = Acorn	DKBZ = Dark Bronze	R = Secondary 10kV/5kA SPD
AM = Americana		2 = 208V	06			D = ANSI C136.41 7-Pin Receptacle (in Base) w/ Shorting Cap	1D = Colony	F = Frosted Acrylic ^{6,7}		C = Fleur-De-Lis	XXXX = RAL Color	T = Secondary Elevated Surge (20kV/10kA)
		3 = 240V	08			E = ANSI C136.41 7-Pin Receptacle (in Base) w/ non-Dimming PE	1M = Colony w/ Crown & Ribs			E = Blossom		U = DALI Programmable
		4 = 277V	10							F = Spike		V1 = Field Adjustable Module ⁵
			12							G = Oak		XXX = Special Options
										X = None		

¹ If globe finial is not desired, choose FINIAL READY = X and FINIAL = X. If FINIAL READY = X, a finial cannot be added later

² A Finial is not required to complete order and can be added later

³ Not Available with Fusing

⁴ Globe Choice affects total lumen output. See Spec Table for additional information.

⁵ Not available with DALI "U" option


⁶ Only available with 1C Globe

⁷ Only available without Finial (Finial Ready = X)

⁸ Lumen offering 07 is only available with the 1M Globe

⁹ Review the Spec Tables for combination of Lumen Output, Distribution, Globe and Globe Material

¹⁰ Not available with 1C Globe



Not all product variations listed on this page are DLC qualified.
Visit www.designlights.org/search to confirm qualifications.

LUMEN OUTPUT	DIST. CODE	GLOBE	GLOBE MATERIAL	TYPICAL INITIAL LUMENS		TYPICAL SYSTEM WATTAGE 120-277V	BUG RATINGS		TM-21-11 LXX (≥10k) @ HOURS		
				4000K	3000K		4000K	3000K	25,000 HR	50,000 HR	60,000 HR
02	A Symmetric	1C Traditional Standard	A Acrylic	2300	2200	16	B1-U4-G2	B1-U4-G2	L96	L95	L94
04				4500	4400	29	B1-U5-G3	B1-U5-G3	L96	L95	L94
06				6600	6400	44	B2-U5-G3	B2-U5-G3	L95	L93	L92
08				8500	8200	59	B2-U5-G4	B2-U5-G3	L94	L91	L90
10				10600	10300	77	B3-U5-G4	B3-U5-G4	L92	L88	L86
12				12600	12200	97	B3-U5-G5	B3-U5-G4	L87	L78	L75
02	A Symmetric	1C Traditional Standard	P Polycarbonate	2200	2100	16	B1-U4-G2	B1-U4-G2	L96	L95	L94
04				4300	4200	29	B1-U5-G3	B1-U5-G3	L96	L95	L94
06				6300	6100	44	B2-U5-G3	B2-U5-G3	L95	L93	L92
08				8200	7900	59	B2-U5-G4	B2-U5-G4	L94	L91	L90
10				10200	9900	77	B3-U5-G4	B3-U5-G4	L92	L88	L86
12				12100	11700	97	B3-U5-G5	B3-U5-G4	L87	L78	L75
02	A Symmetric	1H Classic	A Acrylic	2200	2200	16	B1-U4-G1	B1-U4-G1	L96	L95	L94
04				4500	4300	29	B2-U5-G2	B2-U5-G2	L96	L95	L94
06				6500	6300	44	B2-U5-G2	B2-U5-G2	L95	L93	L92
08				8400	8200	59	B3-U5-G2	B3-U5-G2	L94	L91	L90
10				10500	10200	77	B3-U5-G3	B3-U5-G3	L92	L88	L86
12				12400	12100	97	B3-U5-G3	B3-U5-G3	L87	L78	L75
02	B Asymmetric	1H Classic	A Acrylic	2200	2100	16	B1-U4-G1	B1-U4-G1	L96	L95	L94
04				4400	4300	29	B1-U5-G2	B1-U5-G2	L96	L95	L94
06				6400	6200	44	B1-U5-G3	B1-U5-G3	L95	L93	L92
08				8300	8000	59	B2-U5-G3	B2-U5-G3	L94	L91	L90
10				10300	10000	77	B2-U5-G3	B2-U5-G3	L92	L88	L86
12				12300	11900	97	B2-U5-G3	B2-U5-G3	L87	L78	L75

For additional information on EPAM IES files, please refer to LED.com



Not all product variations listed on this page are DLC qualified.
Visit www.designlights.org/search to confirm qualifications.

LUMEN OUTPUT	DIST. CODE	GLOBE	GLOBE MATERIAL	TYPICAL INITIAL LUMENS		TYPICAL SYSTEM WATTAGE	BUG RATINGS		TM-21-11 LXX (≥10k) @ HOURS		
				4000K	3000K	120-277V	4000K	3000K	25,000 HR	50,000 HR	60,000 HR
02	A Symmetric	1D Colony*	A Acrylic	2800	2700	23	B2-U3-G1	B2-U3-G1	L96	L94	L93
04				4600	4500	37	B2-U3-G2	B2-U3-G2	L96	L94	L93
06				6100	5900	50	B3-U4-G2	B3-U4-G2	L94	L91	L90
08				7800	7600	66	B3-U4-G3	B3-U4-G3	L92	L88	L87
10				9500	9200	86	B3-U5-G3	B3-U4-G3	L87	L79	L76
02	B Asymmetric	1D Colony*	A Acrylic	2800	2700	23	B1-U3-G2	B1-U3-G2	L96	L94	L93
04				4600	4500	37	B2-U3-G3	B2-U3-G3	L96	L94	L93
06				6100	5900	50	B2-U4-G3	B2-U4-G3	L94	L91	L90
08				7800	7600	66	B2-U4-G3	B2-U4-G3	L92	L88	L87
10				9500	9200	86	B3-U4-G3	B3-U4-G3	L87	L79	L76
02	A Symmetric	1M Colony w/ Crown & Ribs	A Acrylic	1900	1900	23	B1-U3-G1	B1-U3-G1	L96	L94	L93
04				4200	4100	50	B2-U3-G1	B1-U3-G2	L94	L91	L90
06				6100	5900	77	B3-U3-G2	B2-U3-G2	L90	L84	L81
07				6600	6400	86	B3-U3-G2	B3-U3-G2	L87	L79	L76
02	B Asymmetric	1M Colony w/ Crown & Ribs	A Acrylic	1900	1900	23	B1-U3-G1	B1-U3-G1	L96	L94	L93
04				4200	4100	50	B1-U3-G2	B1-U3-G2	L94	L91	L90
06				6100	5900	77	B2-U3-G3	B2-U3-G2	L90	L84	L81
07				6600	6400	86	B2-U3-G3	B2-U3-G3	L87	L79	L76


For additional information on EPAM IES files, please refer to LED.com




Not all product variations listed on this page are DLC qualified.
Visit www.designlights.org/search to confirm qualifications.

EPAM
Symmetric

12,600 Lumens
4000K
EPAM01_12A40-1CA__IES




- Mounting Height at 16'
- Initial Footcandle at Grade




- Vertical plane at max Cd horiz. angle 5°
- Horizontal cone at max Cd vert. angle 87°

EPAM
Symmetric

12,100 Lumens
4000K
EPAM01_12A40-1CP__IES




- Mounting Height at 16'
- Initial Footcandle at Grade




- Vertical plane at max Cd horiz. angle 180°
- Horizontal cone at max Cd vert. angle 84°

EPAM
Symmetric

12,400 Lumens
4000K
EPAM01_12A40-1HA__IES




- Mounting Height at 16'
- Initial Footcandle at Grade




- Vertical plane at max Cd horiz. angle 40°
- Horizontal cone at max Cd vert. angle 64°

EPAM
Asymmetric

12,300 Lumens
4000K
EPAM01_12B40-1HB__IES




- Mounting Height at 16'
- Initial Footcandle at Grade




- Vertical plane at max Cd horiz. angle 70°
- Horizontal cone at max Cd vert. angle 61°

EPAM
Symmetric

9,500 Lumens
4000K
EPAM01_10A40-1DA__IES




- Mounting Height at 16'
- Initial Footcandle at Grade




- Vertical plane at max Cd horiz. angle 61°
- Horizontal cone at max Cd vert. angle 35°

EPAM
Asymmetric

9,500 Lumens
4000K
EPAM01_10B40-1DB__IES




- Mounting Height at 16'
- Initial Footcandle at Grade




- Vertical plane at max Cd horiz. angle 70°
- Horizontal cone at max Cd vert. angle 61°

EPAM
Symmetric

6,600 Lumens
4000K
EPAM01_07A40-1MA__IES




- Mounting Height at 16'
- Initial Footcandle at Grade




- Vertical plane at max Cd horiz. angle 61°
- Horizontal cone at max Cd vert. angle 20°

EPAM
Asymmetric

6,600 Lumens
4000K
EPAM01_07B40-1MB__IES




- Mounting Height at 16'
- Initial Footcandle at Grade



- Vertical plane at max Cd horiz. angle 70°
- Horizontal cone at max Cd vert. angle 57°

THE TALISMAN

With roots firmly established in the 20's and 30's the Talisman is an elegant version of several classic originals. In essence it is an 8 fluted version of the octagonal Belmont with the same graceful lines and proportions; the perfect choice to satisfy the tastes of many. It is available in heights from 5' to 32.5' as well as a lighted and nonlighted bollard.



Specification Details*

Description		Catalog Number	"A" Pole Height Above Grade	"D" Tip Dimension	"E" Flare	"B" Direct Burial Length & "F" Dia.	Pole Weight Direct Burial	Pole Weight Base Plate
Talisman Flared Top	11'	KT105	11'	9"	18"	4' 6" x 9 1/2"	1200 lbs	1000 lbs
Talisman Non Flared Top	12'	KT12	12' 0"	5 1/2"	18"	4' 6" x 9 1/2"	1300 lbs	1100 lbs
Talisman Flared Top	14'	KT14	13' 11"	9"	18"	4' 6" x 9 1/2"	1370 lbs	1170 lbs
Talisman Non Flared Top	20'	KTH20	20' 0"	5 3/4"	18"	5' 0" x 9 1/2"	1600 lbs	1400 lbs
Talisman Non Flared Top	25'	KTH25	25' 0"	5 3/8"	18"	5' 0" x 9 1/2"	1800 lbs	1600 lbs
Talisman Non Flared Top	20'	KTT20	20' 0"	7 3/8"	21"	5' 0" x 12"	2270 lbs	2000 lbs
Talisman Non Flared Top	25'	KTT25	25' 0"	6 1/2"	21"	5' 0" x 12"	2470 lbs	2200 lbs
Talisman Non Flared Top	30'	KTT30	30' 0"	5 7/8"	21"	5' 0" x 12"	2630 lbs	2360 lbs
Talisman Non Flared Top	33'	KTT32.5	32' 6"	5 1/2"	21"	6' 0" x 12"	2720 lbs	2450 lbs

* Bollard specification details can be found on our website

How to Catalog for Talisman Concrete Pole

Pole Style

KT
KTH
KTT

KT14 **14'**

Height
5' - 32' 6"

Finish

E – Etched Finish

E **E53**

Color**
10 – Midnight Lace
11 – Eclipse Black
30 – Salt & Pepper
40 – Pearl Gray
90 – Saluki Bronze
E53 Detroit Green

Footing Details

DB – Direct Buried
FBP – Flush Baseplate
SBP – Stub Baseplate

DB **140 30/30**

Tenon (Post Top Mount)
Specify Tenon Size
For example 140 30/30
= 2 7/8" OD & 3" long

Coating

NA – Non Acrylic
A – Acrylic
AG – Anti Graffiti Coating***

GFI **AG**

Options*
DR – Duplex Receptacle
GFI – Ground Fault Duplex Receptacle
SR – 1 Outlet
LRN – Ladder Rest
BPC – Base Plate Cover
AB – Anchor Bolts
BA – Banner Arms
FH – Flag Holders


* Consult website for full listings. ** See decor colors on page 2 for full selection of colors.
***Anti Graffiti Coating is extra, consult factory for more details.

Footing Details


Direct Buried

(Simple and Cost Effective)


1. Auger the setting hole.
2. Set pole in hole and plumb straight.
3. Backfill* with required backfill tamping every 4" to 6".





Baseplate Option 1: FBP




Baseplate Option 2: SBP



*Generally the excavated material can be used for backfill, in some situations better backfill may be required.



Typical Pole Cross Section



Lighted Bollard

Nonlighted Bollard