

HISTORIC DISTRICT COMMISSION APPLICATION FOR WORK APPROVAL

City of Detroit - Planning & Development Department 2 Woodward Avenue, Suite 808 Detroit, Michigan 48226

+1 (949) 903-5608

APPLI	CATI	ON	ID

HDC2025-00639

Detroit, Michigan 40220		11002025-00	1039		
PROPERTY INFORMATION					
ADDRESS(ES): 949 Chicago Blvd					
HISTORIC DISTRICT: Boston-Edison					
Instante District: Boston-Edison					
SCOPE OF WORK: (Check ALL that apply)					
Windows/ Walls/ Painting Doors	Roof/Gutters/ Chimney	Porch/Deck/Balcony	Other		
Demolition Signage X New Building	Addition	Site Improvements (landscape, trees, fence patios, etc.)	es,		
BRIEF PROJECT DESCRIPTION: This project involves the demolition and reconstruction of the existing two-story enclosed rear sunroom located on the east façade of the residence. The structure has sustained significant water and weather-related deterioration, particularly in the lower wall framing, sheathing, and exterior finishes below the upper roof eave. Reconstruction will be completed using standard residential framing and construction methods per current Michigan Residential Code.					
APPLICANT IDENTIFICATION					
APPLICANT IDENTIFICATION TYPE OF APPLICANT: Property Owner/Homeowner					
APPLICANT IDENTIFICATION TYPE OF APPLICANT: Property Owner/Homeowner NAME: Andre Williams	COMPANY NAME: N/A				
TYPE OF APPLICANT: Property Owner/Homeowner	COMPANY NAME: N/A CITY: Detroit	STATE: MI	ZIP: 48202		
TYPE OF APPLICANT: Property Owner/Homeowner NAME: Andre Williams			ZIP: 48202		
TYPE OF APPLICANT: Property Owner/Homeowner NAME: Andre Williams ADDRESS: 949 Chicago Blvd	CITY: Detroit EMAIL: andre@furiousfirm.c		ZIP: 48202		
TYPE OF APPLICANT: Property Owner/Homeowner NAME: Andre Williams ADDRESS: 949 Chicago Blvd PHONE: +1 (949) 903-5608	CITY: Detroit EMAIL: andre@furiousfirm.c	com			
TYPE OF APPLICANT: Property Owner/Homeowner NAME: Andre Williams ADDRESS: 949 Chicago Blvd PHONE: +1 (949) 903-5608 I AGREE TO AND AFFIRM THE FOLLOW I understand that the failure to upload all required of	CITY: Detroit EMAIL: andre@furiousfirm.co ING: documentation may result in the Historic District Commiss ordinances including obtaining	extended review	times for my		
TYPE OF APPLICANT: Property Owner/Homeowner NAME: Andre Williams ADDRESS: 949 Chicago Blvd PHONE: +1 (949) 903-5608 I AGREE TO AND AFFIRM THE FOLLOW I understand that the failure to upload all required of project and/or a denied application. I understand that the review of this application by the responsibility to comply with any other applicable of the complex comp	CITY: Detroit EMAIL: andre@furiousfirm.co ING: documentation may result in the Historic District Commiss ordinances including obtaining eginning the work.	extended review ion does not waiv g appropriate pe	times for my ve my rmits (building,		
TYPE OF APPLICANT: Property Owner/Homeowner NAME: Andre Williams ADDRESS: 949 Chicago Blvd PHONE: +1 (949) 903-5608 I AGREE TO AND AFFIRM THE FOLLOW I understand that the failure to upload all required of project and/or a denied application. I understand that the review of this application by the responsibility to comply with any other applicable of sign, etc.) or other department approvals prior to be the representation of the project and/or occupants.	CITY: Detroit EMAIL: andre@furiousfirm.co ING: documentation may result in the Historic District Commiss ordinances including obtaining eginning the work. It of the subject property and the	extended review ion does not waiv g appropriate pe	times for my ve my rmits (building,		
TYPE OF APPLICANT: Property Owner/Homeowner NAME: Andre Williams ADDRESS: 949 Chicago Blvd PHONE: +1 (949) 903-5608 I AGREE TO AND AFFIRM THE FOLLOW I understand that the failure to upload all required of project and/or a denied application. I understand that the review of this application by the responsibility to comply with any other applicable of sign, etc.) or other department approvals prior to be true and correct. Andre Williams	CITY: Detroit EMAIL: andre@furiousfirm.co ING: documentation may result in the Historic District Commiss ordinances including obtaining eginning the work. Int of the subject property and the	extended review ion does not waiv g appropriate pe	times for my ve my rmits (building,		

andre@furiousfirm.com

NOTE: Based on the scope of work, additional documentation may be required. See www/detroitmi.gov/hdc

for scope-specific requirements.

PROJECT DETAILS - TELL US ABOUT YOUR PROJECT

Instructions: Add project details using the text box in each section. If your details exceed the space provided, attach the details via the attachment icon for that section.

ePLANS PERMIT NUMBER:

(only applicable if you've already applied for permits through ePLANS)

RES2025-03856

GENERAL

1. DESCRIPTION OF EXISTING CONDITION

Please tell us about the current appearance and conditions of the areas you want to change. You may use a few sentences or attach a separate prepared document on the right. (For example, "existing roof on my garage is covered in gray asphalt shingles in poor condition.")

The rear sun-room structure has sustained significant water and weather-related deterioration, particularly in the lower wall framing, sheathing, and exterior finishes below the upper roof eave. This area of the home is in poor condition and could become a hazard if not addressed.

2. PHOTOGRAPHS

Help us understand your project. Please attach photographs of all areas where work is proposed.



3. DESCRIPTION OF PROJECT

In this box, tell us about what you want to do at the areas described above in box #1. (For example, Install new asphalt shingle roofing at garage.)

See Scope of Work pdf attached

Demolition & Rebuild



4. DETAILED SCOPE OF WORK

In this box, please describe all steps necessary to complete the work described in box #3. (For example, "remove existing shingles, replace wood deck as necessary, replace wood eaves, install roof vents, replace rotted fascia boards, paint, clean worksite.")

See attached

Demo 1st & 2nd floor

New structural work

Exterior & Finishes



5. BROCHURES/CUT SHEETS

Please provide information on the products or materials you are proposing to install. For example, a brochure on the brand and color of the shingles proposed.



ADDITIONAL DETAILS	











Scope of Work - Demo and Rebuild of Front Sunroom (1st & 2nd Floor)

949 Chicago Blvd Detroit, MI 48202

Project Description:

This project involves the demolition and reconstruction of the existing two-story enclosed front sunroom located on the east façade of the residence. The structure has sustained significant water and weather-related deterioration, particularly in the lower wall framing, sheathing, and exterior finishes below the upper roof eave. Reconstruction will be completed using standard residential framing and construction methods per current Michigan Residential Code.

Demolition

- Carefully demolish the existing 1st and 2nd floor sunroom down to sound structural framing.
- Remove and dispose of all damaged siding, plaster/stucco, trim, windows, and any compromised structural members.
- Disconnect and cap any electrical or mechanical components serving the existing sunroom.

Structural Work

- Install new 8-inch diameter concrete footings, minimum 42 inches deep, below frost line to support new posts and floor framing.
- Frame new 1st and 2nd floor walls using standard 2x4 wood stud construction.
 (12x9)
- Replace all deteriorated rim joists, sill plates, and wall studs as required.
- Install new subfloor and framing joists where previous damage from water infiltration occurred.
- Add new headers and framing to match original window and door openings.

Exterior & Finishes

- Sheath walls with ½-inch plywood or OSB, covered with weather-resistant barrier.
- Apply new **fiber cement siding and stucco finish** to match existing façade.
- Install new Lincoln aluminum-clad wood windows.

- Replace damaged exterior trim, fascia, soffit, and corner boards.
- Repair and repaint all adjacent wall transitions to ensure weather tightness.

Roof & Water Damage Repairs

- Inspect and repair roof area above the sunroom for **rot**, **flashing failure**, **and sheathing deterioration**.
- Replace any water-damaged roof decking and install new ice & water shield, synthetic underlayment, and shingles to match existing roof.
- Install proper step flashing and counter-flashing at the roof-to-wall intersections to prevent future water intrusion.

Scope of Work - Demo and Rebuild of Front Sunroom (1st & 2nd Floor)

949 Chicago Blvd Detroit, MI 48202

Project Description:

This project involves the demolition and reconstruction of the existing two-story enclosed front sunroom located on the east façade of the residence. The structure has sustained significant water and weather-related deterioration, particularly in the lower wall framing, sheathing, and exterior finishes below the upper roof eave. Reconstruction will be completed using standard residential framing and construction methods per current Michigan Residential Code.

Demolition

- Carefully demolish the existing 1st and 2nd floor sunroom down to sound structural framing.
- Remove and dispose of all damaged siding, plaster/stucco, trim, windows, and any compromised structural members.
- Disconnect and cap any electrical or mechanical components serving the existing sunroom.

Structural Work

- Install new 8-inch diameter concrete footings, minimum 42 inches deep, below frost line to support new posts and floor framing.
- Frame new 1st and 2nd floor walls using standard 2x4 wood stud construction.
 (12x9)
- Replace all deteriorated rim joists, sill plates, and wall studs as required.
- Install new subfloor and framing joists where previous damage from water infiltration occurred.
- Add new headers and framing to match original window and door openings.

Exterior & Finishes

- Sheath walls with ½-inch plywood or OSB, covered with weather-resistant barrier.
- Apply new **fiber cement siding and stucco finish** to match existing façade.
- Install new Lincoln aluminum-clad wood windows.

- Replace damaged exterior trim, fascia, soffit, and corner boards.
- Repair and repaint all adjacent wall transitions to ensure weather tightness.

Roof & Water Damage Repairs

- Inspect and repair roof area above the sunroom for **rot**, **flashing failure**, **and sheathing deterioration**.
- Replace any water-damaged roof decking and install new ice & water shield, synthetic underlayment, and shingles to match existing roof.
- Install proper step flashing and counter-flashing at the roof-to-wall intersections to prevent future water intrusion.

Scope of Work - Demo and Rebuild of Front Sunroom (1st & 2nd Floor)

949 Chicago Blvd Detroit, MI 48202

Project Description:

This project involves the demolition and reconstruction of the existing two-story enclosed front sunroom located on the east façade of the residence. The structure has sustained significant water and weather-related deterioration, particularly in the lower wall framing, sheathing, and exterior finishes below the upper roof eave. Reconstruction will be completed using standard residential framing and construction methods per current Michigan Residential Code.

Demolition

- Carefully demolish the existing 1st and 2nd floor sunroom down to sound structural framing.
- Remove and dispose of all damaged siding, plaster/stucco, trim, windows, and any compromised structural members.
- Disconnect and cap any electrical or mechanical components serving the existing sunroom.

Structural Work

- Install new 8-inch diameter concrete footings, minimum 42 inches deep, below frost line to support new posts and floor framing.
- Frame new 1st and 2nd floor walls using standard 2x4 wood stud construction.
 (12x9)
- Replace all deteriorated rim joists, sill plates, and wall studs as required.
- Install new subfloor and framing joists where previous damage from water infiltration occurred.
- Add new headers and framing to match original window and door openings.

Exterior & Finishes

- Sheath walls with ½-inch plywood or OSB, covered with weather-resistant barrier.
- Apply new **fiber cement siding and stucco finish** to match existing façade.
- Install new Lincoln aluminum-clad wood windows.

- Replace damaged exterior trim, fascia, soffit, and corner boards.
- Repair and repaint all adjacent wall transitions to ensure weather tightness.

Roof & Water Damage Repairs

- Inspect and repair roof area above the sunroom for **rot**, **flashing failure**, **and sheathing deterioration**.
- Replace any water-damaged roof decking and install new ice & water shield, synthetic underlayment, and shingles to match existing roof.
- Install proper step flashing and counter-flashing at the roof-to-wall intersections to prevent future water intrusion.

Scope of Work - Demo and Rebuild of Front Sunroom (1st & 2nd Floor)

949 Chicago Blvd Detroit, MI 48202

Project Description:

This project involves the demolition and reconstruction of the existing two-story enclosed rear sunroom located on the east façade of the residence. The structure has sustained significant water and weather-related deterioration, particularly in the lower wall framing, sheathing, and exterior finishes below the upper roof eave. Reconstruction will be completed using standard residential framing and construction methods per current Michigan Residential Code.

Demolition

- Carefully demolish the existing 1st and 2nd floor sunroom down to sound structural framing.
- Remove and dispose of all damaged siding, plaster/stucco, trim, windows, and any compromised structural members.
- Disconnect and cap any electrical or mechanical components serving the existing sunroom.

Structural Work

- Install new 8-inch diameter concrete footings, minimum 42 inches deep, below frost line to support new posts and floor framing.
- Frame new 1st and 2nd floor walls using standard 2x4 wood stud construction.
 (12x9)
- Replace all deteriorated rim joists, sill plates, and wall studs as required.
- Install new subfloor and framing joists where previous damage from water infiltration occurred.
- Add new headers and framing to match original window and door openings.

Exterior & Finishes

- Sheath walls with ½-inch plywood or OSB, covered with weather-resistant barrier.
- Apply new **fiber cement siding and stucco finish** to match existing façade.
- Install new Lincoln aluminum-clad wood windows.

- Replace damaged exterior trim, fascia, soffit, and corner boards.
- Repair and repaint all adjacent wall transitions to ensure weather tightness.


Roof & Water Damage Repairs

- Inspect and repair roof area above the sunroom for **rot**, **flashing failure**, **and sheathing deterioration**.
- Replace any water-damaged roof decking and install new ice & water shield, synthetic underlayment, and shingles to match existing roof.
- Install proper step flashing and counter-flashing at the roof-to-wall intersections to prevent future water intrusion.





Product Catalog WINDOWS AND PATIO DOORS



With nearly 75 years of manufacturing experience and craftsmanship built into every window and patio door we produce, Lincoln continues to provide products with strong visual appeal and outstanding performance. A long history of satisfied homeowners is proof of our exceptional customer service before and after the sale.

We are continually expanding and refining our list of products, options and accessories to meet ever changing market needs. Our windows and patio doors are independently tested and certified to meet energy efficiency requirements and structural performance expectations. Also, in order to maintain the high level of quality you expect, we test products in-house against rigid industry manufacturing standards.

Whether your project is residential, light commercial or replacement, we are confident Lincoln has the products to meet your needs.



General Information Markets		
Exteriors Aluminum Clad		
Vinyl Clad 7-8 Hybrid 9-10 Primed Wood 11-12 Natural Wood 13-14		
Options		
Exteriors 15-18 Interiors 19-20 Lites & Grilles 21-22 Glass 23-25 Screens .26		
Windows Casement & Awning 27-32 Double Hung 33-38 Glider 39-40 Specialty 41-44		
Patio Doors		
Swing 45-54 Folding 55-56 Slide 57-58 Multi-Slide 59-60 Lift & Slide 61-62		
Series		
Revitalize - Replacement 63-64		





Residential

Every new residential project is the culmination of a persons' dreams. Product selection, from flooring to shingles, are all key elements to fulfillment of that dream. Lincoln windows and patio doors are made to compliment any architectural style in size, shape and color to help your dream become a reality.



Remodeling

Your home is where your heart is. Do a makeover on something you love! There has never been a better time to improve comfort levels, lower energy costs and increase market value. Our Revitalize Series includes remodeling products designed specifically for your next replacement window project.



Light Commercial

A school, library, office complex, country club, fire house, armory, hotel, assisted living facility, or condominium – one thing these examples all have in common is their Lincoln windows. Some are installed in new construction and some as renovations. Lincoln windows, beautiful as residential products, also meet the demands of light commercial applications.

ENVIRONMENTAL COMMITMENT

The Environment

Our management team feels strongly about protecting and preserving the environment and we have implemented programs to reduce landfill waste and lower energy consumption.

We recycle: aluminum, anti-freeze, ballasts, batteries, cardboard, cellular PVC, copper wire, electronics, fluorescent light bulbs, freon, glass, oil, oil filters, paper, plastic bottles, sawdust, scrap metal, shrink wrap, soda cans, steel, tin, tires, vinyl and wood.



Energy Efficiency

Our products are tested and certified for water penetration, air infiltration, structural integrity and thermal performance. We also offer numerous product enhancements to increase energy savings such as thermal breaks, weatherstripping and high performance glass. In addition, we engage in lean and sustainable manufacturing processes and strive to use suppliers that do the same.



Testing and Certification

Our products carry certification by the National Fenestration Rating Council (NFRC). In addition, Lincoln is an ENERGY STAR Partner. One portion of a product's certification is derived from computerized simulation, which computes the thermal value of the product. Another is physical testing to establish air and water infiltration and structural performance. We strive for the best in our windows and doors.







Lincoln, offering color flexibility and structural strength while providing a homeowner with a low maintenance thick frame and sash cladding protects and add structural integrity for Clad Collection is wide-ranging and

performance are all brought to you by the Aluminum Clad Collection and

- Available Product:
- Maintenance:
- Structural Performance: Superior strength and rigidity for
- Thermal Performance: High. Good for meeting Energy



Frame and Sash Finishes

We offer eight standard colors, thirty-eight feature colors, seven spray-on anodized colors and have the ability to match from a customer's sample.

All of our standard, feature and custom color options are painted to AAMA 2605 performance requirements. AAMA 2605 high performance paint is the preferred choice of designers, architects and builders. Exceptional color retention and minimal chalking are leading characteristics of this premium paint finish.







Custom Colors - AAMA 2605



Due to printing limitations, the colors shown are for representation only.

EXTERIORS

Trim

Add that finishing touch to the exterior of your windows and patio doors by adding one of the many brickmould and casings offered by Lincoln. Along with enriching the aesthetics of your home, these factory-applied trims reduce the installation labor

and hassle.

For aluminum clad units, Lincoln offers extruded aluminum brickmould in 2" and 4" widths, Bullnose Casing and 4" flat casing, along with 3 different sill nosing options. All come factory applied and are available in all of our aluminum clad colors.

Also available - a factory applied rigid aluminum nailing flange and color matched drip cap. This .050 extruded option features mitered corners with supplied gaskets.



Rigid Aluminum Nailing Flange

Extruded Aluminum



Note: 4" Brickmould & Flat Casings require installation clips.

The Lincoln vinyl clad windows feature an accessory groove to the exterior, just like our aluminum clad line, which will accept 2" brickmould, 3-1/2" flat casing and 7/8" Sill Nosing. These vinyl trims feature a 1" x 1" J-channel and integral nailing flange. The original window nailing fin remains fully intact strengthening the entire system. Architects will enjoy our attention to detail by providing an authentic sill profile.









EXTERIORS 17

> and doors have trim. Lincoln offers trim builder and the end user. Of course the window in its setting. The exterior trim natures setting.

Tight and Spread Mulls


• Fills void between



Spread Mulls

When your project requires windows and patio doors in multiple-wide configurations, Lincoln has the mulls to make them right. Typical mulling is done with a tight unit to unit mull clip. Spread mulls add additional spacing between windows and patio doors. Popular reasons for utilizing a spread mull would include: accommodating a special opening with standard size windows, to achieve a 'heavier' look and the ability to work around essential structural framing. Spread mulls can be done both vertically and horizontally.

Extruded Aluminum







Panning Systems

Lincoln also offers a panning system for aluminum clad exteriors. These additional trims snap into the accessory groove which can add additional width and height to the exterior appearance of a window or patio door. This system will fill space from a window frame to the building thereby covering the framing material and nail fins. Incorporate an H-Clip and create an adjustable panning used to join two units fairly far apart. The panning system is a nice feature commonly used for remodeling when there are existing and varying openings.







Finishes

Define inner beauty by choosing a time saving, factory applied interior finish from Lincoln.

Natural Wood: Lincoln will leave your interior wood surface sanded smooth, ready for stain and sealer.

Primed: If you plan to paint the interior of your windows and patio doors, have them primed with a white factory applied, water-based acrylic latex primer.

Pre-Finish Options: To take things a step further, we offer factory applied topcoats of paint intended to be your final coat of paint with the nail holes filled reducing jobsite finishing costs. Choose from our traditional Pre-Finish White or contemporary Pre-Finish Black.







Primed

Pre-Finish Black




Trim

Lincoln offers interior trims in ten profiles for radius products. Customers benefit from our ability to shape the trim at the time a unit is produced.



Wood Species

Nothing enhances the look and feel of a room more than the richness and beauty of wood. Lincoln product comes standard with





Pine

For those looking to really enhance the character of a project, Lincoln also offers six additional wood species. The popular red oak, white oak, cherry, alder, mahogany and fir options all come with their own unique color and grain patterns to really enhance the character of the window.



Jamb Extensions

When installing a window, increasing the depth of the window frame to accommodate the wall thickness is sometimes necessary. This can easily be accomplished with the use of jamb extensions. These factory applied extensions are available in all seven wood species.



Here is another opportunity to have your windows and doors made to fit the interior design, décor and style of the room. Additionally, the exterior interacts with the overall architecture and creates fantastic curb appeal. Enhancing windows and doors with lite divisions definitely puts the icing on the cake. Although there are standard lite configurations designated for all products, custom designs are also

Lite & Grille Options

- Simulated Divided Lite (SDL)
- Interior Wood Grille
- Internal Aluminum Grille (GBG)
- Lincoln Divided Lite (LDL)



Simulated Divided Lite

- 5%", 7%", 1 1%" and 2"
- Profiled or Square
- Bronze, Black & Mill Finish
 Shadow Bar



Interior Wood Grille

Single Profile Widths:5%", 1", 1 %" and 1 ¼"

■ Double Profile Width: 7%"

With Surround

Without Surround



Interior Wood Grille (With Surround)





Internal Aluminum Grille

- 11/16" Double Profiled
- Color Matched to Cladding
- Two-Toned (white one side,
 9 standard colors on other side)



Internal Aluminum Grille

Lincoln Divided Lite

- 1/8" and 1 1/4"
- Authentic Divided Lites
- True Historic Appeal



Lincoln Divided Lite (Primed only)

GLASS

The glass in windows and patio doors has the single largest effect on energy efficiency. Lincoln's standard insulated glass offering includes double strength glass combined with a warm edge spacer. For greater energy efficiency, argon is added to all Low-E glass units, at no cost to the customer, with the exception of those units requiring capillary/breather tubes.* Choose Lincoln's standard glass or a combination of the options for appearance, performance and comfort.

* These are units shipped over high elevations. Lincoln does not guarantee that the initial argon fill rate will be maintained over the life of the product. Argon depletion may decrease energy efficiency. For more information, contact your local distributor or Lincoln Wood Products, Inc.

Insulated Glass Construction

Our insulating glass (IG) is constructed with four major components. It's the quality of these components, sheet glass, desiccant material, sealants and spacers that set companies apart.


Let's consider the sheet glass. We exclusively utilize double-strength glass (3.2mm) even on the smallest sizes. Some companies believe this should be an upgrade while we eliminated the thinner glass option many years ago.

Quality desiccant material is used to absorb moisture within the IG unit during assembly and the polyisobutylene sealant provides excellent adhesion to the glass with a low moisture vapor transmission rate for years of outstanding field performance.

Choose one of our premium warm-edge spacer systems to complete your perfect glazing package.



WARM EDGE SPACER



LoĒ-180™


Constructed with a single LoE coating, this glass option is perfect for climates where solar heat gain is welcome. LoE-180™ outperforms clear IG glazing with warmer inside glass temperatures and better UV protection.


Projects looking for passive solar glazing solutions including good U-Value performance in conjunction with higher Solar Heat Gain Coefficients experience positive benefits with LoE-180.™

LoĒ²-272®

Safeguard your home from the elements by using this nearly invisible protection. Consisting of two microscopic layers of silver sealed in the airspace, this glass is a nice step-up from our standard offering.

Obtain an affordable balance of U-value, solar shading, visible light transmittance and UV protection by choosing $Lo\bar{E}^2$ -272°.





Room-side heat reflected back into room by LoĒ insulated glass

Lodz-366™/Neat®

Controlling solar heat gain just became easier with the unparalleled performance of $Lo\bar{E}^3$ -366TM/Neat® glass technology. By adding a third layer of silver coating, $Lo\bar{E}^3$ -366TM/Neat® effectively blocks solar gain and reflects heat more efficiently.


In addition to reducing heat gain, the goal with any high performance glazing is clarity. Lodz-366™/Neat® was produced to show a minimum of exterior "mirror" reflectance and does not require smoke-colored tints that can darken your home's interior.


Dual Low-E2 (LoĒ i89TM/LoĒ²-272[®]) and Dual Low-E3 (LoĒ i89TM/LoĒ³-366[®])

Our most ecologically aware combination of glass products designed for projects requiring extraordinary energy efficiencies.

As the ENERGY STAR® program ratchets up its requirements, our glass offering continues to provide consumers with an ability to comply. Lincoln's Dual Low-E options are the next generation insulating glass packages that tackles these stricter requirements by combining LoDz-272® or Lodz-366® with a room side loE coating (LoĒ-i89™ is on surface #4). Don't worry, LoĒ-i89™ performs well without sacrificing glass clarity, doesn't require special cleaning and provides additional UV protection.

This energy efficient glass lowers U-Values and retains more of your costly heat inside for the Northern and North/Central zones. Assembling Dual Low-E with our foam spacer system further improves U-value performance.





Triple Pane Glass

Experience excellent thermal comfort with Lincoln's most energy conscious glazing selection-Triple Pane Glass. This glass offering utilizes 3 sheets of double strength glass, Cardinal's Endur IG spacers and features an Argon Gas fill. Triple Pane glass is perfect for your new energy efficient home.

Clients enjoy reduced condensation during freezing cold weather, better UV protection and improved Sound Transmission Class (STC) ratings by including Triple Pane glass.





Preserve®

Neat® and Preserve®

Neat*: Combines a permanent layer of silicon dioxide, which causes water to sheet off leaving fewer water spots, and a layer of titanium dioxide that reacts with the sun's UV rays causing organic material on the glass to decompose - no manual activation required.

Preserve*: A low density polyethylene adhesive that protects the glass during shipping and construction making clean-up a quick and easy process.

Specialty Glass Options

The majority of projects utilize clear glass, but occasionally a project requires the use of a specialty glass. Whether it be to conceal the view from the exterior of a building, distort the details of objects through the glass or provide an extra level of safety, we have a variety of specialty glasses that will meet your needs. Our specialty glass options include: laminated, obscure, tempered, tinted and spandrel.

Tinted Glass





Bronze

Obscure Patterns











Reed

CALL: 800.967.2461


Screen Mesh


Screens allow you to enjoy the fresh air while keeping insects and debris out of your home. Lincoln offers three practical options.

BetterVue: Our standard screen mesh. Made of fiberglass, it has thinner strands and a tighter weave than traditional fiberglass screen providing better visibility, increased light transmittance, greater airflow, improved curb appeal and enhanced protection from small insects (no-see-ums), debris and dust.

UltraVue: The least visible of our screen mesh options. The strands of UltraVue are thinner than BetterVue, providing even better airflow, optical clarity and insect protection.

Aluminum (charcoal wire): The most widely used metal for screens and is a great option for homes with pets or kids.





Aluminum

Screen Finishes

Lincoln interior screens are available in five metal frame finishes. Our color-matched PVC corner keys help keep interiors from scuffing during removal and installation. Double Hungs, Gliders and Patio Doors feature color-matched screen frames to match the exterior.

Standard Colors






DOUBLE HUNG WINDOWS

Double hung windows are popular due to their traditional design that compliments so many different styles of homes. They're also easy to operate, maintain and clean.

Lincoln double hungs allow architects, designers and builders to customize and tailor each individual project. Your specialist will create a contemporary edge with the clean lines of our narrow rail sash. Or stick with a strong historical influence by utilizing our traditional wide rail sash. Double hungs offer the flexibility to accommodate many design elements and are a great choice for both residential or light commercial projects.





	Specifications
Maximum RO Width	45 %"
Maximum RO Height	93"
Sash Thickness	1 1/16" thick
Bottom Rail Height	2 11/16"

Double Hung with Wide Rail Sash

- 1. Full 4-9/16" jamb depth.
- 2. Interior wood glazing bead.
- 3. 11/16" warm edge insulating glass.
- 4. 1-7/16" thick sash.
- 5. Traditional wide rail sash profile option.
- 6. Weatherstripped at head, sill and checkrail.
- 7. .050 extruded aluminum on sash and frame. Vinyl exteriors utilize .050 extruded PVC vinyl. Wood units have primed sash on the exterior with cPVC sill, sill nosing, blindstops and brickmould.
- **8.** Recessed jambliner option with inverted balance system.





9———	2
8	4

	Specifications
Maximum RO Width	45 %"
Maximum RO Height	93"
Sash Thickness	1 7/16" thick
Bottom Rail Height	1 ¹½16"

Double Hung with Narrow Rail Sash

- 1. Full 4-9/16" jamb depth.
- 2. Sloped putty-glazed styling.
- 3. 11/16" warm edge insulating glass.
- 4. Contemporary narrow rail sash profile option.
- 5. Low-profile 8° sloped sill.
- **6.** .050 extruded aluminum on sash and frame. Vinyl exteriors utilize .050 extruded PVC vinyl. Wood units have primed sash on the exterior with optional cPVC sill, brickmould and blindstop.
- 7. Full perimeter accessory groove.
- 8. Integral screen channel.
- **9.** Concealed jambliner option with inverted balance system.



Hardware

Locks & Tilt Latches: Available in seven hardware finishes, two low-profile pick resistant locks are used on units with 37 %" box size and wider. Units smaller than 37 %" box size have one lock.

Color matched double hung tilt latches are set into the check rail of the bottom sash and concealed in the top rail on the upper sash. Spring loaded, they release to tilt in with ease. Made to last and out of sight, these lock options are sure to please.







Sash Lift/Pull Handles: Our stylish lift/pull handles are available in three popular finishes that match sash locking hardware. They are also very easy-to-grab and easy to install after the interior finishing process is complete. These handles reduce damage from opening your windows by providing a solid area to grasp.

Not available for narrow rail double hung.





Sash Limiters: Thinking safety? Lincoln offers safe and secure sash limiters. This release mechanism keeps the window from being opened no more than four inches, allows the window to be fully opened for quick emergency exits and resets automatically every time the window is opened - all meeting the requirements of ASTM F2090.





Jambliner Options

Lincoln offers two different jambliner options for our double hung window lines. Both options utilize an inverted balance system for consistent performance and durability.

The standard jambliner comes in either beige or white and is recessed in the frame to minimize it's visibility.

The concealed jambliner takes the design aesthetic a step further. From the exterior, the jambliner is concealed by color matched cladding. From the interior, the jambliner design utilizes a clear pine insert to give more wood warmth when the window is closed.



Standard Jambliner - White Balances Exterior View



Concealed Jambliner - Beige Balances Exterior View



Standard Jambliner - White Balances Interior View



Concealed Jambliner - Beige Balances Interior View

CLICK: lincolnwindows.com



Styles

Double Hung: This arrangement is an ageless window type that offers some unique advantages. Sash tilt in for easy cleaning, ventilation is improved by opening the top and bottom sash equally and classic historical appeal is achieved when using Lincoln double hungs.

Our traditional window is equipped with advanced energy saving features. For example, Lincoln double hung checkrails incorporate the use of interlocks, weatherstrip and high-quality sash locks for a precision fit.



Radius Top Double Hung: Built as a single hung, Lincoln segment head and quarter segment windows are part of our double hung family. By utilizing the same parts and simply fixing the top sash, radius top hung windows can be mixed with traditional double hungs to create exciting elevations.

As with all Lincoln radius shapes, interior trim is available for the finishing touch. Segment head windows include a half screen.




Double Hung Bay: What could be more exciting than installing a Lincoln double hung bay window at the heart of your room? This attractive window combination is sure to add both functionality and flair.

Bay units are constructed using three windows or more. Flankers are aligned with a center unit at 45° or 30° angles. Center units can consist of operating double hungs or studio windows.

Double hung bay windows may include factory-assembled head and seat boards and a cable kit to compensate for overhanging weight and aid in installation.















When only the best will do.

Choose Lincoln for your new construction, remodeling or even light commercial projects. With almost 75 years of manufacturing experience built into every unit, we engineer our windows and patio doors for visual appeal as well as outstanding performance. In addition, Lincoln backs it up with exceptional customer service before and after the sale.

We are continually expanding our list of products, options and accessories. Check us out online for the latest offerings in the building industry. We are confident that we have the perfect windows and patio doors to harmonize with your ideas and designs.



Learn more about our products and options by contacting a local authorized Lincoln dealer or visiting us online at lincolnwindows.com.



Committed to protecting and preserving the environment.

Lincoln Windows is committed to environmental stewardship. As responsible corporate citizens, we are dedicated to manufacturing energy efficient products and managing our resources in a manner that reduces our impact on the environment.



Lincoln Windows is an ENERGY STAR® Partner.



Many of our products carry certification by the National Fenestration Rating Council (NFRC).



Lincoln products carry an extensive warranty. Ask your dealer for complete information.



Lincoln Windows & Patio Doors proudly supports the American Institute of Architects (AIA) Continuing Education System (CES).



Lincoln Wood Products, Inc. 1400 W. Taylor Street • P.O. Box 375 Merrill, Wisconsin 54452-1355 800-967-2461 • Fax: 715-536-9783 www.lincolnwindows.com




TABLE OF CONTENTS

4	Endless Design Possibilities
6	Inspiration
8	Statement Collection™ Products
10	Dream Collection™ Products
12	Hardie® Plank
14	Hardie® Shingle
16	Hardie® Panel
18	Hardie® Trim
20	Hardie® Soffit
22	Complete Exterior by James Hardie™
~4	Trusted Protection
24	
24 26	Tougher than the Elements
	Tougher than the Elements Hardie [™] Zone System
26	o
26 28	Hardie [™] Zone System
26 28 30	Hardie [™] Zone System Unique Formulation
26 28 30	Hardie [™] Zone System Unique Formulation
26 28 30 31	Hardie [™] Zone System Unique Formulation Sustainability
26 28 30 31	Hardie [™] Zone System Unique Formulation Sustainability Long-Lasting Beauty
26 28 30 31 34 36	Hardie [™] Zone System Unique Formulation Sustainability Long-Lasting Beauty Finishing Technology

Hardie[™] Weather Barrier



42



With endless design possibilities that embody your aesthetic, no matter how unique, Hardie® fiber cement exterior solutions give your home a beautiful design without having to sacrifice durability and protection. Trusted by homeowners on over 10 million homes* from coast to coast, and rated the #1 brand of siding in North America, it's clear that the vast product offerings from James Hardie can make the home you've always wanted possible. Revel in the beauty of your home's gorgeous exterior with the unprecedented peace of mind that only Hardie® products can provide. With James Hardie, your dream home is possible.

ENDLESS DESIGN **POSSIBILITIES** With a wide variety of colors, products and textures, you can create the personalized home exterior design that reflects your unique style - and that you'll love for years to come.

TRUSTED PROTECTION

From non-combustible fire resistance to resisting pests, moisture and extreme weather, Hardie® fiber cement helps protect your home and everything you cherish.

LONG-LASTING **BEAUTY**

Enjoy the peace of mind that comes with a low-maintenance exterior, backed by a 30-year non-prorated substrate warranty.**







Endless design possibilities.

Endless ways to express yourself.

ENDLESS DESIGN POSSIBILITIES

Products and colors that complement any style.

With a wide portfolio of products and over 700 pre-finished colors, creating your perfect design style is possible with Hardie® products.

Modern

Whether you crave clean lines and sleek profiles or bold hues, you'll find the perfect colors and styles to add a modern flair to your home that will be sure to make a lasting statement in your neighborhood.

Transitional

Transitional styles beautifully combine contemporary and traditional elements to create a design style that stands out. Mix your favorite profiles and colors to create a fresh look you'll love for years.

Traditional

Traditional homes offer timeless beauty that never goes out of style. Achieve the perfect balance between your home's character and your personal style with a variety of colors and products that add undeniable charm.













ENDLESS DESIGN POSSIBILITIES

Statement Collection™ Products

It's your turn to let your home stand out with our Statement Collection™ products. Curated by our design experts, this collection of Hardie® siding and trim products with ColorPlus® Technology finishes are unique to your home's region. This gorgeous selection is locally stocked in your area, making it easier than ever to find the exterior style of your dreams.

COLORPLUS® TECHNOLOGY

ColorPlus® Technology finishes combine distinct beauty and high performance in a way that no other finish does. They're the easiest way to choose a gorgeous pre-finished color for your house, and feel confident in its staying power.

Hardie® Plank, Hardie® Panel, Hardie® Shingle and Hardie® Trim Batten Color Offering





Scan code to request a sample.



Hardie® Plank

Thickness 5/16 in Length 12 ft planks

Select Cedarmill®

Width 7.25 in 8.25 in

Exposure 6 in 7 in

Hardie® Panel

Thickness 5/16 in

Select Cedarmill® & Smooth

Size 4 ft x 10 ft

Hardie® Shingle

Thickness 1/4 in Length 48 in

Straight Edge Panel Staggered Edge Panel

Height 15.25 in Height 15.25 in

Exposure 7 in **Exposure** 6 in







Hardie® Soffit

Thickness 1/4 in

Vented and Non-Vented Select Cedarmill®

Width 12 in

Length 12 ft

Hardie® Trim

Length 12 ft

4/4 Smooth

Thickness .75 in

Width 3.5 in* 5.5 in 7.25 in 9.25 in* 11.25 in*

5/4 Smooth

Thickness 1 in

Width 3.5 in 5.5 in 7.25 in 9.25 in* 11.25 in

*This size is only available in Arctic White



Hardie® Trim

Length 12 ft

4/4 Roughsawn

Thickness .75 in

Width 3.5 in* 5.5 in* 7.25 in 9.25 in* 11.25 in*

5/4 Roughsawn

Thickness 1 in

Width 3.5 in 5.5 in 7.25 in 9.25 in* 11.25 in*

*This size is only available in Arctic White



Batten Boards

Smooth & Rustic Grain

Thickness .75 in

Width 2.5 in




Dream Collection[™] Products

Looking to further express your sense of style? Look to our Dream Collection™ products.

- Featuring a color palette of over 700 ColorPlus®
 Technology finishes
- Made to order in a wide array of Hardie® siding and trim styles
- Matches elevated design flexibility with the uncompromising performance of our fiber cement products

To see the full 700-color range of the Dream Collection™ products, visit **jameshardie.com/dream**



Blue



Peaceful



Scan code to view colors and request a product sample.









A classic look that stands the test of time.

Hardie® Plank


From Victorians to Colonials, Hardie® Plank is the perfect siding for your style, and has the durability and long-lasting beauty that can transform your home exterior. With endless gorgeous color and plank pairings available, you'll discover a Hardie® Plank style that transforms your home's aesthetic.



Hardie® Plank



Select Cedarmill®





Smooth





Beaded Select Cedarmill®

Width	5.25 in	6.25 in	7.25 in	8.25 in	9.25 in*
Statement Collection [™]					
Dream Collection [™]	•	•	•	•	
Prime	•	•	•	•	•

Beaded Select Cedarmill

Width	8.25 in		
Exposure	7 in		
ColorPlus® Pcs/Pallet	210		
Pcs/Sq.	14.3		
Statement			
Collection™			
Dream			
Collection™	•		

Prime

Classic cedar style in cutting-edge material.

Hardie® Shingle

Restore the look of your grand Cape Cod home or add distinction to your handsome bungalow. Hardie® Shingle embodies the enchanting look of cedar shingles with lower maintenance. You can create your perfect exterior style using Hardie® Shingle around your entire home, or place it in accent areas for an added boost of charm you'll love.

Better than the real thing, Hardie® Shingle resists rotting, curling, warping and splitting.



Hardie® Shingle



Staggered Edge Panel

Staggered Edge Panel

Length	48 in
Height	15.25 in
Exposure	6 in
Prime Pcs/Pallet	100
ColorPlus® Pcs/Pallet	100
Sq/Pallet	2
Pcs/Sq.	50.0
Statement Collection [™]	•
Dream Collection [™]	•
Prime	•



Straight Edge Panel

Straight Edge Panel

Lawath	40 :
Length	48 in
Height	15.25 in
Exposure	7 in
Prime Pcs/Pallet	86
ColorPlus® Pcs/Pallet	86
Sq/Pallet	2
Pcs/Sq.	43.0
Statement Collection [™]	•
Dream Collection [™]	•
Prime	•

Designed for versatility and beautiful performance.

Hardie® Panel

Hardie® Panel delivers style and substance. When combined with Hardie® Trim Batten, it achieves the rustic board-and-batten look that defines your charming cottage or modern farmhouse. Its crisp, clean lines and ability to pair beautifully with other siding products make Hardie® Panel a smart choice for the home of your dreams.




Thickness 5/16 in

4 ft x 12 ft

Hardie® Panel



Select	Cedarmill®	



Smooth



Stucco



Size 4 ft x 8 ft 4 ft x 10 ft

Select Cedarmill®, Smooth, Stucco & Sierra 8

Prime Pcs/Pallet	50	50	50
ColorPlus® Pcs/Pallet	50	_	50
Pcs/Sq.	3.2	2.8	2.5

Select Cedarmill®

Size	4 ft x 8 ft	4 ft x 9 ft	4 ft x 10 ft
Statement Collection [™]			•
Dream Collection [™]	•		•
Prime	•	•	•

Smooth

Size	4 ft x 8 ft	4 ft x 9 ft	4 ft x 10 ft
Statement Collection [™]			•
Dream Collection [™]	•		•
Prime	•	•	•

Stucco

Size	4 ft x 8 ft	4 ft x 9 ft	4 ft x 10 ft
Statement Collection [™]			
Dream Collection [™]	•		•
Prime	•	•	•

Sierra 8

Size	4 ft x 8 ft	4 ft x 9 ft	4 ft x 10 ft
Statement Collection [™]			
Dream Collection [™]			
Prime	•	•	•

A finished look starts with beautiful trim.

Hardie® Trim

Form meets function at every intersection with Hardie® Trim boards. With an authentic look, Hardie® Trim boards provide design flexibility for columns, friezes, doors, windows and other accent areas.


With higher performance to withstand damage from the elements compared to wood trim, Hardie® Trim is the perfect option for a long-lasting home. Hardie® Trim is a low-maintenance and durable accent for your exterior — adding an extra component of beauty to your home.



Hardie® Trim



Collection[™]
Prime



•



4/4 Smooth		Thickness .75 in		Length 12 ft boards	
Width	3.5 in	5.5 in	7.25 in	9.25 in	11.25 in
Prime Pcs/Pallet	312	208	156	104	104
ColorPlus® Pcs/Pallet	312	208	156	104	104
Statement Collection [™]	AW	•	•	AW	AW
Dream Collection [™]	•	•	•	•	•
Prime	•	•	•	•	•

5/4 Roughsawn			Thickness 1 in Length 12 ft boar			ft boards
Width	3.5 in	4.5 in	5.5 in	7.25 in	9.25 in	11.25 in
Prime Pcs/Pallet	240	200	180	120	80	80
ColorPlus® Pcs/Pallet	240	200	180	120	80	80
Statement Collection [™]	•		•	•	AW	AW
Dream Collection [™]	•	•	•	•	•	•
Prime	•	•	•	•	•	•

5/4 Smooth			Thickness 1 in		Length 12 ft boards	
Width	3.5 in	4.5 in	5.5 in	7.25 in	9.25 in	11.25 in
Prime Pcs/Pallet	240	200	160	120	80	80
ColorPlus® Pcs/Pallet	240	200	160	120	80	80
Statement Collection [™]	•		•	•	AW	•
Dream Collection™	•	•	•	•	•	•
Prime	•	•	•	•	•	•

Batten Boards

Thickness	.75 in
Length	12 ft
Width	2.5 in
Prime Pcs/Pallet	437
ColorPlus® Pcs/Pallet	190





Protection in every detail, complete confidence in every area.

Hardie[®] **Soffit**

Every part of your home's exterior matters. With Hardie® Soffit panels, you can live confidently, knowing that gaps between eaves and exterior walls are covered to provide trusted protection.

DID YOU KNOW?

Using vented soffit improves ventilation and reduces the chance of water-vapor condensation that can promote mold, mildew and stains and which can damage your home's framing over time.

In warm climates, vented soffit allows hot, humid air to escape, which not only helps prevent condensation in the attic, but also helps reduce air-conditioning costs.

In cool climates, vented soffit helps prevent condensation from forming on the interior side of the roof sheathing and reduces the chances of roof-damaging ice dams.



Hardie® Soffit



Thickness 1/4 in

Length	12 ft	12 ft	8 ft	8 ft
Width	12 in	16 in	24 in	48 in
Prime Pcs/Pallet	200	150	100	50
ColorPlus® Pcs/Pallet	216	156	108	_

Vented Smooth

Size	12 ft x 12 in	12 ft x 16 in	8 ft x 24 in
Statement Collection [™]			
Dream Collection [™]	•	•	•
Prime	•	•	•

Non-Vented Smooth

Size	12 ft x 12 in	12 ft x 16 in	8 ft x 24 in
Statement Collection [™]			
Dream Collection [™]	•	•	•
Prime	•	•	•

Vented Cedarmill®

Size	12 ft x 12 in	12 ft x 16 in	8 ft x 24 in
Statement Collection [™]	•		
Dream Collection [™]	•	•	•
Prime	•	•	•

Non-Vented Cedarmill®

Size	12 ft x 12 in	12 ft x 16 in	8 ft x 24 in
Statement Collection [™]	•		
Dream Collection [™]	•	•	•
Prime	•	•	•

Complete Exterior by James Hardie[™]

Confidence and beauty all around.



Scan code to visualize Hardie® products on your home.





Top to bottom, our exterior product line is defined by high performance, aesthetics and design options.

With a Complete Exterior by James Hardie™, you can bring your dream home to life without having to choose between protection and long-lasting beauty. Using products from a single, trusted manufacturer that offers exceptional warranties, you'll have complete peace of mind, so you can sit back, relax and enjoy your home's exterior.



Hardie® Shingle

Hardie® Panel & Hardie® Trim Batten





Hardie® Plank

Hardie® Trim Boards



Hardie® Soffit

Durability you can trust.







Tougher than the elements.



Fire

A home's exterior is its first line of defense against extreme weather and fire. Prepare your home for the unpredictable with siding that is non-combustible, won't burn and is recognized by fire departments nationwide.*

Listed for use in wildfire-prone
 Wilderness Urban Interface (WUI)
 zones in the western US.

Cal-Fire Compliant

Fiber Cement Siding





*Hardie® siding complies with ASTM E136 as a noncombustible cladding and is recognized by fire departments across the U.S. including Marietta, GA, Flagstaff, AZ and Orange County, CA. Fiber cement fire resistance does not extend to applied paints or coatings, which may be damaged or char when exposed to flames.







Mother Nature's creatures can wreak havoc on wood-based siding. It can be pecked by birds or damaged by termites or other pests. Hardie® fiber cement holds no appeal for these critters, saving you the maintenance hassle.





Mother Nature

Your siding is exposed to Mother Nature all day, every day. You deserve to feel confident that it can hold its own throughout it all — from the changing seasons to extreme weather.

- FEMA Class 5 flood damage resistance (highest rating)
- Rated for use in High Velocity Hurricane zones by Miami-Dade County, Florida





Water Resistant

From rain to ice to snow, Mother Nature's precipitation patterns leave wood exteriors at risk to cracking, swelling and warping. Take shelter from the storm knowing that your siding is built to resist water damage.





Time

ColorPlus® Technology finishes provide a durable finish that helps resist fading and discoloration that other paint applications may see more quickly over time, so your exterior can keep its good looks longer.

Exterior solutions inspired by nature and designed to help protect your home from it.

Hardie[™] Zone System

Only Hardie® fiber cement exterior products are Engineered for Climate®, designed specifically with your climate zone in mind for optimal performance. In the northern USA and Canada, HZ5® products resist shrinking, swelling and cracking in wet or freezing conditions. HZ10® products help protect homes from hot, humid conditions, blistering sun and more.

With Hardie® siding and trim, your home's exterior will be as tough as it is beautiful.







The highest-quality materials for your highest satisfaction.

Unique Formulation HZ5® Substrate

Not all fiber cement is the same. The Hardie® HZ5® product formulation contains the highest-quality raw materials. Our unique formulation, combined with innovative product design and manufacturing processes, creates a substrate that is specifically engineered to resist moisture, cracking, shrinking and swelling, for increased durability and workability.

Proprietary enhancements create durable Hardie® siding

Perfect balance of strength and workability

Our balance of high-quality Portland cement, sand and cellulose fiber delivers the best combination of strength and workability.

Enhanced moisture resistance for unmatched durability

Patented and proprietary additives are chemically bonded within the HZ5° substrate matrix to provide durable moisture resistance. In addition, Hardie° Plank in HZ5° substrates come with a drip edge to provide improved water management.

Increased dimensional stability

Our siding is engineered at the microscopic level to create a fiber cement composite with superior dimensional stability that helps protect against shrinking and splitting.









Unmatched investment in manufacturing scale and production innovation

- Largest manufacturer of fiber cement in North America
- 5x more capacity than our largest competitor
- More than 100 process and product quality checks
- 100+ scientists and engineers providing dedicated resources for continuous innovation in manufacturing and product development
- More U.S. fiber cement patents than any competitor

Building sustainable communities.

Sustainability is built into our DNA.

At James Hardie, our business is about building better communities that have a lower impact on our environment and are built to last. We operate with a global mindset and at the same time take great care in how our business affects households, our James Hardie community, the local communities in which we live and operate, and across the largest shared community of all, our global ecosystem. Building sustainable communities is at the forefront of our strategy and integral to our success.







James Hardie

↑ Homeowner



Scan code to find out more about our sustainability efforts.







Adding value to our communities

We recognize our ability to impact the communities in which we live and work. While maintaining a global mindset, we put great care into how our business affects local communities. We contribute by sourcing, employing, delivering and giving locally.

Creating an impact

We invest in the local community and aim to locate the plants close to suppliers, customers and potential new employees, as well as sustainable transportation opportunities.

CONTRIBUTED

\$1.42B

To communities in which we operate

HIRED

75%

From the local communities in which we operate

SOURCED

80%

Of raw materials locally

DELIVERED

65%

Of manufactured products locally

The right kind of impact

Having a sustainable impact means minimizing our impact on the environment while supporting resilient local communities. We are committed to minimizing our environmental impact, prioritizing the management of waste, water, energy and emissions.

2030 goals



Energy & Emissions

We aim to minimize our Scope 1+2 Greenhouse gas intensity by 40% from 2019 baseline.



Waste

We aim to minimize manufacturing waste intensity by 50% from 2019 baseline.



Water

We aim to increase water recycling by 20 Million cubic feet/year from 2019 baseline.



Environmental Product Declarations

We aim to have 80% of revenue from products with Environmental Product Declarations (EPD).





Long-lasting beauty by design.



ColorPlus® Technology

ColorPlus® Technology finishes are fully cured on our boards in a controlled factory environment and arrive at your home ready for installation year-round. With prefinished color products, you'll have peace of mind, knowing you'll have a more consistent color and finish that doesn't depend on good weather.

With over 700 colors available, ColorPlus® Technology finishes offer endless design possibilities and help keep your home looking beautiful longer.





Finishing Technology

Primer

A quality primer is the first step to ensuring that the paint color you select expresses your home's true beauty now – and for years to come. Our distinctive primer is climate tested and engineered to enhance the performance of paint on Hardie® fiber cement exterior solutions. It helps to provide consistent, long-lasting paint adhesion, even in the most demanding conditions.

ColorPlus® Technology

Our advanced ColorPlus® Technology finishes deliver the ultimate in aesthetics and performance. Our products aren't simply painted at the factory. Our proprietary coatings are baked onto the board, creating a vibrant, consistent finish that performs better, lasts longer and looks brighter on your home.



Exceptional finish adhesion

Our proprietary coatings are engineered for exceptional adhesion to our substrate and applied to the surface, edges and features for durable performance.



Superior color retention

The finish is cured onto boards for a stronger bond, which allows for exceptional resistance to cracking, peeling and chipping.



Superior UV resistance

ColorPlus® Technology finishes are engineered to retain vibrancy and reduce fade or discoloration from UV rays.

Unparalleled beauty with unparalleled performance.


See the James Hardie difference

James Hardie invented modern fiber cement. Trusted by homeowners on over 10 million homes, we continue to set the standard in premium, high-performance exterior cladding. Our products deliver uncompromising durability and finish quality for a beautiful, lower maintenance exterior.

Our unrivaled investment in R&D and constant innovations in product design, manufacturing and distribution allow us to remain steps ahead of the competition. With the support of our employees and partners, and with our exceptional warranties, we're committed to helping protect your home and investment every step of the way.



*Estimate based on total Hardie® siding sales through 2022 and average housing unit size.





Warranty — for peace of mind

Help protect your home with North America's #1 brand of siding, backed by exceptional warranties.

Unlike other brands, James Hardie doesn't prorate our siding and trim substrate warranty coverage. We stand 100% behind our siding for 30 years and our trim for 15 years.

- Hardie® siding and soffit products come with a 30-year non-prorated limited substrate warranty.
- Hardie® trim products come with a 15-year non-prorated limited substrate warranty.
- ColorPlus® Technology finishes come with a 15-year prorated limited finish warranty.

Non-Prorated Siding Substrate Warranty Coverage by James Hardie



Endorsements — a reputation built on trust

For decades, our fiber cement products have been used to create better places to live. Each new home stands as a testament to our uncompromising quality. That proven track record has earned us the loyalty of millions of homeowners and the endorsements of trusted authorities across the building industry.



Featured on

Magnolia Network's Fixer Upper:

Welcome Home 2021



Featured on HGTV's
Urban Oasis 2022



Green Builder Magazine
Readers' Choice,
"Most Sustainable Product" 2020




#1 Return on Investment*

Re-siding with fiber cement siding provides the #1 return on investment of any major exterior remodeling projects.





Scan code to view the Cost vs. Value Report.



Hardie® Trim

FOR THE PROS

Protection that performs at every layer.

Hardie[™] Weather Barrier

No exterior cladding can prevent 100% of water intrusion. Your home should have an additional line of defense. Hardie™ Weather Barrier provides a superior balance of water resistance and breathability, keeping the area within the wall drier. This helps prevent moisture accumulation that may lead to mold and mildew growth.

INSTALLATION ADVANTAGES

- Thicker, more durable material for easier, quicker installation
- Superior tear resistance helps prevent water infiltration
- Can be installed with staples in place of cap nails for cost savings
- Provides a higher level of performance, no matter what type of cladding you specify



Weather Barrier

 Thickness
 11 mil

 Length
 100 ft
 100 ft
 150 ft

 Width
 3 ft
 9 ft
 9 ft

Pro-Flashing

 Thickness
 20 mil

 Length
 75 ft
 75 ft
 75 ft

 Width
 4 in
 6 in
 9 in

Flex Flashing

 Thickness
 60 mil

 Length
 75 ft
 75 ft

 Width
 6 in
 9 in

Seam Tape

Thickness 3.2 mil Length 164 ft Width 1-7/8 in

Installation Done Right

INSTALLATION ACCESSORIES

Hardie[™] Blade Saw Blades

Manufactured by Diablo, the Hardie™ Blade saw blade is designed specifically to cut fiber cement products and is the only saw blade James Hardie recommends. The blade creates clean, precise cuts while helping to reduce the amount of airborne dust produced.





PacTool® Gecko Gauge

The PacTool® Gecko Gauge is designed to improve the installation experience, allowing one person to hang Hardie® Plank lap siding during installation. Studies suggest the Gecko Gauge can improve the speed of solo installation by 30%.





Finishing Touches

COLORPLUS® TECHNOLOGY ACCESSORIES

Touch-Up Kits

Specially formulated to match ColorPlus® Technology finishes, our touch-up kits offer resistance to aging, color change and chalking. Estimated one kit per 4,000 sq ft of siding or 1,600 sq ft of trim.



Color-Matched Caulk

OSI® QUAD® MAX sealant offers a high-performance sealant solution to color match Statement Collection™ products.* About 18–20 linear feet per tube. Refer to packaging for manufacturer's recommendations.

*For matching Dream Collection™ products, contact your local James Hardie representative.

TRIM ACCESSORIES

Flat Tabs

Eliminate face nails and improve the aesthetic of trim applications around windows, doors and band boards.

Corner Tabs

Use corner tabs to eliminate face nail holes that would detract from the finished look of corner trim installations.



Scan code to view install and technical documents.

